Experimental demonstration of optical switch using gradient optical force

Ding, L.; Song, J. F.; Yu, M. B.; Lo, G. Q.; Kwong, D. L.; Cai, H.; Tao, J. F.

2012

Cai, H., Tao, J. F., Ding, L., Song, J. F., Yu, M. B., Lo, G. Q., et al. (2012). Experimental demonstration of optical switch using gradient optical force. Optical Fiber Communication Conference and Exposition (OFC/NFOEC), 2012 and the National Fiber Optic Engineers Conference, 1-3.

<https://hdl.handle.net/10356/101991>

© 2012 Optical Society of America. This paper was published in Optical Fiber Communication Conference and Exposition (OFC/NFOEC), 2012 and the National Fiber Optic Engineers Conference and is made available as an electronic reprint (preprint) with permission of Optical Society of America. The paper can be found at the following official URL:<http://ieeexplore.ieee.org/xpl/articleDetails.jsp?arnumber=6191976>. One print or electronic copy may be made for personal use only. Systematic or multiple reproduction, distribution to multiple locations via electronic or other means, duplication of any material in this paper for a fee or for commercial purposes, or modification of the content of the paper is prohibited and is subject to penalties under law.

Downloaded on 26 Apr 2023 17:51:13 SGT

Experimental Demonstration of Optical Switch Using Gradient Optical Force

H. Cai¹, J. F. Tao^{1,2}, L. Ding¹, J. F. Song¹, M. B. Yu¹, G. Q. Lo¹, and D. L. Kwong¹

¹Institute of Microelectronics, A*STAR (Agency for Science, Technology and Research), 117685 SINGAPORE

²School of Electrical & Electronic Engineering, Nanyang Technological University, Singapore 639798 SINGAPORE

E-mail: caih@ime.a-star.edu.sg

Abstract: A novel optical switch driven by gradient optical force is demonstrated, allowing weak light to switch a strong one. The proposed optically controlled switch achieves an extinction ratio of 28 dB with ~ns switching speed.

OCIS codes: (220.4880) Optomechanics; (230.7390) Waveguides, planar; (130.3120) Integrated optics devices

1. Introduction

The development of optical communications enables its major change from the current electronic-optical-hybrid network to all-optical network, especially in the backbone [1]. In particular, active optical switching plays a vital role in turning all-optical network into reality. Nowadays, a multitude of photonic switching technologies are candidates for highly integrated optical communication networks, such as electro-optic switches, thermo-optic switches, micro-optoelectromechanical systems based switches, and so on [2-3]. While all these advances do have their virtues, the obvious advantages of waveguide-based devices could be of the economy of scale and easy integration. Furthermore, it is highly desirable to use silicon as the platform to achieve high speed switching.

Optical forces have attracted significant interest, especially in the areas of nano-particle trapping and manipulation [4-5] and opto-mechanically driven nanostructures [6-7] for potential applications such as all optical signal processing. One type of optical force, named as the transverse gradient force, has recently been reported and demonstrated in nanophotonic waveguide systems [8-10], including enabling mechanical displacement of integrated nanophotonic structures. It has also been shown that the gradient optical force is increased by orders of magnitude in evanescently coupled waveguides due to the largely enhanced gradient of the optical field.

In this work, we demonstrate a novel optical switch utilizing the gradient optical force arising from the strong evanescent coupling between two parallel suspended waveguides. The proof-of-concept optical switch obtains a switching contrast of more than 28 dB with a response time of ~20 ns.

2. Switch Design

Fig. 1 Schematic of the optical switch, where λ_1 is the input signal light and λ_2 is the control light.

Fig. 2 The displacement of the suspended slot-waveguide versus the suspended length, at different power levels.

The schematic of the proposed optical switch is illustrated in Fig. 1. It consists of suspended waveguide structures in Mach-Zehnder interferometer (MZI) configuration. One of the MZI arms is arranged as a slot-waveguide, which consists of two parallel suspended waveguides with a narrow gap in-between, forming a doubly-clamped suspension arm; while the other is completely fixed. During the operation, the signal light (λ_1) propagates along the MZI, while another control light (λ_2) with the power of (P) is injected and coupled to the slot-waveguide. As a result, the gradient electromagnetic field within the slot-waveguide produces a strong attractive optical force (F_{opt}) evenly distributed over the waveguide length L , which can be expressed as:

$$\frac{F_{opt}}{L} = -\frac{P}{v_g \omega} \frac{d\omega}{ds} \bigg|_k \quad (1)$$

where ω is the optical input frequency, corresponding to λ_2 , v_g is the group velocity, L is the suspension length of the slot-waveguide, and s is the width of the gap of the slot waveguide. Due to the optical force, a corresponding mechanical displacement (D) of the suspension arm is introduced, and can be expressed as:

$$D = -\frac{PL^4}{32Eha^3v_g\omega} \times \frac{d\omega}{ds} \bigg|_k \quad (2)$$

where E is the waveguide Young's modulus, h and a are the waveguide height and width, respectively. It indicates that D varies proportionally to the power of the control light. Based on the above equations, we calculate the displacement D varying with the optical power, as plotted in Fig. 2. As expected, the displacement increases as the power is strong. Meanwhile, for the same optical input power, the displacement increases when the suspension part becomes longer. However, a longer suspended waveguide may be less robust and less resistant to the effects of external mechanical shock, placing a practical limit on the increase in large displacement obtainable by increasing L .

Due to this displacement, the gap within the slot-waveguide is changed. Therefore, the effective refractive index is changed (Δn_{eff}), leading to a further phase shift ($\Delta \phi_{WG}$) of the signal light. As a result, the output of MZI is switched. In this case, the phase shift induced by the waveguide displacement is given by:

$$\Delta \phi_{WG} = \frac{2\pi}{\lambda} \int_{-L/2}^{L/2} \Delta n_{eff}(x) dx + \Delta \phi_L \quad (3)$$

3. Fabrication and Experimental Results

Based on the theoretical analysis presented in the previous section, the optical force driven switch is designed and fabricated on an SOI-wafer. The scanning electron micrograph (SEM) of the switch is shown in Fig. 3, where a slot-waveguide is suspended from the substrate. The switch has a footprint of $500 \mu\text{m} \times 150 \mu\text{m}$. The suspended beam has a length of $30 \mu\text{m}$ and a cross-section of $300 \text{ nm} \times 340 \text{ nm}$, which allows the single-mode light propagation at low loss. Except for the suspended part, all the waveguides have a silicon core surrounded by $2 \mu\text{m}$ SiO_2 cladding. During fabrication, the device is patterned by deep UV lithography, Si etched by plasma, and SiO_2 deposited to cover Si core as cladding. After that, a thin Si_3N_4 layer (100 nm) is used to protect the parts not to be released. Then a wet-etching process is carried to remove the buried-oxide layer underneath the suspended slot-waveguide with precisely time control. Finally, supercritical carbon-dioxide process is used to clean the wafer and alleviate the stiction problem induced by surface tension of water.

Fig. 3 Scanning electron micrograph (SEM) of optical switch (a) overview. (b) Zoom view of the suspended slot-waveguide, with the coupling gap is 120 nm.

Using the TE-polarized input signal light at 1550 nm and a control light at 1567.6 nm, measurements are conducted to monitor the static performance as well as quantify the response time of the proposed switch. As the magnitude of the optical force varies proportionally to the power of the control light, sufficient control power is needed for a better extinction ratio, as shown in Fig. 4. Therefore, an Erbium doped fiber amplifier (EDFA) is used to amplify the control light. According to the experiment, the extinction ratio of 28 dB is obtained. The switching time is measured by applying a pulse control signal to the switch and monitoring the output power simultaneously using an oscilloscope. The results are shown in Fig. 5, with the rise and fall time are 20.66 ns and 25.55 ns, respectively.

Fig. 4 Measured output power versus EDFA current (for control signal power amplification).

Fig. 5 Measured switching response, in term of normalized output power, when a pulse is applied.

4. Conclusions

We have experimentally demonstrated a novel optical switch driven by gradient optical force. Through a suspended slot-waveguide and optical force driving, the switch obtains a switching contrast of 28 dB with a response time of ~ 20 ns. Such optical force tuning approach may provide considerable room for device performance improvement, as well as open up more applications in future.

References

- [1] S. Saha, E. D. Manley and J. S. Deogun, "Minimizing network cost in all-optical networks," *2009 IEEE 3rd Int. Symposium on Advanced Networks and Telecom. Syst.*, New Delhi, (2009).
- [2] R. L. Espinola, M-C Tsai, J. T. Yardley and R. M. Osgood, Jr, "Fast and low power thermo-optic switch on thin silicon-on-insulator," *IEEE Photon. Technol. Lett.*, 15, 1366 – 1368 (2003).
- [3] W. M. Zhu, X. M. Zhang, A. Q. Liu, H. Cai, T. Jonathan and T. Bourouina, "A micromachined optical double well for thermo-optic switching via resonant tunneling effect," *Appl. Phys. Lett.*, 92, 251101 (2008).
- [4] A. Ashkin, "Acceleration and Trapping of Particles by Radiation Pressure," *Phys. Rev. Lett.*, 24, 156-159 (1970).
- [5] S. Chu, "Laser Manipulation of Atoms and Particles," *Science*, 253, 861-866 (1991).
- [6] G. S. Wiederhecker, L. Chen, A. Gondarenko, M. Lipson, "Controlling photonic structures using optical forces," *Nature* 462, 633-636 (2009).
- [7] D. Van Thourhout and J. Roels, "Optomechanical device actuation through the optical gradient force," *Nature Photon.* 4, 211-217 (2010).
- [8] M. L. Povinelli, M. Loncar, M. Ibanescu, E. J. Smythe, S. G. Johnson, F. Capasso and J. D. Joannopoulos, "Evanescent-wave bonding between optical waveguides," *Opt. Lett.*, 30, 3042-2044 (2005).
- [9] M. Li, W. H. P. Pernice, C. Xiong, T. Baehr-Jones, M. Hochberg and H. X. Tang, "Harnessing optical forces in integrated photonic circuits," *Nature*, 456, 480-484 (2008).
- [10] H. Cai, K. J. Xu, J. M Tsai, G. Q. Lo, D. L. Kwong and A. Q. Liu, "Nano-opto-mechanical linear actuator utilizing gradient optical force," in *Proc. Transducers 2011*, 1709-1712 (2011).