A fully integrated Class-J GaN MMIC power amplifier for 5-GHz WLAN 802.11ax application

Liu, Bei; Mao, Mengda; Boon, Chirn Chye; Choi, Pilsoon; Khanna, Devrishi; Fitzgerald, Eugene A.

2018

Liu, B., Mao, M., Boon, C. C., Choi, P., Khanna, D., & Fitzgerald, E. A. (2018). A fully integrated Class-J GaN MMIC power amplifier for 5-GHz WLAN 802.11ax application. *IEEE Microwave and Wireless Components Letters*, 28(5), 434-436. doi:10.1109/LMWC.2018.2811338

<https://hdl.handle.net/10356/104486>

<https://doi.org/10.1109/LMWC.2018.2811338>

© 2018 IEEE. Personal use of this material is permitted. Permission from IEEE must be obtained for all other uses, in any current or future media, including reprinting/republishing this material for advertising or promotional purposes, creating new collective works, for resale or redistribution to servers or lists, or reuse of any copyrighted component of this work in other works. The published version is available at:
<https://doi.org/10.1109/LMWC.2018.2811338>

Downloaded on 26 Apr 2023 21:03:13 SGT

A Fully Integrated Class-J GaN MMIC Power Amplifier for 5-GHz WLAN 802.11ax Application

Bei Liu, Mengda Mao, Chirn Chye Boon, *Senior Member, IEEE*, Pilsoon Choi, *Member, IEEE*,
Devrishi Khanna, and Eugene A. Fitzgerald

Abstract—This letter presents a fully integrated Class-J GaN MMIC power amplifier (PA), which is fabricated in Woolfspeed 0.25 μm GaN-on-SiC technology. This PA is the first published design for the emerging IEEE 802.11ax application in literature. When tested with 80MHz 256-QAM 802.11ax signal with 11.25 dB peak-to-average power ratio (PAPR), the PA delivers average output power of 27.3 to 30.3 dBm from 4.9 to 5.9 GHz, with power-added efficiency (PAE) of 16.7% to 27.3%, while meeting the standard specification of error vector magnitude (EVM) below -32 dB.

Index Terms—Monolithic microwave circuit (MMIC), 802.11ax, Class-J, GaN power amplifier.

I. INTRODUCTION

RECENTLY, the accelerating growth of smartphones and mobile devices is propelling wireless communication to evolve towards higher data rate. As the successor of 802.11ac standard, 802.11ax introduces OFDMA and utilizes smaller sub-carrier spacing to improve overall spectrum efficiency, especially in high dense Wi-Fi deployment scenario. Besides, higher order 1024-QAM modulation is employed in 802.11ax to increase throughput. The data rate of 802.11ax is expected to be boosted up to 10 Gb/s, to meet the tremendous demand for high data rate application, such as interactive and high-definition video. However, wide bandwidth and complex modulation scheme of 802.11ax result in large PAPR, posing more stringent requirements of linearity and efficiency on power amplifier design than the earlier 802.11 standards. Consequently, design of a highly linear integrated PA with high efficiency remains a great challenge, especially in CMOS process. Since GaN HEMT device exhibits high breakdown voltage and high power density, GaN PA is a good candidate

Fig.1. Simplified equivalent-circuit mode of the transistor in final stage

for 802.11ax application.

In recent years, Class-J mode of operation has drawn much attention to achieve high linearity, high efficiency and wide bandwidth simultaneously [1]–[5]. Class-J mode theoretically has the same efficiency and linearity as conventional Class-AB mode, but do not require open-circuit or short-circuit harmonic termination, which significantly simplifies the design of matching network such that high efficiency and wide bandwidth can be easily achieved. Therefore, Class-J mode is an appropriate choice for PA design to target high efficiency and high linearity over 5-GHz WLAN band.

In this letter, a novel fully integrated Class-J GaN PA for 802.11ax application is demonstrated. During the design, the fundamental and second harmonic termination is theoretically analyzed, providing objective for output matching network design. The proposed PA can deliver saturated output power over 37 dBm with PAE of 48.3%-54.6% across the whole 5-GHz WLAN band. Besides, the PA features excellent linearity that meets the requirements of 802.11ax standards, thus can be potentially used in 802.11ax access point with large coverage range.

II. CLASS-J PA DESIGN

The Class-J mode requires complex fundamental load impedance and pure reactance second-harmonic load impedance [1]–[3], which are defined by

$$Z_{f_0} = \frac{2(V_{DD} - V_k)(1 + j)}{I_{\max}} = R_{opt} + j \cdot R_{opt} \quad (1)$$

$$Z_{2f_0} = \frac{-j \cdot 2(V_{DD} - V_k)}{\frac{2}{3\pi} I_{\max}} = -j \frac{3\pi}{8} R_{opt} \quad (2)$$

in which, $R_{opt} = 2(V_{DD} - V_k) / I_{\max}$ is the optimum load of Class-B operation. In the design, the transistor's size in the final output stage is set at 1.6 mm, and this GaN transistor can

Manuscript received January 4, 2018; accepted February 21, 2018.

This work was supported by the National Research Foundation, Prime Minister's Office, Singapore, through its Campus for Research Excellence and Technological Enterprise Program.

B. Liu, C.-C. Boon, and D. Khanna are with the School of Electrical and Electronic Engineering, Nanyang Technological University, Singapore, 639798 (e-mail: liubei@ntu.edu.sg).

M. Mao is with M/A-COM Technology, Shanghai, 20030, China.

P. Choi and Eugene A. Fitzgerald are with Massachusetts Institute of Technology (MIT), Cambridge, MA 02139 USA.

Fig.5. Photo of the fully integrated GaN die and testing board

Fig.6. Measured performance of CW testing (a) PAE and Psat versus frequency (b) PAE and gain versus output power at different frequency

Fig.7. Measured performance with 802.11ax signal (a) PAE and average output power (b) EVM and PAE in different power level at 5.5 GHz

Fig. 8. Measured constellation, EVM and spectrum with 802.11ax signal

frequency range of 4.9-6 GHz, and the measured saturated output power and PAE are reported in Fig.6 (a). The measured maximum output power and efficiency are between 37-37.68 dBm and 48.3-54.6% from 4.9 GHz to 6 GHz, respectively. The measured power gain and efficiency versus output power at 5, 5.5 and 5.9 GHz are depicted in Fig.6 (b), showing the power gain is above 28.5 dB.

To evaluate the PA's practical performance for 802.11ax application, the PA was tested using 80MHz 802.11ax signal with 256-QAM modulation and 5/6 code rate without digital pre-distortion (DPD). The PAPR of this signal is as high as 11.25 dB. When satisfying the standard specification of $EVM < -32$ dB for 256-QAM modulation, PA delivers average output power of 27.3-30.6 dBm and achieves efficiency of 16.7-27.3%, as shown in Fig. 7 (a). The measured EVM in different output power level and the corresponding efficiency at 5.5 GHz are depicted in Fig.7 (b). The EVM floor of the test signal can only reach to -41 dB due to the imperfection of signal source, resulting in a little degradation in measured EVM performance. Consequently, the PA can only achieve -38.3 dB

TABLE III
PERFORMANCE COMPARISON BETWEEN THE PROPOSED PA AND OTHER INTEGRATED GaN PAs

Ref.	This work	[4]	[7]	[8]	[9]
Freq(GHz)	4.9-5.9	2.2-3.2	5-6	5.2-6.8	5.2-6.2
Psat(dBm)	37-37.68	24-27	47.7	46	42.1-43
PAE(%)	48.3-54.6	48-58	40-43	51.5-56.5	37-41
Gain(dB)	28.5-31.7	7-10	25	25.4-27.7	20
Size(mm ²)	1.28×3.7	2×2	3.2×5.3	3.2×5.3	4.5×3.5

EVM. In addition, the measured constellation, spectrum and EVM of -38.28 dB at 5.5 GHz are demonstrated in Fig. 7. Although EVM of signal with 1024-QAM modulation was not measured due to lack of analysis capacity, the PA is expected to satisfy -35 dB EVM specification for emerging 802.11ax standard with 1024-QAM. Finally, the PA's performance is summarized and compared with other published integrated GaN PAs [7]-[9], reported in Table III.

IV. CONCLUSION

This work introduces a fully integrated Class-J GaN power amplifier designed for 5GHz WLAN 802.11ax systems. To author's knowledge, this PA is the first published design for 802.11ax systems in literature. The measurement results demonstrate the promising performance, showing the PA is of great commercial value. If DPD is employed, PA's performance could be further enhanced. Besides of 802.11ax, the PA can also be used in current 802.11ac systems.

REFERENCES

- [1] S. C. Cripps, P. J. Tasker, A. L. Clarke, and J. Lees, and J. Benedikt, "On the continuity of high efficiency modes in linear RF power amplifiers," *IEEE Microw. Wireless Compon. Lett.*, vol. 19, no. 10, pp. 665-667, Oct. 2009.
- [2] P. Wright, J. Lees, J. Benedikt, P. J. Tasker, and S. C. Cripps., "A methodology for realizing high efficiency class-J in a linear broadband PA," *IEEE Trans. Microw. Theory Techn.*, vol. 57, no. 12, pp. 3196-3204, Dec. 2009.
- [3] Q. Li, S. He, W. Shi, Z. Dai, and Tian. Qi, "Extend the class-B to class-J continuum mode by adding arbitrary harmonic voltage elements," *IEEE Microw. Wireless Compon. Lett.*, vol. 26, no. 7, pp. 522-544, Jul. 2016.
- [4] S. Rezaei, L. Belostotski, F. M. Ghannouchi, and P. Aflaki, "Integrated design of a class-J power amplifier," *IEEE Trans. Microw. Theory Techn.*, vol. 61, no. 4, pp. 1639-1648, Dec. 2013.
- [5] A. Alizadeh, and A., "A broadband integrated class-J power amplifier in GaAs pHEMT technology," *IEEE Trans. Microw. Theory Techn.*, vol. 64, no. 6, pp. 1822-1830, Jun. 2016.
- [6] G. Wilkinson, A. Cappy, F. Heliodore, and E. Playez, "A new method for determining the FET small-signal equivalent circuit," *IEEE Trans. Microw. Theory Techn.*, vol. 36, no. 7, pp. 1151-1159, Jul. 1988.
- [7] X. Yu, H. Sun, Y. Xu, and W. Hong, "C-band 60 W GaN power amplifier MMIC designed with harmonic tuned approach," *Electron. Lett.*, vol. 52, no. 3, pp. 219-221, Feb. 2016.
- [8] Y. S. Noh, and I. B. Yom, "Highly integrated C-band GaN high power amplifier MMIC for phased array applications," *IEEE Microw. Wireless Compon. Lett.*, vol. 25, no. 6, pp. 406-408, Jun. 2015.
- [9] C. Florian, R. Cignani, D. Niessen, and A. Santarelli, "A C-band AlGaIn-GaN MMIC HPA for SAR," *IEEE Microw. Wireless Compon. Lett.*, vol. 22, no. 9, pp. 471-473, Sep. 2012.