Incremental calibration of seat selection preferences in agent-based simulations of public transport scenarios

Andelfinger, Philipp; Chen, Yihao; Su, Boyi; Cai, Wentong; Zehe, Daniel; Eckhoff, David; Knoll, Alois

2019

Andelfinger, P., Chen, Y., Su, B., Cai, W., Zehe, D., Eckhoff, D., & Knoll, A. (2018). Incremental calibration of seat selection preferences in agent-based simulations of public transport scenarios. Proceedings of the 2018 Winter Simulation Conference, 833-844.
doi:10.1109/WSC.2018.8632292

<https://hdl.handle.net/10356/143200>

<https://doi.org/10.1109/WSC.2018.8632292>

© 2018 IEEE. Personal use of this material is permitted. Permission from IEEE must be obtained for all other uses, in any current or future media, including reprinting/republishing this material for advertising or promotional purposes, creating new collective works, for resale or redistribution to servers or lists, or reuse of any copyrighted component of this work in other works. The published version is available at:
<https://doi.org/10.1109/WSC.2018.8632292>.

Downloaded on 26 Apr 2023 16:34:13 SGT

INCREMENTAL CALIBRATION OF AGENT-BASED PEDESTRIAN MODELS USING HUMAN-IN-THE-LOOP SIMULATION

Philipp Andelfinger
Yihao Chen
Boyi Su
Wentong Cai

Daniel Zehe
David Eckhoff
Alois Knoll

TUMCREATE Ltd. and
Nanyang Technological University
1 Create Way
Singapore, 138602, SINGAPORE

TUMCREATE Ltd. and
Technical University of Munich
1 Create Way
Singapore, 138602, SINGAPORE

ABSTRACT

The calibration of agent-based pedestrian simulation models requires empirical data. To avoid cost-intensive real-world experiments, human-in-the-loop simulations can be applied in which simulated pedestrians interact with human-controlled agents. However, the experiment results may be unrealistic if the human participants are presented with agents acting according to an uncalibrated model. We propose an incremental calibration approach that aims to address the circular dependency between the behaviour of human and simulated pedestrians. By incrementally adapting the parameters of the simulated agents to match the behaviour of the human participants, we aim to gradually approach a realistic interaction. We evaluate our approach using the simulation of the boarding procedure of a public transport vehicle in 2D and virtual reality experiments. The calibration results are compared with those gathered from a traditional non-incremental calibration. Our results indicate the feasibility of our approach and highlight the necessity for future research on efficient simulation model calibration.

1 INTRODUCTION

Crowd simulation is a helpful tool to study pedestrian flows in a variety of contexts, e.g., in evacuation scenarios (Pelechano and Badler 2006), in urban planning (Farenc, Boulic, and Thalmann 1999), or to understand passenger movement in public transport systems (Gao and Jia 2016). One method to simulate crowds is to follow an agent-based approach, i.e., each pedestrian autonomously employs a sense, think, act cycle (Hoogendoorn 2001). The agent senses its environment and other agents, computes actions according to a model and then finally carries out the action. There exists a wide range of different behavioural models (e.g. the magnetic force model (Gipps and Marksjö 1985), the Social Force model (Helbing and Molnar 1995), or cellular automata models (Blue and Adler 2001)) that aim at reproducing realistic pedestrian movement.

Applying an easy-to-understand and manageable general-purpose model to realistically simulate crowd movement seems to be intractable, as human behaviour is complex and affected by various factors, e.g. their psychological state and the current context (Sakuma, Mukai, and Kuriyama 2005). Therefore, these models usually have a variety of input parameters that can be calibrated in order to adapt the model to a specific scenario. Calibration is commonly done with the help of empirical data, such as trace files of pedestrians or video footage. The calibration process proceeds by setting the input parameters in a way so that the employed model reproduces the empirical data as closely as possible.

Often, the problem is the availability of this empirical data. Real-world experiments are costly and time intensive as they require a physical environment and possibly a large number of test subjects. High quality (in terms of resolution and frame rate) video footage alleviates this problem, however, the observed behaviour might not generalise easily and is restricted to already existing environments. On top of that, comprehensive video footage of public spaces can be hard to obtain due to prevailing data-protection laws.

One possible solution is to immerse human participants in a virtual reality (VR) environment populated with simulated pedestrians (Shendarkar, Vasudevan, Lee, and Son 2006). The benefits of virtual environments are that the scenario conditions can be changed at low cost and the collection of data is straight forward as the experiment is already of digital nature. When the goal is to calibrate the behaviour models of the simulated agents using the behaviour of the human participant, a causality dilemma arises: the simulated agents will affect the human participants in an unrealistic manner, leading to potentially unrealistic behaviour of the human participant which is then used to calibrate the simulated participants.

To approach this problem, we propose a dynamic data-driven calibration approach in which the behaviour of the simulated agents is gradually and iteratively calibrated to the observed behaviour of the human participants. By continuing the experiment during the calibration process, we aim to create a feedback loop: the human participant reacts to simulated pedestrians that exhibit increasingly realistic behaviour, causing the human participant to also behave in a more realistic manner. Our contributions can be summarized as follows:

- **Incremental calibration method:** We propose a method for the incremental calibration of agent-based pedestrian models using human-in-the-loop experiments.
- **Proof of concept:** We show how our method can be applied by demonstrating its applicability to the calibration of a seat-selection model for public-transport vehicles.
- **Comparison to traditional approaches:** We show that the incremental calibration leads to different results than a calibration in the presence of uncalibrated simulated agents.

While our results do not yet allow us to make statements about the relative quality of the results of the incremental and offline calibration, the substantial differences in the calibration results indicate that further investigation is warranted.

The remainder of the paper is structured as follows: In Section 2 we give a comprehensive overview of related works in the domains of crowd simulation and virtual reality. We explain our general methodology in Section 3 and our specific experiment setup is described in Section 4. We present and discuss our results in Section 5, which is followed by a discussion on the limitations and challenges of the presented approach in Section 6 before concluding in Section 7.

2 RELATED WORK

In the following, we give an overview of existing works on the parametrization of pedestrian models based on real-world data and optimization approaches. Subsequently, we discuss works on model calibration based on observations in virtual reality environments.

2.1 Parametrization of Agent-Based Pedestrian Simulation Models

In agent-based pedestrian simulation, modelling pedestrians is achieved by representing them as autonomous entities that independently react to their environment according to a set of decision-making rules (Zhou, Chen, Cai, Luo, Low, Tian, Tay, Ong, and Hamilton 2010). Frequently, agent-based pedestrian simulation models are applied to study scenarios in the context of public transportation, e.g., to evaluate different bus or train layouts with respect to passenger flow and the required dwell time at stations (Gao and Jia 2016, Rexfelt, Schelenz, Karlsson, and Suescun 2014, Schelenz, Suescun, Wikström, and Karlsson 2012, Schelenz, Suescun, Wikström, and Karlsson 2014), or to evaluate station layouts (Hoogendoorn, Hauser, and Rodrigues 2004).

Hoogendoorn differentiates three levels of pedestrian movement covered by agent-based pedestrian models ((Hoogendoorn 2001), summarized in (Parisi, Gilman, and Moldovan 2009)): the *operational* level addresses the basic walking behaviours, the *tactical* level performs basic planning such as route choices, and the *strategical* level covers higher-level planning.

One of the most common model on the operational level is the Social Force model proposed by Helbing in the context of simulating evacuation processes (Helbing and Molnar 1995). The model computes for each agent an acceleration based on repulsive forces computed from the neighbouring agents' distance and mass. In the present paper, we rely on the Social Force model for basic walking behaviour and on simple rules on the tactical and operational levels (specified in Section 4).

While crowd simulation models determine the general behaviour of agents, their mathematical formulation typically contains a number of parameters for which suitable numerical values must be found according to a given scenario. For instance, on the operational level, the Social Force model has multiple parameters, some of which lack a direct interpretation, complicating the prediction of the effects on the observed agent behaviour (Kretz, Lohmiller, and Sukennik 2017). On the strategical level, parameters for the agents' decision-making must be configured, e.g., their preference for a certain seat inside a train (Schelenz, Suescun, Karlsson, and Wikström 2013), the movement and decision making on the platform before boarding the vehicle (Daamen and Hoogendoorn 2004), and the passengers' choices of destinations and routes (Alam and Werth 2008).

Kretz et al. investigate how a user equilibrium can be reached when calibrating pedestrian models for a given scenario (Kretz, Lehmann, and Hofsäß 2014). The authors limit the route choices to a limited number of fixed routes generated from the scenario geometry. Crociani et al. simulate pedestrian movement on a cellular grid and achieve a user equilibrium or system optimum, depending on the cost function used to make route choices (Crociani and Lämmel 2016).

Methods that aim to achieve a system optimum or user equilibrium do not require empirical data, and it has been argued that the results still reflect some of the properties of real-world systems. However, the results do not reflect the effects of non-optimal decision-making, e.g., due to social factors (Kretz, Lehmann, and Hofsäß 2014).

To calibrate pedestrian model parameters to real-world observations, most existing work relies on video footage (Berrou, Beecham, Quaglia, Kagarlis, and Gerodimos 2007, Hoogendoorn, Daamen, and Bovy 2003). Video footage is either collected during regular operations or from dedicated experiments with volunteer participants. Sometimes, physical mockups are constructed to serve as the environment for the experiment (Rexfelt, Schelenz, Karlsson, and Suescun 2014).

Kretz et al. provide guidelines on how to calibrate the parameters of the Social Force model against empirical data (Kretz, Lohmiller, and Sukennik 2017). The suggested calibration process is an algorithm that determines suitable parameters according to the general relationships between the model parameters and the output statistics. The process is iterative and includes feedback, i.e., simulations are performed to determine the next change in parameters.

Rudloff et al. calibrate a model of passengers boarding and alighting a subway train against video footage gathered in experiments using a mockup of the subway train door area (Rudloff, Bauer, Matyus, and Seer 2011). They collected the times when passengers pass the train door, as well as the location of the pedestrians. Three sets of parameters are calibrated: the positions of passengers while waiting to board, parameters guiding the starting times of the boarding and alighting, and the parameters of the Social Force model. A simulation-based optimization process relying on a genetic algorithm was applied for calibration. The main part of the objective function is the absolute error between the crossing times of the passengers in the video footage and in the simulation.

Benner et al. calibrate a simulation model of pedestrians passing through a narrow corridor against trajectory data from a real-world experiment (Benner, Lohmiller, and Sukennik 2017). They varied the Social Force parameters to fit the number of pedestrian within the corridor. Since a reasonable fit could not be achieved this way, the model was extended to include sets of agents with different desired velocities.

Voloshin et al. perform a simulation-based optimization to calibrate parameters of the Social Force model against video footage of pedestrians at a metro station (Voloshin, Rybokononko, and Karbovskii 2015). A simulation-based optimization process using a genetic algorithm is used to adapt the parameters. The objective function determines the error with respect to the number of agents, the flow, the passage time, as well as the number of overlaps among pedestrians and between pedestrians and obstacles.

The main difference between the discussed related work and our approach is that we assume that insufficient empirical data is available to calibrate the system. Our approach focuses on extracting calibration data from virtual reality experiments when only a limited number of participants is available and simulated agents are needed to populate the system.

2.2 Pedestrian Model Calibration in Virtual Reality Environments

Collecting calibration data from real-world experiments is time consuming and costly. In some existing works, experiments with human participants immersed in a virtual-reality environment were performed to gather the data required for calibration.

Shendarkar et al. gather pedestrian behaviours in an emergency response scenario from human-in-the-loop experiments in a virtual-reality environment (Shendarkar, Vasudevan, Lee, and Son 2006). The observed behaviours are used to parametrize agent behaviours modelled using the Belief, Desire, and Intention (BDI) framework. In the simulated emergency scenario, agents escape a scene made up of paths with multiple intersections and obstacles. Path choice weights were directly gathered from the observed frequencies in the human-in-the-loop experiments.

Kretz et al. gather path choices of pedestrians when presented with a choice of multiple doors with varying numbers of other pedestrians inside a virtual reality environment (Kretz, Hengst, Roca, Arias, Friedberger, and Hanebeck 2011). They avoid the need for human participants for creating congestion at the doors by relying on simulated agents. Agents behaved according to the Social Force model and the “dynamic potential” model for determining the desired direction and velocity.

The existing literature relies on “offline” calibration approaches, i.e., modifications to the parameter combinations are applied to the simulated crowd only after the experiment. In the above works, this approach is sufficient since there is only limited feedback with respect to the parameters being calibrated, i.e., adapting the crowd behaviour according to new observations would not affect the human participants’ behaviour strongly. However, we argue that when the crowd model parameters to be calibrated may affect the human participants’ behaviour, the partial calibration results should be fed back into the experiment.

3 INCREMENTAL CALIBRATION APPROACH

In the following, we describe the proposed approach on the example of a model calibration for simulating passengers boarding a public transit vehicle and selecting a seat. Figure 1 illustrates the building blocks and calibration work flow. The overall goal is to gather observational data of the human participant’s behaviour in order to parametrise an agent-based pedestrian model so that seat selection preferences are represented in a realistic manner.

To this end, human participants as well as simulated agents share an environment and are repeatedly assigned the task of boarding a public transport vehicle starting from a randomized position near the vehicle door. We refer to each repetition as a *calibration cycle*. Each calibration cycle starts with participants and simulated agents starting to move from the outside of the vehicle to the inside and select a seat. The calibration cycle ends when each agent and participant have found a seat or a maximum time has passed. At this point, if an agent or the participant are still moving, they are considered standing. The simulated agents may affect the human participant’s behaviour by occupying some of the seats or by obstructing some areas and paths inside the vehicle. In the first calibration cycle, the simulated agents perform their actions according to parameter values chosen manually, e.g., based on a domain expert’s estimation, using

Figure 1: Incremental calibration approach: the parameters guiding the agent behaviour are adapted incrementally according to observations of the human participant’s behaviour.

Figure 2: Autonomous vehicle layout used in the experiments (dark grey: vehicle walls, grey: area not available for standing, light grey: standing area, yellow: leaning seats, orange: seats).

empirical data from similar experiments, or entirely at random. The actions of the human participants as well as the simulated agents during a *calibration cycle* are monitored and stored as an *observation*.

After the boarding task has been completed by the human participants, a new parametrization of the simulated agents’ behavioural model is produced by an *aggregator* to reflect the new knowledge gained about the participant’s behaviour. Depending on the type of the considered parameters, the parameter values can be derived directly from the observations, e.g., the frequency at which a specific seat is selected over multiple calibration cycles. In other cases, there may not be a trivial relationship between the observations and agent parameters that lead to similar behaviour. Then, a black-box optimization may be performed at each optimization cycle or periodically to determine a suitable parameter combination.

There are various options for adapting the parameters at the end of each calibration cycle. In the simplest case, the parameters that match the most recent observation are used in the next cycle. However, to avoid oscillation, it may be necessary to also consider the parameter combinations matching previous observations, e.g., by computing a weighted average over all cycles.

Over the course of the calibration process, the human participant interacts with agents that more and more closely imitate the participant’s previous behaviours. Through the resulting feedback, we aim to allow the human participant to gradually exhibit more realistic behaviours, improving in turn the realism in the behaviour of the simulated agents.

The vehicle’s interior design and layout used in the experiments is similar to upcoming autonomous vehicles to be used in autonomous public transport. Since currently, there are very few examples in which autonomous public transport vehicles are already in extensive use, pedestrian simulations may be applied to evaluate the effects of different vehicle interior layouts on the boarding and alighting times of passengers. The vehicle layout used in our experiments is shown in Figure 2. Different areas within the vehicle are signified by their colours. The seats are numbered, index 12 signifying any position in the standing area.

A meaningful estimation of the boarding and alighting times requires a realistic model of the passengers behaviour both on the operational and the tactical level. At the end of multiple calibration cycles with many human participants, the agents should exhibit behaviours similar to humans entering a public transport vehicle.

4 EXPERIMENT SETUP

We introduce two different experimental setups in which a human participant repeatedly boards a public transport vehicle while the seat preferences of the simulated agents are incrementally calibrated to the observed preferences of the participant. In the **2D top-down seat selection**, the participant controls a

passenger in a 2D representation of the boarding scenario. In the **VR immersive seat selection**, the participant performs the boarding in a 3D environment using a head-mounted display (HMD) and a hand-held controller.

In both environments, we focus on calibrating the seat selection preferences, while future work includes calibration of the Social Force parameters, which guide the distance-keeping between agents. For simplicity, we assume that the vehicle is empty when the boarding process starts and that the seat selection preferences can be expressed solely by the probabilities to select the different seats.

We conducted the experiment with only a single human participant at a time. Performing experiments with more than one human participant at a time will require considerations of aspects such as the weighting of observations and the generation of multiple types of agents, which we leave to future work. After each human participant has gone through both calibration processes, the experiment is replicated with a different person. In effect, the outcome of each calibration process in the present study is a parametrization of the seat selection assuming that all agents share the preferences of the respective human participant.

The *calibration cycles* terminate once all simulated agents have chosen a position in the vehicle. Both the 2D and the VR experiment rely on the same agent behaviour, which we modelled using the agent-based simulation framework CrowdTools (Luo, Zhou, Cai, Low, and Lees 2009). The movement of the simulated agent is performed using the Social Force model (Helbing and Molnar 1995), with path planning according to the shortest path to the selected seat. Each simulated agent selects a target seat according to the probabilities derived from the observations of the human participant in the previous calibration cycles.

2D top-down seat selection: In the 2D top-down seat selection (Figure 3a), the participants can see a top-down view of the vehicle and some surrounding space. One of the agents (represented by circles) can be controlled by moving the mouse in the desired direction. Once the participant is satisfied with the position, the seat selection is terminated by pressing a mouse button, after which the agent can no longer be moved. Simulated agents move until they have reached their desired position or the maximum time has passed.

VR immersive seat selection: In the VR immersive seat selection (Figure 3b), participants wear a *head-mounted display* (HMD) to conduct the experiment in a virtual reality environment. The participant selects the direction of movement by rotating a controller and holds a button to move in the given direction. In this experiment, we terminate each calibration cycle once the participant indicates verbally that the current position is satisfactory.

The experiments were performed by 9 human participants aged between 22 and 30, three of which were female, six of which were male. In addition to the experiment data, a questionnaire collected data about the public transport travel patterns and familiarity with public transport. The main question asked in the questionnaire was how often the participants rely on public transport. 8 of the participants answered *daily*, while the remaining participant answered *2-3 times a week*. After the experiment, the participants were asked what they based their seat selection on. Common answers included: proximity to windows and exits, sitting in the direction in which the vehicle is going (right to left), distance to other agents (e.g., expectation to sit alone, one seat in between passengers).

5 RESULTS

The two main questions we aim to answer in our evaluation are:

- Are the seat selection preferences affected strongly by the choice of 2D or VR environment?
- How do the measurement results differ between the experiment with uncalibrated agents and the incrementally calibrated agents?

5.1 Seat Selection Preferences

We first consider the results from the 2D experiments. Figure 4 shows how the seat selections of two participants evolved over the course of the experiment. We show the results both for uncalibrated agents

Figure 3: Screenshots of the two virtual environments.

Figure 4: Example of the seat selection frequencies over the course of the experiment for two participants.

and incrementally calibrated agents. The plots show the relative frequency for the human participants to occupy a certain seat after a given number of calibration cycles. Visually, we can observe that a larger variety of seats were selected when agents were calibrated incrementally. This general trend was observed for a number of participants and will be quantified in Section 5.2.

Looking at the seat selection probabilities at the end of the experiment, we observe that with uncalibrated agents, the diversity in the seat selection by the human participant is quite limited and that the probability distribution of the seats seems wider when agents are calibrated incrementally. Since the incrementally calibrated agents adopt the behaviour of the human participants, there is higher competition for the most preferred seats. These results indicate that the incremental calibration helps expose secondary preferences that are expressed only when the most preferred seats are favoured by other passengers as well.

Figure 5: Examples of the seat selection frequencies over the course of the experiment for two participants, comparing the results from the 2D and the 3D VR experiment.

5.2 Entropy of Seat Selection Frequencies

The entropy of the probability of selecting a specific seat in each calibration cycle can be used to describe the statistical dispersion of the observed seat probabilities. The entropy is maximal when all seats are equally likely and minimal when the probability of one particular seat is 1.

In Figure 6 two different participant’s entropies over all calibration cycles can be seen. In both cases, the participants’ seat choices were more diverse with the incremental calibration. In contrast to these results, in Figure 7 the incremental and calibrated entropy values do not differ significantly, i.e., the diversity in the participant’s seat selection was barely affected when agents competed for the same seats.

Figure 8 shows a ranked list of entropy differences between the calibration approaches for each participant after the last calibration cycle. It can be observed that the entropy difference is positive for all but one participant, i.e., the choice of seats became more diverse using the incremental calibration approach. This is caused by agents competing for the same seats as the human participant would, frequently forcing the human participant to choose a different seat.

Lastly, we compared the results obtained using the VR environment to the ones obtained using the simple 2D interface. Figure 9 shows the Bhattacharyya coefficient of the seat selection probabilities over the calibration cycles. A value of 0 indicates that there is no overlap between the two distributions, a value of 1 signifies that both distributions are identical. We observe that the results with both methods are similar but not identical, emphasising the influence of the chosen experiment setup. This is further illustrated by the histogram over all approaches shown in Figure 10 The popularity of some seats can be observed across all setups, with the aforementioned differences of the uncalibrated approach.

Figure 6: Entropy of the seat selection frequencies in the 2D experiment over the calibration cycles for two different participants with and without incremental calibration.

Figure 7: Entropy of the seat selection frequencies for participant 3, with slightly lower entropy compared to incremental calibration.

Figure 8: Sorted final entropy difference between uncalibrated and incrementally calibrated agents. Colouring according to k-means, $k = 4$

6 DISCUSSION

This article can only be a first step towards incremental calibration of agent-based models using a human-in-the-loop approach. There are still open questions that need to be addressed, some of them of a general nature, others specific to the use case of seat selection in public transport vehicles.

When setting up experiments with humans in virtual environments, there are several challenges: First, the design of the experiment itself can have a significant impact on the outcome, e.g., how the starting conditions are chosen as well as the look and feel of the virtual environment.

Second, the number of iterations may be larger than a participant is willing to carry out. We observed that even after 50 iterations, there was still visible change in the seat selection behaviour for some of the participants. Potentially, faster converge may be achieved by starting the experiment with partially trained agents or by weighting recent observations higher, although preliminary experiments indicated that the latter introduces large variations. Techniques from the field of Serious Games (Rüppel and Schatz 2011) could encourage the participants to conduct more iterations so that more reliable data can be collected. Additionally, we assume every passenger to behave the same when in reality the crowd mix might significantly affect the seat occupancy (Schelenz, Suescun, Wikström, and Karlsson 2012). Some passengers might be more resolute in conquering a seat, elderly people are slower but may be offered a seat, other passengers may wish to stand instead of sit, etc. With a large enough test subject set, it is possible to create different

Figure 9: Bhattacharyya coefficient of VR and 2D across all calibration approaches.

Figure 10: Average seat selection probability across all calibration approaches

personas based on the observations made in the experiment. These personas could then be assigned to different agents to reflect a more realistic crowd mix.

The approach we demonstrated in this paper can be considered naive as we neglect psychological rules affecting seat selection altogether and reduce the problem to simple probabilities. For example, some passengers may prefer a window seat or may avoid sitting directly next to someone else if other seats are still available (Berkovich, Lu, Levine, and Reddy 2013). On top of that, passengers travelling together are more likely to sit next to each other. When asking the participants in our human-in-the-loop simulation why a certain seat choice was made, we observed these rationales, even to the extent that some participants in fact articulated that they choose their seat according to their thermal comfort, i.e., not directly exposed to air conditioning or close to other passengers. Ideally, reducing all these factors to a black box and only considering the resulting seat selection probability would allow us to neglect these complex relations as the final result would inherently include them. To which extent this approach is feasible and which parameters still need to be considered is specific to the application and needs to be evaluated carefully.

Our approach can be applied to calibrate more sophisticated models, however, more holistic data collection is then required, potentially further increasing the number of iterations. In fact, the potential applications of the incremental calibration method include all scenarios where agents affect each other in a feedback loop, e.g., path selection (Shendarkar, Vasudevan, Lee, and Son 2006), Social Force intensity (Kretz, Lohmiller, and Sukennik 2017), or even acceleration or lane change behaviour in traffic simulation (Brockfeld, Kühne, and Wagner 2004). One interesting research direction is the combination of our method with machine learning techniques, e.g., Q-Learning or Neural Networks. The behaviour of an agent would be controlled by a model trained on the observations from previous calibration cycles under the expectation that with each cycle, it reflects the human behaviour more closely. However, the selection of inputs to these models is still challenging and specific to the application.

The main issue certainly is to determine whether the presented approach actually leads to more realistic agent behaviour. With the lack of ground truth data, it is difficult to assess the quality of the calibrated model. The obvious questions whether the output statistics converge to a ground truth value therefore remains unanswered and will be the focus of future work. A ground truth can be obtained in real-world tests using a physical environment with a real vehicle or a mockup, or by analysing video footage.

7 CONCLUSION

In this article, we presented an approach for the incremental calibration of pedestrian models using human-in-the-loop simulation. We propose to use virtual environments such as a simple 2D graphical user interface or a more sophisticated virtual reality where simulated and human-controlled agents interact. With every

calibration cycle, the simulated agents attempt to adopt the previously observed human behaviour, which in turn affects the human participants in their choices, leading to different behaviour compared to experiments with agents that behave according to fixed model parameters.

Our method can facilitate the calibration process when the system under evaluation does not (yet) exist or when empirical data is sparse or not available. While the model investigated in our case study is rather simple, our approach can be extended to more complex decision making models and is not limited to output statistics.

In future work, we intend to compare the final calibrated model parameters obtained with our approach to a full-featured field trial with only human participants. This will allow us to gain better insights in the applicability as well as the limitations of our approach.

ACKNOWLEDGMENT

This work was financially supported by the Singapore National Research Foundation under its Campus for Research Excellence And Technological Enterprise (CREATE) programme. The authors would like to extend their gratitude to their colleagues Dr Henriette Cornet and Goran Marinkovic in the Design for Autonomous Mobility group at TUMCREATE for the permission to use their vehicle layout.

REFERENCES

- Alam, S. J., and B. Werth. 2008. "Studying emergence of clusters in a bus passengers seating preference model". *Transportation Research Part C: Emerging Technologies* 16(5):593 – 614.
- Benner, H., J. Lohmiller, and P. Sukennik. 2017, January. "Is Calibration a Straight-Forward Task if Detailed Trajectory Data is Available?". Technical report, PTV Group.
- Berkovich, A., A. Lu, B. Levine, and A. Reddy. 2013. "Observed customer seating and standing behavior and seat preferences on board subway cars in new york city". *Transportation Research Record: Journal of the Transportation Research Board* 2353(4):33–46.
- Berrou, J. L., J. Beecham, P. Quaglia, M. A. Kagarlis, and A. Gerodimos. 2007. "Calibration and validation of the Legion simulation model using empirical data". In *Pedestrian and Evacuation Dynamics 2005*, 167–181. Springer.
- Blue, V. J., and J. L. Adler. 2001. "Cellular automata microsimulation for modeling bi-directional pedestrian walkways". *Transportation Research Part B: Methodological* 35(3):293–312.
- Brockfeld, E., R. Kühne, and P. Wagner. 2004. "Calibration and validation of microscopic traffic flow models". *Transportation Research Record: Journal of the Transportation Research Board* 1876:62–70.
- Crociani, L., and G. Lämmel. 2016. "Multidestination Pedestrian Flows in Equilibrium: A Cellular Automaton-Based Approach". *Computer-Aided Civil and Infrastructure Engineering* 31(6):432–448.
- Daamen, W., and S. Hoogendoorn. 2004. "Pedestrian traffic flow operations on a platform: observations and comparison with simulation tool SimPed". *WIT Transactions on The Built Environment* 74:125–134.
- Farenc, N., R. Boulic, and D. Thalmann. 1999. "An Informed Environment Dedicated to the simulation of virtual humans in urban context". In *Annual Conference of the European Association for Computer Graphics (EUROGRAPHICS '99)*, 309–318. Milan, Italy.
- Gao, L., and L. Jia. 2016, December. "Modeling and Simulation of Passenger Flow Distribution in Urban Rail Transit Hub Platform". Technical Report 2016090085, Preprints.
- Gipps, P. G., and B. Marksjö. 1985. "A micro-simulation model for pedestrian flows". *Mathematics and computers in simulation* 27(2-3):95–105.
- Helbing, D., and P. Molnar. 1995. "Social force model for pedestrian dynamics". *Physical review E* 51(5):4282.
- Hoogendoorn, S., M. Hauser, and N. Rodrigues. 2004. "Applying microscopic pedestrian flow simulation to railway station design evaluation in Lisbon, Portugal". *Transportation Research Record: Journal of the Transportation Research Board* 1878:83–94.

- Hoogendoorn, S. P. 2001. *Pedestrian and Evacuation Dynamics*, Chapter Microscopic Pedestrian Wayfinding and Dynamics Modeling, 123–154. Springer.
- Hoogendoorn, S. P., W. Daamen, and P. H. Bovy. 2003, January. “Extracting Microscopic Pedestrian Characteristics from Video Data”. In *Transportation Research Board Annual Meeting*, 1–15. Washington DC, USA.
- Kretz, T., S. Hengst, V. Roca, A. P. Arias, S. Friedberger, and U. D. Hanebeck. 2011. “Calibrating dynamic pedestrian route choice with an extended range telepresence system”. In *International Conference on Computer Vision Workshops (ICCV Workshops)*, 166–172. IEEE.
- Kretz, T., K. Lehmann, and I. Hofsäß. 2014. “User equilibrium route assignment for microscopic pedestrian simulation”. *Advances in Complex Systems* 17(02):1450010.
- Kretz, T., J. Lohmiller, and P. Sukennik. 2017. “Some Indications on how to Calibrate the Social Force Model of Pedestrian Dynamics”. Technical Report 1801.00276, arXiv.
- Luo, L., S. Zhou, W. Cai, M. Y. H. Low, and M. Lees. 2009, September. “Toward a generic framework for modeling human behaviors in crowd simulation”. In *International Joint Conferences on Web Intelligence and Intelligent Agent Technologies (WI-IAT’09)*, Volume 2, 275–278. Milan, Italy: IEEE.
- Parisi, D. R., M. Gilman, and H. Moldovan. 2009. “A modification of the social force model can reproduce experimental data of pedestrian flows in normal conditions”. *Physica A: Statistical Mechanics and its Applications* 388(17):3600–3608.
- Pelechano, N., and N. I. Badler. 2006, November. “Modeling crowd and trained leader behavior during building evacuation”. *IEEE Computer Graphics and Applications* 26(6):80–86.
- Rexfelt, O., T. Schelenz, M. Karlsson, and A. Suescun. 2014. “Evaluating the effects of bus design on passenger flow: Is agent-based simulation a feasible approach?”. *Transportation Research Part C: Emerging Technologies* 38:16–27.
- Rudloff, C., D. Bauer, T. Matyus, and S. Seer. 2011. “Mind the gap: Boarding and alighting processes using the social force paradigm calibrated on experimental data”. In *2011 14th International IEEE Conference on Intelligent Transportation Systems (ITSC)*, 353–358. IEEE.
- Rüppel, U., and K. Schatz. 2011. “Designing a BIM-based serious game for fire safety evacuation simulations”. *Advanced Engineering Informatics* 25(4):600–611.
- Sakuma, T., T. Mukai, and S. Kuriyama. 2005. “Psychological model for animating crowded pedestrians”. *Computer Animation and Virtual Worlds* 16(3-4):343–351.
- Schelenz, T., Á. Suescun, M. Karlsson, and L. Wikström. 2013. “Decision making algorithm for bus passenger simulation during the vehicle design process”. *Transport Policy* 25:178–185.
- Schelenz, T., Á. Suescun, L. Wikström, and M. Karlsson. 2012. “Passenger-centered design of future buses using agent-based simulation”. *Procedia-Social and Behavioral Sciences* 48:1662–1671.
- Schelenz, T., Á. Suescun, L. Wikström, and M. Karlsson. 2014. “Application of agent based simulation for evaluating a bus layout design from passengers perspective”. *Transportation Research Part C: Emerging Technologies* 43:222–229.
- Shendarkar, A., K. Vasudevan, S. Lee, and Y.-J. Son. 2006. “Crowd simulation for emergency response using BDI agent based on virtual reality”. In *Proceedings of the Winter Simulation Conference*, 545–553.
- Voloshin, D., D. Rybokonenko, and V. Karbovskii. 2015. “Optimization-based Calibration for Micro-level Agent-based Simulation of Pedestrian Behavior in Public Spaces”. *Procedia Computer Science* 66:372–381.
- Zhou, S., D. Chen, W. Cai, L. Luo, M. Y. H. Low, F. Tian, V. S.-H. Tay, D. W. S. Ong, and B. D. Hamilton. 2010. “Crowd modeling and simulation technologies”. *ACM Transactions on Modeling and Computer Simulation (TOMACS)* 20(4):20.