Self evolving Takagi-Sugeno-Kang fuzzy neural network.

Nguyen Ngoc Nam

2012

Nguyen, N. N. (2012). Self evolving Takagi-Sugeno-Kang fuzzy neural network. Doctoral thesis, Nanyang Technological University, Singapore.

<https://hdl.handle.net/10356/50807>

<https://doi.org/10.32657/10356/50807>

SELF-EVOLVING TAKAGI-SUGENO-KANG FUZZY NEURAL NETWORK

Nguyen Ngoc Nam

Department of Computer Engineering

Nanyang Technological University

A thesis submitted to the Nanyang Technological University in
fulfillment of the requirement for the degree of

Doctor of Philosophy

2012

Self-Evolving Takagi-Sugeno-Kang Fuzzy Neural Network

by

Nguyen Ngoc Nam

**A thesis submitted to the Nanyang Technological University in fulfillment of the
requirement for the degree of Doctor of Philosophy**

January 2012

Summary

Fuzzy neural networks is a popular combination in soft computing that unites the human-like reasoning style of fuzzy systems with the connectionist structure and learning ability of neural networks. There are two types of fuzzy neural networks, namely the Mamdani model, which is focused on interpretability, and the Takagi-Sugeno-Kang (TSK) model, which is focused on accuracy. The main advantage of the TSK-model over the Mamdani-model is its ability to achieve superior system modeling accuracy. TSK fuzzy neural networks are widely preferred over their Mamdani counterparts in dynamic and complex real-life problems that require high precision.

This Thesis is mainly focused on addressing the existing problems of TSK fuzzy neural networks. Existing TSK models proposed in the literature can be broadly classified into three classes. Class I TSK models are essentially fuzzy systems that are unable to learn in an incremental manner. Class II TSK networks, on the other hand, are able to learn in incremental manner, but are generally constrained to time-invariant environments. In practice, many real-life problems are time-variant, in which the characteristics of the underlying data-generating processes might change over time. Class III TSK networks are referred to as evolving fuzzy systems. They adopt incremental learning approaches and attempt to solve time-variant problems. However, many

evolving systems still encounter three critical issues; namely: 1) Their fuzzy rule base can only grow, 2) They do not consider the interpretability of the knowledge bases and 3) They cannot give accurate solutions when solving complex time-variant data sets that exhibit drift and shift behaviors.

In this Thesis, a generic self-evolving Takagi–Sugeno–Kang fuzzy framework (GSETSK) is proposed to overcome the above-listed deficiencies of existing TSK networks with the following contributions:

A novel fuzzy clustering algorithm known as Multidimensional-Scaling Growing Clustering (MSGC) is proposed to empower GSETSK with the incremental learning ability. MSGC also employs a novel merging approach to ensure a compact and interpretable knowledge base in the GSETSK framework. MSGC is inspired by human cognitive process models and it can work in fast-changing time-variant environments.

To keep an up-to-date fuzzy rule base when dealing with time-variant problems, a novel ‘gradual’-forgetting-based rule pruning approach is proposed to unlearn outdated data by deleting obsolete rules. It adopts the Hebbian learning mechanism behind the long-term potentiation phenomenon in the brain. It can detect the drift and shift behaviors in time-variant problems and give accurate solutions for such problems.

A recurrent version of GSETSK, the RSETSK (Recurrent Self-Evolving TSK Fuzzy Neural Network) is also presented. This extension aims to improve the ability of GSETSK in dealing with dynamic and temporal problems by implementing a recurrent rule layer in its architecture.

The proposed fuzzy neural networks have been successfully applied in three real life applications; namely: 1) Stock Market Trading System, 2) Option Trading and Hedging and 3) Traffic Prediction. The encouraging results suggest that the proposed networks can be used in more challenging real-life applications in the areas of medical or financial data analysis, signal processing and biometrics.

Acknowledgements

I would like to acknowledge the guidance, the support and the motivation from my supervisor, Assoc. Prof. Quek Hiok Chai. His profound knowledge in Computational Intelligence has inspired and has shaped my directions into this promising field of research.

I would like to thank the Center for Computational Intelligence (C2I) and the lab technicians, Tan Swee Huat and Lau Boon Chee, for providing the support and the necessary facilities. I would also like to thank my friends and colleagues in C2I for the fruitful research and academic discussions; namely, Tan Wi-Meng Javan, Cheu Eng Yow, Ting Chan Wai, Tung Whye Loon, Tung Sau Wai and Richard Jayadi Oentaryo.

I would also like to express my gratitude to my parents for their continued support in my education.

Finally, I would like to express my appreciation to the School of Computer Engineering, Nanyang Technological University for funding my scholarship.

Table of Contents

Abstract.....	I
Acknowledgements.....	III
Table of Contents	IV
List of Figures	VIII
List of Tables.....	XI
Chapter 1 Introduction	1
1.1 Background	1
1.2 Takagi-Sugeno-Kang Fuzzy Neural Networks	2
1.3 Problem Statement	3
1.4 Contribution	6
1.5 Organization of the Thesis	7
Chapter 2 Literature Review.....	8
2.1 Introduction	8
2.2 Neural Networks	8
2.2.1 Characteristics of Neural Networks	8
2.2.2 Basic Concepts of Neural Networks	9
2.2.3.1 Processing Elements	9
2.2.3.2 Connections.....	10
2.2.3.3 Learning Rules	11
2.2.3 Advantages and Issues of Neural Networks	12
2.3 Fuzzy Systems.....	13
2.3.1 Advantages and Issues of Fuzzy Systems.....	14
2.3.2 Interpretability – Accuracy Trade Off	15
2.4 Fuzzy Neural Networks.....	17
2.4.1 Generating Membership Functions.....	17
2.4.1.1 Clustering: Fuzzy C-Means (FCM) Algorithm.....	22
2.4.1.2 Clustering: Learning Vector Quantization(LVQ) Algorithm	24

2.4.1.3 Comparison of Popular Clustering Techniques	25
2.4.2 Identifying Fuzzy Rules.....	26
2.4.3 Specifying Reasoning Methods	28
2.4.4 Parameter Learning.....	28
2.5 Self-Evolving TSK Fuzzy Neural Networks.....	29
2.5.1 Introduction	29
2.5.2 Self-Evolving Learning Approach	30
2.6 Unlearning Motivations for Evolving TSK Fuzzy Neural Networks.....	32
2.6.1 Concept Drifting	33
2.6.2 Concept Shifting	35
2.7 Summary	36
2.7.1 Online Incremental Learning in Time-Variant Environments.....	36
2.7.2 Unlearning Strategy to Address Time-Variant Problems	37
2.7.3 Compact and Interpretable Knowledge Base.....	39
2.7.4 Research Challenges	40
Chapter 3 Generic Self Evolving TSK Fuzzy Neural Network (GSETSK)	41
3.1 Introduction.....	41
3.2 Architecture & Neural Computations.....	43
3.2.1 Forward Reasoning	45
3.2.2 Backward Computations of GSETSK	48
3.2.2.1 Computing Output Error of Each Fuzzy Rule	48
3.2.2.2 Determining Backward Firing Strength of Each Fuzzy Rule.....	49
3.2.3 Fuzzy Rule Potentials	51
3.3 Structure Learning of GSETSK	53
3.3.1 Multidimensional-Scaling Growing Clustering.....	53
3.3.1.1 Merging of Fuzzy Membership Functions.....	56
3.3.1.2 Comparison Among Existing Clustering Techniques	60
3.3.2 Rule Pruning Algorithm	61
3.4 Parameter Learning of GSETSK.....	65
3.5 Simulation Results & Analysis	67
3.5.1 Online Identification of a Nonlinear Dynamic System With Nonvarying Characteristics	67

	3.5.2 Analysis Using a Nonlinear Dynamic System With Time-Varying Characteristics.....	71
	3.5.3 Benchmark on Mackey-Glass Time Series.....	74
	3.6 Summary	77
Chapter 4	Recurrent Self Evolving TSK Fuzzy Neural Network (RSETSK)	79
	4.1 Introduction	79
	4.2 Architecture & Neural Computations.....	81
	4.2.1 Recurrent Properties in RSETSK	82
	4.2.2 Fuzzy Rule Potentials in RSETSK	83
	4.3 Learning Algorithms of RSETSK.....	84
	4.4 Simulation Results & Analysis	87
	4.4.1 Online Identification of a Nonlinear Dynamic System.....	87
	4.4.2 Analysis Using a Nonlinear Dynamic System With Regime-shifting Properties	91
	4.4.3 Analysis Using Dow Jones Index Time Series	94
	4.5 Summary	98
Chapter 5	Stock Market Trading System – A Financial Case Study	99
	5.1 Introduction	99
	5.2 Stock Trading System Using RSETSK.....	101
	5.3 Experiments On Real-world Financial Data	106
	5.3.1 Experimental Setup.....	106
	5.3.2 Experimental Results and Analysis	108
	5.3.2.1 Analysis using IBM Stock	108
	5.3.2.2 Analysis Using Singapore Exchange Limited Stock	113
	5.4 Summary	117
Chapter 6	Option Trading & Hedging System – A Real World Application	119
	6.1 Introduction	119
	6.2 Option Trading System Using GSETSK.....	121
	6.3 Experiments On Real-world Financial Data	123
	6.3.1 Experimental Setup.....	123
	6.3.2 Experimental Results and Analysis	125
	6.3.2.1 Analysis using GBPUSD Currency Futures	125
	6.3.2.2 Analysis using Gold Futures and Options.....	129

	6.4 Summary	131
Chapter 7	Traffic Prediction – A Real-life Case Study.....	133
	7.1 Introduction	133
	7.2 Experiments on Real-world Traffic Data	134
	7.2.1 Experimental Setup.....	134
	7.2.2 Experimental Results and Analysis	136
	7.3 Summary	145
Chapter 8	Conclusions & Future Work	146
	8.1 Conclusion.....	146
	8.1.1 Theoretical Contributions	147
	8.1.2 Practical Contributions	148
	8.1.2.1 Self-Evolving Takagi–Sugeno–Kang Fuzzy Framework	148
	8.1.2.2 Recurrent Self-Evolving Takagi-Sugeno-Kang Fuzzy	
	Neural Network	149
	8.2 Limitations	151
	8.3 Future Research Directions	153
	8.3.1 Extensions to the Proposed Networks	153
	8.3.1.1 Online Feature Selection.....	153
	8.3.1.2 Consequent Terms Selection	154
	8.3.1.3 Type-2 Implementation	156
	8.3.2 Application Domains for the Proposed Networks	157
	Bibliography	159
	Author’s Publications	167

List of Figures

Figure 1-1: Motivations & Research objectives.....	5
Figure 2-1: A typical single-layered feed-forward network.....	10
Figure 2-2: A typical multi-layered feed-forward network.....	11
Figure 2-3: A typical single-layered recurrent network	11
Figure 2-4: A typical fuzzy system	14
Figure 2-5: Trapezoidal membership function and Gaussian membership function.....	18
Figure 2-6: Fuzzy membership functions representing linguistic terms “slow”, “moderate”, “fast”	21
Figure 2-7: An evolving cluster drifts to a new region	34
Figure 2-8: Concept drift in time-space domain.....	34
Figure 2-9: Apple stock prices in period 2001-2011	35
Figure 2-10: Concept shift in time-space domain	35
Figure 2-11: Two types of knowledge base: (a) Deteriorated with highly overlapping and indistinguishable fuzzy sets; (b) Interpretable with highly distinguishable fuzzy sets.....	40
Figure 3-1: Structure of the GSETSK network	44
Figure 3-2: The Gaussian membership function $\mu(0, \sigma_{back}(t))$	50
Figure 3-3: Three possible actions in the <i>CheckKnowledgeBase</i> procedure.....	58
Figure 3-4: The willingness parameter WP decreases after each expansion.....	59
Figure 3-5: A typical example of how the potential of a fuzzy rule can change over time.....	62
Figure 3-6: The flowchart of GSETSK learning process	64
Figure 3-7: GSETSK’s modeling performance and the fuzzy sets derived by GSETSK, SAFIS and SONFIN, respectively, for comparison.....	70
Figure 3-8: GSETSK’s modeling performance during time $t \in [900, 2100]$	73
Figure 3-9: The evolution of GSETSK’s fuzzy rule base and online learning error of GSETSK during the simulation	73
Figure 3-10: The evolution of the fuzzy rules for SAFIS, eTS, Simpl_eTS and GSETSK	76
Figure 3-11: Semantic interpretation of the fuzzy sets in GSETSK for the Mackey-Glass data set	77
Figure 4-1: Structure of the RSETSK network	81

Figure 4-2: Nonlinear Dynamic System (a) Outputs of the plant and the performance of RSETSK (b) Fuzzy sets derived by RSETSK	89
Figure 4-3: RSETSK's modeling performance during time $t \in [1, 3000]$	93
Figure 4-4: RSETSK's self-evolving process (a) The evolution of RSETSK's fuzzy rule base (b) Online learning error of RSETSK	94
Figure 4-5: Dow Jones time series forecasting results	96
Figure 4-6: The evolution of the fuzzy rules in RSETSK	97
Figure 4-7: Highly interpretable knowledge base derived by RSETSK	97
Figure 5-1: Trading system without a predictive model	104
Figure 5-2: Trading system with RSETSK predictive model	104
Figure 5-3: Price and trading signals on IBM	110
Figure 5-4: Portfolio values on IBM achieved by the trading systems with different predictive models.	111
Figure 5-5: Enlarged part of Figure 5-3 from time $t=900$ to $t=1000$	112
Figure 5-6: Semantic interpretation of the fuzzy sets derived in RSETSK	113
Figure 5-7: Price and trading signals on SGX	115
Figure 5-8: Portfolio values on SGX achieved by the trading systems	115
Figure 5-9: SGX time series forecasting results	116
Figure 5-10: The evolution of the fuzzy rules in RSETSK	117
Figure 6-1: Trading system with GSETSK predictive model	122
Figure 6-2: Price prediction on GBPUSD futures using GSETSK	126
Figure 6-3: Price prediction on GBPUSD futures using RSPOP	126
Figure 6-4: Semantic interpretation of the fuzzy sets derived in GSETSK	128
Figure 6-5: Price prediction for the gold data set using GSETSK	130
Figure 6-6: Trend prediction accuracy for the gold data set	131
Figure 7-1: Location of site 29 along PIE (Singapore) and (b) actual site at exit 15	135
Figure 7-2: Traffic densities of three lanes along Pan Island Expressway	135
Figure 7-3: Traffic modeling and prediction results of GSETSK for lane L1 at time $t+5$ across three-cross validation groups	138
Figure 7-4: Traffic modeling and prediction results of RSETSK for lane L1 at time $t+5$ across three-cross validation groups	139
Figure 7-5: Traffic flow forecast results for GSETSK, RSETSK and the various benchmarked NFSs	141

Figure 7-6: The fuzzy sets derived by GSETSK during the training set of CV1 for lane L1 traffic prediction at time $t+5$	144
Figure 8-1: Type-2 fuzzy set with uncertainty mean.....	156

List of Tables

Table 2-1: Comparison among existing clustering techniques.....	25
Table 2-2: Taxonomy of TSK fuzzy neural networks proposed in the literature.....	31
Table 2-3: Comparison among self-evolving TSK fuzzy neural networks.....	39
Table 3-1: Comparison among existing clustering techniques.....	60
Table 3-2: Comparison of GSETSK with other evolving models.....	68
Table 3-3: Comparison of GSETSK with other benchmarked models.....	74
Table 4-1: Comparison of RSETSK against other recurrent models.....	90
Table 4-2: Forecasting 50 years of Dow Jones Index.....	95
Table 5-1: Comparison of different prediction systems on IBM stock.....	109
Table 5-2: Comparison of different trading systems on IBM stock.....	112
Table 5-3: Comparison of different trading systems on SGX stock.....	115
Table 5-4: Fuzzy rules extracted from RSETSK.....	118
Table 6-1: Comparison of different predictive models on GBPUSD futures dataset.....	127
Table 6-2: Profits generated on different option strike prices using the proposed option trading system.....	129
Table 6-3: Comparison of different trading systems on gold futures.....	130
Table 7-1: Benchmarking of results of the highway traffic flow prediction experiment.....	143
Table 7-2: Semantic interpretation of fuzzy rules in GSETSK.....	144

Chapter 1: Introduction

An investment in knowledge pays the best interest.

Benjamin Franklin (1706-1790)

1.1 Background

The concept of *soft computing*, which was introduced by Zadeh [1], serves to highlight the emergence of computing methodologies in which the focus is on exploiting the tolerance for imprecision and uncertainty to achieve tractability, robustness and low solution cost. In effect, the role model for soft computing is the *human mind*. Many studies on the *human cognitive process* have been done to explore the way human being reasons and works out solution to a complex problem. The results of these studies led to a new breed of intelligent systems and machines with human-like performances. The principal components of Soft Computing are **Fuzzy Logic**, **Neural Network**, **Evolutionary Computation**, **Machine Learning** and **Probabilistic Reasoning**. In fact, many real life problems can be solved most effectively by using these components of Soft Computing in combination rather than using each component exclusively. A prominent example of a particularly effective combination of these components is known as '*neuro fuzzy computing*'.

NEURO *fuzzy computing* is a popular framework for solving problems in soft computing due to its capability to combine the human-like reasoning style of *fuzzy systems* with the connectionist structure and learning ability of *neural networks* [2]. Neuro-fuzzy hybridization is also widely known as *fuzzy neural networks* (FNN) or *neuro-fuzzy systems* (NFS). The main strength of the neuro-fuzzy approach is that it can provide insights to the user about the symbolic knowledge embedded within the network [3]. Neuro fuzzy computing is widely applied in commercial and

industrial applications. It also attracts the growing interest of researchers, scientists, engineers and students in various scientific and engineering areas.

1.2 Takagi-Sugeno-Kang Fuzzy Neural Networks

Fuzzy neural networks combine the advantages of fuzzy logic and neural network for modeling data. Neural networks are low-level computational structures and algorithms that offer good performance when dealing with data, while fuzzy logic techniques offer the ability of dealing with issues such as reasoning on a higher level. However, fuzzy systems do not have much learning ability, while neural networks work like *black boxes* which do not allow users to extract knowledge from the systems or incorporate symbolic knowledge into the systems. The hybrid fuzzy neural networks address the demerits of both fuzzy systems and neural networks. More specially, fuzzy neural networks can generalize from data, generate fuzzy rules to create a linguistic model of the problem domain and learn/tune the system parameters. This is in contrast against traditional fuzzy systems in which the knowledge base must be inserted by experts and the system parameters must be tuned manually to achieve the desired results.

Fuzzy neural networks can be broadly classified into two types. The first type is the linguistic fuzzy neural networks that are focused on interpretability, mainly using the Mamdani model [4]. The second type, on the other hand, is the precise fuzzy neural networks that are focused on accuracy, mainly using the **Takagi-Sugeno-Kang** (TSK) model [5]. The main advantage of the TSK-model over the Mamdani-model is its ability to achieve *higher level of system modeling accuracy* while using a lesser number of rules. This Thesis is mainly focused on addressing the existing problems of TSK fuzzy neural networks.

1.3 Problem Statement

Existing TSK models proposed in the literature can be broadly classified into three classes. Class I TSK models are essentially fuzzy systems that are *unable to learn in an incremental manner*. To be considered as an incremental sequential learning approach, a learning system must satisfy the following criteria [6].

- 1) All the training observations are sequentially presented to the learning system.
- 2) At any time, only one training observation is seen and learnt.
- 3) A training observation is discarded as soon as the learning procedure for that particular observation is completed.
- 4) The learning system has no prior knowledge as to how many total training observations will be presented.

Popular systems such as ANFIS [7], SOFNN [8], and DFNN [9] belong to class I. There is a continuing trend of using TSK neural networks for solving function approximation and regression-centric problems. In practice, these problems are *online*, meaning that the data is not all available prior to training but is sequentially presented to the learning system. Thus, incremental learning is preferred over offline learning in TSK networks.

Class II TSK networks, on the other hand, are able to learn in an incremental manner, but are generally limited to time-invariant environments. In real life, *time-variant* problems, which most often occurred in many areas of engineering, usually possess non-stationary, temporal data streams which are modified continuously by the ever-changing underlying data-generating processes. Dynamic approaches such as FITSK [10] and DENFIS [11] are candidates for class II. Online incremental learning in these approaches is only appropriate for time-invariant problems

in which the underlying data-generating processes do not change with time. These systems cannot handle more complex time-variant data sets. DENFIS implicitly assumes prior knowledge of the upper and lower bounds of the data set to normalize data before learning [12]. The approaches in FITSK [10] and [13] require the number of clusters or rules to be specified prior to training, which is an impossible task in time-variant problems.

Lastly, Class III TSK networks are fuzzy systems that adopt incremental learning approaches and attempt to solve time-variant problems. However, many Class III systems still encounter three critical issues; namely: 1) Their fuzzy rule base can only grow, 2) They do not consider the interpretability of the knowledge bases and 3) They cannot give accurate solutions when solving complex time-variant data sets that exhibit drift and shift behaviors (or regime shifting properties). Most of the systems [14], [15], [16], [17]-[18] do not possess an unlearning algorithm, which may lead to the collection of obsolete knowledge over time and thus degrade the level of human interpretability of the resultant knowledge base. Unlearning, which stemmed from neurobiology, was introduced by Hopfield *et al* in 1983 [19] to implement an idea of Crick and Mitchinson [20] about the function of dream sleep. In [21], it was demonstrated that unlearning greatly improves network performance by means such as enhancing network storage capacity. In addition, unlearning is an efficient way to address the concept drifts and shifts which are the ‘concept changes’ of the underlying distribution of online data streams as it separates past data from new data by decaying the effects of past data on the final outputs. To deal with fast-changing time-variant problems, an efficient unlearning algorithm is needed. Besides, most of the existing TSK systems do not consider the semantic meaning of their derived knowledge bases. Systems such as SONFIN [15], RSONFIN [22], TRFN [23] use gradient descent algorithms to heuristically tune their membership functions, thus results in indistinguishable fuzzy sets. It is difficult to derive any human interpretable knowledge from the structure of such systems. Figure 1-1 summarizes the motivations and research objectives of this Thesis.

Figure 1-1: Motivations & Research Objectives

1.4 Contribution

This thesis focuses on the development of a generic Takagi-Sugeno-Kang framework that can overcome the deficiencies of existing TSK networks mentioned above. It has the following characteristics:

- 1) Able to learn in an incremental manner with high accuracy.
- 2) Able to work in fast-changing time-variant environments.
- 3) Able to derive a compact and interpretable rule base with highly distinguishable fuzzy sets.
- 4) Able to unlearn obsolete data to keep a current rule base and address the drift and shift behaviors of time-variant problems.

The framework is termed the generic *self-evolving Takagi–Sugeno–Kang fuzzy framework* (GSETSK). A novel fuzzy clustering algorithm known as Multidimensional-Scaling Growing Clustering (MSGC) is proposed to empower GSETSK with an incremental learning ability. MSGC also employs a novel merging approach to ensure a compact and interpretable knowledge base in the GSETSK framework. MSGC is inspired by human cognitive process models and it can work in fast-changing time-variant environments. To keep an up-to-date fuzzy rule base when dealing with time-variant problems, a novel ‘gradual’-forgetting-based rule pruning approach is proposed to unlearn outdated data by deleting obsolete rules. It adopts the Hebbian learning mechanism behind the long-term potentiation phenomenon in the brain. It can detect the drift and shift behaviors in time-variant problems and give accurate solutions for such problems. A recurrent version of GSETSK, the RSETSK (Recurrent Self-Evolving TSK Fuzzy Neural Network) is also presented. This extension aims to improve the ability of GSETSK in dealing with dynamic and temporal problems. The proposed fuzzy neural networks have been

successfully applied to three real life applications, namely: 1) Stock Market Trading System, 2) Option Trading and Hedging and 3) Traffic Prediction.

1.5 Organization of the thesis

This thesis is organized as follows:

- Chapter 2 presents a literature review about the fields that are related to this research work. A brief introduction on related systems and existing techniques is given.
- Chapter 3 presents the architecture and the learning algorithm of the proposed Generic Self-Evolving Takagi-Sugeno-Kang Fuzzy Neural Network (GSETSK). The performance of the network is evaluated through applications on three benchmarking case-studies: 1) Nonlinear dynamic system with nonvarying characteristics; 2) Nonlinear dynamic system with time-varying characteristics; and 3) Mackey-Glass time series.
- Chapter 4 presents an extension of GSETSK, the RSETSK (Recurrent Self-Evolving TSK Fuzzy Neural Network). This extension aims to improve the ability of GSETSK in dealing with dynamic and temporal problems by implementing a recurrent rule layer in its architecture.
- Chapter 5 to Chapter 7 present successful applications of the proposed networks on three real-world problems; namely: 1) Stock Market Trading System, 2) Option Trading and Hedging and 3) Traffic Prediction.
- Chapter 8 concludes this research and suggests directions for future work.

Chapter 2: Literature Review

Most of the fundamental ideas of science are essentially simple, and may, as a rule, be expressed in a language comprehensible to everyone.

Albert Einstein (1879-1955)

2.1 Introduction

This section presents a brief literature review of the components in *soft computing* that are relevant to this research, specifically, *neural networks*, *fuzzy systems* and the *hybrid fuzzy neural networks*. The advantages and drawbacks of modeling data using neural networks and fuzzy systems are discussed, then how existing fuzzy neural networks overcome the drawbacks are mentioned. Lastly, the deficiencies of existing *Takagi-Sugeno-Kang* fuzzy neural networks are briefly reviewed.

2.2 Neural Networks

An **artificial neural network**, usually called "neural network", is a mathematical model or computational model that tries to simulate the structure and/or functional aspects of biological neural networks of the human brain. Neural networks are a promising new generation of information processing systems. They possess the ability to learn, recall and generalize from training patterns or data. Artificial neural networks are good at various tasks such as pattern identification, function approximation, optimization, and data clustering.

2.2.1 Characteristics of Neural Networks

In summary, an artificial neural network is a parallel information processing structure with the following characteristics [4]:

- It is a neural inspired mathematical model.

- It consists of a large number of highly interconnected processing elements called neurons or nodes.
- Its connections (weights) hold the knowledge of the system.
- A processing element can dynamically respond to its input stimulus, and the response completely depends on its local information; that is, the state of the node. The input signals arrive at the node via neuron connections and connection weights.
- It has the ability to learn, recall, and generalize from training data by assigning or adjusting the connection weights. If input signals are new to the network, neural network can sensibly detect that and automatically adjust its connection weights and even the network structure to optimize its performance.
- Its collective behavior demonstrates the computational power, and no single neuron carries specific information (distributed representation property). Therefore, the performance of a neural network is severely affected under faulty conditions such as damaged neurons or broken connections.

2.2.2 Basic Concepts of Neural Networks

2.2.2.1 Processing Elements

Neural networks consist of a large number of processing elements called *neurons* or *nodes*. The information processing of a neuron consists of two parts: input and output. Associated with the input of a neuron is an aggregation function f which serves to combine information from external sources or other neurons into a net input to the neuron. The links between neurons are associated with weights. Each neuron has an internal state called its activation or activity level that is a function of the inputs it has received.

2.2.2.2 Connections

A neural network consists of a set of highly interconnected neurons such that each neuron output is connected through weights to other neurons or back to itself. The structure that organizes the neurons and the connection geometry among them define the functionality of a neural network. It is important to point out where the connection originates and terminates besides specifying the function of each neuron.

A common artificial neural network consists of three layers of neurons: a layer of **input** neurons is connected to a layer of **hidden** neurons, which is connected to a layer of **output** neurons.

Neural networks are often classified as *single layer* or *multi-layer*. In single-layer networks, all neurons are connected to one another. They are of more potential computational power than hierarchically structured multi-layer networks. Multi-layer networks can be *feed-forward* networks in which signal flows from the input to output or *recurrent* networks in which there are closed-loop signal paths. The feedback of signals can be from a neuron back to itself, to its neighboring neurons in the same layer or to neurons in the preceding layers.

Figure 2-1 shows a single-layered *feed-forward* network.

Figure 2-1: A typical single-layered feed-forward network.

Figure 2-2 shows a multi-layered *feed-forward* network.

Figure 2-2: A typical multi-layered feed-forward network.

Figure 2-3 shows a single-layered recurrent network.

Figure 2-3: A typical single-layered recurrent network

2.2.2.3 Learning Rules

The third important element of neural networks is the learning rules. There are two kinds of learning in neural networks: *structure* learning which focuses on the modification of the connections between the neurons and *parameter* learning which concerns the update of the weights connecting the neurons. Parameter and structural learning may be performed separately

or simultaneously. In parameter learning, there are three types of training available - *supervised*, *reinforcement* and *unsupervised* training.

2.2.3 Advantages and Issues of Neural Networks

Neural networks are used to solve real life problems by modeling the data. The first advantage of modeling data using neural networks is that they are able to learn from numerical data without explicit requirement of the functional or distributional form of the underlying model [24]. Second, they are universal function approximators that can approximate any function with good accuracy [25]. They are also nonlinear models that can flexibly model complex real world data. Neural networks also have good fault-tolerance characteristics because of their distributed knowledge representational attribute. Last but not least, they are able to model given problem domains and derive reasonable outputs in response to the inputs. However, neural networks also have many issues listed as follow:

1. *Neural networks are black box models* [26]. More specifically, there is no way to extract the embedded knowledge from the weight matrix of a trained neural network in relation to the dynamics of the problem domain that it has modeled. There is also no way to explain how a particular decision is arrived at in a human interpretable way.
2. *Neural networks cannot make use of a priori knowledge*. Since neural networks are black box models, one cannot incorporate a priori knowledge. Thus, neural networks have to acquire knowledge from scratch.
3. *Neural network cannot solve the stability and plasticity dilemma*. Once trained, a neural network cannot incorporate new data or information.
4. *It is hard to derive the optimization of network structure of neural networks* since there is no guideline in constructing neural networks. Their users have to deal with a large

number of variables [26] such as choice of neural network model, choice of number of neurons and number of hidden layers.

2.3 Fuzzy Systems

Fuzzy systems are based on the concepts of fuzzy set theory, if-then fuzzy rules and fuzzy reasoning. Due to their multidisciplinary nature, fuzzy systems are also known by other names such *fuzzy inference systems* [27], *fuzzy expert systems* [28], *fuzzy rule-based system* [29], *fuzzy models* [5], *fuzzy logic controllers* [30].

The concept of fuzzy sets was introduced by Professor Zadeh A. Lotfi in 1965. The theory of fuzzy sets or fuzzy logic provides a mathematical framework to represent vagueness in linguistic, to capture the uncertainties associated with the *human cognitive processes*, such as thinking and reasoning. The fuzzy systems, which are empowered by the fuzzy logic concepts, are used as control or expert systems. Figure 2-4 shows a typical fuzzy system, with the following main components:

- *Input fuzzifier* - transforms crisp measured data (e.g., Tom is 1.8m in height) into suitable linguistic values (i.e., fuzzy sets, for example “average”, or “tall”).
- *Fuzzy rule base* – stores the linguistic fuzzy rules in the form of “if-then” associated with the system. It controls the actions in response to the input fuzzified by the input fuzzifier. Fuzzy rules, together with fuzzy sets, form the *fuzzy knowledge base*.
- *Inference engine* – performs the inference procedure to derive appropriate outputs from the given inputs using the fuzzy rules and an inference/reasoning scheme.
- *Output defuzzifier* – transforms the fuzzified outputs derived by the inference engine to crisp values.

Figure 2-4: A typical fuzzy system

2.3.1 Advantages and Issues of Fuzzy Systems

Fuzzy systems utilize high-level **IF-THEN** fuzzy rules to model the problem domain in solving problems. Because the fuzzy rules are intuitive to the understanding of the human user, knowledge can be easily extracted from the systems. *A priori* knowledge from human experts can be incorporated into the model that comprises of linguistic expressions formulated in the form of if-then fuzzy rules [31]. Fuzzy systems offer the ability of dealing with issues such as reasoning on a higher level using the human-like reasoning style.

However, fuzzy systems also have severe drawbacks. They are unable to formulate the fuzzy knowledge base including the *membership functions* and the if-then fuzzy rules from available numerical data [4]. The fuzzy rules are inserted into the systems by experts so they may be inaccurate and biased as opinions may differ with different experts. The experts also have to deal with the optimization of the membership functions and the if-then fuzzy rules in the knowledge base from numerical data [4]. This may be impossible for a complex system with many variables.

The above drawbacks of fuzzy systems can be addressed by integrating with neural networks to create the hybrid fuzzy neural networks which will be discussed later.

2.3.2 Interpretability – Accuracy Trade Off

Fuzzy logic was motivated by two objectives. First, it aims to ease difficulties in developing and analyzing complex systems with high accuracy. Second, it is motivated by observing that human reasoning can make use of concepts and knowledge that are vague, imprecise and incomplete. Therefore, modeling problem domains using fuzzy systems is also mainly characterized by two characteristics: *interpretability* and *accuracy*. Interpretability concerns the capability of the fuzzy model to express the behavior of the modeled system in a human understandable way. Accuracy concerns the capability of the fuzzy model in representing the modeled system that can approximate the desired outputs in response to the input data. Interpretability of a fuzzy system depends on several factors such as the model structure, the number of input variables, the number of if-then fuzzy rules and the number of linguistic terms. Accuracy of a fuzzy system depends on how close the approximation of the fuzzy model is to the response of the real system that is being modeled.

In reality, there is a trade-off between interpretability and accuracy. In other words, in fuzzy systems, to achieve high degree of interpretability and accuracy is a contradictory task. Normally only one of the two properties dominates (the other). Professor Lotfi Zadeh (1973) also stated in the *Principle of Incompatibility* that “*as the complexity of a system increases, our ability to make precise and yet significant statements about its behavior diminishes until a threshold is reached beyond which precision and significance (or relevance) become almost mutually exclusive*” [32].

Therefore, the fuzzy models are categorized into two types: *linguistic fuzzy models* which focus on interpretability, mainly using the Mamdani model [33] given in (2.1); and *precise fuzzy models* that focus on accuracy, mainly using the Takagi-Sugeno-Kang (TSK) [34] model given in (2.2).

$$R_i : \text{IF } x_1 \text{ is } A_{i,1} \text{ AND } \dots \text{ AND } x_{n1} \text{ is } A_{i,n1} \text{ THEN } y \text{ is } B_i \quad (2.1)$$

$$R_i : \text{IF } x_1 \text{ is } A_{i,1} \text{ AND } \dots \text{ AND } x_{n1} \text{ is } A_{i,n1} \text{ THEN } y = b_0 + b_1x_1 + \dots + b_{n1}x_{n1} \quad (2.2)$$

where $x = [x_1, \dots, x_{n1}]$ and y are the input vector and the output value, respectively. $A_{i,k}$ represents the membership function of the input label x_k for the i^{th} fuzzy rule; B_i represents the membership function of the output label y for the i^{th} fuzzy rule in (2.1), $[b_0, \dots, b_{n1}]$ represents a set of consequent parameters of the i^{th} fuzzy rule in (2.2), $n1$ is the number of inputs.

The main motivation for the TSK model is to reduce the number of rules required by the Mamdani model, especially for complex and high-dimensional problems. To achieve this goal, the TSK model replaces the fuzzy sets in the consequent of the Mamdani rule with a linear equation of the input variables. Therefore, the TSK model has decreased interpretability but increased representative power compared to the Mamdani model. For a more comprehensive coverage on interpretability versus accuracy, please refer to [35]. As this Thesis is focused on addressing dynamic and complicated real-life problems that require high precision, the TSK model is chosen over the Mamdani model. Some examples of such real-life problems are stock price and commodity price prediction problems, as briefly discussed later in Chapter 5 and 6. TSK models have also been widely applied in many other areas of engineering, finance and biometrics.

2.4 Fuzzy Neural Networks

Neural network and fuzzy system both are popular approaches and are widely used in different fields and applications. However, both have their own advantages and drawbacks. The integration of neural network and fuzzy system creates a hybrid model that can address the issues of both approaches. The hybrid model *fuzzy neural network* can learn new knowledge or use *a prior* knowledge to shorten its training cycle. Meanwhile it exhibits the understandable human-like style of reasoning through its linguistic model that comprises of if-then fuzzy rules and linguistic terms described by the membership functions. The terms *fuzzy neural network* and *neuro-fuzzy system* can be used interchangeably. The following lists the characteristics of the network structure of a fuzzy neural network.

- *It represents a set of IF-THEN fuzzy rules* with each fuzzy rule may use more than one linguistic variable in its antecedent and consequent section;
- Each input/output linguistic variable is described by an input/output linguistic term; and
- Each input/output term is represented by exactly one fuzzy set only.

There are three important aspects that should be considered in constructing a fuzzy neural network [36], including: *generating membership functions* for input/output linguistic terms, *identifying the if-then fuzzy rules* for the rule base, and *specifying the reasoning method* for the reasoning mechanism. These important aspects will be discussed briefly in the following sections.

2.4.1 Generating Membership Functions

Generating membership functions is an important aspect in designing a fuzzy neural network. Determining appropriate membership functions can help to *enhance the accuracy performance* of the system and to *reduce the number of redundant rules*. The most commonly used membership

functions are triangular, trapezoidal, Gaussian and bell-shaped. Equation (2.3) and (2.4) mathematically describe the trapezoidal and Gaussian membership functions. Triangular and bell-shaped membership functions can be described by equation (2.3) using parameters such that $\beta = \gamma$ and by equation (2.4) using parameters such that $\alpha = \gamma$ and $\beta = \delta$, respectively.

$$\mu_T(x; \alpha, \beta, \gamma, \delta) = \begin{cases} 0 & x \leq \alpha \text{ or } x \geq \delta \\ \frac{x - \alpha}{\beta - \alpha} & \alpha < x < \beta \\ 1 & \beta \leq x \leq \gamma \\ \frac{\delta - x}{\delta - \gamma} & \gamma < x < \delta \end{cases} \quad (2.3)$$

$$\mu_G(x; \alpha, \beta, \gamma, \delta) = \begin{cases} e^{-\frac{(x-\beta)^2}{2\alpha^2}} & x < \beta \\ 1 & \beta \leq x \leq \delta \\ e^{-\frac{(x-\delta)^2}{2\gamma^2}} & x > \delta \end{cases} \quad (2.4)$$

Figure 2-5: (a) Trapezoidal membership function $\mu_T(x; 3,4,6,8)$ (b) Gaussian membership function $\mu_G(x; 0.5,4,1,6)$

There are several approaches to the generation of fuzzy membership functions:

- *Heuristics* – uses predefined shapes for membership functions and has been used successfully in rule-based pattern recognition applications. Unfortunately, the shapes of the heuristic membership functions are inflexible to model all kinds of data. Moreover, the parameters associated with the membership functions must be provided by experts [37].
- *Histograms* – provides information regarding the distribution of input values, which can be modeled by parameterized functions such as Gaussian, thus directly yielding membership functions. This approach is easy to implement and the membership functions can be used for classifying data [37], but the histograms of different classes frequently overlap, therefore the applicability for finding linguistic terms is limited.
- *Nearest neighbors* – employs the technique that assigns class memberships to a sample instead of a particular class, where the class memberships depend on the sample's distance from its nearest neighbors. The primary use of the nearest neighbor techniques involves situations where the a priori probabilities and class conditional densities are unknown. The algorithm is simple however it does not generate smooth membership curves in overlapping regions.
- *Neural networks* – generates membership functions from labeled training data. In order to generate class membership values, a multilayer network is trained using a suitable training algorithm such as the back-propagation algorithm. This approach is capable of generating complex membership functions for classifying data. However the membership values are not necessarily indicative of the similarity of a feature to a class and the shapes of the membership functions are unpredictable in regions where there is no training data [37].

- *Clustering* – organizes data into clusters such that data within a cluster are more similar to each other than data in other clusters. The parameters of the membership functions will be determined based on the attributes of the clusters such as cluster's center location or cluster's width. Generally, clustering techniques may be classified into *hierarchical*-based and *partition*-based techniques. The main drawback of hierarchical clustering is that the clustering is static, and the data points assigned to a given cluster in the early stages cannot move to a different cluster [38]. *Partition*-based techniques, on the other hands, are dynamic, however, require prior knowledge such as the number of clusters in the training data. Even though some recent clustering algorithms such as the *Robust Agglomerative Gaussian Mixture Decomposition* (RAGMD), and the *Adaptive Resonance Theory* (ART) do not require the specification of the number of clusters, other parameters that affect the number of clusters generated are required. The parameters required are, namely, the retention ratio P in RAGMD [37], and the vigilance criterion ρ in ART [38]. Furthermore, the partition-based clustering techniques suffer from the stability-plasticity dilemma in which new information cannot be learned after training has been completed. In fuzzy neural networks, clustering is widely applied to generate membership functions. For example, the *Learning Vector Quantization* algorithm [39] is widely employed for Mamdani models [40] [41]. Meanwhile the *Fuzzy C-Means algorithm* [42] is widely employed for TSK models. These two algorithms are briefly described in Section 2.4.1.1 and 2.4.1.2.

One of the main objectives of using fuzzy neural networks is to capture and abstract humanly interpretable linguistic expressions from available numerical data. Therefore the membership functions generated have to reconcile with the semantic properties of a linguistic variable [35]. Linguistic variable is an important concept in fuzzy logic and plays a key role in many of its application, especially in the realm of fuzzy expert systems. A linguistic variable is formally

defined by Zadeh (1975) [32,43-44] with a quintuple $(x, T(x), U, G, M)$ where x is the name of the variable; $T(x)$ is the linguistic term set of x ; U is a universe of discourse; G is a syntactic rule for generating the names of values of x ; and M is a semantic rule that associates each value of x with its meaning. Each linguistic term is characterized by a fuzzy set that is described mathematically using a membership function.

In Figure 2-6, an example of a linguistic variable x named $x = \text{"speed"}$ with $U = [0, 100]$ is given. It is characterized by three linguistic terms $T(x) = \{\text{"slow"}, \text{"moderate"}, \text{"fast"}\}$ where each of these linguistic terms is assigned one of the three triangular or trapezoidal membership functions by a semantic rule M . These membership functions cover the entire universe of discourse $U = [0, 100]$ of the linguistic variable x . The common characteristics of all the fuzzy sets described by the membership functions in Figure 2-6 that characterize the linguistic terms of $T(x)$ are *normalized* and *convex*. Plus, the linguistic terms also followed a *partial ordering*, e.g., $\text{"slow"} \prec \text{"moderate"} \prec \text{"fast"}$.

Figure 2-6: Fuzzy membership functions representing linguistic terms “slow”, “moderate”, “fast”

There are still many controversial discussions about the definition of interpretability and its criteria for linguistic variables. However, the formal definitions on the semantic properties of interpretable linguistic variables were proposed as follow [45] :

- *Coverage* – membership functions $\mu_{X_i}(x)$ where $X_i \in T(x)$ can cover the entire universe of discourse. More specifically, $\forall x \in U$, $\exists X_i \in T(x)$ such that $\mu_{X_i}(x) > 0$.
- *Normalized* – membership function $\mu_{X_i}(x)$ where $X_i \in T(x)$ is normalized if $\exists X_i \in T(x)$ such that $\mu_{X_i}(x) = 1$.
- *Convex* – membership function $\mu_{X_i}(x)$ where $X_i \in T(x)$ is convex if $\forall x, y, z \in X_i$:

$$x \leq y \leq z \Rightarrow \mu_{X_i}(y) \geq \min(\mu_{X_i}(x), \mu_{X_i}(z))$$
.
- *Ordered* – membership function $\mu_{X_i}(x)$ where $X_i \in T(x) = \{X_1, X_2, \dots, X_i, \dots, X_n\}$ is ordered if $X_1 \prec X_2 \prec \dots \prec X_i \prec \dots \prec X_n$.

where the symbol $\prec$ denotes a partial ordering such that $X_1 \prec X_2$ denotes X_1 precedes X_2 .

In practice, a fuzzy knowledge base is considered interpretable if it contains *highly distinguishable* fuzzy sets which have the above semantic properties.

2.4.1.1 Clustering: Fuzzy C-Means (FCM) Algorithm

Fuzzy C-Means algorithm is widely employed to generate membership functions in TSK models.

Step 1: Given data set $\mathbf{X} = \{X_1, X_2, \dots, X_k, \dots, X_n\}$, define c as the number of clusters, m as the exponent weight and a small positive number ε as the terminating criterion.

Step 2: Initialize iteration $T = 0$ and randomly initialize fuzzy pseudo-partition $\mathbf{P}^{(0)}$. A fuzzy pseudo-partition of $\mathbf{P}$ is a family of fuzzy subsets $\mathbf{P} = \{P_1, P_2, \dots, P_c\}$ which satisfies (2.5) and (2.6),

$$\sum_{i=1}^c \mu_i(X_k) = 1 \quad \forall k \in \{1, 2, \dots, n\}, \quad (2.5)$$

$$0 < \sum_{k=1}^n \mu_i(X_k) < n \quad \forall i \in \{1, 2, \dots, c\}, \quad (2.6)$$

where $\mu_i(X_k)$ denotes the membership of X_k in fuzzy subset P_i .

Step 3: Compute the cluster centers $V_1^{(T)}, V_2^{(T)}, \dots, V_j^{(T)}, \dots, V_c^{(T)}$ for $\mathbf{P}^{(T)}$ using (2.7),

$$V_j^{(T)} = \frac{\sum_{k=1}^n (\mu_j(X_k))^m X_k}{\sum_{k=1}^n (\mu_j(X_k))^m} \quad \text{for } j = 1 \dots c \quad (2.7)$$

Step 4: Update $\mathbf{P}^{(T+1)}$ with (2.8),

$$\mu_i^{(T+1)}(X_k) = \left(\frac{\sum_{j=1}^c \left(\frac{\|X_k - V_i^{(T)}\|^2}{\|X_k - V_j^{(T)}\|^2} \right)^{\frac{1}{m-1}}}{\sum_{j=1}^c \left(\frac{\|X_k - V_i^{(T)}\|^2}{\|X_k - V_j^{(T)}\|^2} \right)^{\frac{1}{m-1}}} \right)^{-1} \quad \text{for } i = 1 \dots c, k = 1 \dots n \quad (2.8)$$

If $\|X_k - V_j^{(T)}\|^2 = 0$ then $\mu_i^{(T+1)}(X_k) = 1$ and $\mu_j^{(T+1)}(X_k) = 0$ for $j = 1 \dots c, j \neq i$

Step 5: Compare $\mathbf{P}^{(T+1)}$ with $\mathbf{P}^{(T)}$ using (2.9),

$$E = \left\| \mathbf{P}^{(T+1)} - \mathbf{P}^{(T)} \right\| = \sum_{j=1}^c \sum_{k=1}^n \left| \mu_j^{(T+1)}(X_k) - \mu_j^{(T)}(X_k) \right| \quad (2.9)$$

If $E > \varepsilon$ then $T = T + 1$ and go to step 3. If $E \leq \varepsilon$ then stop.

2.4.1.2 Clustering: Learning Vector Quantization (LVQ) Algorithm

Learning Vector Quantization algorithm is widely employed to generate membership functions in Mamdani models.

Step 1: Given data set $\mathbf{X} = \{X_1, X_2, \dots, X_k, \dots, X_n\}$ define c as the number of clusters, α as the learning constant where $0 < \alpha < 1$, a small positive ε as the terminating criterion and $T_{\max}$ as the maximum number of iterations.

Step 2: Initialize iteration $T = 0$, weights $V = \{V_1^{(0)}, V_2^{(0)}, \dots, V_j^{(0)}, \dots, V_c^{(0)}\}$ and initial learning constant $\alpha^{(0)} = \alpha$.

Step 3: For $T = 0 \dots T_{\max}$:

For $k = 1 \dots n$:

a. Find winner w using (2.10),

$$\|X_k - V_w^{(T)}\| = \min_j (\|X_k - V_j^{(T)}\|) \text{ for } j = 1 \dots c \quad (2.10)$$

b. Update the weights of the winner with (2.11),

$$V_w^{(T+1)} = V_w^{(T)} + \alpha^{(T)} (X_k - V_w^{(T)}) \quad (2.11)$$

End for k

c. Compute $E^{(T+1)}$ using (2.12),

$$E^{(T+1)} = \|V^{(T+1)} - V^{(T)}\|^2 = \sum_{j=1}^c \|V_j^{(T+1)} - V_j^{(T)}\|^2 \quad (2.12)$$

- d. If $E^{(T+1)} \leq \varepsilon$ stop, else adjust learning rate $\alpha^{(T+1)}$ to satisfy (2.13) and (2.14),

$$\sum_{T=0}^{\infty} \alpha^{(T)} = \infty \quad (2.13)$$

$$\sum_{T=0}^{\infty} (\alpha^{(T)})^2 = \infty \quad (2.14)$$

End for T

Both FCM and LVQ are offline clustering techniques. They are batch-learning approaches, meaning they require the training data to be available before training. In addition, they require the number of clusters to be specified in advance. Hence, they are not applicable for online applications.

2.4.1.3 Comparison of Popular Clustering Techniques

This Section benchmarks some of the existing clustering techniques proposed in the literature, namely FCM [42], LVQ [39], FLVQ [46], FKP [47], PFKP [47], and ECM [11]. They are widely used in fuzzy neural networks. Table 2-1 illustrates the comparisons of the various techniques.

Table 2-1: Comparison among existing clustering techniques

Features	Clustering techniques					
	FCM	FKP	PFKP	LVQ	FLVQ	ECM
Type of learning	Offline	Offline	Offline	Online	Online	Online
A prior knowledge of number of cluster	Y	Y	Y	Y	Y	N
A prior knowledge of upper/lower bounds of dataset	N	N	N	N	N	Y

Y=Yes, N=No

From Table 2-1, FCM [42], FKP [47], PFKP [47] perform clustering in the offline mode. All the clustering techniques in Table 2-1, with the exception of ECM, require the number of clusters to be defined prior to training. ECM is an incremental clustering technique, however it cannot handle complex time-variant data sets because it implicitly assumes prior knowledge of the upper and lower bounds of the data sets before learning.

2.4.2 Identifying Fuzzy Rules

Identifying interpretable if-then fuzzy rules is the *most important aspect* in designing a fuzzy neural network as the main objective of using fuzzy neural networks is to abstract humanly interpretable fuzzy rule base from numerical data. A fuzzy rule base is a linguistic model of a problem domain. It is characterized by a collection of high-level **IF-THEN** fuzzy rules. The IF-THEN fuzzy rules contribute in modeling the dynamics of the problem domain and the associated response action/behavior of a human expert in handling the problem. In short, the fuzzy rules help to model the problem domain from a human perspective (linguistic model) rather than the physical perspective (mathematical models). The form of the if-then fuzzy rules used in linguistic fuzzy neural networks based on the Mamdani model is given in (2.1). Another form used in precise fuzzy neural networks based on the TSK model is given in (2.2), in which the antecedents are linguistic terms but the consequent is a function of the inputs. Below is an example of a fuzzy rule base which is formed by if-then fuzzy rules.

Rule 1: If traffic condition is *heavy* and road condition is *slippery*, then speed is very *slow*

Rule 2: If traffic condition is *light* and road condition is *slippery*, then speed is *slow*

Rule 3: If traffic condition is *heavy* and road condition is *dry*, then speed is *slow*

Rule 4: If traffic condition is *light* and road condition is *dry*, then speed is *fast*

This fuzzy rule base constituting of four fuzzy rules describes how a driver decides on his driving speed depending on the condition of the road and traffic. In the four fuzzy rules, *traffic condition* and *road condition* are the input linguistic variables; *speed* is the output linguistic variable; the vague terms *very slow*, *slow*, *fast*, *heavy*, *light*, *slippery* and *dry* are the linguistic terms. These linguistic terms are associated with fuzzy sets mathematically described by membership functions on the universe of discourse of *traffic condition*, *road condition* and *speed* values.

There are a number of approaches to identify if-then fuzzy rules from numerical data [38,48-52].

They can be categorized as follows:

- *Expert knowledge* – capitalizes on the information that human experts provide including fuzzy linguistic terms and if-then fuzzy rules. In the next step, neural network learning techniques are then employed to perform optimization on the fuzzy linguistic terms and if-then fuzzy rules. Even though the advantage of this approach is fast learning convergence, it might be biased or incorrect due to the biased and imprecise information from different experts [50].
- *Supervised learning* – employs supervised learning that uses back-propagation to identify the if-then fuzzy rules. Even though the advantage of this approach is the capability of modeling nonlinear data accurately [53], it works like black box which does not reveal any semantic interpretability from the results [50].
- *Hybrid learning* – comprises of two different stages. The first stage is unsupervised learning in which self-organized learning or clustering is used to generate the membership functions, and competitive learning is used to identify the if-then fuzzy rules. The second stage is supervised learning in which back-propagation is used to optimize the parameters of the input and output membership functions [50]. The advantage of this approach is that it can increase the accuracy of the abstracted model

through the unconstrained optimization in the second stage. However, at the end, the membership functions are deviated from human-interpretable linguistic terms [54]. Back-propagation algorithms normally result in highly overlapping fuzzy sets which deteriorates human interpretability.

2.4.3 Specifying Reasoning Methods

Specifying reasoning methods is another important aspect in designing a fuzzy neural network. A reasoning method, or equivalently, an approximate reasoning method, is an inference process by which a possibly imprecise conclusion is deduced from a collection of imprecise premises [55]. The inference process in fuzzy neural networks mimics human reasoning in the sense that a human being has to make decisions based on incomplete, vague and fuzzy information. In fuzzy neural networks, the reasoning method defines the mathematical operations that are used to perform inference on the collection of if-then fuzzy rules and given facts to derive outputs for solving problems. In practice, an *online* reasoning method, which interleaves with (rule) learning process, is preferred over an offline reasoning method.

2.4.4 Parameter Learning

The learning process of a fuzzy neural network normally consists of two phases: structural learning and parameter learning. Structural learning comprises of the above mentioned steps such as generating membership functions and identifying rules. Parameter learning concerns about tuning the parameters of each derived rule such as connection weights and membership functions in order to achieve higher accuracy learning performance. Currently, there are many parameter learning methods, each with pros and cons. For instance, in the popular ANFIS [7] fuzzy neural network, two learning phases have been employed: forward and backward learning. In the forward learning phase, all the antecedent parameters of ANFIS are fixed, and all the consequent

parameters are tuned using the Kalman filter algorithm [4]. For backward learning, all the consequent parameters are fixed, and the antecedent parameters are adjusted by the back propagation delta learning method [56]. Gradient descent [4] and recursive-least-square algorithms [4] are widely used for tuning parameters in TSK fuzzy neural networks.

2.5 Self-evolving TSK Fuzzy Neural Networks

2.5.1 Introduction

The main focus of this Thesis is the Takagi-Sugeno-Kang fuzzy neural networks. Existing TSK networks proposed in the literature can be broadly classified into three classes as briefly discussed in Section 1.3. Table 2-2 illustrates the taxonomy of TSK fuzzy neural networks.

Recently, TSK fuzzy neural networks are widely applied for solving function approximation and regression-centric problems. In practice, most of these problems are *online* [17], meaning that the data in these problems is not all available at the beginning but is sequentially presented. New data keeps coming at every instant of time. A typical example of such problems is the stock price prediction problem. In the stock market, a stock price can change at every tick, and it can hit a new high or low that was not reached before, at any time. *Static* (or *non-constructive*) fuzzy neural networks which employ offline batch learning algorithms are not sufficient to address such a problem, as it might be impossible to acquire all the training data before learning. Furthermore, static systems cannot incorporate new data after training, which renders them useless when dealing with online problems. A popular example of static systems is ANFIS [7], which possesses a fixed structure. Some *self-organizing* (or *constructive* [57]) networks such as DFNN [9] and SOFNN [8] are also not suitable to address online problems as they are unable to learn in an incremental manner. They basically employ pseudo-incremental learning approaches [58], in which a copy of the training data is usually kept for the tuning phase or for performing rule

pruning later. Considering the growing scale in volume of stock trading information, a complete revisit of past data would be extremely costly. ANFIS, DFNN and SOFNN belong to Class I TSK networks.

Many self-organizing learning systems in Class II TSK networks [10-11,13] have been developed to solve online problems. These self-organizing approaches are able to learn incrementally, however they are generally limited to time-invariant environments. In real life, many online problems are *time-variant*. In such problems, the characteristics of the underlying data-generating processes might change with time, and no prior knowledge about the number of clusters/rules or the upper/lower bound of the dataset is provided. Thus, self-organizing learning algorithms which require some prior knowledge about the dataset are generally unable to address time-variant problems.

2.5.2 Self-evolving Learning Approach

To address online time-variant problems which have nonstationary characteristics, a class of *self-evolving* [17] TSK fuzzy neural networks (Class III) has been developed. These evolving systems generally employ incremental sequential learning [6], or simply incremental learning approach. In practical online applications, incremental learning is preferred over batch learning as it greatly improves the efficiency of online systems. More specifically, incremental learning does not require data to be stored, thus it uses much less memory. In addition, it can help the learning system to quickly incorporate new data since it only involves incremental updates. This advantage is illustrated in stock market trading activities, in which huge and growing trading data sets need to be processed daily. To be considered as an incremental sequential learning approach, a learning system must satisfy four criteria as defined in [6]. The criteria are listed below.

- 1) All the training observations are sequentially (one-by-one) presented to the learning system.
- 2) At any time, only one training observation is seen and learnt.
- 3) A training observation is discarded as soon as the learning procedure for that particular observation is completed.
- 4) The learning system has no prior knowledge as to how many total training observations will be presented.

Self-evolving systems in Class III TSK networks such as [14-18] adopt incremental learning approaches and attempt to solve time-variant problems. However, many evolving systems do not possess an unlearning algorithm, which may lead to the collection of obsolete knowledge over time and thus degrade the level of human interpretability of the resultant knowledge base. In these systems, older and newer information are treated equally. Hence, even though these systems can work in time-variant environments by evolving with the data stream, or self-constructing the knowledge base without prior knowledge of the data sets, they might not give the most accurate solutions for time-variant problems, as briefly discussed in the next Section.

Table 2-2: Taxonomy of TSK fuzzy neural networks proposed in the literature

TSK Networks	Class III	Class II	Class I
Type	Self-evolving	Self-organizing	Static/Self-organizing
Data stream	Time-variant	Time-invariant	Time-invariant
Learning schema	Incremental without any prior assumptions of data	Incremental with assumptions of data	Batch-learning or pseudo-incremental
Examples	SONFIN [15], eTS [17], FLEXFIS [16], TSK-FCMAC [18], RSONFIN [22], TRFN [23], RSEFNN [59], SEIT2FNN [60]	DENFIS [11], FITSK [10], [13]	ANFIS [7], DFNN [9], SOFNN [8], GA-TSKfnn [61], MSTSK [62]

2.6 Unlearning Motivations for Evolving TSK Fuzzy Neural Networks

Unlearning, which stemmed from neurobiology, was introduced by Hopfield *et al* in 1983 [19] to implement an idea of Crick and Mitchinson [20] about the function of dream sleep. In [21], it was demonstrated that unlearning greatly improves network performance such as the enhancement of network storage capacity. Although many self-evolving systems attempt to address time-variant problems by employing incremental learning, they still lack an efficient unlearning algorithm. Thus, they encounter two critical issues, namely: 1) their fuzzy rule base can only grow, and 2) they cannot give the most accurate solution when solving complex time-variant data sets that exhibit regime-shifting properties. These two issues are presented below.

First, evolving systems which employ incremental learning generally learn new data by creating more rules. In such evolving systems, the number of fuzzy sets and fuzzy rules will grow monotonically. Their fuzzy rule bases retain many obsolete rules, which can no longer describe the current data characteristics, especially when dealing with time-variant problems. This leads to confusing fuzzy rule bases with many redundant rules, and thus deteriorates human interpretability.

Second, when working in time-variant environments, evolving systems without unlearning capabilities are unable to provide the most accurate solutions. Data streams in time-variant problems evolve over time, where past data are generally less important than current data. Besides having *temporal* characteristics (meaning explicitly dependent on time), time-variant problems also exhibit *regime shifting* properties. To clearly understand the term ‘regime shifting’, one must understand the definition of ‘concept drift’ and ‘concept shift’ as described below.

2.6.1 Concept drifting

In machine learning literature, concept drifting and concept shifting [63] are two different types of ‘concept change’ of the underlying distribution of online data streams [64]. To clarify, concept, which is normally interpreted as a cognitive unit of meaning, here refers to the set of cognitive patterns that define the underlying statistical properties of the data streams. Concept drift refers to a gradual evolution of the concept over time. Concept drift is said to appear in a data stream when that data stream’s underlying data-generating processes change and the data distribution slides through the data space from one region to another. It concerns the time-space representation of the data streams. While the concept of (data) density is represented in the data space domain, drift and shift are concepts in the joint data time-space domain [64]. A typical real-life example of concept drift is weather prediction rules that may vary radically with the season [63]. Other obvious examples are music trends, fashion trends, or investment trends that may change with time. It can be easily observed that all processes that occur in human activities, such as financial, biological processes are likely to experience concept drifts.

To illustrate concept drift, one may consider a data cluster moving from one region to another. Consider in 2-D spatial data space, the original data points marked by diamond samples, which changes over time into a data distribution marked by circular samples, as illustrated in Figure 2-7. If a conventional clustering process would be applied that weights all new incoming samples equally, the cluster center would end up exactly in the middle of the combined data cloud, averaging old and new data, which is wrong (marked by the star shape). An efficient learning technique should be able to detect such a drift in data distribution and treat old data and new data differently, and the cluster center would end up correctly in the middle of the new data cloud (new concept).

Figure 2-7: An evolving cluster drifts to a new region

Figure 2-8: Concept drift in time-space domain

Figure 2-8 illustrates concept drift in time-space domain. Back to the stock prices prediction example, one can observe that stock traders are more concerned about the current stock prices than the past stock prices. For a specific stock, the past stock trading rules might become obsolete, as the stock trading range has been shifted, as illustrated in Figure 2-9. From Figure 2-9, one can observe that the Apple stock (extracted from Google Finance website) was mainly traded in the range $[10, 200]$ during the period 2001-2008, and it was mainly traded in the range $[90, 350]$ during the period 2009-2011. Thus, the trading rules which were considered relevant in the period 2001-2009 might be irrelevant in the period 2009-2011.

Figure 2-9: Apple stock prices in period 2001-2011

2.6.2 Concept shifting

Concept shifting is an extreme form of concept drifting. It refers to the abrupt change in the underlying concept, or simply means the displacement of the old data distribution with a new data distribution within a short time. Instantaneous changes in data distribution would cause the learning model to produce inaccurate results if it continues to use the old concept. Concept shifting is also termed as ‘regime shifting’ in this Thesis. Figure 2-10 illustrates concept shift in time-space domain. Without correcting for this concept shift, the learning model would derive inaccurate outputs which lie between the old and new conceptual boundaries.

Figure 2-10: Concept shift in time-space domain

Many real life problems are likely to experience concept drifts and shifts, in which newer data is considered more important (and relevant) than older data. Drift and shift handling was already applied in other machine learning techniques such as support vector machines [65-66], ensemble classifiers [67], and instance-based (lazy) learning approaches [68-69]. However, currently very few fuzzy neural networks have attempted to address this issue. Many existing evolving fuzzy systems which treat older information and newer information equally are unable to detect concept drifts and shifts [64]. Thus, they are unable to give the most accurate results when dealing with the data sets that exhibit regime shifting properties. Drifts and shifts indicate the necessity of (gradual) unlearning previously learned relationships (in terms of structure and parameters) during the incremental learning process as they are no longer valid and should hence be removed from the model (for instance, consider completely new trading rules when the stock market conditions change) [64]. Unlearning is an efficient way to address the concept drift and shift in online data streams. It separates past data from new data by decaying the effects of past data on the final outputs. Thus, to deal with fast-changing time-variant problems, learning systems should also adopt unlearning algorithms.

2.7 Research Challenges

This section surmises issues and weakness of existing TSK fuzzy neural networks that this Thesis attempts to address. They are briefly discussed as follows.

2.7.1 Online Incremental Learning in Time-Variant Environments.

Online incremental learning is necessary in real-life applications. As analyzed in Section 2.5.1, Class I TSK networks such as ANFIS [7], DFNN [9], and SOFNN [8] violate the criteria to be considered as an incremental learning approach. Class II TSK networks such as DENFIS [11],

FITSK [10] improve from Class I by employing incremental learning, however they still cannot address time-variant problems.

To address this problem, the Thesis relies on a novel clustering technique known as Multidimensional Growing Clustering (MSGC). MSGC can learn incrementally without any assumptions about the dataset. MSGC is inspired by human cognitive process models [70], as explained in Chapter 3.

2.7.2 Unlearning Strategy to Address Time-Variant Problems

As many existing evolving TSK systems do not possess unlearning capabilities, they are unable to provide the most accurate and up-to-date solutions when solving complex time-variant data sets that show drift and shift behaviors. A comparison among evolving TSK systems in the literature is shown in Table 2-3. From 1998-2010, Juang et al. proposed a class of feed-forward and recurrent self-evolving networks such as SONFIN [15], RSONFIN [22], TRFN [23] and RSEFNN [59] to address online problems. However, these networks do not take unlearning into consideration. Based on Juang's works, many other improved networks were developed such as HO-RNFS [71], T-SORNFN [72]. Juang et al. also proposed type-2 TSK fuzzy neural networks such as SEIT2FNN [60] and IT2FNN-SVR [73] to handle problems with uncertainties such as noisy data. Other popular evolving systems such as eTS [17], FLEXFIS [16], and [14] were proposed during 2004-2008. In 2009, Ting and Quek [18] proposed a simple network termed as TSK^0 -FCMAC to regulate the blood glucose levels in diabetes patients. Since all of these networks do not possess unlearning algorithms, their number of membership functions and fuzzy rules grow monotonically, resulting in confusing knowledge bases with many obsolete rules. In addition, these networks cannot detect and address concept drifts and shifts in complex time-variant problems. Simpl_eTS [74] is among a few TSK networks ([64,74-76]) that possess an unlearning algorithm. It is a modification of eTS with a rule-pruning algorithm which monitors

the population of each rule. If a rule amounts to less than 1% of the total data samples at that current moment, it is considered as obsolete, and it will be pruned. This approach considers the contribution of old data and new data equally in determining the obsolete rules, thus it cannot detect drifts and shifts in online data streams [64]. In systems such as eTS+ [76] and xTS [75], the *age* of a cluster is used to determine if a rule (cluster) is obsolete. However, the age of the cluster in [75-76] is determined by a self-driven formula which does not incorporate the membership degrees of the samples forming that cluster. In 2010, Lughofer and Angelov [64] are the first to apply drift and shift handling in fuzzy systems. They proposed a method for autonomous detection of drifts and shifts in data streams based on the age of the fuzzy rule. This method computes the age of the fuzzy rule based on a self-driven mathematical formula, which is not biologically plausible. In addition, the method detects the drift and shift by observing the gradient of the age, which is a complicated process.

For unlearning, this Thesis proposed a novel ‘brain-inspired’ rule pruning algorithm which applies a ‘gradual’ forgetting approach and adopts the Hebbian learning mechanism behind the long-term potentiation phenomenon [77] in the brain. This approach is simple, computationally efficient and biologically plausible.

Table 2-3: Comparison among self-evolving TSK fuzzy neural networks

TSK Networks [Author, year of publication] [references]	Network Structure	Fuzzy Logic Type	Un- learning	Antecedent Parameters Tuning method
SONFIN [Juang and Lin, 1998] [15]	Feed-forward	Type-1	No	Gradient descent
RSONFIN [Juang and Lin, 1999] [22]	Recurrent	Type-1	No	Gradient descent
TRFN [Juang, 2000][23]	Recurrent	Type-1	No	Gradient descent
eTS [Angelov and Filev, 2004] [17]	Feed-forward	Type-1	No	Recursive update of potential
Simpl. eTS [Angelov and Filev, 2005] [74]	Feed-forward	Type-1	Yes	Recursive update of scatter
xTS [Angelov and Zhou, 2006] [75]	Feed-forward	Type-1	Yes	NM
HO-RNFS [Theocharis, 2006] [71]	Recurrent	Type-1	No	Gradient descent
FLEXFIS [Lughofer, 2008] [16]	Feed-forward	Type-1	No	Winner-take-all like algorithm
SEIT2FNN [Juang and Tso, 2008] [60]	Feed-forward	Type-2	No	Gradient descent
TSK-FCMAC [Ting and Quek ,2009] [18]	Feed-forward	Type-1	No	NM
RSEFNN [Juang et al., 2010] [59]	Recurrent	Type-1	No	Gradient descent
eTS+ [Angelov, 2010] [76]	Feed-forward	Type-1	Yes	NM
T-SORNFN [Chen, 2010] [72]	Recurrent	Type-1	No	Gradient descent
IT2FNN-SVR [Juang et al., 2010] [73]	Feed-forward	Type-2	No	NM
ds-eTS [Lughofer and Angelov,2011][64]	Feed-forward	Type-1	Yes	Gradient descent

NM = Not Mentioned.

2.7.3 Compact and Interpretable Knowledge Base

Many existing TSK networks [15,22-23,59] do not take in consideration of the interpretability of the knowledge base. They generally employ back-propagation or gradient descent algorithms to heuristically tune the widths of their antecedent membership functions, which can results in highly overlapping and indistinguishable fuzzy sets. Thus, the semantic meaning of the derived knowledge base is deteriorated. SONFIN [15] and its recurrent version, RSONFIN [22], set the

widths of fuzzy sets in all input dimensions to be the same during learning. New fuzzy sets are created whenever a new rule is identified, which is redundant.

Figure 2-11: Two types of knowledge base: (a) Deteriorated with highly overlapping and indistinguishable fuzzy sets; (b) Interpretable with highly distinguishable fuzzy sets.

To overcome this issue, a novel merging approach is employed in the proposed MSGC technique. This approach can prevent the derived fuzzy sets from expanding too many times to protect their semantic meanings. Together with the proposed rule pruning strategy, MSGC helps to maintain a compact and understandable knowledge base, which can be illustrated in the experiments throughout this Thesis.

2.7.4 Summary

This Thesis proposes novel learning/unlearning algorithms to address the above-listed deficiencies of existing TSK networks. Most of real-life problems require solutions with incremental learning ability, high accuracy and fast speed. In addition, the interpretability of the knowledge bases derived is another important aspect to consider when designing solutions for such complex problems. This Thesis takes all such issues into consideration. The next Chapter 3 provides a detailed mathematics and insights to the generic TSK framework that is developed to pursue the motivations of this Thesis.

Chapter 3: Generic Self Evolving TSK Fuzzy Neural Network (GSETSK)

You cannot teach a man anything; you can only help him discover it in himself.

Galileo Galilei (1564-1642)

3.1 Introduction

This chapter presents the architecture and the learning algorithm of the proposed Generic Self-Evolving Takagi-Sugeno-Kang Fuzzy Neural Network (GSETSK). GSETSK attempts to address the existing problems of TSK fuzzy neural networks as identified in Section 2.7. Another goal in designing GSETSK is achieving a fast and efficient framework that can be applied in real-life applications which require high precision. GSETSK can learn in an incremental manner and can work in time-variant environments. GSETSK's initial empty rule base is empty. New rules are sequentially added to the rule base by a novel fuzzy clustering algorithm termed as MSGC. MSGC is completely data-driven and does not require prior knowledge of the numbers of clusters or rules present in the training data set. In addition, MSGC does not assume the upper or lower bounds of the data set. Highly overlapping membership functions are merged and obsolete rules are constantly pruned to derive a compact fuzzy rule base while maintaining a high level of modeling accuracy. A detailed comparison between the proposed MSGC and other clustering/rule generating algorithms is briefly presented in Section 3.3.1. In order to implement the unlearning motivation, a novel rule pruning algorithm which applies a 'gradual' forgetting approach and adopts the Hebbian learning mechanism behind the long-term potentiation phenomenon [77] in the brain, is proposed. For parameter tuning, GSETSK employs a localized version of *the*

recursive least-square algorithm [78] for high-accuracy online learning performance. The parameter tuning phase is used only for tuning the consequent parameters of the fuzzy rules. The dynamic learning/unlearning mechanisms in GSETSK help to ensure an efficient and fast framework that can be applied for real-life applications.

This chapter is organized as follows. Section 3.2 briefly discusses the general structure of the GSETSK and its neural computations. Section 3.3 presents the structural learning phase and its rule pruning algorithm. Section 3.4 discusses its parameter learning phase. Section 3.5 briefly evaluates the performance of the GSETSK models using three different simulations. These simulations have the following goals:

1. Demonstrate the online incremental learning ability of GSETSK in complex environments such as the nonlinear dynamic system with nonvarying characteristics (in Section 3.5.1). The derived knowledge base of GSETSK is also illustrated, to show that the proposed MSGC algorithm can generate a compact rule base with highly distinguishable fuzzy sets.
2. Demonstrate the ability of GSETSK to work in time-variant environments such as the nonlinear dynamic system with time-varying characteristics (in Section 3.5.2). The evolving rule base of GSETSK is also illustrated, to show how GSETSK can keep a current and relevant rule base in time-variant problems.
3. Demonstrate the superior performance of GSETSK when benchmarked against other evolving models using the Mackey-Glass time series prediction simulation (in Section 3.5.3).

3.2 Architecture & Neural Computations

The GSETSK model is basically an FNN [4] that consists of six layers of computing nodes as shown in Figure 3-1. They are: Layer I (the input layer), Layer II (the input linguistic layer), Layer III (the rule layer), Layer IV (the normalization layer), Layer V (the consequent layer) and Layer VI (the output layer). From Figure 3-1, the structure of the proposed GSETSK model defines a set of TSK-type IF-THEN fuzzy rules. The fuzzy rules are incrementally constructed by presenting the training observations $\{\cdots (X(t), d(t)) \cdots\}$ sequentially (one-by-one), where $X(t)$ and $d(t)$ denote the vectors containing the inputs and the corresponding desired outputs, respectively, at any time t . Each fuzzy rule R_k in GSETSK has the form shown in (3.1).

$$\begin{aligned} R_k : & \text{ IF } (x_1 \text{ is } IL_{1,j_1^k}) \text{ AND } \cdots (x_i \text{ is } IL_{i,j_i^k}) \cdots \text{ AND } (x_n \text{ is } IL_{n,j_n^k}) \\ & \text{ THEN } y_k = b_{ok} + b_{1k}x_1 + \cdots + b_{ik}x_i + \cdots + b_{nk}x_n \end{aligned} \quad (3.1)$$

where $X = [x_1, \dots, x_i, \dots, x_n]^T$ represents the numeric inputs of GSETSK;

IL_{i,j_i^k} ($j_i = 1, \dots, J_i(t)$, $k = 1, \dots, K(t)$) denotes the j_i th linguistic label of the input x_i

that is part of the antecedent of rule R_k ; $J_i(t)$ is the number of fuzzy sets of x_i ; $K(t)$ is the number of fuzzy rules at time t ;

y_k is the crisp output of rule R_k ;

n is the number of inputs;

$[b_{ok}, \dots, b_{nk}]$ represents a set of consequent parameters of rule R_k .

For simplicity, the proposed GSETSK network is modeled as a *multiple-input–single-output* (MISO) network. A *multiple-input–multiple-output* (MIMO) network can be viewed as an

aggregation of MISOs. For clarity of subsequent discussion, the output of a node in Figure 3-1 is denoted by z with the superscripts denoting its layer and the subscripts denoting its origin. For example, z_i^I is the output of the i th node in layer I. All the outputs of a layer are propagated to the inputs of the connecting nodes at the next layer.

Figure 3-1: Structure of the GSETSK network

Each input node I_i may connect to a different number of input linguistic nodes $J_i(t)$. Hence the total number of nodes in layer II at each time t is $\sum_{i=1}^n J_i(t)$. Also, at each time t , layer III consists of $K(t)$ rule nodes R_k . It should be noted that $K(t)$ and $J_i(t)$ change over time, increasing to accommodate new data or decreasing to keep a compact fuzzy rule base. Each rule

node R_k is directly connected to a normalization node N_k in layer IV. Subsequently, each normalization node N_k is directly connected to a consequent node C_k in layer V. Hence, the numbers of nodes in layer III, layer IV and layer V are the same. For clarity of subsequent discussion, the variables i and j are used to refer to arbitrary nodes in layers I, II, and the variable k for layer III, IV, V respectively. The output node at layer VI is a summation node which connects to all nodes in layer V.

Detailed mathematic functions of each layer of GSETSK are presented below.

3.2.1 Forward Reasoning

Layer I: Input Layer

$$Z_i^I = x_i, \quad i = 1, \dots, n \quad (3.2)$$

Layer I nodes are called *linguistic nodes*. They represent linguistic variables such as ‘speed’, ‘price’ etc. Each node receives only one element of the vectored data input, and outputs to several nodes of the next layer.

Layer II: Input Linguistic Layer

$$Z_{i,j_i}^{II} = \mu_{i,j_i}(Z_i^I) = \mu_{i,j_i}(x_i), \quad i = 1, \dots, n, \quad j_i = 1, \dots, J_i(t) \quad (3.3)$$

where μ_{i,j_i} is a fuzzy membership function of the *fuzzy linguistic node* IL_{i,j_i} .

Layer II nodes are called *input-label nodes*. They represent labels such as ‘fast’, ‘slow’ etc. They constitute the antecedent of the fuzzy rules in GSETSK. The label IL_{i,j_i} denotes the j th linguistic label of the i th linguistic variable input. The input linguistic layer measures *the matching degree* of each input with its corresponding linguistic nodes. Each linguistic node in this layer has a Gaussian membership function with its center and width dynamically computed during the

structural learning phase. With the use of Gaussian membership function, (3.3) can be expressed as in (3.4),

$$Z_{i,j_i}^{II} = \mu_{i,j_i}(x_i) = e^{-\frac{(x_i - m_{i,j_i})^2}{\sigma_{i,j_i}^2}}, \quad i = 1, \dots, n, \quad j_i = 1, \dots, J_i(t) \quad (3.4)$$

where m_{i,j_i} and σ_{i,j_i} are, respectively, the center and the width of the Gaussian membership function of the j_i th linguistic label of the i th linguistic variable input x_i .

Layer III: Rule Layer

Each node in rule-base layer represents a single Sugeno-type fuzzy rule and is called a *rule node*.

The net output or the firing strength of a rule node R_k is computed based on the activation of its antecedents as in (3.5),

$$r_k = Z_k^{III} = \min(Z_{1,j_1^k}^{II}, \dots, Z_{i,j_i^k}^{II}, \dots, Z_{n,j_n^k}^{II}), \quad k = 1, \dots, K(t) \quad (3.5)$$

where $Z_{i,j_i^k}^{II}$ is the output of the j_i^k th linguistic label of the i th linguistic variable input x_i that connects to the k th rule; r_k is the forward firing strength of R_k .

Layer IV: Normalization layer

Each node in this layer computes the normalized firing strength of a fuzzy rule as in (3.6),

$$\omega_k = Z_k^{IV} = \frac{Z_k^{III}}{\sum_{k=1}^{K(t)} Z_k^{III}}, \quad k = 1, \dots, K(t) \quad (3.6)$$

where ω_k is the normalized firing strength.

Layer V: Consequence Layer

Each node in this layer represents a TSK rule. The outputs of this layer are weighted with their incoming normalized firing strengths as in (3.7),

$$Z_k^V = Z_k^{IV} f_k(X), \quad k = 1, \dots, K(t) \quad (3.7)$$

where $f_k(X)$ is a linear function of consequent node C_k .

Layer VI: Summation Layer

The output node in this layer corresponds to the output of the GSETSK model. It combines the activations of all its consequent nodes in layer V as in (3.8),

$$Z^{VI} = \sum_{k=1}^{K(t)} Z_k^V \quad (3.8)$$

where Z_k^V is the output of consequent node C_k in layer V. The output node in this layer corresponds to the output of the GSETSK model.

Although the GSETSK appears structurally similar to other evolving networks such as SONFIN[15], FLEXFIS [16] and eTS [17], there are distinct differences between them. SONFIN uses back-propagation to tune its membership functions, which can result in highly overlapping and indistinguishable membership functions. The number of membership functions and fuzzy rules in FLEXFIS and eTS will grow monotonically, especially when solving time-variant problems. Ouyang *et al.* [14] proposed a merge-based fuzzy clustering algorithm to merge highly similar clusters. However, this algorithm does not prune irrelevant rules, which results in a continuously growing fuzzy rule base over time. In contrast, the GSETSK employs a Hebbian-based rule pruning algorithm which takes into consideration the *backward connections* from layer VI to layer III via layer V as presented in Section 3.2.2 and Section 3.2.3. This novel rule pruning algorithm ensures a compact and up-to-date fuzzy rule base in the GSETSK network.

3.2.2 Backward Computations of GSETSK

The backward connections from layer VI to layer III via layer V in the GSETSK solely serve the purpose of computing the potentials of the fuzzy rules in GSETSK. These fuzzy rule potentials will subsequently be used to determine if the rules will be pruned or kept. Inspired by the learning algorithm in POPFNN [79], the GSETSK adopts the Hebbian learning mechanism to compute its fuzzy rule potentials. However, POPFNN [79] and its family of networks [47,80-81] are of Mamdani-type fuzzy neural networks in which the output of each fuzzy rule is a set of fuzzy linguistic labels. The Hebbian learning algorithm employed in POPFNN is based on the firing strengths of the rules nodes (forward firing) and the membership values derived at the output-label nodes (backward firing).

In contrast, the GSETSK model adopts the TSK's fuzzy model and the output of each rule in GSETSK has the form of a linear function of the input vector. Hence, a novel approach to compute the fuzzy rule potentials based on the observed training data pair $(X(t), d(t))$ is proposed in GSETSK. At each rule node R_k , the forward firing strength r_k has been described in (3.5); and the backward firing strength r_k^{back} is computed in two steps as follows.

3.2.2.1 Computing Output Error of Each Fuzzy Rule

Layer V (Backward Operation): At time t , the desired output $d(t)$ is directly transmitted to each consequent node C_k in layer V. The output of the linear function of the consequent node C_k in response to the input $X(t)$ is a crisp value $y_k(t)$ given by (3.9),

$$y_k(t) = b_{ok}(t) + b_{1k}(t)x_1(t) + \dots + b_{ik}(t)x_i(t) + \dots + b_{nk}(t)x_n(t), \quad k = 1, \dots, K(t) \quad (3.9)$$

where $[b_{0k}(t), \dots, b_{nk}(t)]$ represents a set of consequent parameters of rule R_k at time t . Note that y_k is the output of the fuzzy rule R_k . It is different from Z_k^V , which is the output of the consequent node C_k . For each rule R_k , the difference between the computed output $y_k(t)$ and the desired output $d(t)$ is given by

$$e_k(t) = |d(t) - y_k(t)|, \quad k = 1, \dots, K(t) \quad (3.10)$$

where $e_k(t)$ is the output error of rule R_k at time t .

3.2.2.2 Determining Backward Firing Strength of Each Fuzzy Rule

Layer V (Backward Operation): The values $\{e_1(t), \dots, e_k(t), \dots, e_{K(t)}(t)\}$ will then be used to form a Gaussian membership function with the mean of zero and the width (or variance) at time t formulated in (3.11),

$$\sigma_{back}(t) = \frac{\sum_{k=1}^{K(t)} e_k(t)}{K(t)\sqrt{\pi}} \quad (3.11)$$

This membership function measures how closely the computed output $y_k(t)$ can approximate the desired output $d(t)$. Denote $\mu(0, \sigma_{back}(t))$ as the Gaussian membership function with center 0 and width $\sigma_{back}(t)$. Figure 3-2 shows such a Gaussian membership function, which can be approximated by an isosceles triangle with unity height and the length of its bottom edge equal to $2\sigma_{back}(t)\sqrt{\pi}$ [82].

Figure 3-2: The Gaussian membership function $\mu(0, \sigma_{back}(t))$.

The backward firing strength of r_k^{back} of rule R_k at time t is then determined by (3.12),

$$r_k^{back}(t) = \mu(0, \sigma_{back}(t), e_k(t)) = \exp(-e_k(t)^2 / \sigma_{back}(t)^2) \quad (3.12)$$

In Mamdani-type models such as POPFNN, the backward firing strength of a fuzzy rule is defined by how close the desired output is to the centers of the membership functions in the rule's output-label nodes. The idea in GSETSK is similar. At layer V, the Gaussian function $\mu(0, \sigma_{back}(t))$ is formulated to measure the degree of closeness between the desired output $d(t)$ and the computed output $y_k(t)$. When $\mu(0, \sigma_k(t), e_k(t)) = 1$, $e_k(t) = 0$, and $y_k(t) = d(t)$. The smaller the value of $e_k(t)$, the greater the value of $\mu(0, \sigma_k(t), e_k(t))$. That also means the closer the computed output $y_k(t)$ is to the desired output $d(t)$, the greater the backward firing strength of rule R_k . It can be observed from (3.11) that the width $\sigma_{back}(t)$ is constructed using the average of the errors of all rules at time t . This approach is built on the idea that the existing fuzzy rules in GSETSK at time t should be compared against each other in terms of how well they can approximate the desired output. However, it should be noted that the backward firing strength only forms a part of the formula to calculate the fuzzy rule potentials as presented in Section 3.2.3.

3.2.3 Fuzzy Rule Potentials

GSETSK is an online model which functions by interleaving reasoning (testing) and learning (training) activities. At any time t , GSETSK carries out the activities as follows.

1. It performs structural learning to formulate the fuzzy rules and to learn the membership functions using the input $X(t)$ as presented in Section 3.3.
2. It performs forward reasoning to approximately infer the output $y(t)$ based on the input $X(t)$ and its knowledge at time $(t-1)$ as presented in Section 3.2.
3. It performs tuning of the network parameters using the recursive least square algorithm as presented in Section 3.4.
4. It performs backward computing to update its fuzzy rule potentials to keep an up-to-date knowledge base by pruning outdated rules.

GSETSK relies on fuzzy rule potentials in its rule-pruning algorithm to delete obsolete fuzzy rules that can no longer describe the current observed data characteristics. The potential P_k of a fuzzy rule R_k in GSETSK indicates its importance or influence in the entire rule base of the system. At any time t , the potential P_k of a fuzzy rule R_k can be recursively computed based on the current training data $(X(t), d(t))$ as shown in (3.13),

$$P_k(t) = P_k(t-1) + r_k(X(t)) \times r_k^{back}(d(t)) \quad k = 1, \dots, K(t) \quad (3.13)$$

where $P_k(t-1)$ is the potential of rule R_k at time $(t-1)$; $r_k(X(t))$ is the forward firing strength of rule R_k as given in (3.5); and $r_k^{back}(d(t))$ is the backward firing strength of rule R_k as given in (3.12).

Equation (3.13) indicates that the importance of a fuzzy rule R_k in GSETSK is reinforced if its input antecedents and computed output can closely mimic the information expressed in the training pair $(X(t), d(t))$. This totally complies with the Hebbian learning mechanism behind the long-term potentiation phenomenon [77] in the brain. The mechanism is based on the Hebb theory which states that the synaptic connections of the associative memories formed in the brain are strengthened when coincident pre-synaptic and post-synaptic activities occur.

To account for complex time-variant data sets, GSETSK needs to separate its new learning from its old learning to avoid catastrophic forgetting [83]. More specifically, GSETSK needs to decay the effects of its old learning as new data pairs become available. This is achieved by a forgetting mechanism that gradually removes the outdated rules from GSETSK. This helps to maintain a set of up-to-date fuzzy rules that best describes the current characteristics of the incoming data. Furthermore, the rule base will be more compact and can be better interpreted by human experts. This is done by adding a forgetting factor to the original formulation described in (3.13) and is now given in (3.14),

$$P_k(t) = \lambda P_k(t-1) + r_k(X(t)) \times r_k^{back}(d(t)) \quad \lambda \in (0,1] \quad k = 1, \dots, K(t) \quad (3.14)$$

where λ is the forgetting factor. The smaller λ is, the faster the effects of old learning decay. The rule R_k will be pruned if $P_k(t)$ falls below the predefined parameter $thresP$. The details of the rule pruning algorithm in GSETSK will be presented in Section 3.3.2.

3.3 Structure Learning of GSETSK

At each arrival of data observations $(X(t), d(t))$, GSETSK performs its learning process which consists of two phases; namely structural and parameter learning. This section describes the structural learning phase of GSETSK.

GSETSK employs a novel clustering technique known as Multidimensional-Scaling Growing Clustering (MSGC) to partition the input space from the training data to formulate its fuzzy rules. Initially there is no rule in the rule base of the GSETSK network. New rules are sequentially added to the rule base if the existing rules are not sufficient to describe the new data. Highly overlapping membership functions will be merged and obsolete rules will be constantly pruned based on their fuzzy potentials.

3.3.1 Multidimensional-Scaling Growing Clustering

The MSGC has the following advantages:

- 1) It does not require the number of cluster/fuzzy rules to be specified prior to training.
- 2) It does not require prior knowledge about the upper/lower bounds of the datasets.
- 3) It can quickly learn in an incremental manner.
- 4) It can ensure a compact and interpretable knowledge base.

In MSGC, each fuzzy rule is a cluster which is identified in the multidimensional input space. After a cluster is identified, the corresponding 1-D membership function for each input dimension is derived by decomposing the multidimensional cluster. The multidimensional scaling approach in the MSGC technique is inspired by human cognitive process models [70]. Multidimensional scaling is normally used to provide a visual representation of the pattern of proximities among a

set of objects. A simple example of multidimensional scaling is that in order to distinguish two bottles of whisky (objects), the experts must compare the shapes of the bottles or the taste of tots of whisky (stimuli). Multidimensional scaling representations have been employed as the underpinnings of a number of successful cognitive process models [84]. In these models, the spatial stimulus representations generated by multidimensional scaling are manipulated by processes that model cognitive phenomena [70]. In MSGC, the clusters are manipulated by the corresponding 1-D membership functions.

The clustering process is described as follows. Assume the arrival of a new training data pair $(X(t), d(t))$, where $X(t) = [x_1(t), \dots, x_i(t), \dots, x_n(t)]^T$. Initially, there is no cluster identified, i.e. $K(t) = 0$. If $(X(t), d(t))$ is the first incoming training observation (i.e. $t = 1$), MSGC immediately creates a new cluster and projects the newly created cluster to the 1-D inputs to form the Gaussian membership functions as described by (3.15) and (3.16),

$$m_{i,J_i(t+1)} = x_i(t) \quad (3.15)$$

$$\sigma_{i,J_i(t+1)} = v_i \quad (3.16)$$

where $m_{i,J_i(t+1)}$ and $\sigma_{i,J_i(t+1)}$ are the center and width of the input label $IL_{i,J_i(t+1)}$, $J_i(t+1) = 1$, respectively; and v_i is a predefined constant which can be set to some arbitrary values or based on a user's prior observations. A new cluster corresponds to a new rule node in layer III.

For the next training observations, MSGC will determine whether a new rule should be created to cover the new data or not, based on the rule firing strengths as computed using (3.5) (page 46). At time t , MSGC performs a partial activation of the GSETSK network via the forward connections of layers I-III to derive the firing strengths $r_k(X(t))$, $k = 1, \dots, K(t)$.

The maximum firing strength is then determined using (3.17),

$$\rho = \arg \max_{1 \leq k \leq K(t)} r_k(X(t)) \quad (3.17)$$

where ρ indicates that the ρ^{th} rule achieves the maximum firing strength among all existing fuzzy rules in the rule base.

A new rule is created if $r_\rho(X(t)) < \theta$, where $\theta \in (0,1)$ is a predefined threshold. θ controls the number of rules created. The higher the value of θ , the more rules are created. In order to achieve a balance between having highly distinguishable clusters (rules) and using a sufficient number of rules, θ is normally predefined at 0.4. After a rule (cluster) is created, the corresponding 1-D Gaussian membership function for each input dimension is formulated. The center of the new membership function in the i th dimension is set using (3.15). However, to determine the width of the new membership function in the i th dimension, $\sigma_{i,J_i(t+1)}$, an extra step is taken as follows. Denote ε as the ε th input label in the i th dimension that has the largest matching degree with $x_i(t)$. ε can be found using (3.18),

$$\varepsilon = \arg \max_{1 \leq j \leq J_i(t)} e^{-\frac{(x_i(t) - m_{i,j})^2}{\sigma_{i,j}^2}} \quad (3.18)$$

The width of the new membership function in the i th dimension, $\sigma_{i,J_i(t+1)}$ can be determined by (3.19),

$$\sigma_{i,J_i(t+1)} = \eta \left| x_i(t) - m_{i,\varepsilon} \right| \quad (3.19)$$

where $m_{i,\varepsilon}$ is the center of the membership function that is nearest to $x_i(t)$; and $\eta \geq 0$ is a predefined constant that determines the degree of overlap between two arbitrary membership

functions. It can be observed that the width $\sigma_{i,J_i(t+1)}$ is directly proportional to the distance between $x_i(t)$ and the center of the nearest fuzzy set. The greater η , the bigger the width of a newly created fuzzy set. η is set at 0.5 in all experiments in this paper. The widths of the 1-D membership functions will not be tuned during the parameter learning phase of the GSETSK, therefore they are carefully set using (3.19) to make sure the membership functions are sufficient to cover the entire input space. Any highly overlapping fuzzy sets will be merged as presented in Section 3.3.1.1. It should be noted that the min operation in (3.5) can ensure that, for any rule R_k , when the matching degree $Z_{i,J_i^k}^{II}$ in any arbitrary i th input dimension is small, the firing strength r_k will be small. This subsequently leads to the weakening of the fuzzy rule R_k 's potential, which is computed using (3.14). As a result, R_k can potentially be pruned and replaced by a new fuzzy rule which has new membership functions that represent the current data better. This dynamic mechanism ensures highly distinguishable fuzzy sets that can well-represent data with time-varying characteristics in GSETSK.

3.3.1.1 Merging of Fuzzy Membership Functions

The MSGC technique employed in GSETSK is sufficient to maintain a consistent and compact rule base by performing the procedure *CheckKnowledgeBase* which consists of two steps, namely *CheckSimilarity* and *MergeMembership*. Denote $\mu(m_{i,J_i(t+1)}, \sigma_{i,J_i(t+1)})$ as the new membership function in the i th dimension. After $\mu(m_{i,J_i(t+1)}, \sigma_{i,J_i(t+1)})$ is created using (3.15) and (3.19), the step *CheckSimilarity* is carried out to measure the similarity between $\mu(m_{i,J_i(t+1)}, \sigma_{i,J_i(t+1)})$ and its nearest membership function $\mu(m_{i,\varepsilon}, \sigma_{i,\varepsilon})$.

To determine the similarity measure of two Gaussian fuzzy sets, a fuzzy subset-hood measure [85] is computed. The fuzzy subset-hood measure which defines the degree that fuzzy set A is a subset of fuzzy set B can be approximated by (3.20) [10].

$$S(A, B) = \frac{\max_{x \in U} (\min(\mu_A(x), \mu_B(x)))}{\max_{x \in U} (\mu_A(x))} = \frac{\max_{x \in U} (\min(\mu_A(x), \mu_B(x)))}{1} \quad (3.20)$$

At time t , the procedure *CheckKnowledgeBase* is performed as follows:

Procedure *CheckKnowledgeBase*

Begin

Perform *CheckSimilarity* to determine $S(\mu(m_{i,J_i(t+1)}, \sigma_{i,J_i(t+1)}), \mu(m_{i,\varepsilon}, \sigma_{i,\varepsilon}))$, which is the similarity between the newly created fuzzy set and its nearest membership function $\mu(m_{i,\varepsilon}, \sigma_{i,\varepsilon})$.

IF $S(\mu(m_{i,J_i(t+1)}, \sigma_{i,J_i(t+1)}), \mu(m_{i,\varepsilon}, \sigma_{i,\varepsilon})) > thresA$

Replace the newly created fuzzy set with the ε th one; set $J_i(t+1) = J_i(t)$

ELSE IF $S(\mu(m_{i,J_i(t+1)}, \sigma_{i,J_i(t+1)}), \mu(m_{i,\varepsilon}, \sigma_{i,\varepsilon})) > thresB$

MergeMembership; set $J_i(t+1) = J_i(t)$

ELSE Accept the newly created fuzzy set; set $J_i(t+1) = J_i(t) + 1$ }

End

In the above procedure, $thresA$ and $thresB$ ($thresA > thresB$) are two predefined similarity thresholds used to determine three actions as illustrated in Figure 3-3. The three actions that can be performed in the *CheckKnowledgeBase* procedure are:

1. The newly created fuzzy set is merged with its nearest membership function to create a larger fuzzy set, as shown in Figure 3-3(a).
2. The newly created fuzzy set is replaced by its nearest membership function, as shown in Figure 3-3(b).
3. The newly created fuzzy set is accepted, as shown in Figure 3-3(c).

These two thresholds determine the number of fuzzy sets created. The higher the value of $thresA$ and $thresB$, the more fuzzy sets are created. However, $thresA$ is normally preset at 0.8, which has the semantic meaning that if the matching degree between the new membership function and the ε th membership function is over 80% then the new membership function should be replaced by the ε th one. Similarly, $thresB$ is preset at 0.7. The semantic meaning is that if the matching degree between the new membership function and the ε th membership function is over 70% but below 80%, these two membership functions should be merged. The thresholds of 70% and 80% are considered reasonable for similarity measures [86].

Figure 3-3: Three possible actions in the *CheckKnowledgeBase* procedure

The *MergeMembership* step in the *CheckKnowledgeBase* procedure attempts to merge two highly overlapping membership functions into a Gaussian function with a larger width. However, to maintain the meaning of a membership function and to prevent a membership function from expanding too many times, a *Willingness Parameter (WP)* is employed. *WP* indicates the willingness of a membership function to expand/merge with another membership function. *WP* decreases each time the membership function performs an expansion. At time t , a membership function will not be allowed to merge if its $WP(t) \leq 0$. The parameter *WP* maintains the semantic meaning of a fuzzy set by preventing its width from growing overly large. For the ε th fuzzy set, its *WP* at time t is determined by (3.21),

$$WP(t) = WP(t_u) - \underbrace{(1.5 - WP(t_u))}_{\text{always} \geq 1} \times \underbrace{(1 - S(\mu(m_{i,J_i(t+1)}, \sigma_{i,J_i(t+1)}), \mu(m_{i,\varepsilon}, \sigma_{i,\varepsilon})))}_{\text{always} \geq 0}, \quad (3.21)$$

$$WP(0) = 0.5$$

where t_u indicates the last time when the ε th fuzzy set expands.

The initial value of *WP* is set at 0.5 to make sure *WP* always decreases. The smaller the similarity measure between $\mu(m_{i,J_i(t+1)}, \sigma_{i,J_i(t+1)})$ and $\mu(m_{i,\varepsilon}, \sigma_{i,\varepsilon})$ in (3.21) (meaning the harder it is for the two membership functions to merge), the faster the *WP* of the ε th fuzzy set decreases. Figure 3-4 illustrates how *WP* behaves. Note that the ε th fuzzy set only expands when $S(\mu(m_{i,J_i(t+1)}, \sigma_{i,J_i(t+1)}), \mu(m_{i,\varepsilon}, \sigma_{i,\varepsilon})) \in (thresB, thresA]$.

Figure 3-4: The willingness parameter *WP* decreases after each expansion.

Consider that a Gaussian membership function can be approximated by an isosceles triangle with unity height and the length of its bottom edge equal to $2\sigma\sqrt{\pi}$ [82]; the width and center of the new membership function after merging two arbitrary membership functions (m_1, σ_1) and (m_2, σ_2) , $(m_1 > m_2)$ are determined by (3.22) and (3.23),

$$\sigma_{new} = \frac{m_1 - m_2 + (\sigma_1 + \sigma_2)\sqrt{\pi}}{2\sqrt{\pi}} \quad (3.22)$$

$$m_{new} = [m_1 + m_2 + (\sigma_1 - \sigma_2)\sqrt{\pi}] / 2 \quad (3.23)$$

Merging two membership functions will create a new one with a larger width which can cover a larger region. This leads to fewer fuzzy sets in each dimension. In addition, the fuzzy sets are highly distinguishable. The MSGC clustering technique ensures a consistent and compact knowledge base in the GSETSK network.

3.3.1.2 Comparison Among Existing Clustering Techniques

This section benchmarks MSGC against some of the existing clustering techniques discussed in Section 2.4.1.3, namely FCM [42], LVQ [39], FLVQ [46], FKP [47], PFKP [47], and ECM [11].

Table 3-1: Comparison among existing clustering techniques

Features	Clustering techniques						
	FCM	FKP	PFKP	LVQ	FLVQ	ECM	MSGC
Type of learning	Offline	Offline	Offline	Online	Online	Online	Online
A prior knowledge of number of cluster	Y	Y	Y	Y	Y	N	N
A prior knowledge of upper/lower bounds of dataset	N	N	N	N	N	Y	N
Parameter tuning required	Y	Y	Y	Y	Y	Y	N
Merging functional	N	N	N	N	N	N	Y

Y=Yes, N=No

As can be observed from Table 3-1, MSGC possesses many preferred features, when benchmarked against other popular clustering techniques. In GSETSK, the membership functions need not to be tuned, thus improves the network training speed. Besides, Gaussian membership functions are used to ensure high accuracy as GSETSK attempts to work in real-life fast-changing time-variant environments which require high precision.

3.3.2 Rule Pruning Algorithm

The rule-pruning process in the GSETSK is to remove obsolete fuzzy rules that no longer can model the current data characteristics, and to maintain a compact and current rule base. This can improve the level of human interpretability of the resultant fuzzy rule base. The computed fuzzy rules potentials P_k , $k = 1, \dots, K(t)$ as described in (3.14) are employed to determine which rules will be pruned. At time t , the rule R_k will be pruned if $P_k(t) < \text{thresP}$, where thresP is a predefined parameter. The greater thresP is, the more obsolete rules in GSETSK will be pruned. thresP is normally preset to 0.5. It should be noted that the potential of a newly created rule is defined as unity. The semantic meaning of setting thresP at 0.5 is that if a rule loses half of its initial potential, it should be pruned. Parameters such as thresA , thresB , and thresP can be set to the constants specified above in any experiment, as they only serve to provide the semantic meanings for these constants. After a set of obsolete rules are pruned, the number of rules $K(t+1)$ will be updated accordingly. The rule pruning process may result in obsolete fuzzy label(s) which are not connected to any rule node(s). Therefore, GSETSK will scan through each i th input dimension to accordingly remove any obsolete label and update $J_i(t)$.

Simpl_eTS [74] is among a few TSK fuzzy networks that employs a rule pruning algorithm. Its algorithm monitors the population of each rule. If a rule amounts to less than 1% of the total data samples at that current moment, it will be pruned. This approach considers the contribution of old

data and new data equally in determining the obsolete rules, thus it cannot detect drifts and shifts in online data streams [64].

Together with the novel clustering technique MSGC, the proposed rule pruning algorithm helps GSETSK to address the drift and shift (or regime shifting) behaviors of time-variant data sets. The fuzzy rule potentials in GSETSK work as indicators to detect any drift and shift in the data distribution. Figure 3-5 shows an example of how a rule potential can change over time.

Figure 3-5: A typical example of how the potential of a fuzzy rule can change over time

It should be noted that the proposed rule pruning algorithm cannot work perfectly without the MSGC algorithm. The min operation in (3.5) can ensure that, for any rule R_k , when the matching degree z_{i,j_i^k}'' in any arbitrary i th input dimension is small, the firing strength r_k will be small.

That means that if there is any shift/drift in the data distribution of the input space, the firing strength r_k will be affected. Then, the fuzzy rule R_k 's potential will be weakening, and subsequently, the rule R_k can potentially be pruned and replaced by a new fuzzy rule which has new membership functions that is better representation of the new data distribution.

The proposed rule pruning algorithm in GSETSK is simple, biologically plausible, and fast as it only requires a recursive computation. As analyzed in Section 2.6, most of existing evolving TSK systems cannot give the most accurate solutions for time-variant problems which exhibit regime shifting properties. This can later be demonstrated by the experimental results in Section 3.5. It is obvious that all processes that occur in human activities, such as financial, biological processes are likely to experience concept drifts. In many real life problems, newer data is considered more important (and relevant) than older data. Thus, addressing drifts and shifts is an essential matter that TSK fuzzy neural networks should take into consideration. In the next section, the second phase of learning in GSETSK which is the parameter tuning phase is presented. Figure 3-6 shows the flowchart of the GSETSK learning process.

Figure 3-6: The flowchart of GSETSK learning process.

3.4 Parameter Learning of GSETSK

In this phase, only the consequent parameters in the consequent nodes at layer V will be tuned. In GSETSK, the output node at layer VI, based on the observed data pair (X, D) , is shown in (3.24),

$$\begin{aligned}
 y &= \sum_{k=1}^{K(t)} Z_k^V \\
 &= \sum_{k=1}^{K(t)} \omega_k f_k(X) = \sum_{k=1}^{K(t)} \omega_k [b_{0k} + b_{1k}x_1 + \dots + b_{ik}x_i + \dots + b_{nk}x_n]
 \end{aligned} \tag{3.24}$$

where $B_k = [b_{0k}, \dots, b_{ik}, \dots, b_{nk}]^T$ is the parameter vector of the consequent node C_k ; ω_k is the normalized firing strength at the normalization node N_k .

Assuming that the GSETSK network models a system with T number of training samples $(X(1), d(1)), \dots, (X(t), d(t)), \dots, (X(T), d(T))$. GSETSK adapts a localized version of the recursive linear-least-squares (RLS) algorithm [78] as presented in [10] to reduce the space complexity and the computational cost as well as to enhance the training speed. Assuming that a rule R_k stays in the fuzzy rule base after T number of training samples, and assuming that the GSETSK has only two inputs x_1 and x_2 , a local approximation that can represent the input-output relationships at the consequent node C_k is shown in (3.25),

$$\begin{bmatrix} \omega_k(1) & \omega_k(1)x_1(1) & \omega_k(1)x_2(1) \\ \vdots & \vdots & \vdots \\ \omega_k(t) & \omega_k(t)x_1(t) & \omega_k(t)x_2(t) \\ \vdots & \vdots & \vdots \\ \omega_k(T) & \omega_k(T)x_1(T) & \omega_k(T)x_2(T) \end{bmatrix} \times \begin{bmatrix} b_{0k} \\ b_{1k} \\ b_{2k} \end{bmatrix} = \begin{bmatrix} \omega_k(1)d(1) \\ \vdots \\ \omega_k(t)d(t) \\ \vdots \\ \omega_k(T)d(T) \end{bmatrix} \tag{3.25}$$

Equation (3.25) can be represented in the form of

$$\mathbf{A} \times \mathbf{B} = \mathbf{D} \quad (3.26).$$

Denote a_p as the p^{th} row of the matrix $\mathbf{A}$. Using RLS, $\mathbf{B}$ can be iteratively estimated as

$$\begin{aligned} B_{p+1} &= B_p + C_{p+1} a_{p+1}^T (d^{(p+1)} - a_{p+1} B_p) \\ C_{p+1} &= \frac{1}{\lambda} \left[C_p - \frac{C_p a_{p+1}^T a_{p+1} C_p}{\lambda + a_{p+1} C_p a_{p+1}^T} \right] \end{aligned} \quad (3.27)$$

where $\lambda \in (0,1]$ is the forgetting factor, with an initial condition $C_0 = \mathcal{G} \mathbf{I}$ where $\mathcal{G}$ is a large positive number and $\mathbf{I}$ is the identity matrix of dimension $\beta \times \beta$, where β is the number of consequent parameters of one rule. The localized version of RLS algorithm empowers the GSETSK with fast training ability [10]. The computational cost for this algorithm is only $O((n+1)^2 \times K(t))$ where n is the number of inputs and $K(t)$ is the number of fuzzy rules at time t . For each newly created rule $R_{K(t+1)}$, its parameters are determined by the weighted average of the parameters of the other rules [17]. The weights are the normalized firing strengths of the existing rules. More specifically, the parameters for the rule $R_{K(t+1)}$ are initialized as in (3.28),

$$b_{i,K(t+1)} = \sum_{k=1}^{K(t)} \omega_k b_{i,k} \quad i = 1, \dots, n \quad (3.28)$$

where $[b_{0k}, \dots, b_{ik}, \dots, b_{nk}]^T$ is the parameter vector of the rule R_k and ω_k is the normalized firing strength of the rule R_k . Extensive experiments were conducted to evaluate the performance of the proposed GSETSK against other established neural fuzzy systems. The results are presented in the next section.

3.5 Simulation Results & Analysis

Three different simulations were performed to evaluate the performance of GSETSK, they are, namely: 1) Nonlinear Dynamic System With Nonvarying Characteristics; 2) Nonlinear Dynamic System With Time-Varying Characteristics; and 3) Mackey-Glass Time Series. The background information of the data sets and the objectives of the simulations are given in the respective subsections. In these experiments, an important parameter that needs to be predefined is λ , the forgetting factor which is used in (3.14) to determine the fuzzy rule potentials. The smaller λ is, the faster GSETSK can ‘forget’. In many research works [58], λ is normally set to be in the range [0.97, 0.99]. λ is set at 0.99 in the following experiments.

3.5.1 Online Identification of a Nonlinear Dynamic System With Nonvarying Characteristics

This benchmark investigates the online learning ability of GSETSK to approximate a nonlinear dynamic plant with non time-varying characteristics as described in [12] and [15]. The plant to be learnt is defined by the difference equation (3.29):

$$y(t+1) = \frac{y(t)}{1 + y^2(t)} + u^3(t) \quad (3.29)$$

where $u(t) = \sin(2\pi t / 100)$ is the current input signal and $y(t)$ is the current output signal of the system.

The initial conditions $(u(t), y(t))$ are given as $(0, 0)$, $u(t) \in [-1.0, 1.0]$ and $y(t) \in [-1.5, 1.5]$.

The output of the plant behaves nonlinearly depending on both its past value and input. The purpose is to predict $y(t+1)$ when given $(u(t), y(t))$. 50,000 and 200 observation data points

are, respectively, generated for the purpose of training and evaluating the performance of the proposed GSETSK.

Figure 3-7 shows the highly distinguishable membership functions derived by the GSETSK model and its approximation performance on the test set with 200 data points. One can observe that GSETSK is able to approximate the actual outputs well. In this simulation, the models to be evaluated are MRAN [87], RANEKF [88], SAFIS [12], SONFIN [15], eTS [17], and Simpl_eTS [74]. These models employ incremental learning. Among them, eTS, Simpl_eTS and SONFIN are TSK fuzzy systems. MRAN and RANEKF are radial basis function neural networks. SAFIS is not a TSK model but it is based on the functional equivalence of a radial basis function neural network and a fuzzy system. Table 3-2 benchmarks the performances of the models in this simulation.

Table 3-2: Comparison of GSETSK with other evolving models

Network	Type	Testing RMSE	No of Rules
MRAN	Neural Net	0.0129	10 rule nodes
RANEKF	Neural Net	0.0184	11 rule nodes
SAFIS	Hybrid	0.0116	8 fuzzy rules
SONFIN	T-S	0.0130	10 fuzzy rules
eTS	T-S	0.0082	19 fuzzy rules
Simpl_eTS	T-S	0.0122	18 fuzzy rules
GSETSK	T-S	0.0012	8 fuzzy rules

Table 3-2 shows that GSETSK outperforms the MRAN and RANEKF networks, delivering higher accuracy with fewer rules. It should be noted that MRAN and RANEKF are radial basis function neural networks, therefore they behave like black-box models. Thus, there is no way to explain the derived rules in a human interpretable way. GSETSK can also achieve significantly better results than other TSK systems such as eTS, Simpl_eTS and SONFIN in terms of the number of rules identified and the prediction accuracies for the unseen data in the test set. Only SAFIS can generalize the training data set with the same number of rules as GSETSK. However

SAFIS provides significantly lower prediction accuracy (RMSE = 0.0116). Furthermore, the fuzzy membership functions generated by SAFIS's structural learning process are highly overlapping, which makes it difficult to derive any human interpretable knowledge from the structure of SAFIS. This can be shown in Figure 3-7(d).

For comparison, Figure 3-7 shows the fuzzy membership functions for two inputs [i.e. $(u(t), y(t))$] and an output $y(t+1)$ that GSETSK, SAFIS and SONFIN created to model the nonlinear dynamic plant using the training set described earlier. One can observe that the fuzzy membership functions derived using GSETSK are highly distinguishable, unlike the highly overlapping fuzzy sets derived in SAFIS. There are only 8 fuzzy sets in total generated in GSETSK for both input dimensions, compared against 12 fuzzy sets generated in SONFIN. It should be noted that SONFIN needs to perform fuzzy measure on its membership functions after tuning with back-propagation to achieve results shown in Figure 3-7. This demonstrates that GSETSK derives a more compact and more meaningful interpretable fuzzy rule base than SAFIS or SONFIN and at the same time still achieving favorable accuracy. The average training time reported by GSETSK for 50,000 observations is only 19.01 ± 0.12 s. The total network size is 35 nodes (2 input nodes, 1 output node, 8 nodes for each layer from layer II to layer V) after training 50,000 observations.

Figure 3-7: GSETSK's modeling performance and the fuzzy sets derived by GSETSK, SAFIS and SONFIN, respectively, for comparison.

3.5.2 Analysis Using a Nonlinear Dynamic System With Time-Varying Characteristics

This benchmark investigates the online learning ability of GSETSK to provide an approximate of the nonlinear dynamic plant with time-varying characteristics. The properties of the nonlinear dynamic plant described in Section 3.5.1 are modified as shown in (3.30),

$$y(t+1) = \frac{y(t)}{1+y^2(t)} + u^3(t) + n(t) \quad (3.30)$$

where $n(t)$ is a disturbance to be introduced into the system as shown in (3.31),

$$n(t) = \begin{cases} 0 & 1 \leq t \leq 1000 \text{ and } t \geq 2001 \\ 0.5 & 1001 \leq t \leq 1500 \\ 1 & 1501 \leq t \leq 2000 \end{cases} \quad (3.31)$$

In this benchmark, the GSETSK model is employed to perform online learning of the characteristics of the modified nonlinear dynamic plant for a duration of $t \in [1, 3000]$. It should be noted that the time-variant data generated by this nonlinear dynamic plant exhibits regime shifting properties. More specifically, the data ranges in this simulation vary with time.

Figure 3-8 shows the online modeling performances of the proposed GSETSK. It can easily be observed that GSETSK is able to accurately capture and model the underlying dynamics of the nonlinear dynamic plant described in (3.30). GSETSK continuously changes its structure and parameters to track the new system characteristics in three different scenarios 1) the disturbance is introduced at time $t = 1000$; 2) the disturbance is modified at time $t = 1500$; and 3) the disturbance is removed at time $t = 2000$. More specially, GSETSK creates new rules to learn the underlying characteristics of the new data, then performs parameter tuning to adjust its parameters, and lastly deletes obsolete rules that no longer can describe the new system

characteristics. This results in a dynamic and compact fuzzy rule base in GSETSK. As shown in Figure 3-9, the rule base in GSETSK evolves during the simulation. During time $t \in [1, 200]$, the number of rules gradually moves upward as the network attempts to learn and model the new data. From time $t \in [201, 1000]$, the GSETSK stops adding new rules and the number of rules remains at 10 as these rules are sufficient to describe the current data. There is a significant spike in the GSETSK learning error at time $t = 1000$ as can be observed in Figure 3-9. Also, the number of rules in the GSETSK starts climbing up when the disturbance is introduced to the system at time $t = 1000$. This is due to the GSETSK beginning to evolve in response to the changes in the underlying characteristics of the nonlinear plant. During time $t \in [1001, 1500]$, the number of rules stabilizes at 14 and then gradually decreases to 11 as the obsolete rules that were learnt during time $t \in [1, 1000]$ are gradually pruned from the fuzzy rule base of the GSETSK. This whole process repeats again when the disturbance is modified at time $t = 1500$ and finally, when the disturbance is removed at time $t = 2000$. It should be noted that during time $t \in [1501, 2000]$, the number of rules reaches 10 again, but these 10 rules are different from the 10 rules that the GSETSK learns during the period $t \in [1, 1000]$. This explains why the dynamic GSETSK continues to create new rules to learn the original data again after the disturbance is completely removed at time $t = 2000$.

As mentioned in Section 3.3.3, while Simpl_eTS totally relies on new data in its rule pruning algorithm, GSETSK employs a ‘gradual’ forgetting approach which is based on the fuzzy rule potentials. This explains why the number of rules in the GSETSK stays at 11 long after the disturbance is completely removed at time $t = 2000$, while 10 rules are enough to describe the original data during time $t \in [1, 1000]$. This is because there is one ‘obsolete’ rule that still has its incrementally computed fuzzy rule potential remaining above the pruning threshold. This rule has

been repeatedly activated during the period $t \in [1001, 2000]$. It might be redundant in the period $t \in [2001, 3000]$ but it can enable GSETSK to respond more efficiently if more similar disturbances are introduced to the system from time $t = 3000$ onwards. The average training time reported by GSETSK for 3000 observations is only $2.172 \pm 0.08s$. This demonstrates GSETSK's fast learning ability in incremental time-variant environments.

Figure 3-8: GSETSK's modeling performance during time $t \in [900, 2100]$

Figure 3-9: The evolution of GSETSK's fuzzy rule base and online learning error of GSETSK during the simulation.

3.5.3 Benchmark on Mackey-Glass Time Series

The dynamics of the Mackey–Glass differential delay equation are defined in (3.32). This time series is a popular benchmark problem considered by many researchers. The time series is computed as suggested in Jang’s thesis [89].

$$y(t) = \frac{0.2 y(t - \tau)}{1 + y^{10}(t - \tau)} - 0.1 y(t) \quad (3.32)$$

The fourth-order Runge-Kutta method was applied to compute 6000 observations with time step of 0.1, initial condition: $y(0) = 1.2$, $\tau = 17$ and $y(t) = 0$ for $t < 0$. The goal of the task was to use known values of the time series of past 18, 12, 6, and current time $[y(t - 18), y(t - 12), y(t - 6), y(t)]$ to predict the values $y(t + 85)$ (same as in [11]). From the computed series, 3000 input-output data pairs from $201 \leq t \leq 3000$ were extracted and used as training data; 500 data pairs from $5001 \leq t \leq 5500$ were used as testing data.

Table 3-3 tabulates the performances of the models in this benchmark study. The nondimensional error index (NDEI [90]) which is defined as the root mean-square error (RMSE) divided by the standard deviation of the target series is used to compare the model performance. The evolving models evaluated are RAN [91], eTS [17], Simpl_eTS [74], SAFIS [12] and GSETSK. In this simulation, $\eta = 0.5$ and two values of forgetting factor $\lambda = 0.99$ and $\lambda = 0.97$ are chosen.

Table 3-3: Comparison of GSETSK with other benchmarked models

Network	NDEI	Rules (nodes, units)
SAFIS	0.380	21 rules
eTS	0.356	99 fuzzy rules
Simpl_eTS	0.376	21 fuzzy rules
RAN	0.373	113 units
GSETSK ($\lambda = 0.99$)	0.330	37 fuzzy rules
GSETSK ($\lambda = 0.97$)	0.410	20 fuzzy rules

It can be seen from Table 3-3 that all the models achieve comparable prediction accuracies. When using the forgetting rate $\lambda = 0.99$, GSETSK achieves the smallest NDEI, at the cost of using more rules than SAFIS and Simpl_eTS. However, as mentioned in the first benchmark study (see Section 3.5.1), SAFIS produces membership functions that are highly overlapping, which leads to difficulty in deriving human interpretable knowledge. When using the forgetting rate $\lambda = 0.97$, GSETSK tends to forget the learnt rules faster, resulting in smallest number of rules among all the models, but at the cost of having the highest NDEI. It should be noted that the data set in this simulation is non time-varying, and the testing data is used with the recalling procedure. Thus, if the rules learnt in GSETSK are forgotten quickly during the learning (training) procedure, then the accuracy achieved by GSETSK will drop during the testing (recalling) procedure. This happens when some rules which are learnt during the training procedure and are relevant to the data during the testing procedure might already be pruned before testing is performed. This is a trade-off between achieving high prediction accuracy and having a compact and up-to-date fuzzy rule base that GSETSK encounters in recall. However, it should be noted that GSETSK is designed to perform swift learning in time-varying environments by achieving a dynamic and current rule base. Compared to the rule pruning algorithm employed in Simpl_eTS, the approach in GSETSK can respond more efficiently if repeated disturbances occur in the time-varying environment, as has been analyzed earlier in the second benchmark (see Section 3.5.2). Figure 3-10 shows the evolution of the fuzzy rules for SAFIS, eTS, Simpl_eTS and GSETSK. Figure 3-11 shows the membership functions that GSETSK creates in the benchmark using the forgetting rate $\lambda = 0.97$. It can be observed that the membership functions in GSETSK are highly distinguishable.

(a)

(b)

Figure 3-10: The evolution of the fuzzy rules for (a) SAFIS, eTS, Simpl_eTS and (b) GSETSK

Figure 3-11: Semantic interpretation of the fuzzy sets in GSETSK for the Mackey-Glass data set.

3.6 Summary

This chapter presents a novel self-evolving Takagi–Sugeno–Kang fuzzy framework named GSETSK. It adopts an online data-driven incremental-learning-based-approach using the perspective of strict online learning as defined in [6]. GSETSK can account for time-varying characteristics for time-variant environments. GSETSK also attempts to address the issue of achieving compact and up-to-date fuzzy rule bases in TSK models by using a simple and biologically plausible rule pruning approach. This algorithm enables GSETSK to model complex and time-variant problems which exhibit regime shifting properties. It also improves the interpretability of derived knowledge bases by using a novel fuzzy set merging approach.

The GSETSK network employs a novel clustering technique known as MSGC to compute the bell-shaped (Gaussian) fuzzy sets during its structure learning. MSGC does not require *prior*

knowledge of the number of cluster/fuzzy rules in the data set. Using a dynamic approach as stated in Section 3.2.1, MSGC attempts to generate a compact fuzzy rule base with highly distinguishable fuzzy sets which do not require parameter-tuning. In addition, GSETSK also employs a ‘gradual’-forgetting-based rule pruning approach which is based on the fuzzy rule potentials to delete obsolete rules in its fuzzy rule base over time. This is the main difference between GSETSK and other evolving TSK fuzzy systems. It enables GSETSK to possess an up-to-date and better interpretable fuzzy rule base while maintaining a high level of modeling accuracy when operating in time-varying conditions. It also helps GSETSK to efficiently and accurately address time-variant problems which exhibit regime-shifting properties. The fuzzy rule potentials in GSETSK are reinforced or weakened depending on the relevance between the fuzzy rules and the current data using brain-like learning mechanisms. This provides GSETSK with a ‘smooth’ learning ability in time-variant environments in which disturbances might occur repeatedly. To tune the consequent parameters, GSETSK adopts a localized version of the *recursive linear-least-squares (RLS) algorithm* for high accuracy with fast speed.

The performance of the GSETSK network was evaluated using three simulations. The results of the GSETSK network are encouraging when benchmarked against other evolving neural networks and TSK fuzzy systems. GSETSK can be used in more challenging real-life applications in the areas of medical or financial data analysis, signal processing and biometrics. The work in [92] demonstrates the effectiveness of using the GSETSK network in the modeling and forecasting of real-life stock prices. It is a preliminary work on building an effective stock trading decision model that can be applied on real-life stock dataset. Such a stock trading system is presented in Chapter 5 in full details. The next chapter presents an enhanced recurrent version of GSETSK which is focused on dealing with temporal problems.

Chapter 4: Recurrent Self Evolving TSK Fuzzy Neural Network (RSETSK)

Anyone who stops learning is old, whether at twenty or eighty. Anyone who keeps learning stays young. The greatest thing in life is to keep your mind young.

Henry Ford (1863-1947)

4.1 Introduction

Extensive experimentation has shown that the class of feedforward fuzzy neural networks is capable of obtaining successful results in complex real life applications, including modeling and control of highly complex systems. However, their counterparts, recurrent fuzzy neural networks, have been shown to work better for applications involving temporal relationships, which most often occurred in many areas of engineering. In such applications, the output is often a nonlinear function of past output or past input or both. To solve such type of problems, a feedforward network such as GSETSK generally requires the knowledge of number of delayed input and output in advance. However, in practice, the exact order of the temporal problem is usually unknown. Furthermore, using feedforward network in temporal problems will increase the input dimension and results in a large network size [23]. Hence, there is a continuing trend of using recurrent fuzzy neural networks for dealing with temporal and dynamic problems. The main reason is recurrent networks are capable of implementing memories which give them the possibility of retaining information to be used later. By their inherent characteristic of memorizing past information, recurrent networks are good candidates to process patterns with spatio-temporal dependencies, such as nonlinear prediction of time series [93]. Thus, this chapter proposes a novel recurrent fuzzy neural network called RSETSK (recurrent self-evolving Takagi-

Sugeno-Kang fuzzy neural network). RSETSK is an enhanced version of GSETSK to address temporal problems. Similar to GSETSK, RSETSK is able to address the time-variant data sets that exhibit drift and shift behaviors.

This chapter is organized as follows. Section 4.2 briefly discusses the general structure of RSETSK and the differences between RSETSK and GSETSK. Section 4.3 presents its learning algorithms. Section 4.4 briefly evaluates the performance of the RSETSK models using three different simulations. These simulations have the following goals:

1. Demonstrate the online incremental learning ability of RSETSK in complex environments such as the nonlinear dynamic temporal system with nonvarying characteristics (in Section 4.4.1). The number of rules derived in RSETSK also demonstrates that RSETSK can result in smaller network size compared to its non-recurrent version GSETSK.
2. Demonstrate the ability of RSETSK to work in time-variant environments such as the nonlinear dynamic temporal system with time-varying characteristics (in Section 4.4.2). The evolving rule base of RSETSK is also illustrated, to show how RSETSK can keep a current and relevant rule base in temporal problems.
3. Demonstrate the superior performance of RSETSK when benchmarked against other evolving models using the Dow Jones Index Time Series prediction problem (in Section 4.4.3)

4.2 Architecture & Neural Computations

Figure 4-1 shows the six-layer structure of the proposed RSETSK model, which is almost similar to the GSETSK model. The detailed mathematical functions of each layer of RSETSK are also similar to its non-recurrent version, GSETSK. However there are two main differences between RSETSK and GSETSK. They are: 1) Layer III in RSETSK is a recurrent layer 2) RSETSK has backward connections from layer VI to layer IV via layer V. These differences are briefly presented below.

Figure 4-1: Structure of the RSETSK network

4.2.1 Recurrent Properties in RSETSK

Layer III in RSETSK is a recurrent rule layer. Each node in this rule-base layer represents a single Sugeno-type fuzzy rule and is termed a *rule node*. The spatial firing strength of a rule node R_k is computed based on the activation of its antecedents as in (4.1),

$$r_k(X) = \min_{i=1,\dots,n} (\mu_{i,j_k^i}(x_i)), \quad k = 1, \dots, K(t) \quad (4.1)$$

where $\mu_{i,j_k^i}(x_i)$ is the membership value of the j_k^i th linguistic label of the i th input x_i that connects to the k th rule, as illustrated in Figure 4-1; and r_k is the forward spatial firing strength of R_k . The spatial firing strength r_k is only a part of the output of a rule node. Note that each node in this layer has an internal feedback loop. At time t , the output of a recurrent rule node R_k is a temporal firing strength $\psi_k(X(t))$, which is a combination of the current spatial firing strength $r_k(X(t))$ and the previous temporal firing strength $\psi_k(X(t-1))$ as in (4.2),

$$\psi_k(X(t)) = (1 - \beta_k(t))r_k(X(t)) + \beta_k(t)\psi_{k-1}(X(t-1)) \quad (4.2)$$

where $\beta_k(t) \in [0,1]$ is a feedback weight that determines how the previous temporal firing strength affects the current one. The feedback weights are initialized randomly and will be subsequently tuned in the parameter learning phase.

Although the RSETSK appears structurally similar to other recurrent self-evolving networks such as RSONFIN [22], TRFN [23], HO-RNFS [71], and RSEFNN [59], there are distinct differences between them. In the recurrent systems mentioned above, the membership functions are highly overlapping and indistinguishable due to the use of back-propagation or gradient descent algorithms to heuristically tune the membership functions. In addition, the number of membership functions and fuzzy rules in these systems will grow monotonically, especially when working in

time-variant environments where new data keeps coming in continuously. In contrast, the RSETSK employs a Hebbian-based rule pruning algorithm which takes into consideration the *backward connections* from layer VI to layer IV via layer V.

4.2.2 Fuzzy Rule Potentials in RSETSK

RSETSK uses the backward connections from layer VI to layer IV via layer V to compute its fuzzy rule potentials, which is quite different from the GSETSK model. In GSETSK, the backward connections are from layer VI to layer III via layer V. The reason is the forward firing strengths of the rule nodes at layer III in GSETSK are already in the range $(0, 1]$, thus they can be used directly in (3.13) to compute the fuzzy rule potentials, together with their backward counterparts. In contrast, the temporal firing strengths of the recurrent rule nodes at layer III in RSETSK (computed as in (4.2)) are not normalized, thus the normalized firing strengths at layer IV are used instead to compute the fuzzy rule potentials. The rule pruning algorithm in RSETSK is similar its non-recurrent version's pruning algorithm. The RSETSK also adopts the Hebbian learning mechanism to compute its fuzzy rule potentials. For each rule R_k , the forward normalized temporal firing strength ω_k has been described in (4.2), and the backward firing strength ω_k^{back} is similarly computed in two steps as in GSETSK.

Currently, there are very few recurrent networks that possess a rule pruning algorithm. Although recurrent networks can memorize the patterns with spatio-temporal dependencies, these well-memorized patterns can be obsolete in many cases, especially in datasets that exhibit regime shifting properties, in which the data ranges may vary over time. RSETSK implements a rule-pruning algorithm which relies on fuzzy rule potentials to delete obsolete fuzzy rules that can no longer describe the current observed data characteristics. The potential P_k of a rule R_k in RSETSK indicates its importance or influence in the entire rule base of the system. So the idea of

pruning a rule is simple: If a rule is no longer important, it should be deleted. At any time t , the potential P_k of a fuzzy rule R_k can be recursively computed based on the current training data $(X(t), d(t))$ as shown in (4.3),

$$P_k(t) = \lambda P_k(t-1) + \psi_k(X(t)) \times \psi_k^{back}(d(t)) \quad \lambda \in (0,1] \quad k = 1, \dots, K(t) \quad (4.3)$$

where $P_k(t-1)$ is the potential of rule R_k at time $(t-1)$; $\omega_k(X(t))$ is the forward firing strength of rule R_k as given in (4.2); and $\omega_k^{back}(d(t))$ is the backward firing strength of rule R_k , λ is the forgetting factor. The smaller λ is, the faster the effects of old learning decay. The rule R_k will be pruned if $P_k(t)$ falls below the predefined parameter $thresP$. This helps to maintain a set of up-to-date fuzzy rules that best describes the current characteristics of the incoming data. Furthermore, the rule base will be more compact and can be better interpreted by human experts.

4.3 Learning Algorithms of RSETSK

At each arrival of data observations $(X(t), d(t))$, RSETSK performs its learning process which consists of two phases; namely structural and parameter learning. Its structural learning phase which is similar to GSETSK is not described here. This section only discusses the parameter learning phase of RSETSK. The primary objective of this phase is to minimize the difference [denoted as error $E(t)$] between the computed network output $y(t)$ and the desired output $d(t)$ as formulated in (4.4),

$$\text{minimize} \quad E(t) = \frac{1}{2} [y(t) - d(t)]^2 \quad (4.4)$$

Similar to GSETSK, RSETSK also use the recursive least square algorithm (RLS) [78] to tune its consequent parameters. The output at layer VI based on the observed data pair (X, D) is shown in (4.5),

$$\begin{aligned}
 y &= \sum_{k=1}^{K(t)} o_k \\
 &= \sum_{k=1}^{K(t)} \omega_k f_k(X) = \sum_{k=1}^{K(t)} \omega_k [b_{0k} + b_{1k}x_1 + \dots + b_{ik}x_i + \dots + b_{nk}x_n]
 \end{aligned} \tag{4.5}$$

where $B_k = [b_{0k}, \dots, b_{ik}, \dots, b_{nk}]^T$ is the parameter vector of the consequent node F_k ; ω_k is the normalized firing strength at the normalization node N_k . Assume that the RSETSK network models a system with T training samples $(X(1), d(1)), \dots, (X(t), d(t)), \dots, (X(T), d(T))$.

Also assume that a rule R_k stays in the fuzzy rule base after T training samples, and the RSETSK has only two inputs x_1 and x_2 . A local approximation that can represent the input-output relationships at the consequent node F_k is shown in (4.6),

$$\begin{bmatrix} \omega_k(1) & \omega_k(1)x_1(1) & \omega_k(1)x_2(1) \\ \vdots & \vdots & \vdots \\ \omega_k(t) & \omega_k(t)x_1(t) & \omega_k(t)x_2(t) \\ \vdots & \vdots & \vdots \\ \omega_k(T) & \omega_k(T)x_1(T) & \omega_k(T)x_2(T) \end{bmatrix} \times \begin{bmatrix} b_{0k} \\ b_{1k} \\ b_{2k} \end{bmatrix} = \begin{bmatrix} \omega_k(1)d(1) \\ \vdots \\ \omega_k(t)d(t) \\ \vdots \\ \omega_k(T)d(T) \end{bmatrix} \tag{4.6}$$

Or matrix form:

$$\mathbf{A} \times \mathbf{B} = \mathbf{D} \tag{4.7}$$

Denote a_p as the p^{th} row of the matrix $\mathbf{A}$. Using RLS, $\mathbf{B}$ can be iteratively estimated as in (4.8).

$$\begin{aligned}
 B_{p+1} &= B_p + C_{p+1} a_{p+1}^T (d^{(p+1)} - a_{p+1} B_p) \\
 C_{p+1} &= \frac{1}{\lambda} \left[C_p - \frac{C_p a_{p+1}^T a_{p+1} C_p}{\lambda + a_{p+1} C_p a_{p+1}^T} \right]
 \end{aligned} \tag{4.8}$$

where $\lambda \in (0,1]$ is a forgetting factor, with initial condition $C_0 = \vartheta \mathbf{I}$ where ϑ is a large positive number and $\mathbf{I}$ is the identity matrix of dimension $\beta \times \beta$, where β is the number of consequent parameters of one rule.

In order to further improve the speed of the parameter learning phase, a new approach can be considered, in which not all the rules in RSETSK need to perform parameter tuning. Only the consequent parameters of the most important rules are tuned. Assume the current rule base of RSETSK is $\{R_k\}_{k=1,\dots,K(t)}$. The fuzzy rule potentials determined in (4.3) can be used to rank the fuzzy rules in the descending order of importance. The parameter tuning process can be performed as follows.

Repeat

- 1) Find the most important rule $R_{k'}$ in $\{R_k\}_{k=1,\dots,K(t)}$ which has not been tuned:

$$k' = \arg \max_{1 \leq k \leq K(t)} P_k(t) \tag{4.9}$$

- 2) Tune the parameters of rule $R_{k'}$ using (4.8). Activate the network to get the new output $o_{k'new}$. Get the new network output y_{new} as in (4.10),

$$y_{new} = y_{old} - o_{k'old} + o_{k'new} \tag{4.10}$$

- 3) Get the new network error $E_{new}(t)$ using (4.4).
- 4) Mark the rule $R_{k'}$ as having been tuned.

Until $E_{new}(t) < thresE$ or all rules have been tuned.

The feedback weight $\beta_k(t)$ is tuned by gradient descent algorithm as in (4.11)

$$\beta_k(t) = \beta_k(t) - \phi \frac{\partial E(t)}{\partial \beta_k(t)} \quad (4.11)$$

where ϕ is a learning constant and

$$\begin{aligned} \frac{\partial E(t)}{\partial \beta_k(t)} &= \frac{\partial E(t)}{\partial y(t)} \cdot \frac{\partial y(t)}{\partial \omega_k(t)} \cdot \frac{\partial \omega_k(t)}{\partial \beta_k(t)} \\ &= (y(t) - d(t)) \cdot f_k(X(t)) \cdot \frac{\sum_{k=1}^{K(t)} \psi_k(t) - \psi_k(t)}{\psi_k^2(t)} \cdot (\psi_k(t-1) - r_k(t)) \end{aligned} \quad (4.12)$$

4.4 Simulation Results & Analysis

Three different simulations were performed to evaluate the performance of RSETSK. They are, namely: 1) Nonlinear Dynamic System; 2) Nonlinear Dynamic System With Regime-shifting Properties; and 3) Dow Jones Index Time Series. Similarly to GSTSK, in all experiments, two important predefined parameters need to be noted. They are, namely: 1) λ - the forgetting factor, and 2) η - the overlapping degree.

4.4.1 Online Identification of a Nonlinear Dynamic System

This experiment investigates the online learning ability of RSETSK to approximate a nonlinear dynamic plant as described in [22] and [23]. The plant to be learnt is defined by (4.13):

$$y_p(t+1) = f(y_p(t), y_p(t-1), y_p(t-2), u(t), u(t-1)) \quad (4.13)$$

where

$$f(x_1, x_2, x_3, x_4, x_5) = \frac{x_1 x_2 x_3 x_4 x_5 (x_3 - 1) + x_4}{1 + x_3^2 + x_2^2} \quad (4.14)$$

As seen from (4.13), the output of the plant depends on three previous outputs and two previous inputs. Normally, a feedforward network needs five input nodes to feed the appropriate past values of output y_p and input u . However, due to the recurrent property of RSETSK, only the current values $y_p(t)$ and $u(t)$ needed to be used as inputs in the network. The feedback structure of the RSETSK is able to capture the dependence of the system's output on past output and input values. To compare with previous studies on the problem, the training is done with 10 epochs of 900 time steps each. The input $u(t)$ is an independent and identically distributed uniform sequence over the interval $[-2, 2]$ for half of the 900 time steps, and a sinusoidal $1.05 \sin(\pi k / 45)$ for the remaining time period. Note that there is no repetition of the training data in any of the 10 epochs. In this experiment, $\lambda = 0.99$ and $\eta = 0.5$ are chosen. The models to be evaluated are memory neural network [94], RFNN [95], RSONFIN [22], TRFN [23], HORNFS [71], and RSEFNN [59]. These models are all recurrent networks. A similar experiment has been done in [22] to verify the superior performance of the recurrent networks over feedforward networks. For the testing experiments, the following input signal is used:

$$u(t) = \begin{cases} \sin(\pi t / 25) & t < 250 \\ 1.0 & 250 \leq t < 500 \\ -1.0 & 500 \leq t < 750 \\ 0.3 \sin(\pi t / 25) + 0.1 \sin(\pi t / 32) + 0.6 \sin(\pi t / 10) & 750 \leq t < 1000 \end{cases} \quad (4.15)$$

Table 4-1 benchmarks the performances of the models in this experiment. Figure 4-2 shows the highly distinguishable membership functions derived by the RSETSK model and the performance of RSETSK. One can observe that RSETSK can closely mimic the actual outputs.

(a)

(b)

Figure 4-2: Nonlinear Dynamic System (a) Outputs of the plant and the performance of RSETSK (b) Fuzzy sets derived by RSETSK

Table 4-1: Comparison of RSETSK against other recurrent models

Network	Training time steps	Training RMSE	Testing RMSE	No of Rules
Memory neural net	90000	0.1521	0.2742	NA
TRFN-S	9000	0.0084	0.0346	3
RSONFIN	9000	0.0248	0.0780	4
HO-RNFS	9000	0.0542	0.0815	3
RSEFNN-LF	9000	0.0199	0.0397	4
RFNN	10000	0.0114	0.0575	16
GSETSK	9000	0.0201	0.0062	5
RSETSK	9000	0.0198	0.0057	4

Table 4-1 shows that RSETSK outperforms the other networks in terms of testing RSME, while using a comparable number of rules. It should be noted that memory neural network [94] behaves like black-box models, in which there is no way to derive any human interpretable rules. RSETSK can also achieve significantly better results than other recurrent systems in training RSME, except TRFN-S and RFNN. However, RFNN is a network with a fixed structure, which requires the number of rules to be specified prior to training. All recurrent models such as TRFN-S [23], RSONFIN [22], HO-RNFS [71], and RSEFNN [59] employ gradient descent or back-propagation algorithms to tune the centers and widths of their fuzzy sets in their parameter training phase, which eventually leads to highly overlapping fuzzy sets. Hence, it is difficult to derive human interpretable knowledge from the structure of these recurrent models.

In RSONFIN [22] and RSEFNN [59], there are 9 and 8 fuzzy sets, respectively, generated in the two input variables $y_p(t)$ and $u(t)$. In RSETSK, only 4 fuzzy sets are generated in the two input variables. Figure 4-2 shows the fuzzy membership functions for two inputs that RSETSK created to model the nonlinear dynamic plant using the training set described earlier. One can observe

that the fuzzy membership functions derived using RSETSK are highly distinguishable. The merging approach in RSETSK helps the network to derive a compact and meaningful interpretable fuzzy rule base while still achieving favorable accuracy.

4.4.2 Analysis Using a Nonlinear Dynamic System With Regime-shifting Properties

This experiment investigates the online learning ability of RSETSK to provide an approximate of the nonlinear dynamic plant with regime shifting properties. The properties of the nonlinear dynamic plant described in Section 4.4.2 are modified as shown in (4.16),

$$y_p(t+1) = f(y_p(t), y_p(t-1), y_p(t-2), u(t), u(t-1)) + n(t) \quad (4.16)$$

where $n(t)$ is a disturbance to be introduced into the system given by

$$n(t) = \begin{cases} 0 & 1 \leq t \leq 1000 \text{ and } t \geq 2001 \\ 2 & 1001 \leq t \leq 2000 \end{cases} \quad (4.17)$$

In this experiment, the RSETSK model is employed to perform online learning of the characteristics of the modified nonlinear dynamic plant for a duration of $t \in [1, 3000]$. It should be noted that the time-variant data generated by this nonlinear dynamic plant exhibits regime shifting properties. More specifically, the data ranges in this experiment vary with time. For the entire simulation $t \in [1, 3000]$, the control inputs $u(t)$ are generated as follows.

$$u(t) = \begin{cases} \sin(\pi t / 25) & (t \bmod 1000) < 250 \\ 1.0 & 250 \leq (t \bmod 1000) < 500 \\ -1.0 & 500 \leq (t \bmod 1000) < 750 \\ 0.3 \sin(\pi t / 25) + 0.1 \sin(\pi t / 32) + 0.6 \sin(\pi t / 10) & 750 \leq (t \bmod 1000) < 1000 \end{cases} \quad (4.18)$$

Figure 4-3 shows the online modeling performances of the proposed RSETSK. It can easily be observed that RSETSK is able to accurately capture and model the underlying dynamics of the nonlinear dynamic plant described in (4.16). The RSETSK continuously changes its structure and parameters to track the new system characteristics in two different scenarios 1) the disturbance is introduced at time $t = 1000$; 2) the disturbance is removed at time $t = 2000$. More specifically, RSETSK creates new rules to learn the underlying characteristics of the new data, then performs parameter tuning to adjust its parameters, and lastly deletes obsolete rules that no longer can describe the new system characteristics. This results in a dynamic and compact fuzzy rule base in RSETSK. As shown in Figure 4-4, the rule base in RSETSK evolves during the simulation. During time $t \in [1, 250]$, the number of rules gradually moves upward as the network attempts to learn and model the new data. From time $t \in [250, 1000]$, the RSETSK stops adding new rules and the number of rules remains at 4 as these rules are sufficient to describe the current data. At time $t = 1000$, there is a significant shift in input data range as can be observed in Figure 4-3. Also, the number of rules in the RSETSK starts climbing up when the disturbance is introduced to the system at time $t = 1000$. This is due to the RSETSK beginning to evolve in response to the changes in the underlying characteristics of the nonlinear plant. During time $t \in [1001, 1500]$, the number of rules goes up to 7 and then gradually decreases to 5 as the obsolete rules that were learnt during time $t \in [1, 1000]$ are gradually pruned from the fuzzy rule base of the RSETSK. It should be noted that during time $t \in [1750, 2000]$, the number of rules stabilizes at 6. Among these 6 rules, 4 of them are new rules that are learnt during time $t \in [1000, 2000]$, the remaining two are obsolete rules that are learnt during time $t \in [1, 1000]$. Not all the obsolete rules are pruned during time $t \in [1000, 2000]$, because RSETSK employs a ‘gradual’ forgetting approach which is based on the fuzzy rule potentials. Since the potentials of some obsolete rules are still above the pruning threshold, the rules are not pruned yet. They will be pruned, if in the next time

steps they are still not activated. This whole process repeats again when the disturbance is removed at time $t = 2000$. RSETSK continues to create new rules to relearn the original data after the disturbance is completely removed at time $t = 2000$. The number of rules finally stabilizes at 4 again after the rules learnt during time $t \in [1000, 2000]$ are pruned.

It can be observed that, in this experiment, if RSETSK does not possess a rule pruning algorithm, it might finish the learning process with 8 rules, with many of which being obsolete. Existing recurrent networks such as RSONFIN [22], TRFN [23], HO-RNFS [71], and RSEFNN [59] do not consider this issue, resulting in obsolete rule bases with many redundant rules when they deal with time-variant datasets with regime shifting properties as in this experiment. G-FNN recurrent networks [96] basically employ the outputs of their feedforward version to feed back to their fuzzy rules. No internal memory structure is implemented in G-FNN, so their recurrent models do not have much advantage over their feedforward models [96]. Although a rule pruning algorithm is mentioned in G-FNN, the approach's computational cost is high. Also, since GFNN does not differentiate between new data and past data, well-learnt information in GFNN can be easily forgotten. The 'gradual' forgetting approach in RSETSK allows 'smooth' learning in time-variant environments in which disturbances might occur repeatedly. The average training time reported by RSETSK for 3000 observations is only $1.855 \pm 0.08s$. This demonstrates RSETSK's fast learning ability in incremental time-variant environments.

Figure 4-3: RSETSK's modeling performance during time $t \in [1, 3000]$

**Figure 4-4: RSETSK's self-evolving process (a) The evolution of RSETSK's fuzzy rule base
(b) Online learning error of RSETSK**

4.4.3 Analysis Using Dow Jones Index Time Series

This experiment investigates the online learning ability of RSETSK using a real-world financial time-series based on the Dow Jones Industrial Average (DJIA) market index. About 50 years of daily index values were collected from the Yahoo! Finance website on the ticker symbol “^DJI” for the period from January 4, 1960 to December 31, 2010, which provided 12,838 data points for the experiment. Figure 4-5 shows the time-variant behavior of the time series with a nonuniform distribution in the range $[535.76, 14165.00]$. It can be observed that after a long quiet time in the period 1960-1980, there are significant shifts in data ranges after the 1980s. The daily movements also become sharper with many noteworthy peaks and troughs. It should be noted that RSETSK is an online structure which does not require any prior knowledge of the complete set of

data points at any point in time. In this experiment, RSETSK attempts to perform an online simulation of the daily forecast of the Dow Jones index using the following input and output vectors

$$\text{input vector} = [y(t-3), y(t-2), y(t-1), y(t)]$$

$$\text{output vector} = [y(t+1)]$$

where $y(t)$ is the absolute value from the Dow Jones index time series.

Previous studies [97] have shown that evidence of nonlinear predictability in the stock market can be found using past data values. In this experiment, the system output does not depend only on the 4 past states $y(t-3)$, $y(t-2)$, $y(t-1)$ and $y(t)$ but also on other further past states. A feedforward network with these 4 states normally does not include past states beyond $y(t-3)$. In contrast, the recurrent structure in RSETSK can memorize the past states prior to $y(t-3)$ for output prediction. Based on availability constraints, the experiment was benchmarked against DENFIS [11] and GSETSK as a reference model. DENFIS is a feedforward self-evolving network but it is not fully online as it implicitly assumes prior knowledge of the upper and lower bounds of the data set to normalize data before learning.

Table 4-2: Forecasting 50 years of Dow Jones Index

Network	R	NDEI	No of Rules
DENFIS	0.998	0.019	6
GSETSK	0.998	0.022	8
RSETSK	0.998	0.020	6

Figure 4-5 shows that RSETSK can quickly mimic the movements of the time series. All the peaks and troughs are well predicted. It can be seen from Table 4-2 that RSETSK has almost similar results as DENFIS although RSETSK performs the estimation completely online without

prior knowledge of the complete data set. Also, from Figure 4-6, one can observe that the rule base in RSETSK evolves over time. More specifically, new rules are added to describe new data and obsolete rules are pruned to maintain a compact and up-to-date rule base at all time. During the simulation, there are at least 7 major reorganizations in the rule base. RSETSK outperforms its feedforward version GSETSK in this experiment. The average simulation time reported by RSETSK for 12,838 data points is only 8.375 ± 0.05 s. This demonstrates RSETSK's fast learning ability in real-life problems.

Figure 4-5: Dow Jones time series forecasting results.

Figure 4-6: The evolution of the fuzzy rules in RSETSK

Figure 4-7: Highly interpretable knowledge base derived by RSETSK.

4.5 Summary

This chapter presents a novel recurrent self-evolving Takagi–Sugeno–Kang fuzzy framework named RSETSK. Similar to its non-recurrent version GSETSK, it employs MSGC for its structural learning phase and adopts an online data-driven incremental-learning-based-approach. The main difference between RSETSK and GSETSK is that Layer III in RSETSK is a recurrent layer. This recurrent structure allows RSETSK to address temporal problems better than GSETSK, resulting in a smaller network size. It also does not require the knowledge of number of delayed input and output in advance. The performance of the RSETSK network was evaluated using three simulations. The results of the RSETSK network are encouraging when benchmarked against other recurrent systems. The third experiment, a stock index prediction simulation, demonstrates the applicability of RSETSK in real world problems.

Chapter 5: Stock Market Trading System – A Financial Case Study

People who are high-level investors are not concerned about the market going up or going down because their knowledge will allow them to make money either way.

Robert Kiyosaki (1947-)

5.1 Introduction

The prediction of stock market movements has become a thriving research topic and, if successful, may result in substantial financial rewards. In practice, there are two major approaches to the analysis of stock market movement prediction; namely: Fundamental and technical analysis. Fundamental analysis is based on economic, financial and other qualitative and quantitative factors to estimate the intrinsic values of the securities [98]. Technical analysis is based on the foundation that history will repeat itself and that the correlation between price and volume reveals market behaviors [99]. More specifically, this approach studies past market data to predict future movements. A well known hypothesis amongst academics, the Efficient Market Hypothesis (EMH) [100], suggests that the prediction of stock market prices is futile and implies that the technical analysis approach to forecasting is invalid. However, the hypothesis is highly controversial. Many recent works [101-103] from statistical and behavioral finance perspectives have challenged the EMH and have exemplified the evidence on the predictability of stock market using technical analysis. In the real world, technical analysis is becoming more popular and is widely used among traders and financial professionals.

Recently, computational intelligence techniques such as neural networks [104] are widely used for stock market prices or stock market trend prediction [105]. Neural networks are extensively

employed for technical financial forecasting because of their ability to learn non-linear complex patterns in data and self-adaptation for various statistical distributions. More specifically, they are universal function approximators, meaning that they can capture and model any input-output relationship given the right data and configuration. In [106], the authors reported that neural networks outperformed other non-neural approaches in most of forecasting studies. In [97], a single layer feedforward neural network was used to predict security returns from past real-world returns. The results indicate strong evidence of nonlinear predictability in stock market returns. In [107], a neural network was employed to predict the proper time to move money into and out of the stock market. The results significantly outperformed the buy-and-hold strategy. However, despite yielding promising results in stock market prediction, neural networks are mainly considered as black-box models because their knowledge is represented by links and weights. There is no way to derive any human interpretable information from the networks.

Subsequently, there is a continuing trend in using fuzzy neural networks (FNNs) [4] to predict the stock market. Some works that applied FNNs in forecasting stocks are [99], [108-112]. In [108], an Adaptive Neural Fuzzy Inference System (ANFIS) [7] is used to predict future trends. In [99], ANFIS is used to control the stock market process model. The disadvantage of ANFIS is that it is unable to learn in an incremental manner [6] due to its fixed structure. In [109], a rough-set based neuro-fuzzy system named RSPOP was used as a stock predictive model which employs the time-delayed price difference forecast approach. The approach is claimed to perform better than the price forecast approach because it avoids the deterministic shifts in range of values of out-of-sample forecasts. However, RSPOP employs a batch learning approach and is computationally expensive because of its post-training process based on rough-set theory for information and optimization [58]. In [112], a hybrid system integrating a wavelet and TSK fuzzy rules is proposed. The method employs offline learning algorithm and requires preprocessing of data. In

[110], a FNN called GLC is proposed for predicting stock prices. The advantage of GLC is that it can address the time-variant datasets. In [111], a trading system using a hierarchical coevolutionary fuzzy system to predict a series of percentage price oscillator (PPO) is proposed. Both GLC [110] and HiCEFS [111] employ genetic algorithms, which are generally slow and computationally costly.

In this chapter, we propose a stock trading decision model with a novel price prediction model empowered by RSETSK, a recurrent self-evolving Takagi-Sugeno-Kang fuzzy neural network. RSETSK possesses dynamic structure with online learning/unlearning abilities and can learn incrementally in time-variant environments. It is fast, interpretable, biologically plausible, and potentially, of superior performance. Unlike existing price prediction models, RSETSK employs a novel rule pruning algorithm to keep a compact and current rule base at all times. Besides, by inheriting the advantages of recurrent networks, RSETSK is able to outperform other prediction models in the literature in terms of accuracy.

5.2 Stock Trading System Using RSETSK

The main approach in stock trading is to identify early trends and maintain an investment position (long, short, or hold) until evidence indicates that the trend has reversed. It is obvious that trends in stock prices can be very volatile, almost chaotic at times. Investors generally rely on two types of market analysis to identify the trends: fundamental and technical. Fundamental analysis focuses on the reasons of price movement, and this process is very complicated since there are so many factors that may affect the price change such as political, psychotically events [113]. Technical analysis [101] is the study of market action, based on the foundation that the market action discounts everything. It assumes that anything that can possibly affect the market is already reflected in the prices, and all the new information will be immediately reflected in those prices. Compared with fundamental analysis, technical analysis can be easily performed for any

stock because it only analyzes the historical quantitative data that are easy to obtain, such as the price and volume. Thus, stock trading systems usually employ the results of the technical analysis to generate trading signals accordingly.

In this section, a stock trading system with the RSETSK predictive model is presented. In order to assess the trading performance of the proposed approach, a stock trading system without a predictive model is also introduced. Profits and losses generated by all systems will be compared. Assume the price value of a security is represented as a time series $u(T)$, where $u(t)$ represents a value at time instant t . In all systems, the trading action at time t is denoted as $F(t)$ where $F(t) \in \{-1, 1\}$ with -1 and 1 representing the buy and sell actions, respectively. The trading system return is subsequently modeled by the final portfolio value using a multiplicative return $R(t)$ [114] given in (5.1),

$$R(t) = R(t-1)\{1 + r(t)F(t-1)\} \{1 - \delta |F(t) - F(t-1)|\} \quad (5.1)$$

where $r(t) = \{u(t) / u(t-1)\} - 1$; δ is the transaction cost rate, which is assumed to be a fraction of the transacted price value.

There are numerous ways to generate buy and sell signals using technical analysis techniques. One of the simplest and most popular approaches for deciding when to buy and sell is using moving averages [97,115]. Moving averages (MAs) smooth the price data to define the current trend direction and filter the noise. There are many variants of MAs used in technical analysis. Among them, MACD [103] (moving average convergence/divergence) oscillator originally developed by Gerald Appel is widely used due to its simplicity and efficiency. MACD is a computation of the difference between two *exponential moving averages* (EMAs) [103] of closing prices. Exponential moving averages highlight recent changes in a stock's price. The

EMA of a price series is given as in (5.4). By comparing EMAs of different lengths, the MACD can gauge changes in the trend of a security. MACD consists of *Fast* signal given in (5.2) and *Slow* signal given in (5.3). The *Fast* signal computes the difference between the $\mathcal{G}_{long}$ EMA and the $\mathcal{G}_{short}$ EMA of time series $u(T)$ where $\mathcal{G}_{long} > \mathcal{G}_{short}$. The *Slow* signal computes the $\mathcal{G}_{slow}$ EMA of the *Fast* signal.

$$\text{fast}(t) = \text{EMA}_{\mathcal{G}_{short}}^u(t) - \text{EMA}_{\mathcal{G}_{long}}^u(t) \quad (5.2)$$

$$\text{slow}(t) = \text{EMA}_{\mathcal{G}_{slow}}^{\text{fast}}(t) \quad (5.3)$$

$$\text{EMA}_{\mathcal{G}}^u(t) = \kappa u(t) + (1 - \kappa) \text{EMA}_{\mathcal{G}}^u(t-1) \quad (5.4)$$

where $\kappa = 2 / (\mathcal{G} + 1)$, $\mathcal{G}$ is the number of time instants of the moving average; and $\text{EMA}_{\mathcal{G}}^u(t)$ is the $\mathcal{G}$ EMA of time instant t . In practice, the *Slow* signal of MACD can be used to generate the buy/sell signal, as illustrated in (5.5),

$$F(t) = \text{sign}(\text{slow}(t)) \quad (5.5)$$

where $F(t)$ is the trading action at time t .

Equation (5.5) has the meaning that at time t , if the MACD *Slow* signal of a security is below 0, a sell action should be triggered, and vice versa for the buy action. However, in order to reduce the number of false trading actions by eliminating the “whiplash” signals which happen when the *Slow* signal slightly fluctuates around zero, a whipsaw signal filter is introduced as in (5.6),

$$F(t) = \begin{cases} 1, & \text{when } \text{slow}(t) > \varepsilon \\ -1, & \text{when } \text{slow}(t) < -\varepsilon \\ F(t-1), & \text{otherwise} \end{cases} \quad (5.6)$$

where ε is the width of the whipsaw signal filter. The stock trading system without a predictive model using MACD to generate trading decisions is shown Figure 5-1. The work in [109] has further demonstrated that trading systems using moving average trading rules are able to achieve high returns as compared against other trading strategies as shown in [115].

Figure 5-1: Trading system without a predictive model.

Figure 5-2: Trading system with RSETSK predictive model.

However, using MACD to generate trading decisions does not always work perfectly. That is because MACD is a trend following indicator which can identify the current trend but is unable to forecast the trend in the future. Since the MACD is based on moving averages, it is inherently a lagging indicator. Thus, the stock trading system without a predictive model always generates buy or sell decisions late after the actual trend reversal. In order to take prompt trading action, a predictive model should be adopted. Figure 5-2 shows the proposed stock trading system with RSETSK as a predictive model. The historical price series is represented in n -tuples

$[u(t - n + 1), \dots, u(t - 1), u(t)]$, where n is the embedding dimension. The n -tuples are used as inputs to the RSETSK predictive model to predict the future price, $u'(t + 1)$. In this system, the RSETSK predictive model is trained using supervised learning, using one training instant at a time. This is the main difference between the proposed RSETSK predictive model and other existing predictive models. Other models such as [99,109,111] employ a batch learning approach in which a set of data needs to be available before training. RSETSK follows a strict online learning approach which satisfies the following criteria.

- 1) All the training observations are sequentially (one-by-one) presented to the learning system.
- 2) At any time, only one training observation is seen and learnt.
- 3) A training observation is discarded as soon as the learning procedure for that particular observation is completed.
- 4) The learning system has no prior knowledge as to how many total training observations will be presented.

These criteria are defined in [6] to be considered incremental sequential learning approaches. They are much desired in fast changing environments such as stock price predictions, because in real life, a full training data set may not be available at the beginning. RSETSK functions by interleaving reasoning (testing) and learning (training) activities. It is different from other systems [99,109,111] that need to be trained first before testing. It should be noted that a stock price series is chaotic, evolving and time-variant. Thus, a well-trained static predictive model might not work for new incoming data. RSETSK can continuously learn new data because it is essentially a self-evolving system which takes in consideration of time-variant problems. The predicted price, $u'(t + 1)$, is then used for the computation of the moving averages as given in (5.7)-(5.9). The trading signal $F(t)$ is decided by the forecast value $u'(t + 1)$ as in (5.10),

$$\text{fast}(t+1) = \text{EMA}_{\mathcal{G}_{short}}^{u'}(t+1) - \text{EMA}_{\mathcal{G}_{long}}^{u'}(t+1) \quad (5.7)$$

$$\text{slow}(t+1) = \text{EMA}_{\mathcal{G}_{slow}}^{\text{fast}}(t+1) \quad (5.8)$$

$$\text{EMA}_{\mathcal{G}}^{u'}(t) = \kappa u'(t+1) + (1 - \kappa) \text{EMA}_{\mathcal{G}}^{u'}(t) \quad (5.9)$$

$$F(t) = \begin{cases} 1, & \text{when } \text{slow}(t+1) > \varepsilon \\ -1, & \text{when } \text{slow}(t+1) < -\varepsilon \\ F(t-1), & \text{otherwise} \end{cases} \quad (5.10)$$

where $\kappa = 2 / (\mathcal{G} + 1)$, $\mathcal{G}$ is the number of time instants of the moving average, and $u'(t+1)$ is the forecast price value for time instant $(t+1)$. Extensive experiments were conducted to evaluate the performance of the proposed RSETSK stock trading model. The results are presented in the next section.

5.3 Experiments On Real-world Financial Data

5.3.1 Experimental Setup

In this section, the proposed stock trading system with the RSETSK predictive model is used to trade the actual stocks in the real-world stock market. The forecasting performances of the RSETSK predictive model are benchmarked against other well-known FNNs, such as dynamic evolving neural-fuzzy inference system (DENFIS) [11], and rough set-based pseudo outer-product fuzzy neural network (RSPOP) [116]. The trading performances of all trading systems including the proposed trading system using RSETSK, the simple buy-and-hold strategy, the trading system without prediction, the trading system with perfect prediction and the trading systems with other predictive models (DENFIS, RSPOP) are evaluated using the historical data of International Business Machines Corporation (IBM) and Singapore Exchange Limited (SGX)

stock. All the predictive models are constructed as five-input one-output systems and configured with default parameters. In these experiments, the trading signals for trading system without predictive model is computed using (5.2)–(5.5). The trading signals for trading system with RSETSK, DENFIS and RSPOP predictive models are computed using (5.7)–(5.10). The trading signals for trading system with perfect prediction are also computed using (5.7)–(5.10), but the predicted $u'(t+1)$ is replaced with the actual future price $u(t+1)$. The portfolio end value $R(T)$ is computed using (5.1), where the initial portfolio value $R(0) = 1.0$ and the transaction cost rate is $\delta = 0.2$. The final multiplicative return $R(T)$ is an important factor to evaluate all the trading systems in this experiment. The width of the whipsaw signal filter $\varepsilon = 0.1\%$ is used in (5.10).

In the first experiment, all the predictive models are trained in a batch learning mode, meaning that the full training data set is available before training. The predictive models are then trained to predict the other out-of-sample data set (testing set). The training and testing sets are partitioned from the historical price series and do not overlap. Then, the simple buy-and-hold strategy, the trading system without prediction, the trading system with perfect prediction, and the trading systems with different predictive model are evaluated with the out-of-sample data set using the final portfolio value $R(T)$.

In the second experiment, the predictive models are trained in an incremental online mode. There is no full training set available at the beginning. All the training observations are sequentially (one-by-one) presented to the predictive models. As RSPOP employs a batch learning approach, it is not applicable in this experiment. Only DENFIS and RSETSK are applied in this experiment. Both DENFIS and RSETSK are evolving systems that can continuously learn new data. They function by interleaving reasoning (testing) and learning (training) activities, meaning that they

are able to learn from the current training instant and use the learnt knowledge to predict the output of the next training instant. In the real world, this online learning approach is more desirable than the batch learning approach, as real-world data is always complicated, time-varying and evolving.

5.3.2 Experimental Results and Analysis

5.3.2.1 Analysis using IBM Stock

The predictive models are trained with five previous values of the price series as inputs. The experimental price series consists of 4852 price values obtained from the Yahoo Finance website on the counter NYSE:IBM from the period of January 2nd, 1992 to April 1st, 2011. The in-sample training data set is constructed using the first 2296 data points and the out-of-sample test data set is constructed using the more recent 2556 data points. Trading signals are generated using heuristically chosen moving average parameters 12, 8, and 5 (g_{long} , g_{short} , g_{slow}) and the portfolio end values are computed with a transaction cost of 0.2%.

Table 5-1 shows the benchmarking results of different prediction systems, including the mean square error and the prediction accuracy indicated by the Pearson correlation [117] between the actual, and predicted $u'(t+1)$ series. More specifically, RSETSK is benchmarked against other fuzzy neural networks such as DENFIS [11] and RSPOP [109] and non-fuzzy neural networks such as radial basis function networks (RBFN [118]) and feed-forward neural network trained using back-propagation (FFNN-BP [119]).

Table 5-1: Comparison of different prediction systems on IBM stock

Network	MSE	R
FFNN-BP	13.52	0.564
RBFN	5.38	0.782
RSPOP	4.25	0.853
DENFIS	2.15	0.994
RSETSK	1.86	0.997

FFNN-BP is configured with 10 hidden neurons and is trained for 100 training iterations using a learning rate of 0.025. It should be noted that all systems in Table 5-1, except RSETSK, are not online networks. More specifically, FFNN-BP, RBFN, and RSPOP employ batch learning approaches. DENFIS uses incremental learning approach, but requires the lower/upper bounds of the dataset to be specified prior to training. RSETSK outperforms these networks in term of accuracy. FFNN-BP and RBFN are neural networks, thus ones cannot derive any human interpretable information from them. As the purpose of this experiment is to demonstrate that RSETSK is fast, of superior performance, and interpretable when dealing with stock price prediction problems, FFNN-BP and RBFN are not used as benchmarks in the later part of this experiment.

Table 5-2 shows the benchmarking results of different trading systems, including the portfolio end value $R(T)$, the number of rules generated, and the prediction accuracy indicated by the Pearson correlation [117] between the actual, and predicted $u'(t+1)$ series. In Table 5-2, the TS-WOP and TS-PP denote the trading system without prediction, and with perfect prediction, respectively; the trading systems with DENFIS, RSPOP and RSETSK are denoted as TS-DENFIS, TS-RSPOP and TS-RSETSK, respectively. The out-of-sample price series and the trading signals generated are shown in Figure 5-3. The series of portfolio multiplicative return for different trading systems are shown in Figure 5-4. One important parameter in RSETSK that needs to be set properly is the forgetting factor λ . λ is normally set in the range [0.97, 0.99]. As

this is a recall experiment, λ is set to be 0.99. Previous studies [97] have shown the evidence of nonlinear predictability in the stock market using past data values. In this experiment, the system output $u'(t+1)$ does not depend only on the five past states $u(t-4), u(t-3), u(t-2), u(t-1)$, and $u(t)$ but also on other further past states. A feedforward network (like DENFIS or RSPOP) with these five states normally does not include past states beyond $u(t-4)$. In contrast, the recurrent structure in RSETSK can memorize the past states prior to $u(t-4)$ for output prediction [22].

Figure 5-3: Price and trading signals on IBM.

Figure 5-4: Portfolio values on IBM achieved by the trading systems with different predictive models.

It can be observed that RSETSK outperforms the other predictive models (DENFIS and RSPOP) in term of accuracy and number of fuzzy rules. RSETSK can achieve the highest accuracy of 0.997 using only 9 rules. The stock trading system using RSETSK achieves the highest final return $R(T) = 5.32$, among the trading systems with predictive model. Compared with the trading systems using DENFIS and RSPOP, the trading system with RSETSK achieved an increase of 2.87 and 3.17 in final portfolio value $R(T)$, respectively.

One can observe from Table 5-2 that the simple buy-and-hold strategy only achieved a final portfolio value of $R(T) = 1.63$. The trading system without a predictive model yielded a slightly higher portfolio end value of $R(T) = 1.72$. As shown in Table 5-2, the trading systems with predictive models yielded higher returns than the trading system without predictive model and yielded lower returns than the trading system with perfect prediction. More specifically, the

proposed trading system with RSETSK predictive model yielded an increase of 3.60 in $R(T)$ when compared against the trading system without predictive model.

Table 5-2: Comparison of different trading systems on IBM stock

Network	R	No of Fuzzy Rules	$R(T)$
Buy&Hold	N.A	N.A	1.63
TS-WOP	N.A	N.A	1.72
TS-WPP	N.A	N.A	7.54
TS-RSPOP	0.853	15	2.15
TS-DENFIS	0.994	12	2.45
TS-RSETSK	0.997	9	5.32

Figure 5-5 is the enlarged part of Figure 5-3 from time $t = 900$ to 1000. As shown in Figure 5-5, the trading system with RSETSK predictive model generated the buy and sell signals earlier through the use of the predictive value $u'(t+1)$. Based on this advantage, the proposed stock trading systems with RSPOP, DENFIS, and RSETSK predictive model yielded a higher return than the trading system without a predictive model. However, the trading systems with predictive models are unable to forecast with exact accuracy, unlike the trading system with perfect prediction, which uses the actual future price value $u'(t+1) = u(t+1)$. Therefore the trading systems with predictive models yielded a lower portfolio end value than the trading system with perfect prediction. The average training time reported by RSETSK is only 1.93 ± 0.05 s.

Figure 5-5: Enlarged part of Figure 5-3 from time $t=900$ to $t=1000$

Figure 5-6 shows the membership functions generated in the knowledge base of RSETSK after training. It can be easily observed that all the membership functions are highly distinguishable. There are in total only 15 membership functions generated in five input dimensions. One can easily assign semantic meanings for the derived fuzzy sets, as shown in Figure 5-6.

Figure 5-6: Semantic interpretation of the fuzzy sets derived in RSETSK

5.3.2.2 Analysis Using Singapore Exchange Limited (SGX) Stock

This experiment investigates the online learning ability of RSETSK using a real-world financial time-series based on the SGX stock times series. About 6 years of daily index values were

collected from the Yahoo! Finance website on the ticker symbol S68.SI for the period from Jan 3, 2005 to April 1, 2011, which provided 1,592 data points for the experiment. Figure 5-7 shows the time-variant behavior of the time series with a nonuniform distribution in the range [1.78, 16.40]. Only DENFIS and RSETSK are applied as predictive models in this experiment as they are evolving systems that adopt incremental learning approach [6]. Both systems attempt to perform an online simulation of the daily forecast of the SGX stock prices using five previous values of the price series as inputs. Reasoning (testing) and learning (training) activities are performed simultaneously. Trading signals are generated using heuristically chosen moving average parameters 12, 8, 5 and the portfolio end values are computed with a transaction cost of 0.2%. In this online simulation, the forgetting factor λ in RSETSK is set to be 0.97 so that RSETSK can unlearn fast to keep a compact and current rule base.

As shown in Table 5-3, RSETSK outperforms DENFIS in term of accuracy and number of rules. RSETSK achieved the accuracy of 0.9979 using only 4 rules, while DENFIS yielded the accuracy of 0.9965 using 6 rules. It should be noted that DENFIS is not fully online. In contrast, RSETSK is fully online and it does not require any prior knowledge of the complete set of data points at any point in time. As a result, the stock trading system using RSETSK achieves the higher final return of $R(T) = 11.40$. Compared with the trading system using DENFIS, the trading system with RSETSK achieved an increase of 1.11 in final portfolio value $R(T)$. The simple buy-and-hold achieved a final portfolio value $R(T) = 4.41$. The trading system without a predictive model yielded a slightly higher portfolio end value of $R(T) = 5.85$. The results again show that the trading systems with predictive models yielded higher returns than the trading system without forecast model and yielded lower returns than the trading system with perfect prediction. Figure 5-7 shows the price series and the trading signals generated. Figure 5-8 shows the series of portfolio multiplicative return for different trading systems.

Table 5-3: Comparison of different trading systems on SGX stock

Network	Buy&Hold	TS-WOP	TS-WPP	TS-DENFIS	TS-RSETSK
$R(T)$	4.41	5.85	15.44	10.31	11.40
No. of Rules	N.A	N.A	N.A	6	4
R	N.A	N.A	N.A	0.9965	0.9979

Figure 5-7: Price and trading signals on SGX. **Figure 5-8. Portfolio values on SGX achieved by the trading systems.**

Figure 5-9 shows that RSETSK can quickly mimic the movements of the time series throughout the online simulation. All the peaks and troughs are well predicted. Also, from Figure 5-10, one can observe that the rule base in RSETSK evolves over time. More specifically, new rules are added to describe new data and obsolete rules are pruned to maintain a compact and up-to-date rule base at all times. This is an important feature of RSETSK. During the simulation, there are at least 4 major reorganizations in the RSETSK rule base, as marked in Figure 5-10. The reorganizations correspond to the trajectory shifts in the SGX price series, as shown in Figure 5-9. The number of rules in other self-evolving systems such as DENFIS will only grow with time, in which many rules will become obsolete. In contrast, RSETSK always attempts to improve the currency of the rule base by slowly unlearning the old data. This characteristic is desired in fast and evolving problems such as time series prediction, as it improves the level of human expert interpretability of the derived fuzzy rule base. This is also applied in real life trading, as stock traders pay more attention to what are working now, not in the past. Table 5-4 lists the fuzzy rules derived by RSETSK. The average simulation time reported by RSETSK for 1,592 data points is only 0.82 ± 0.05 s. This demonstrates RSETSK's fast learning ability in real-life problems.

Figure 5-9: SGX time series forecasting results.

Figure 5-10: The evolution of the fuzzy rules in RSETSK

Table 5-4: Fuzzy rules extracted from RSETSK

Rule	$y(t-4)$	$y(t-3)$	$y(t-2)$	$y(t-1)$	$y(t)$
R_1	low	low	low	-	low
R_2	low	low	low	-	high
R_3	low	high	high	-	high
R_4	high	high	high	-	high

5.4 Summary

A trading system with a novel predictive model empowered by the recurrent self-evolving Takagi–Sugeno–Kang fuzzy network is presented. The RSETSK predictive model adopts an online incremental-learning-based-approach to forecast the future security prices in order to generate profitable trading decisions. RSETSK possesses many features which are desired in evolving problems such as time series prediction. First, it is an online structure which does not require *prior* knowledge of the number of cluster/fuzzy rules in the data set. Second, for using a novel rule pruning algorithm, RSETSK’s fuzzy rule base is kept compact and up-to-date at all times, with highly distinguishable fuzzy sets. The recurrent structure in RSETSK results in a high level of modeling accuracy when working with time-variant datasets. Two types of experiments were carried out to evaluate the performance of RSTSK. The first one is a recall experiment. The second experiment is an online simulation. Results in both experiments show that the RSETSK provides accurate prediction of stock trend and that the trading system with RSETSK is able to yield higher profit than the simple buy-and-hold strategy, the trading system without prediction,

and the trading systems with other predictive models. The second experiment shows that RSETSK is able to achieve a dynamic, compact and current resultant rule base. However, it should be noted that the settings of the parameters of the moving averages can heavily affect the profitability of the trading systems. And the trading results may vary for different stocks. A generic guideline or an automated approach to selecting the optimal parameters for different stocks can be considered as possible future works.

Chapter 6: Option Trading & Hedging System – A Real World Application

It's not whether you're right or wrong that's important, but how much money you make when you're right and how much you lose when you're wrong.

George Soros (1930 -)

6.1 Introduction

Financial organizations nowadays are increasingly trading in options and other derivative securities to reduce their exposure to the erratic price fluctuations of the economic markets. Research has thus flourished that aims at supplementing traders' expertise and traditional financial tools with the power of non-parametric, numerical computing techniques such as neural networks and neural fuzzy systems [120]. These non-parametric pricing models attempt to address the limitations of traditional models whose parameters are calibrated to match only certain conditions, by pricing and risk-managing financial derivatives in a model-free approach. Their goal is to eliminate model risk by assuming as little as possible and, in particular, no pre-specified model.

Neural networks are extensively employed for financial models because of their ability to learn complex non-linear patterns in data and self-adaptation for various statistical distributions. However, despite yielding promising results in financial applications, neural networks are mainly considered as black-box models because their knowledge is represented by links and weights. There is no way to derive any human interpretable information from the networks. Besides, they are generally applicable and reliable only when a huge amount of representative data is available. In 1988, White [121] was the first to use neural networks for market forecasting. Since then, there

have been many studies using neural networks to predict the financial markets [97,107,122]. However, the amount of research work dedicated to the commodities market is still insignificant.

Recently, there is a continuing trend in using *neural fuzzy systems* (NFSs) [4] for developing financial models. NFSs combine the human-like reasoning style of fuzzy systems with the connectionist structure and learning ability of neural networks [2]. The advantage of neuro-fuzzy approach is that it can provide insights to the user about the symbolic knowledge embedded within the network. More specifically, NFSs can generalize from training data, learn/tune system parameters, and generate the fuzzy rules to create a linguistic model of the problem domain. Although many neural fuzzy based trading models have been developed for stock trading or currency trading, only a few current works [123-124] are focused on enhancing and protecting trading results using options. Options, as a derivative security, provide a means to manage financial risks. They are powerful tools for hedging and speculation, without which the means of creating portfolios and trading strategies would be very limited. The buyer of an option enters into a contract with the right, but not the obligation, to purchase or sell an underlying asset at a later date at a price agreed upon today.

In [123], Tung and Quek proposed a self-organizing network, GenSoFNN, which emulates the information handling and knowledge acquisition of the hippocampal memory [125]. In [124], Teddy et al. proposed a localized learning network, PSECMAC, which is inspired by the neurophysiological aspects of the human cerebellum. Both of these approaches are focused on finding mis-priced arbitrage opportunities to take up trading positions. These systems can learn incrementally from online data streams. However, they face some major challenges. First, they do not possess an unlearning algorithm, which may lead to the collection of obsolete knowledge over time and thus degrade the level of human interpretability of the resultant knowledge base. Second, in these systems, older and newer information are treated equally. Hence, they might not

give accurate solutions for online problems which exhibit regime shifting properties, e.g option pricing problem.

This chapter investigates an option trading decision model with a price prediction model empowered by a generic self-evolving Takagi-Sugeno-Kang [4] fuzzy neural network (GSETSK). The proposed prediction system is employed in practice within a hedging system to ensure that the user is not left exposed to unnecessary risks. Extensive experiments are conducted using real-world datasets such as Gold and British pound-Dollar futures and options. This chapter is organized as follows. Section 6.2 presents the structure of the option trading system and the trading strategy. Section 6.3 evaluates the performance of the novel GSETSK-based trading system using real-world data.

6.2 Option Trading System Using GSETSK

Similar to the approach used in the stock trading case study in Chapter 5, in this chapter, technical analysis is used to generate trading decisions. The main approach is still to identify early trends of the underlying assets and maintain an investment position (long, short, or hold) until evidence indicates that the trend has reversed.

In this section, an option trading system with the GSETSK predictive model is presented. Figure 6-1 shows the proposed option trading system with GSETSK as a predictive model. In this option trading system, again, MACD [103] is used due to its simplicity and efficiency. More specifically, MACD is used to predict the security's trend. In practice, a natural strategy for aggressive traders is to use the predicted trend to take a position in the security. However, a more conservative strategy is preferable for other traders [120]. They perform the trading in options only to minimize the risk. By doing so, they reduce the rate of return on investment, but they also

can reduce the exposure to price fluctuations. Thus, they can minimize losses in unforeseen circumstances, which cannot be done in direct trading strategies.

Figure 6-1: Trading system with GSETSK predictive model.

Arbitrage is a popular trading strategy in option trading. An arbitrage opportunity arises when the Law of One Piece [126] is violated [123]. Arbitrage can help investors to construct a zero investment portfolio with a sure profit. In practice, arbitrage happens when there is a price difference between two or more markets. A trader can strike a combination of matching deals that take advantage of the imbalance, and thus make profit on the difference between the market prices.

In our proposed option trading system, an interesting arbitrage trade strategy is employed. It is called Delta Hedging Trading Strategy [126]. This strategy is basically the construction of positions that do not react to small changes in the price of the underlying security. A trader can perform delta hedging by establishing a short (or long) position in the asset that the option can be converted into. This strategy has been shown to deliver better average returns than those explained by common measures of risk [120]. Assume a trader decides to short a security. In order to perform a delta hedge, he would buy a number of call options to cover the risk of taking a naked short on the security. When the security's price goes down, the trader's portfolio will result a profit because the short position becomes more profitable than the cost of buying the

options. On another hand, an increase in price also leads to a profit, because the rise in the price of the call options is greater than the loss from the short position. If the asset does not move in the expected direction, the trader only loses the investment made in buying the option contracts (which is substantially less than investing in the asset itself). This example illustrates how we can design a hedge to offset any excesses in the underlying security or asset, here in this paper the currency or gold price.

In order to perform a delta hedge on a portfolio, a trader needs to determine the number of contracts to be written to hedge the portfolio. Assuming for instance a portfolio value of \$10,000 and an option contract value of 100 times the current option value, the number of contracts can be calculated as in (6.1)-(6.2) below [120].

$$\text{No. of contract} = \frac{\text{Portfolio value}}{\text{Option delta} \times \text{Option contract value}} \quad (6.1)$$

$$\text{Option delta} = N(d_1) \quad (6.2)$$

$$\text{where } d_1 = \frac{\ln(S_0 / X) + (\sigma^2 / 2)T}{\sigma \sqrt{T}}.$$

The option delta that appears in (6.1) is defined in (6.2), where S_0 is the current asset price, X is the exercise price, σ is the volatility, T is the time to maturity (in years), and N is the cumulative distribution function of the standard normal distribution.

In our proposed trading system, the GSETSK predictive model is used to predict the future prices of the underlying asset for the next L days. It also predicts the future trends using MACD. Then the trading system will make trading decisions based on the circumstances, such as whether the option is trading in-the-money or out-of-money or whether the future trend is up or down. For instance, if future trend is down, the trader shorts the asset, buys call options today and exercises

them when the price reaches the expected lowest level. It should be noticed that the options are assumed to be American style options which allow the trader to exercise them whenever desired. In order to determine whether the future price trend is up or down, a GSETSK predictive model computes the MACD *slow* signal for L days later, it would predict an uptrend if all the latest predicted $\lfloor L/2 \rfloor$ predicted *slow*' is greater than the filter width ε (which can be mathematically described by (6.3)).

$$\text{Future trend} = \begin{cases} \text{up} & \text{if } \forall l \in \{L - \lfloor L/2 \rfloor + 1, \dots, L\} : \text{slow}'(t+l) > \varepsilon \\ \text{down} & \text{if } \forall l \in \{L - \lfloor L/2 \rfloor + 1, \dots, L\} : \text{slow}'(t+l) < \varepsilon \end{cases} \quad (6.3)$$

where ε is the width of the whipsaw signal filter to reduce the number of false trading actions by eliminating the “whiplash” signals. This trading system uses options instead of directly trading in the underlying asset itself. This helps to minimize risks arising from unpredictable price movements. Extensive experiments were conducted to evaluate the performance of the proposed GSETSK trading model. The results are presented in the next section.

6.3 Experiments On Real-world Financial Data

6.3.1 Experimental Setup

In this section, the proposed option trading system with the GSETSK predictive model is used to trade the actual future and options in the real-world market. The forecasting performances of the GSETSK predictive model are benchmarked against other well-known NFSs, such as the dynamic evolving neural-fuzzy inference system (DENFIS) [11], and the rough set-based pseudo outer-product fuzzy neural network (RSPOP) [116]. The data used for training and testing the networks is the Gold and British Pound-Dollar futures and options. Figures 6-2 and 6-5 show the complex and time-variant behaviors of the data sets. Daily samples of this data were obtained

from the Bloomberg and Data Stream databases. To simplify the experiment setup, transaction costs are ignored here. In the first experiment, all the predictive models (DENFIS, RSPOP, GSETSK) are trained in a batch learning mode, meaning that the full training data set is available before training. The predictive models are then trained to predict the other out-of-sample data set (testing set). The training set and testing set which are partitioned from the historical price series do not overlap. Then, the trading systems with different predictive model (DENFIS, RSPOP and GSETSK) are evaluated by observing their arbitrage performances using real-life GBP vs. USD currency future option with various strike prices.

In the second experiment, the predictive models are trained in an incremental online mode. There is no full training set available at the beginning. All the training observations are sequentially (one-by-one) presented to the predictive models. As RSPOP employs a batch learning approach, it is not applicable in this experiment. Only DENFIS and GSETSK are used in this experiment. All the predictive models (DENFIS, RSPOP and GSETSK) are configured with default parameters. Two prediction values have been considered to compare the performances of these predictive models. The first is the future trend (buy/sell signal) of the market (the likely direction of the price i.e., to rise or fall, in the next L days). L is set to be 5 in all experiments, which mean the predictive models would predict the trend for the next 5 days. The second prediction value is the actual price of the asset.

6.3.2 Experimental Results and Analysis

6.3.2.1 Analysis using GBPUSD Currency Futures

In this experiment, the British pound vs. US dollar data was obtained from CME 2000–2002. The data consists of the daily closing quotes of the GBP versus USD currency futures and the daily closing bid/ask prices of American style call options on such futures during the period of October

2002 to June 2003. In total, 792 data samples are available in the futures option data set, which contains the historic real-world pricing data for the call options with five different strike prices. The various option strike prices are \$158, \$160, \$162, \$166 and \$168, with 159, 158, 173, 137 and 165 data samples respectively. The strike prices reflect the path of the index during the time-to-maturity period.

Figure 6-2: Price prediction on GBPUSD futures using GSETSK.

Figure 6-3: Price prediction on GBPUSD futures using RSPOP.

Figure 6-2 shows the out-of-sample price series predicted by GSETSK for the period February 4th, 2002 to September 10th, 2002. It can be easily observed that GSETSK can closely mimic the movement of the real price data. Table 6-1 shows the benchmarking results of different predictive models, the number of rules generated, and the prediction accuracy indicated by the Pearson correlation [117] between the actual, and predicted price, and the nondimensional error index (NDEI) which is defined as the root mean squared error divided by the standard deviation of the true output values [31]. It can be observed that GSETSK outperforms the other predictive models (DENFIS and RSPOP) in term of accuracy and number of rules. GSETSK can achieve the highest accuracy of 0.988 using only 5 rules. It should be noted that RSPOP employs batch learning approach, while GSETSK still employs incremental learning in this recall experiment. Figure 6-3 shows the out-of-sample price series predicted by RSPOP. This algorithm's performance depends significantly on the availability of a huge amount of training data. Thus it performs poorly in this experiment, where small training data set is provided.

Table 6-1: Comparison of different predictive models on GBPUSD futures dataset

Network	R	NDEI	No of Rules
RSPOP	0.909	0.431	9
DENFIS	0.983	0.203	6
GSETSK	0.988	0.177	5

Figure 6-4 shows the membership functions generated in the knowledge base of GSETSK after training. It can be easily observed that all the membership functions are highly distinguishable. There are only 15 membership functions generated in five input dimensions in total. One can easily assign semantic meanings for the derived fuzzy sets, as shown in Figure 6-4.

Figure 6-4: Semantic interpretation of the fuzzy sets derived in GSETSK

The trading results have been computed based on the Strike price, exercise price, etc. using delta hedging, the number of options to be bought or sold is calculated, and the trades executed. Table 6-2 shows the profits obtained using this option trading system with GSETSK predictive models for call options with various exercise prices. The average return on investment is a promising 5.97%.

**Table 6-2: Profits generated on different option strike prices
using the proposed option trading system**

Strike Price	<i>Profit Obtained</i>
\$155	4.28
\$156	7.12
\$158	-4.35
\$160	-3.27
\$162	18.72
\$164	13.29

6.3.2.2 Analysis using Gold Futures and Options

This experiment investigates the online learning ability of GSETSK using a real-world gold data, which was collected from COMEX for 2000–2002. In total, 741 data samples are available in the gold futures data set. Figure 6-5 shows the time-variant behavior of the time series with a nonuniform distribution in the range [268.6, 360.6]. Only DENFIS and GSETSK are used as predictive models in this experiment as they are evolving systems that adopt incremental learning approach [6]. Both systems attempt to perform an online simulation of the forecast of the gold futures using five previous values of the price series as inputs. Reasoning (testing) and learning (training) activities are performed simultaneously. Trading signals are generated using heuristically chosen moving average parameters 12, 8, 5.

As shown in Table 6-3, GSETSK outperforms DENFIS in term of accuracy and number of rules. GSETSK achieved the accuracy of 0.981 using only 8 rules, while DENFIS yielded an accuracy of 0.972 using 8 rules. It should be noted that DENFIS is not fully online, while GSETSK is a self-evolving system that does not require any prior knowledge of the complete set of data points at any point in time. From Figure 6-5, one can observe that GSETSK can quickly mimic the movements of the time series throughout the online simulation. All the peaks and troughs are well

predicted. Figure 6-6 shows the trend prediction accuracy with the desired and predicted trend results for gold data. One can easily observe that the predicted trend values by GSETSK are quite accurately and follow closely the desired trend values. On the whole, the GSETSK predictive model is able to follow the market trend with good accuracy. The average simulation time reported by GSETSK for 742 data points is only 0.82 ± 0.05 s. This demonstrates GSETSK's fast learning ability in real-life problems.

Table 6-3: Comparison of different trading systems on gold futures

Network	R	NDEI	No. of Rules
DENFIS	0.972	0.228	10
GSETSK	0.981	0.201	8

Figure 6-5: Price prediction for the gold data set using GSETSK

Figure 6-6: Trend prediction accuracy for the gold data set

6.4 Summary

In this chapter, an option trading decision model with a price prediction model empowered by a generic self-evolving Takagi-Sugeno-Kang fuzzy neural network (GSETSK) is briefly discussed. The proposed prediction system is employed in practice within a hedging system to ensure that the user is not left exposed to unnecessary risks. Existing predictive models cannot provide insights to the user about the semantic meanings of the derived knowledge. Besides, they treat older and newer information equally, and thus cannot give accurate solutions for online problems which exhibit shifting properties such as time series prediction problems. GSETSK attempts to address these problems. Despite not having a recurrent structure, GSETSK still achieves encouraging results in experiments using real-world datasets including Gold and British pound-Dollar futures and options. Results in these experiments show that the GSETSK provides accurate prediction of price trend and that the trading system with GSETSK is able to yield higher profit than the trading systems with other established predictive models. Using these predictions a portfolio can be designed allowing the user to use the benefit of forecasting values provided to

take profitable and safe positions in the market. In the next chapter, both GSETSK and its recurrent version RSETSK would be benchmarked in another real-life case study which is the traffic prediction problem.

Chapter 7: Traffic Prediction – A Real-life Case Study

Everything is theoretically impossible, until it is done. One could write a history of science in reverse by assembling the solemn pronouncements of highest authority about what could not be done and could never happen.

Robert Heinlein (1907-1988)

7.1 Introduction

Transportation is one of the major concerns for any fast growing city. The prediction of traffic flow has the potential to improve traffic conditions and trim down travel delays. It is becoming an interesting research topic that many local transport authorities around the world strive to address. With more vehicles on the road, there is a strong need for a traffic prediction system that can facilitate better utilization of available road capacity. The needed system can be used to analyze real-time traffic data to estimate traffic conditions so that local transport authorities can develop effective traffic control strategies based on the traffic estimations. The traffic prediction system can also be used by travelers to make timely and informed travel decisions. This chapter presents such a traffic prediction system, which is implemented using the proposed networks, GSETSK and RSETSK.

Traffic engineers have resorted to alternative methods such as neural networks, but despite some promising results, the difficulties in their design and implementation remain unresolved. In addition, the opaqueness of trained networks prevents the understanding of the underlying models. Subsequently, fuzzy neural networks which combine the human-like reasoning style of fuzzy systems with the connectionist structure and learning ability of neural networks have been being used for traffic prediction. In [127], a fuzzy neural network based on the Hebbian–

Mamdani rule reduction architecture is employed to predict the traffic flow in an expressway in Singapore. In [38], a generic self-organizing fuzzy neural network (GenSoFNN) which adopts a pseudo-incrementally learning approach is proposed to address the same problem. However, both of these methods are not able to adapt to new information as they generally use offline learning methods. In real life, traffic prediction is an online problem with new data coming at every instant of time. A dynamic prediction model that can continuously adapt to new information is preferred over a static prediction model. GSETSK and RSETSK are self-evolving systems which can incrementally learn with high accuracy without any prior assumption about the data sets. In addition, they can derive a compact and interpretable rule base with highly distinguishable fuzzy sets. Finally, they are able to unlearn obsolete data to keep a current rule base and address the drift and shift behaviors of traffic data. This chapter is organized as follows. Section 7.2 evaluates the performance of the proposed networks (GSETSK and RSETSK) on real-world traffic data. Section 7.3 concludes the chapter.

7.2 Experiments on Real-world Traffic Data

7.2.1 Experimental Setup

This experiment is conducted to evaluate the effectiveness of the proposed networks in data modeling and prediction using a set of highway traffic flow data. The raw traffic flow data for the simulation was obtained from [128]. The data were collected using loop detectors embedded beneath the road surface of the Pan Island Expressway (PIE) in Singapore (see Figure 7-1). The traffic data set has four input attributes: normalized time and the traffic densities of the three highway lanes [38].

Figure 7-1: Location of site 29 along PIE (Singapore) and (b) actual site at exit 15

Figure 7-2: Traffic densities of three lanes along Pan Island Expressway

The data are normalized in the following manner. The lane traffic density is computed by the number of vehicles per kilometer per lane. The final lane density is normalized by the average density of the respective lane.

7.2.3 Experimental Results and Analysis

In this experiment, the traffic flow trend at the site is modeled using the proposed networks. The trained networks are then used to predict the traffic density of a particular (selected) lane at a time $t + \tau$, where $\tau = 5, 15, 30, 45$ and 60 min. The traffic flow density data for the three straight lanes spanning a period of six days from September 5 to 10, 1996 is depicted as in Figure 7-2. During the simulation, three cross-validation groups of training and test sets are used: CV1, CV2, and CV3. The performance of the proposed networks are benchmarked against other established fuzzy neural networks using the MSE and Pearson correlation coefficient [129] as in (7.1) and (7.2).

$$MSE(a, b) = \frac{1}{n} (a - b)^T (a - b) \quad (7.1)$$

where

MSE MSE function;

a, b 2 data vectors;

n number of elements in the data vector.

$$R(a, b) = \frac{C(a, b)}{\sqrt{C(a, a)C(b, b)}} \quad (7.2)$$

where

R Pearson correlation coefficient function;

a, b 2 data vectors;

$C(.,.)$ covariance between two data vectors.

Figures 7-3 shows the respective modeling (recall) and predicting (generalization) performances of the GSETSK on lane 1 traffic density using training and test sets of CV1, CV2, and CV3 at $\tau = 5$. Figures 7-4 shows the respective modeling (recall) and predicting (generalization) performances of the RSETSK on lane 1 traffic density using training and test sets of CV1, CV2, and CV3 at $\tau = 5$.

From Figure 7-3, it can be observed that the GSETSK network is able to accurately capture and model the underlying dynamics governing the flow of traffic of lane L1. It also accurately predicts the traffic trends of lane L1 for a prediction horizon of 5 min (i.e $t+5$). Figure 7-4 shows that RSETSK performs better than its feed-forward counterpart in many cases. Figure 7-5 shows the average Pearson values and the average MSEs derived from the three cross-validation groups of each time interval with respect to the three different lanes L1, L2 and L3 using the various benchmarked NFSs. In all scenarios, the proposed GSETSK and RSETSK networks are proven to perform better than other benchmarked NFSs by achieving higher accuracy (Pearson values) and lower prediction errors. The results also show that the proposed networks are able to provide reasonable forecasts of the unseen future traffic conditions.

Figure 7-3: Traffic modeling and prediction results of GSETSK for lane L1 at time $t+5$ across three-cross validation groups.

Figure 7-4: Traffic modeling and prediction results of RSETSK for lane L1 at time $t+5$ across three-cross validation groups.

(a)

Figure 7-5: Traffic flow forecast results for GSETSK, RSETSK and the various benchmarked NFSs (a) Prediction accuracy across 3 lanes (b) Prediction error across 3 lanes

Table 7-1 benchmarks the proposed networks against other established architectures. They are, namely: the Hebbian-rule-reduction-based Mamdani network (Hebb-R-R) [127], rough-set-based POPFNN-CRI (RSPOP) [116] , POPFNN-CRI [47], GenSoFNN [38], EFuNN [130], and DENFIS [11]. The Hebb-R-R, RSPOP-CRI, and POPFNN-CRI networks are batch-learning models while GenSoFNN is a self-organizing network that uses pseudoincremental learning approach. EFuNN and DENFIS are evolving fuzzy rule-based systems. Among the benchmarked models, DENFIS is the only TSK network. Table 7-1 benchmarks the average R, the average MSE, and their standard deviations as well as the average number of rules derived for the various prediction horizons using the proposed models (GSETSK and RSETSK) and the other models for predicting of the traffic densities across the three lanes. It can be observed that the proposed models outperform other models in terms of the number of rules identified and the prediction accuracies for the unseen data in the test set. In addition, the proposed models employ incremental learning approach, meaning that they can continuously adapt to new information. Thus, they can be considered as suitable candidates for addressing online traffic prediction problems.

The specifications for the system to conduct this experiment are listed as follows:

- Intel Core Duo CPU, Q9400 @ 2.66GHz
- 4.00 GB of RAM
- Window 7 Enterprise version
- Microsoft Visual Studio 2008

The real-time performance of the proposed GSETSK network is shown by the average training time for all the 45 traffic simulations (based on the three straight lanes with five prediction horizons and three cross-validation groups for each prediction horizon). The average simulation

time reported by GSETSK is only 0.85 ± 0.05 s. This demonstrates GSETSK's fast learning ability in real-life traffic prediction problems.

Table 7-1: Benchmarking of results of the highway traffic flow prediction experiment

Network	Rule-learning	Average R (Stdev)	Average MSE (Stdev)	Average # rules
Hebb-R-R	Batch	0.864 (± 0.046)	0.114 (± 0.042)	8.1
RSPOP-CRI	Batch	0.834 (± 0.041)	0.146 (± 0.038)	14.4
POPFNN-CRI	Batch	0.814 (± 0.042)	0.173 (± 0.053)	40.0
GenSoFNN	Pseudo-Inc	0.813 (± 0.028)	0.164 (± 0.037)	50.0
EFuNN	Evolving	0.798 (± 0.050)	0.189 (± 0.041)	234.5
eFSM	Evolving	0.840 (± 0.043)	0.154 (± 0.040)	20.3
DENFIS	Evolving	0.831 (± 0.051)	0.153 (± 0.054)	9.7
GSETSK	Evolving	0.875 (± 0.042)	0.132 (± 0.040)	8.9
RSETSK	Evolving	0.893 (± 0.043)	0.131 (± 0.040)	8.5

Figure 7-6 shows the highly distinguishable membership functions derived by the GSETSK model using the training set of cross validation group CV1 for the predicting of lane L1 traffic trends at time $t+5$. A total of 8 rules are identified by GSETSK based on the given training data. There are only 9 fuzzy sets in total generated in GSETSK for all input dimensions. To illustrate the intuitiveness of the fuzzy rules identified, a mapping of semantic labels to each fuzzy membership function is performed. As formulated in [32,43-44], a linguistic variable is characterized by a quintuple $(L, T(L), U, G, M)$, where L is the name of the variable; $T(L)$ is the linguistic term set of L ; U is a universe of discourse; G is a syntactic rule that generates $T(L)$; and M is a semantic rule that associates each $T(L)$ with its meaning. Here, the names L of the input linguistic variables

of the data set are [Time t , L1-D(t), L2-D(t), L3-D(t)] respectively, where L1-D(t), L2-D(t), and L3-D(t) are the traffic densities of the three lanes at time t . A mapping of semantic labels such as $T(.) = [\text{Morning}, \text{Evening}]$ for the first input variable or $T(.) = [\text{Low}, \text{Medium}, \text{High}]$ for the other inputs reveals the intuitiveness of the 8 rules identified in GSETSK as shown in Table 7-2.

Figure 7-6: The fuzzy sets derived by GSETSK during the training set of CV1 for lane L1 traffic prediction at time $t+5$

Table 7-2: Semantic interpretation of fuzzy rules in GSETSK

Rule	Time t	L1-D(t)	L2-D(t)	L3-D(t)
01	Morning	Low	Low	Low
02	Morning	High	High	Medium
03	Morning	High	High	Low
04	Morning	Low	High	Medium
05	Evening	Low	Low	Low
06	Morning	High	Low	Low
07	Morning	High	Low	High
08	Morning	High	Low	Medium

Using the same training set of cross validation group CV1 for the predicting of lane L1 traffic trends at time $t+5$, the RSETSK model identifies only 8 fuzzy sets in total. The average training time is also around $0.81 \pm 0.07s$. The fuzzy sets derived are highly distinguishable. The results show that the proposed networks can be promising candidates for real-life traffic prediction systems.

7.3 Summary

This chapter investigates the application of the proposed networks (GSETSK and RSETSK) on the prediction of traffic trends. Traffic prediction is becoming a popular topic of research and it has the potential to improve traffic conditions and trim down travel delays. The performances of the proposed networks are evaluated by comparing the results with other established methods. The results show that GSETSK and RSETSK outperform other methods in terms of the number of rules identified and the prediction accuracies. Besides, the proposed networks derive an interpretable rule base with highly distinguishable fuzzy sets which can be easily comprehended. It should be noted that GSETSK and RSETSK can learn incrementally with high accuracy without any prior assumption about the data sets. Their fast learning ability makes them viable candidates for the online traffic prediction applications.

Chapter 8: Conclusions & Future Work

The learning and knowledge that we have, is, at the most, but little compared with that of which we are ignorant.

Plato (423 BC-347 BC)

8.1 Conclusion

The advantages of combining fuzzy systems and neural networks have led to the active research interest in the field of fuzzy neural systems. This Thesis is mainly focused on addressing the existing problems of Takagi-Sugeno-Kang fuzzy neural networks which are mainly used for solving dynamic and complex real-life problems that require high precision. Existing TSK models proposed in the literature can be broadly classified into three classes. Class I TSK models are essentially fuzzy systems that are unable to learn in an incremental manner. Class II TSK networks, on the other hand, are able to learn in incremental manner, but are generally limited to time-invariant environments. Class III TSK networks are fuzzy systems that adopt incremental learning approaches and attempt to solve time-variant problems. However, many Class III systems still encounter three critical issues; namely: 1) Their fuzzy rule base can only grow, 2) They do not consider the interpretability of the knowledge bases and 3) They cannot give accurate solutions when solving complex time-variant data sets that exhibit drift and shift behaviors (or regime shifting properties).

This Thesis focuses on the development of a novel online biologically plausible fuzzy neural network that can address the mentioned deficiencies of TSK networks. This final chapter summarizes the contributions achieved by the research in this Thesis, the constraints of the proposed computational models, and the possible directions for future research efforts.

8.1.1 Theoretical Contributions

The theoretical works of this Thesis are summarized as follows:

- This thesis proposes the basis for a self-evolving TSK framework which is fast and efficient and can be applied in real-life applications that require high precision. The framework adopts an incremental online learning approach and has the ability to work in time-variant environments. The motivations for developing self-evolving online learning computational models for solving real-life problems are highlighted in Section 2.5.
- This thesis highlights that unlearning, which is stemmed from neurobiology, is necessary in self-evolving systems that attempt to address time-variant problems. In Section 2.6, the thesis describes that unlearning is an efficient way to address the concept drift and shift in online data streams. This thesis proposes a novel ‘gradual’ unlearning approach that adopts the Hebbian learning mechanism behind the long-term potentiation phenomenon in the brain (see Section 3.2).
- This thesis describes that overlapping and indistinguishable fuzzy sets in the knowledge base of a fuzzy neural network can deteriorate its interpretability. In Section 3.3, the thesis proposes a novel merging approach to derive a compact and understandable knowledge base in a fuzzy neural network.
- This thesis highlights that recurrent fuzzy neural networks are better candidates than feedforward networks for solving problems involving temporal relationships. This thesis proposes a recurrent self-evolving framework in Section 4.2 to address dynamic and temporal problems more efficiently.

8.1.2 Practical Contributions

The practical contributions of this thesis are summarized as follows:

8.1.2.1 Self-Evolving Takagi–Sugeno–Kang Fuzzy Framework

Generic self-evolving Takagi–Sugeno–Kang fuzzy framework (GSETSK) is an economic and fast framework that can be applied in modeling many real-world applications with good semantics, high precision and ease. The ‘backbone’ of the framework is a novel fuzzy clustering algorithm known as Multidimensional-Scaling Growing Clustering (MSGC) which empowers GSETSK with an incremental learning ability. MSGC is completely data-driven and does not require prior knowledge of the numbers of clusters or rules present in the training data set. In addition, MSGC does not assume the upper or lower bounds of the data set. MSGC is inspired by human cognitive process models and it can work in fast-changing time-variant environments.

MSGC also employs a novel merging approach to ensure a compact and interpretable knowledge base in the GSETSK framework as described in Chapter 3. Highly overlapping membership functions are merged and obsolete rules are constantly pruned to derive a compact fuzzy rule base while maintaining a high level of modeling accuracy.

To keep an up-to-date fuzzy rule base when dealing with time-variant problems, a novel ‘gradual’-forgetting-based rule pruning approach is proposed to unlearn outdated data by deleting obsolete rules. This approach is simple, biologically plausible and efficient. It adopts the Hebbian learning mechanism behind the long-term potentiation phenomenon in the brain. It can detect the drift and shift behaviors in time-variant problems and give accurate solutions for such problems.

The performance of GSETSK has been demonstrated in three benchmarking case studies. In Section 3.5.1, GSETSK has shown its online learning ability in complex environments, more specifically, a nonlinear dynamic system with non-varying characteristics. The derived

knowledge base of GSETSK, which is compact with highly distinguishable fuzzy sets, is illustrated. Section 3.5.2 proves the ability of GSETSK to work in time-variant problems. The section also features the evolving rule base of GSETSK to illustrate the learning/unlearning mechanisms in GSETSK. Section 3.5.3 shows the superior performance of GSETSK in solving a well-known regression problem; which is the Mackey-glass time series predictions. In general, GSETSK has shown that it is a viable candidate for solving complex and time-variant problems which require high accuracy.

In Chapter 6, an option trading and hedging system using GSETSK as a predictive model is presented. The proposed prediction system is employed in practice within a hedging system to ensure that the trader is not left exposed to unnecessary risks. The GSETSK predictive model is more advantageous than existing predictive models because it provides insights to the trader about the semantic meanings of the derived knowledge and it addresses the shifting properties of the time series. Results in the experiments on real-life data show that GSETSK provides accurate prediction of price trends and that the trading system with GSETSK is able to yield higher profit than the trading systems with other established predictive models. Using these predictions a portfolio can be designed allowing the user to use the benefit of forecasting values provided to take profitable and safe positions in the market.

8.1.2.2 Recurrent Self-Evolving Takagi-Sugeno-Kang Fuzzy Neural Network

A recurrent version of GSETSK, the RSETSK (Recurrent Self-Evolving TSK Fuzzy Neural Network) is presented in Chapter 4. This extension aims to improve the ability of GSETSK in dealing with dynamic and temporal problems.

Unlike GSETSK, RSETSK does not require the knowledge of the number of delayed input and output in advance when solving temporal problems. The main difference between RSETSK and

its non-recurrent version is its inherent recurrent structure which empowers it with the ability to process patterns with spatio-temporal dependencies better.

Extensive experiments were conducted to evaluate the performance of RSETSK. Section 4.4.1 shows its superior online learning ability in complex environments such as the nonlinear temporal problem with nonvarying characteristics. In this simulation, RSETSK outperforms other recurrent networks in the literature in terms of accuracy and the number of rules. The derived knowledge base of RSETSK is compact and meaningful. In Section 4.4.2, the rule evolution process of RSETSK is shown to explain why unlearning is needed in recurrent fuzzy neural. In Section 4.4.3, RSETSK is benchmarked against its non recurrent version GSETSK using the Dow Jones Index Time Series dataset. The case study in Section 4.4.3 shows that RSETSK is an excellent alternative over its non-recurrent version in solving problems that exhibit temporal behaviors.

In Chapter 5, a stock market trading system using a novel price prediction model empowered by RSETSK is proposed. The RSETSK predictive model is able to forecast the future security prices in order to generate profitable trading decisions using technical analysis, more specially, using the simple and efficient MACD oscillator. Compared to existing predictive models, RSETSK possesses many features which are desired in evolving problems such as time series prediction. The recurrent structure in RSETSK results in a high level of modeling accuracy when working with time-variant stock datasets. Extensive experiments show that the RSETSK provides accurate prediction of stock trend and that the trading system with RSETSK is able to yield higher profit than the simple buy-and-hold strategy, the trading system without prediction, and the trading systems with other predictive models.

In Chapter 7, a traffic prediction system to forecast traffic trends using RSETSK is presented. The experimental results showed that RSETSK performs better than its feedforward counterpart, GSETSK.

To conclude, the research achievements in this thesis concur with the research objectives highlighted in Figure 1-1.

8.2 Limitations

This work presents the development of a Takagi-Sugeno-Kang fuzzy neural framework to address the existing problems of TSK systems. Even though the proposed architectures have shown promising results, some further issues can still be investigated:

- Currently, the input and output features have all been empirically selected. No feature selection step to remove redundant attributes is employed in the proposed networks. Feature subset selection is a preprocessing step in computational learning tasks. It generates significant computational advantages by reducing the input dimensionality and alleviates the “curse of dimensionality” when dealing with large dimensional problem. It also helps to achieve improvement in the interpretability of the learning system by reducing the number of rules. As the proposed networks are online system, an online feature selection that is workable in time-variant environments is required.
- The main advantage of the TSK-model over the Mamdani-model is its ability to achieve higher level of system modeling accuracy. More specifically, TSK model can represent a complex system in term of fewer TSK-type rules. Furthermore, the TSK-model can give better accuracy with the same number of rules when compared to the Mamdani-model. Normally, a typical TSK fuzzy rule has the form shown in (8.1) which is a linear equation involving the input terms and their consequent parameters.

$$R_i : \text{IF } x_1 \text{ is } A_{i,1} \text{ AND } \dots \text{ AND } x_{n1} \text{ is } A_{i,n1} \text{ THEN } y = b_0 + b_1x_1 + \dots + b_{n1}x_{n1} \quad (8.1)$$

where $x = [x_1, \dots, x_{n1}]$ and y are the input vector and the output value, respectively. $A_{i,k}$ represents the membership function of the input label x_k for the i^{th} fuzzy rule; $[b_0, \dots, b_{n1}]$ represents a set of consequent parameters of the i^{th} fuzzy rule, $n1$ is the number of inputs. If the dimension of the input or output space is high, the number of terms used in the linear equation can be large even though some terms are, in fact, of little significance. The interpretability of the TSK network can be improved if the number of terms can be reduced. Insignificant terms should be removed from the network. Hence, instead of using the linear combination of all the input variables as the consequent part, only the most significant input variables should be used as the consequent terms. This will further improve the interpretability of fuzzy rules in the proposed networks. Thus, an online term reduction approach should be devised to achieve this goal.

- The proposed networks are type-1 fuzzy logic systems (FLSs). Type-2 FLSs [131] appear to be a more promising method than their type-1 counterparts in handling problems with uncertainties such as noisy data and different word meanings. That is, type-2 fuzzy sets allow researchers to model and minimize the effects of uncertainties in rule-based systems. Some examples of uncertainties are: (1) the words that are used in antecedents and consequents of rules can mean different things to different people; (2) consequents obtained by polling a group of experts will often be different for the same rule, because the experts will not necessarily be in agreement [132]. Type-1 FLSs are certain, therefore they are unable to directly handle these uncertainties. In contrast, type-2 FLSs are proven to be useful in handling these uncertainties. Extending the current proposed networks to type-2 can help to improve their abilities in dealing with uncertainties and noisy data. It also helps to further improve their accuracy in dealing with complex uncertain real-life problems.

8.3 Future Research Directions

This section presents two possible directions for future research; namely 1) the extensions to the proposed networks, and 2) the application domains for the proposed networks.

8.3.1 Extensions to the Proposed Networks

8.3.1.1 Online Feature Selection

Feature selection is important in many practical problems as it can help learning systems to achieve both generalization performance and fast learning ability. There are mainly two feature selection approaches: *filter approach* where the features are selected independently from the modeling system and *wrapper approach* where features are selected using the modeling system. The filter approach employs statistics computed from the empirical data distribution [133] or semantics-preserving information contained within the empirical dataset [3]. The wrapper approach can yield better performance at the expense of increased computational effort [134]. Feature selection approaches are often offline algorithms, such as principal component analysis (PCA) [135], linear discriminant analysis (LDA) [136], sensitivity analysis [137], or decision tree [138]. However, most of real-life problems are online, meaning that the data is not all available at the beginning but is sequential presented. Thus, an online incremental feature selection approach is required to deal with such online problems.

Many incremental feature selection methods have been proposed, such as incremental principal component analysis (IPCA) [139], incremental linear discriminant analysis (ILDA) [140]. In [139], Hall et al. proposed a method to incremental update the eigenvectors and eigenvalues to determine the most important features. In [141], Pang et al. proposed an ILDA algorithm to incrementally update a between-class scatter matrix and within-class scatter matrix. In [142], an ILDA algorithm based on the singular decomposition technique is proposed. In [143], an

extended version of IPCA which uses the accumulation ratio as the IPCA feature selection is proposed. The accumulation ratio will change every instant of time when a new sample comes. In [144], a new method which employ a resource allocation network with long-term memory (RAN-LTM) is proposed. This approach seems promising to be used in fuzzy neural networks.

In conclusion, an in-depth study is needed to explore the possibility of using an online feature selection approach in the proposed networks (GSETSK and RSETSK). Furthermore, a deselection approach should also be considered to remove insignificant features in online data streams with nonstationary characteristics.

8.3.1.2 Consequent Terms Selection

TSK network generally can model complex systems with higher accuracy while using fewer number of rules than Mamdani network. However, if the dimension of the input space is high, the number of terms used in the linear equation of each TSK fuzzy rule is also large. Thus, insignificant consequent terms should be removed from the TSK fuzzy rules to ensure a more compact and better interpretable TSK network. Only the most significant input variables should be used as the consequent terms.

Several algorithms have been developed in order to identify the significant consequent terms such as the *Sensitivity Calculation Method* [145]; the *Competitive Learning method* [48]; the *Weight Decay Method* [145]. In [145], a network pruning method based on the estimation of the sensitivity of the global cost function is proposed. In [48], competitive learning is used to identify the terms with larger weights and delete those with smaller one. However these methods cannot detect the correlation between candidate terms. This leads to the inaccuracy in computing the significance degree of each term, eventually the inaccuracy in finding the significant terms. Another pruning method which uses backpropagation learning to decay the weights of the insignificant terms to zero is proposed in [145]. However, this approach is slow and cannot

guarantee that the most significant terms can be determined. Besides, all the above methods are not applicable for online learning systems. In [15], the significant terms are chosen and incrementally added to the network whenever the parameter learning cannot further improve the network output accuracy during the on-line learning process. This method is efficient; however it uses many heuristic parameters.

A better algorithm should be devised in order to achieve the significant terms for each fuzzy rule. The algorithm should be applicable in online learning systems such as GSETSK and RSETSK. Rough-set approach [146] is gaining more popularity recently and it can be considered as a potential solution. Rough set theory was introduced by Pawlak to deal with imprecise or vague concepts. A rough set is a formal approximation of a crisp set by a pair of sets which gives the *lower* and the *upper* approximation of the original set. The lower approximation describes the domain objects that are known with certainty to belong to the subset of interest, whereas the upper approximation describes the objects that possibly belong to the subset. There are two fundamental but important concepts of rough set knowledge reduction: a *reduct* and the *core*. A reduct of knowledge is its critical part, which is sufficient enough to define all basic concepts in the considered knowledge, whereas the core is the most important part of the knowledge. The knowledge of decision rules is represented by the value attribute pair in the rough set knowledge reduction [146]. With the representation of decision rules as such, rough set theory then provides the logical methods employing *attribute dispensability* and *decision rule consistency* for knowledge reduction and analysis.

Attribute dispensability is defined as follows: an attribute $R \in \mathbf{R}$ is dispensable if it satisfies

$$IND(\mathbf{R}) = IND(\mathbf{R} - \{R\}) \quad (8.2)$$

in which $IND(\mathbf{R})$ is the indiscernibility relation over $\mathbf{R}$, which is the intersection of all equivalence relations belonging to $\mathbf{R}$.

Decision rule consistency is defined as follows: when a decision rule $\varphi \rightarrow \psi$ satisfies a system S , the decision rule is consistent in the system S if and only if for any decision rule $\varphi' \rightarrow \psi'$ in S , $\varphi = \varphi'$ implies $\psi = \psi'$.

Rough set are generally employed in offline applications [109]. However, recently, rough set are applied in online applications as well [147]. Thus, rough set can be considered in the future work to reduce the number of input terms by identifying the insignificant terms for each single fuzzy rule.

8.3.1.3 Type-2 Implementation

In this work, the proposed networks are actually type-1 fuzzy logic systems. However the proposed networks can easily be extended to type-2 fuzzy logic systems (FLSs) [131] [132]. Type-2 FLSs are extensions of type-1 FLSs, where the membership value of a type-2 fuzzy set is a type-1 fuzzy number. A typical type-2 fuzzy set is shown in Figure 8-1.

Figure 8-1: Type-2 fuzzy set with uncertainty mean

Consider extending the proposed GSETSK network to an interval type-2 fuzzy system. Each rule of type-2 GSETSK (GSETSK-II) will have the following form:

$$Rule_i : \text{IF } x_1 \text{ is } \tilde{A}_{i,1} \text{ AND } \dots \text{ AND } x_{n1} \text{ is } \tilde{A}_{i,n1} \text{ THEN } y = \tilde{b}_0 + \tilde{b}_1 x_1 + \dots + \tilde{b}_{n1} x_{n1} \quad (8.3)$$

where $\tilde{A}_{i,j}$ are interval type-2 fuzzy sets, and $\tilde{b}_i$ are interval sets, with

$$\tilde{b}_i = [c_i - s_i, c_i + s_i]$$

where c_i determines the center of the interval and s_i determines the interval range.

Extending the current proposed networks to type-2 can help to improve their abilities in dealing with uncertainties and noisy data. It also helps to further improve their accuracy in dealing with complex uncertain real-life problems. Thus, an in-depth study on how to extend the proposed networks to type-2 should be carefully investigated.

8.3.2 Application Domains for the Proposed Networks

The proposed fuzzy neural networks have been successfully applied in three real life applications; namely: 1) Stock Market Trading System, 2) Option Trading and Hedging and 3) Traffic Prediction. The encouraging results suggest that the proposed networks can be used in more challenging real-life applications in the areas of medical or financial data analysis, signal processing and biometrics. The proposed stock trading system in Chapter 5 and the proposed option trading system in Chapter 6 were designed to be able to adapt to many technical analysis approaches. In fact, it is possible to use a combination of multiple technical indicators to devise trading systems with better accuracy based on the proposed systems.

The fuzzy rules identified by the proposed networks based on the real-life data can help experts to better understand how the networks achieve the final results. This can empower the experts the

ability to evaluate or monitor the performance of the networks in the fields that require high accuracy performance such as blood glucose regulation for diabetes mellitus patients.

Bibliography

- [1] L. A. Zadeh, "Fuzzy logic, neural networks, and soft computing," *Commun. ACM*, vol. 37, pp. 77-84, 1994.
- [2] S. Mitra and Y. Hayashi, "Neuro-fuzzy rule generation: survey in soft computing framework," *IEEE Trans. Neural Netw.*, vol. 11, pp. 748-768, 2000.
- [3] Q. Shen and R. Jensen, "Semantics-preserving dimensionality reduction: rough and fuzzy-rough-based approaches," *IEEE Trans. Knowl. Data Eng.*, vol. 16, pp. 1457-1471, 2004.
- [4] C. T. Lin and C. S. G. Lee, *Neural Fuzzy Systems: A Neuro-Fuzzy Synergism to Intelligent Systems*. New Jersey: Prentice Hall PTR, 1996.
- [5] T. Takagi and M. Sugeno, "Fuzzy Identification of Systems and its Applications to Modeling and Control," *IEEE Trans. Sys., Man, Cybern.*, vol. 15, pp. 116-132, 1985.
- [6] G.-B. Huang, P. Saratchandran, and N. Sundararajan, "A generalized growing and pruning RBF (GGAP-RBF) neural network for function approximation," *IEEE Trans. Neural Netw.*, vol. 16, pp. 57-67, Jan. 2005.
- [7] R. Jang, "ANFIS: adaptive-network-based fuzzy inference system," *IEEE Trans. Sys., Man, Cybern. B*, vol. 23, pp. 665-685, 1993.
- [8] G. Leng, G. Prasad, and T. M. McGinnity, "An on-line algorithm for creating self-organizing fuzzy neural networks," *Neural Netw.*, vol. 17, pp. 1477-1493, 2004.
- [9] S. Wu and M. J. Er, "Dynamic fuzzy neural networks: A novel approach to function approximation," *IEEE Trans. Syst. Man Cybern. B, Cybern.*, vol. 30, pp. 358-364, Apr. 2000.
- [10] K. H. Quah and C. Quek, "FITSK: online local learning with generic fuzzy input Takagi-Sugeno-Kang fuzzy framework for nonlinear system estimation," *IEEE Trans. Sys., Man, Cybern. B*, vol. 36, pp. 166-178, 2006.
- [11] N. K. Kasabov and Q. Song, "DENFIS: Dynamic evolving neural-fuzzy inference system and its application for time-series prediction," *IEEE Trans. Sys., Man, Cybern. B*, vol. 10, pp. 144-154, 2002.
- [12] H. J. Rong, N. Sundararajan, G. B. Huang, and P. Saratchandran, "Sequential adaptive fuzzy inference system (SAFIS) for nonlinear system identification and prediction," *Fuzzy Sets Syst.*, vol. 157, pp. 1260-1275, 2006.
- [13] D. Kukolj and E. Levi, "Identification of complex systems based on neural and Takagi-Sugeno fuzzy model," *IEEE Trans. Sys., Man, Cybern. B*, vol. 34, pp. 272-282, 2004.
- [14] C. S. Ouyang, W. J. Lee, and S. J. Lee, "A TSK-type neuro fuzzy network approach to system modeling problems," *IEEE Trans. Sys., Man, Cybern. B*, vol. 35, pp. 751-767, 2005.
- [15] C. F. Juang and C. T. Lin, "An online self-constructing neural fuzzy inference network and its applications," *IEEE Trans. Fuzzy Syst.*, vol. 6, pp. 12-32, 1998.
- [16] E. D. Lughofer, "FLEXFIS: A robust incremental learning approach for evolving Takagi-Sugeno fuzzy models," *IEEE Trans. Fuzzy Syst.*, vol. 16, pp. 1393-1410, Dec. 2008.
- [17] P. P. Angelov and D. P. Filev, "An approach to online identification of Takagi-Sugeno fuzzy models," *IEEE Trans. Sys., Man, Cybern. B*, vol. 34, pp. 484-498, 2004.
- [18] C. W. Ting and C. Quek, "A Novel Blood Glucose Regulation Using TSK0-FCMAC: A Fuzzy CMAC Based on the Zero-Ordered TSK Fuzzy Inference Scheme," *IEEE Trans. Neural Netw.*, vol. 20, pp. 856 - 871 2009.
- [19] M. Adya and F. Collopy, "How effective are neural networks at forecasting and prediction? A review and evaluation," *Int. J. Forecasting*, vol. 17, pp. 481-495, 1998.

- [20] F. Crick and G. Mitchinson, "The function of dream sleep," *Nature*, vol. 304, pp. 111-114, 1983.
- [21] S. Wimbauer and J. L. v. Hemmen, "Hebbian Unlearning," in *Proc. Analysis of Dynamical Cognitive System, Advance Course*, 1995, pp. 121-136.
- [22] C. F. Juang and C. T. Lin, "A recurrent self-organizing neural fuzzy inference system," *IEEE Trans. Neural Netw.*, vol. 10, pp. 828-845, 1999.
- [23] C. F. Juang, "A TSK-type recurrent fuzzy network for dynamic systems processing by neural network and genetic algorithms," *IEEE Trans. Fuzzy Syst.*, vol. 10, pp. 155-1170, 2002.
- [24] S. S. Haykin, *Neural Networks: A Comprehensive Foundation*. New Jersey: Prentice Hall, 1999.
- [25] K. Hornik, "Approximation capabilities of multilayer feedforward networks," *Neural Netw.*, vol. 4, pp. 251-257, 1991.
- [26] J. Sjoberg, Q. Zhang, L. Ljung, A. Benveniste, B. Deylon, and P.-Y. e. al., "Nonlinear Black-Box Modeling in System Identification: a Unified Overview: Trends in System Identification," *Automatica*, vol. 31, pp. 1691-1724, 1995.
- [27] J.-S.R.Jang and C.-T. Sun, *Neuro-fuzzy and soft computing: a computational approach to learning and machine intelligence*: Upper Saddle River, NJ: Prentice Hall, 1995.
- [28] A. Kandel, *Fuzzy expert systems*. Boca Raton, FL: CRC Press, 1992.
- [29] A. Lotfi, H. C. Andersen, and A. C. Tsoi, "Matrix formulation of fuzzy rule-based systems " *IEEE Trans. Syst. Man Cybern. B, Cybern.*, vol. 26, pp. 332-340, 1996.
- [30] C. C. Lee, "Fuzzy logic in control systems: fuzzy logic controller," *IEEE Trans. Syst. Man Cybern. B, Cybern.*, vol. 20, pp. 404-418, 1990.
- [31] J.-S.R.Jang, C.-T. Sun, and M. Eiji, *Neuro-fuzzy and soft computing: a computational approach to learning and machine intelligence*. New Jersey: Prentice Hall, 1997.
- [32] L. A. Zadeh, "The concept of a linguistic variable and its application to approximate reasoning-III," *Information Sciences*, vol. 9, pp. 43-80, 1975c.
- [33] E. H. Mamdani, "Application of fuzzy logic to approximate reasoning using linguistic systems," *IEEE Trans. Comput.*, pp. 1182-1191, 1977.
- [34] T. Takagi and M. Sugeno, "Fuzzy identification of systems and its application to modeling and control," *IEEE Trans. Syst., Man, Cybern. B*, vol. 15, pp. 116-132, Feb. 1985.
- [35] J. Casillas, O. Cordón, F. Herrera, and L. Magdalena, *Interpretability Issues in Fuzzy Modeling (Studies in fuzziness and soft computing, No. 128)*. Berlin: Springer-Verlag, 2003.
- [36] J.-S. R. Jang and C.-T. Sun, "Neuro-fuzzy modeling and control," in *Proc. of the IEEE*, 1995, pp. 378-406.
- [37] S. Medasani, J. Kim, and R. Krishnapuram, "An overview of membership function generation techniques for pattern recognition," *International Journal of Approximate Reasoning*, vol. 19, pp. 391-417, 1998.
- [38] W. L. Tung and C. Quek, "GenSoFNN: a generic self-organizing fuzzy neural network," *IEEE Trans. Neural Netw.*, vol. 13, pp. 1075-1086, 2002.
- [39] T. Kohonen, *Self-Organization and Associative Memory*. Berlin, New York: Springer-Verlag, 1989.
- [40] R. W. Zhou and C. Quek, "POPFNN: A Pseudo Outer-product Based Fuzzy Neural Network," *Neural Networks*, vol. 9, pp. 1569-1581.
- [41] C. T. Lin, "A neural fuzzy control system with structure and parameter learning," *Fuzzy Sets and Systems*, vol. 70, pp. 183-212, 1995.

- [42] J. C. Bezdek, *Pattern Recognition with Fuzzy Objective Function Algorithms*. New York: Plenum Press, 1981.
- [43] L. A. Zadeh, "The concept of a linguistic variable and its application to approximate reasoning-I," *Information Sciences*, vol. 8, pp. 199–249, 1975a.
- [44] L. A. Zadeh, "The concept of a linguistic variable and its application to approximate reasoning-II," *Information Sciences*, vol. 8, pp. 301–357, 1975b.
- [45] R. Mikut, J. Jakel, and L. Groll, "Interpretability issues in data-based learning of fuzzy systems," *Fuzzy Sets and Systems*, vol. 150, pp. 179-197, 2005.
- [46] F. L. Chung and T. Lee, "Fuzzy Learning Vector Quantization," in *Int. Joint Conf. Neural Networks*, 1993, pp. 2739-2742.
- [47] K. K. Ang, C. Quek, and M. Pasquier, "POPFNN-CRI(S): pseudo outer product based fuzzy neural network using the compositional rule of inference and singleton fuzzifier," *IEEE Trans. Sys., Man, Cybern. B*, vol. 33, 2003.
- [48] C. T. Lin and C. S. G. Lee, "Neural-network-based fuzzy logic control and decision system," *IEEE Trans. Comput.*, vol. 40, pp. 1320-1336, 1991.
- [49] R. R. Yager, "Modeling and formulating fuzzy knowledge bases using neural networks," *Neural Netw.*, vol. 7, pp. 1273-1283, 1994.
- [50] C. Quek and R. W. Zhou, "The POP learning algorithms: reducing work in identifying fuzzy rules," *Neural Netw.*, vol. 14, pp. 1431-1445, 2001.
- [51] I. Hayashi, H. Nomura, H. Yamasaki, and H. Wakami, "Construction of fuzzy inference rules by NDF and NDFL," *Int. J Approx. Reason.*, vol. 6, pp. 241-266, 1992.
- [52] H. Ishibuchi and H. Tanaka, "Interpolation of fuzzy if-then rules by neural networks," *Int. J Approx. Reason.*, vol. 10, pp. 3-27, 1994.
- [53] C. Quek and W. L. Tung, "A novel approach to the derivation of fuzzy membership functions using the Falcon-MART architecture," *Pattern Recognit. Lett.*, vol. 22, pp. 941-958, 2001.
- [54] J. V. d. Oliveira, "Towards neuro-linguistic modeling: Constraints for optimization of membership functions," *Fuzzy Sets and Systems*, vol. 106, pp. 357-380, 1999.
- [55] L. A. Zadeh, "Calculus of fuzzy restrictions," in *Fuzzy sets, fuzzy logic, and fuzzy systems: selected papers by Lotfi A. Zadeh*, ed: World Scientific Publishing Co., Inc., 1996, pp. 210-237.
- [56] S. Horikawa, T. Furuhashi, and Y. Uchikawa, "On fuzzy modeling using fuzzy neural networks with the backpropagation algorithm," *IEEE Trans. Neural Netw.*, vol. 3, pp. 801–806, 1992.
- [57] L. Franco, D. A. Elizondo, and J. e. M. Jerez, *Constructive Neural Networks (Studies in Computational Intelligence)*: Berlin Heidelberg Germany: Springer-Verlag, 2010.
- [58] W. L. Tung and C. Quek, "eFSM--a novel online neural-fuzzy semantic memory model," *IEEE Trans. Neural Netw.*, vol. 21, pp. 136-157, 2010.
- [59] C. F. Juang, Y. Y. Lin, and C. C. Tu, "A recurrent self-evolving fuzzy neural network with local feedbacks and its application to dynamic system processing," *Fuzzy Set Syst.*, vol. 161, pp. 2552-2568, 2010.
- [60] C. F. Juang and Y.-W. Tsao, "A Self-Evolving Interval Type-2 Fuzzy Neural Network With Online Structure and Parameter Learning," *IEEE Trans. Fuzzy Syst.*, vol. 16, pp. 1411 - 1424, 2008.
- [61] A. M. Tang, C. Quek, and G. S. Ng, "GA-TSKfnn: Parameters tuning of fuzzy neural network using genetic algorithms," *Expert Syst. Appl.*, vol. 29, pp. 769-781, 2005.
- [62] D. Wang, C. Quek, and G. S. Ng, "Novel Self-Organizing Takagi Sugeno Kang Fuzzy Neural Networks Based on ART-like Clustering," *Neural Processing Letters*, vol. 20, pp. 39 - 51, 2004.

- [63] A. Tsymbal, "The problem of concept drift: definitions and related work, Technical Report TCD-CS-2004-15," *Department of Computer Science, Trinity College Dublin, Ireland*, 2004.
- [64] E. Lughofer and P. Angelov, "Handling drifts and shifts in on-line data streams with evolving fuzzy systems," *Appl. Soft Comput.*, vol. 11, pp. 1568-4946, 2011.
- [65] T. J. R. Klinkenberg, "Detection concept drift with support vector machines," in *Proc. Seventh Int. Conf. Mach. Learning (ICML)*, Morgan Kaufmann, 2000, pp. 487-494.
- [66] R. Klinkenberg, "Learning drifting concepts: example selection vs. example weighting," *Intelligent Data Analysis*, vol. 8, pp. 281-300, 2004.
- [67] S. Ramamurthy and R. Bhatnagar, "Tracking recurrent concept drift in streaming data using ensemble classifiers," in *Proceedings of the Sixth International Conference on Machine Learning and Applications (ICMLA)*, 2007, pp. 404-409.
- [68] J. Beringer and E. Hüllermeier, "Efficient instance-based learning on data streams," *Intelligent Data Analysis*, vol. 11, pp. 627-650, 2007.
- [69] S. J. Delany, P. Cunningham, A. Tsymbal, and L. Coyle, "A case-based technique for tracking concept drift in spam filtering," *Knowledge-Based Systems*, vol. 18, pp. 187-195, 2005.
- [70] D. L. Michael, "Determining the dimensionality of multidimensional scaling representations for cognitive modeling," *J Math Psychol*, vol. 45, pp. 149 - 166, 2001.
- [71] J. B. Theoharis, "A high-order recurrent neuro-fuzzy system with internal dynamics: Application to the adaptive noise cancellation," *Fuzzy Set Syst.*, vol. 157, pp. 471-500, 2006.
- [72] C.-S. Chen, "TSK-Type Self-Organizing Recurrent-Neural-Fuzzy Control of Linear Microstepping Motor Drives," *IEEE Trans. Power Electron.*, vol. 25, pp. 2253 - 2265 2010.
- [73] C. F. Juang, R.-B. Huang, and W.-Y. Cheng, "An Interval Type-2 Fuzzy-Neural Network With Support-Vector Regression for Noisy Regression Problems," *IEEE Trans. Fuzzy Syst.*, vol. 18, pp. 686-699, 2010.
- [74] P. P. Angelov and D. P. Filev, "Simpl_eTS: A simplified method for learning evolving Takagi-Sugeno fuzzy models," presented at the Proc. 14th IEEE Int. Conf. Fuzzy Syst., Reno, NV, 2005.
- [75] P. Angelov and X. Zhou, "Evolving fuzzy systems from data streams in real-time," presented at the International Symposium on Evolving Fuzzy Systems, Ambleside, UK, 2006.
- [76] P. Angelov, "Evolving Takagi-Sugeno Fuzzy Systems From Streaming Data (eTS+)," in *Evolving Intelligent Systems: Methodology and Applications*, ed: John Wiley & Sons, 2010.
- [77] J. R. Whitlock, A. J. Heynen, M. G. Shuler, and M. F. Bear, "Learning induces long-term potentiation in the hippocampus," *Science*, vol. 313, pp. 1093-1097, 2006.
- [78] M. H. Hayes, *Recursive Least Squares: Statistical Digital Signal Processing and Modeling*. Wiley, 1996.
- [79] R. W. Zhou and C. Quek, "POPFNN: A Pseudo Outer-product Based Fuzzy Neural Network," *Neural Netw.*, vol. 9, pp. 1569-1581, 1996.
- [80] C. Quek and R. Zhou, "POPFNN-AARS(S): A pseudo outer-product based fuzzy neural network," *IEEE Trans. Syst. Man Cybern. B, Cybern.*, vol. 29, pp. 859-870, Dec. 1999.
- [81] C. Quek and R. Zhou, "Structure and learning algorithms of a nonsingleton input fuzzy neural network based on the approximate analogical reasoning schema," *Fuzzy Sets Syst.*, vol. 157, pp. 1814-1831, 2006.

- [82] C. T. Lin and C. S. G. Lee, "Real-time supervised structure/parameter learning for fuzzy neural network," *IEEE Int. Conf. Fuzzy Syst.*, vol. 1283-1291, 1992.
- [83] R. M. French, "Catastrophic forgetting in connectionist networks," presented at the Encyclopedia of Cognitive Science, L. Nadel, Ed. London, U.K, 2003.
- [84] R. M. Nosofsky, "Similarity scaling and cognitive process models," *Annual Review of Psychology*, vol. 43, pp. 25-53, 1992.
- [85] J. Yen and R. Langari, *Fuzzy Logic: Intelligence, Control and Information*. Englewood Cliffs, NJ: Prentice Hall, 1999.
- [86] I. B. Turksen and Z. Zhong, "An approximate analogical reasoning approach based on similarity measure and interval valued fuzzy sets," *Fuzzy Sets Syst.*, vol. 34, pp. 323-346, 1990.
- [87] Y. W. Lu, N. Sundararajan, and P. Saratchandran, "A sequential learning scheme for function approximation using minimal radial basis function (RBF) neural networks," *Neural Comput.*, vol. 9, pp. 461-478, 1997.
- [88] V. Kadirkamanathan and M. Niranjan, "A function estimation approach to sequential learning with neural networks," *Neural Comput.*, vol. 5, pp. 954-975, 1993.
- [89] J. S. Jang, "Neuro-Fuzzy Modeling: Architecture, Analyzes and Applications," *Ph.D dissertation, Dept. Elect. Eng. Comput. Sci., Univ. California, Berkeley*, 1992.
- [90] R. S. C. III, "Predicting the Mackey-glass timeseries with cascade-Correlation learning," *Proc. 1990 Connectionist Models Summer School*, pp. 117-123, 1990.
- [91] J. Platt, "A resource allocation network for function interpolation," *Neural Computat.*, vol. 3, pp. 213-225, 1991.
- [92] N. N. Nguyen and C. Quek, "Stock Price Prediction using Generic Self-Evolving Takagi-Sugeno-Kang (GSETSK) Fuzzy Neural Network," presented at the Proc. IJCNN'2010 Neural Networks, 2010.
- [93] E. P. Santos and F. J. V. Zuben, "Efficient second-order learning algorithm for discrete-time recurrent neural networks," in *Recurrent Neural Networks: Design and Applications*, L. R. Medsker and L. C. Jain, Eds., ed Fla, USA: CRC Press, 2000, pp. 47-75.
- [94] P. S. Sastry, G. Santharam, and K. P. Unnikrishnan, "Memory neural networks for identification and control of dynamic systems," *IEEE Trans. Neural Netw.*, vol. 5, pp. 306-319, 1994.
- [95] C.H.Lee and C.C.Teng, "Identification and control of dynamic systems using recurrent fuzzy neural networks," *IEEE Trans. Fuzzy Syst.*, vol. 8, pp. 349-366, 2000.
- [96] Y. Gao and M. J. Er., "NARMAX time series model prediction: feed-forward and recurrent fuzzy neural network approaches," *Fuzzy Sets Syst.*, vol. 150, pp. 331-350, 2005.
- [97] R. Gencay, "The predictability of security returns with simple technical trading rules," *J. Empir. Finance*, vol. 5, pp. 347-359, 1998.
- [98] B. Graham and D. Dodd, *Security Analysis: Principles and Techniques*. New York: McGraw-Hill, 1940.
- [99] G. S. Atsalakis and K. P. Valavanis, "Forecasting stock market short-term trends using a neuro-fuzzy based methodology," *Expert Syst. Appl.*, vol. 36, pp. 10696-10707, 2009.
- [100] E. F. Fama, "Efficient capital markets: II," *J. Finance*, vol. 46, pp. 1575-1617, Dec. 1991.
- [101] A. W. Lo, H. Mamaysky, and J. Wang, "Foundations of technical analysis: Computational algorithms, statistical inference, and empirical implementation," *J. Finance*, vol. 55, pp. 1705-1765, 2000.

- [102] A. Shleifer, *Inefficient Markets: An Introduction to Behavioral Finance*. New York: Oxford Univ. Press, 2000.
- [103] T. Plummer and A. Ridley, *Forecasting Financial Markets: The Psychological Dynamics of Successful Investing*, 4th ed. London, U.K.: Kogan Page, 2003.
- [104] S. Haykin, *Neural Networks: A Comprehensive Foundation*, 2nd ed. Englewood Cliffs, NJ: Prentice-Hall, 1998.
- [105] E. M. Azoff, *Neural Network Time Series Forecasting of Financial Markets*. New York: Wiley, 1994.
- [106] M. Adya and F. Collopy, "How effective are neural networks at forecasting and prediction? A review and evaluation," *Int. J. Forecasting*, vol. 17, pp. 481–495, 1998.
- [107] M. Austin and C. Looney, "Security market timing using neural network models," *New Rev. Appl. Expert Syst.*, vol. 3, pp. 3-14, 1997.
- [108] P. Cheng, C. Quek, and M. L. Mah, "Predicting the impact of anticipatory action on US stock market—An event study using ANFIS (a neural fuzzy model)," *Comput. Intell.*, vol. 23, pp. 117–141, 2007.
- [109] K. K. Ang and C. Quek, "Stock Trading Using RSPOP: A Novel Rough Set-Based Neuro-Fuzzy Approach," *IEEE Trans. Neural Netw.*, vol. 17, pp. 1301-1315, 2006.
- [110] T. Z. Tan, C. Quek, and G. S. Ng, "Biological brain-inspired genetic complementary learning for stock market and bank failure prediction," *Comput. Intell.*, vol. 23, pp. 236–261, 2007.
- [111] H. Huang, M. Pasquier, and C. Quek, "Financial Market Trading System With a Hierarchical Coevolutionary Fuzzy Predictive Model," *IEEE Trans. Evol. Comput.*, vol. 13, pp. 56-70, 2009.
- [112] P. C. Chang and C. Y. Fan, "A Hybrid System Integrating a Wavelet and TSK Fuzzy Rules for Stock Price Forecasting," *IEEE Trans. Syst., Man, Cybern. B*, vol. 38, pp. 802 - 815, 2008
- [113] J. S. Abarbanell and B. J. Bushee, "Fundamental analysis, future earnings, and stock prices," *J. Account. Res.*, vol. 35, pp. 1-24, 1997.
- [114] J. Moody, L. Wu, Y. Liao, and M. Saffell, "Performance functions and reinforcement learning for trading systems and portfolios," *Journal of Forecasting*, vol. 17, pp. 441-470, 1998.
- [115] W. Brock, J. Lakonishok, and B. LeBaron, "Simple technical trading rules and the stochastic properties of stock returns," *J. Finance*, vol. 47, pp. 1731–1764, 1992.
- [116] K. K. Ang and C. Quek, "RSPOP: Rough Set-Based Pseudo Outer-Product Fuzzy Rule Identification Algorithm," *Neural Comput.*, vol. 17, pp. 205-243, 2005.
- [117] R. N. Goldman and J. S. Weinberg, *Statistics: An Introduction*. NJ: Prentice-Hall, 1985.
- [118] S. Chen, C. F. N. Cowan, and P. M. Grant, "Orthogonal least squares learning algorithm for radial basis," *IEEE Trans. Neural Netw.*, vol. 2, pp. 302–309, 1991.
- [119] D. E. Rumelhart, G. E. Hinton, R. J. Williams, D. E. Rumelhart, and J. L. McClelland, "Learning internal representations by error propagation," in *Parallel Distributed Processing: Explorations in the Microstructure of Cognition*. vol. 1, ed: Cambridge, MA:MIT Press, 1986.
- [120] C. Quek, M. Pasquier, and N. Kumar, "A novel recurrent neural network-based prediction system for option trading and hedging," *Appl. Intell.*, vol. 29, pp. 138-151, 2008.
- [121] H. White, "Economic prediction using neural networks: the case of IBM daily stock returns," in *Proceedings of the 2nd Annual IEEE conference on neural networks*, 1988, pp. 451–458.

- [122] W. Chiang, T. Urban, and G. Baldridge, "A neural network approach to mutual fund net asset value forecasting," *Omega Int J Manag Sci*, vol. 24, pp. 205–215, 1996.
- [123] W. L. Tung and C. Quek, "GenSo-OPATS: A brain-inspired dynamically evolving option pricing model and arbitrage trading system," in *Proc. IEEE CEC*, Edinburgh, Scotland, 2005, pp. 2429–2436.
- [124] S. D. Teddy, E. M.-K. Lai, and C. Quek, "A cerebellar associative memory approach to option pricing and arbitrage trading," *Neurocomputing*, vol. 71, 2008.
- [125] M. A. Gluck and C. E. Myers, *Gateway to memory: an introduction to neural network modeling of the hippocampus and learning*. Cambridge: Mass., MIT Press, 2001.
- [126] D. M. Chance, *An Introduction to Derivatives & Risk Management*, 6 ed.: Thomson (South-Western), 2004.
- [127] F. Liu, C. Quek, and G. Ng, "A novel generic hebbian ordering-based fuzzy rule base reduction approach to mamdani neuro-fuzzy system," *Neural Comput.*, vol. 19, pp. 1656–1680, 2007.
- [128] G. K. Tan, "Feasibility of predicting congestion states with neural networks," Final Year Project, School of Civil Structural Engineering, Nanyang Technological Univ., Singapore, 1997.
- [129] R. N. Goldman and J. S. Weinberg, *Statistics: An Introduction*. NJ: Prentice-Hall, 1985.
- [130] N. K. Kasabov, "Evolving fuzzy neural networks for supervised/unsupervised online knowledge-based learning," *IEEE Trans. Sys., Man, Cybern., B*, vol. 31, pp. 902–918, 2001.
- [131] N. N. Karnik, J. M. Mendel, and Q. Liang, "Type-2 fuzzy logic systems," *IEEE Trans. Fuzzy Syst.*, vol. 7, pp. 643–658, 1999.
- [132] J. M. Mendel and R. I. John, "Type-2 fuzzy sets made simple," *IEEE Trans. Fuzzy Syst.*, vol. 10, pp. 117–127, 2002.
- [133] T. W. S. Chow and D. Huang, "Estimating optimal feature subsets using efficient estimation of high-dimensional mutual information," *IEEE Trans. Neural Netw.*, vol. 16, pp. 213–224, 2005.
- [134] R. Kohavi and G. H. John, "Wrappers for feature subset selection," *Artificial Intelligence*, vol. 97, pp. 273–324, 1997.
- [135] R. W. Preisendorfer, *Principle Component Analysis in Meteorology and Oceanography*: Elsevier Science Publishing Company, 1988.
- [136] A. M. Martinez and A. C. Kak, "PCA versus LDA," *IEEE Trans. Pattern Anal. Mach. Intell.*, vol. 23, pp. 228–233, 2001.
- [137] T. Hastie, R. Tibshirani, and J. Friedman, *The elements of statistical learning: Data Mining, Inference, and Prediction*, 2 ed.: Springer, 2009.
- [138] J. Abonyi, J. A. Roubos, and F. Szeifert, "Data-Driven Generation of Compact, Accurate, and Linguistically-Sound Fuzzy Classifiers Based on a Decision-Tree Initialization," *Int. J Approx. Reason.*, vol. 32, pp. 1–21, 2002.
- [139] P. M. Hall, D. Marshall, and R. R. Martin, "Incremental Eigenanalysis for Classification," in *British Machine Vision Conference*, 1998, pp. 286–295.
- [140] J. Weng, Y. Zhang, and W. S. Hwang, "Candid covariance-free incremental principal component analysis," *IEEE Trans. Pattern Anal. Mach. Intell.*, vol. 25, pp. 1034–1040, 2003.
- [141] S. Pang, S. Ozawa, and N. Kasabov, "Incremental linear discriminant analysis for classification of data streams," *IEEE Trans. Syst. Man Cybern. B, Cybern.*, vol. 35, pp. 905–914, 2005.
- [142] H. Zhao and P. C. Yuen, "Incremental linear discriminant analysis for face recognition," *IEEE Trans. Syst. Man Cybern. B, Cybern.*, vol. 38, pp. 210–221, 2008.

- [143] S. Ozawa, S. Pang, and N. Kasabov, "A modified incremental principal component analysis for on-line learning of feature space and classifier," in *PRICAI 2004: Trends in Artificial Intelligence*, 2004, pp. 231-240.
- [144] S. Ozawa, S. L. Toh, S. Abe, S. Pang, and N. Kasabov, "Incremental learning of feature space and classifier for face recognition," *Neural Netw.*, vol. 18, pp. 575-584, 2005.
- [145] R. Reed, "Pruning algorithms—A survey," *IEEE Trans. Neural Netw.*, vol. 4, pp. 740–747, 1993.
- [146] Z. Pawlak, *Rough Sets: Theoretical Aspects of Reasoning about Data*: Kluwer Academic Publishers, 1992.
- [147] M.-B. Pang and G.-G. He, "Chaos Rapid Recognition of Traffic Flow by Using Rough Set Neural Network," in *International Symposiums on Information Processing 2008*, pp. 168 - 172.

Author's Publication

N. N. Nguyen and C. Quek, "RSFCMAC: A novel rough set-based rule reduction approach for fuzzy CMAC architecture with yager-inference-scheme " presented at the IEEE Int. Conf. on Fuzzy Syst., 2009.

N. N. Nguyen and C. Quek, "Stock Price Prediction using Generic Self-Evolving Takagi-Sugeno-Kang (GSETSK) Fuzzy Neural Network," presented at the Proc. IJCNN'2010 Neural Networks, 2010.

N. N. Nguyen and C. Quek, "GSETSK - A Generic Self Evolving TSK Fuzzy Neural Network," *Appl. Soft Comput.*, undergoing review.

N. N. Nguyen and C. Quek, "Stock Market Trading System With a Recurrent Self-Evolving TSK Predictive Model," *Int. J. Forecasting*, undergoing 2nd revision.

N. N. Nguyen and C. Quek, "A Recurrent Self-Evolving TSK Fuzzy Neural Network for Option Trading and Hedging," *Int. J. Forecasting*, paper under preparation.

N. N. Nguyen and C. Quek, "Traffic Prediction using a Generic Self-Evolving Takagi-Sugeno-Kang (GSETSK) Fuzzy Neural Network," presented at the Proc. IJCNN'2012 Neural Networks, submitted for publication.