Green energy and content-aware data transmissions in maritime wireless communication networks

Yang, Tingting; Zheng, Zhongming; Liang, Hao; Deng, Ruilong; Cheng, Nan; Shen, Xuemin

2014

Yang, T., Zheng, Z., Liang, H., Deng, R., Cheng, N., & Shen, X. (2014). Green energy and content-aware data transmissions in maritime wireless communication networks. IEEE Transactions on Intelligent Transportation Systems, 16(2), 751-762.

<https://hdl.handle.net/10356/79399>

<https://doi.org/10.1109/TITS.2014.2343958>

© 2014 IEEE. Personal use of this material is permitted. Permission from IEEE must be obtained for all other uses, in any current or future media, including reprinting/republishing this material for advertising or promotional purposes, creating new collective works, for resale or redistribution to servers or lists, or reuse of any copyrighted component of this work in other works. The published version is available at: [<http://dx.doi.org/10.1109/TITS.2014.2343958>].

Downloaded on 26 Apr 2023 14:28:40 SGT

Green Energy and Content Aware Data Transmissions in Maritime Wireless Communication Networks

Tingting Yang, *Member, IEEE*, Zhongming Zheng, *Student Member, IEEE*, Hao Liang, *Member, IEEE*, Ruilong Deng, *Student Member, IEEE*, Nan Cheng, *Student Member, IEEE*, Xuemin (Sherman) Shen, *Fellow, IEEE*

Abstract—In this paper, we investigate the network throughput and energy sustainability of green-energy-powered maritime wireless communication networks. Specifically, we study how to optimize the schedule of data traffic tasks to maximize the network throughput with Worldwide Interoperability for Microwave Access (WiMAX) technology. To this end, we formulate it as an optimization problem to maximize weight of the total delivered data packets, while ensuring that harvested energy can successfully support transmission tasks. The formulated energy and content aware vessel throughput maximize problem (EVTMP) is proved to be $\mathcal{NP}$ -complete. We propose a green energy and content aware data transmission framework that incorporates the energy limitation of both infostations and Delay Tolerant Network (DTN) throw-boxes. The green energy buffer is modeled $G/G/1$ queue, and two heuristic algorithms are designed to optimize the transmission throughput and energy sustainability. Extensive simulations demonstrate that our proposed algorithms can provide simple yet efficient solutions in a maritime wireless communication network with sustainable energy.

I. INTRODUCTION

With the advances of wireless technologies, maritime wireless communication network is emerging as one of the important information transmission systems. Generally, the transmissions in maritime wireless networks can be classified into two types: terrestrial and satellite communication [1]. By utilizing the legacy analog high frequency/medium frequency (HF/MF) and very high frequency (VHF) radios, long/medium or short range ship-to-shore and ship-to-ship communications near port water can be enabled, respectively. However, such transmissions are not able to provide high rate services. With satellite communications, Fleet Broadband (FBB), the transmission can achieve a high data rate of up to 432kbps,

but launching satellites into orbits leads to prohibitive service fees. Compared with land-based wireless communication, the maritime wireless networks suffer the much higher costs for devices deployment, energy consumption and maintenance of maritime wireless networks. Therefore, it is essential to develop a novel, cost-effective wide-band maritime communication network by innovative communication technologies from the land to the sea.

Green energy refers to eco-friendly and sustainable energy sources, e.g. wind, solar, modern biomass, etc. Among a variety of green energy sources, wind power grows rapidly at the rate of 30% annually, which achieved 198GW all over the world in 2010. Solar power is another popular green energy source, and cumulative global photovoltaic (PV) installations surpassed 40GW at the end of 2010 [2]. Moreover, with the development of green energy technology, crystalline silicon devices can approach the theoretical limiting efficiency of 29%. Motivated by the relative high performance-cost ratio, solar and wind power are two of the most common energy sources that have been extensively used to power wireless networks, especially the network infrastructure. For instance, the Green WiFi initiative has developed a low cost, solar-powered, standardized WiFi solution for providing Internet access to developing areas [3]. The wind-powered wireless mesh networks are also applied for emergency network deployment after disasters [4].

The advances of green wireless networks have provided an alternative energy for maritime wireless networks, which can significantly decrease the cost of maritime wireless networks establishment and maintenance. For instance, due to the long coastline, some infostations may be constructed on the island or other remote areas, and thus it might be prohibitive and inconvenient to use cable to connect electricity grid and access to the island for maintenance. By using green energy, the infostations can be constructed easily and less maintenance is required, which can significantly reduce the cost. However, unlike traditional electricity grid, green energy highly depends on its position, local weather and time, which makes the green energy inherently variable or even intermittent with time. Thus, the fundamental design criterion and the main performance metric under the scenario of green-energy-powered maritime wireless networks are shifted from energy efficiency to energy sustainability. Combining with green energy supplies, the challenges of the maritime wireless communication networks are different with the applications of green-energy-

Tingting Yang is with the Navigation College, Dalian Maritime University, 1 Linghai Road, Dalian, Liaoning, China 116026 (e-mail: yangtingting820523@163.com)

Zhongming Zheng, Nan Cheng and Xuemin (Sherman) Shen are with the Department of Electrical and Computer Engineering, University of Waterloo, 200 University Avenue West, Waterloo, Ontario, Canada N2L 3G1 (e-mail: {z25zheng, n5cheng, sshen}@uwaterloo.ca)

Hao Liang is with the Department of Electrical and Computer Engineering, University of Alberta, 116 St. and 85 Ave., Edmonton, Alberta, Canada T6G 2V4 (e-mail: hao2@ualberta.ca)

Ruilong Deng is with the School of Electrical and Electronics Engineering, Nanyang Technological University, Singapore S639798 (e-mail: rldeng@ntu.edu.sg)

This work was supported by China Postdoctoral Science Foundation under Grants 2013M530900, NSFC, Science and technology research program of Liaoning under Grants L2014213, NSERC, Canada, Research Funds for the Central Universities, China Postdoctoral International Academic Exchange Fund, and also supported by China Scholarship Council.

based terrestrial wireless communication networks or maritime wireless communication networks with traditional energy [5]. In green-energy-powered maritime wireless networks, we have to consider not only the energy sustainability of each BS, but also the distinctive challenges of maritime wireless networks, e.g., wireless coverage, various mobility patterns and high-speed mobility, which is normally different from the concern of terrestrial wireless communication networks.

In this paper, we focus on optimizing the schedule of data traffic tasks to maximize the network throughput in maritime wireless networks powered with green energy. We redefine the throughput as the summation of weights of delivered data packets. In the following context, we take uploading surveillance video clips from seagoing vessel to authority on land as an application paradigm. Specifically, WiMAX/store-carry-and-forward interworking maritime wireless network is devised to overcome the restrictions of long-distance traffic at sea and intermittent infostations deployment, where the infostations and Delay Tolerant Network (DTN) throw-boxes [6] are powered by green energy. Under this network scenario, the data traffic scheduling should consider the energy sustainability to guarantee the successful data transmission. Aiming at maximizing network performance with stored and harvested energy, single-vessel transmission scheme and two-vessel cooperative transmission scheme are respectively designed to employ the available transmission opportunities, i.e., infostations and DTNs. In order to maximize the weight of data delivered, the proposed schemes study how to maximize the throughput of the delivered data packets, by scheduling the packets delivered through infostations or DTN, subject to the energy constraint. To the best of our knowledge, our work is the first to investigate such data packet scheduling issue in maritime wireless networks powered by renewable energy sources.

The main contributions of this work are shown as follows:

- We formulate the energy and content aware vessel throughput maximization problem, and prove that the formulated problem is $\mathcal{NP}$ -complete. Then, the energy buffer of infostations and DTN throw box are modeled as a $G/G/1$ queue, and a diffusion approximation method is engaged to investigate transient states, e.g., energy depletion duration and maximum carry delay.
- Based on energy buffer model, two algorithms are proposed, called leaky bucket energy buffer based decentralized online algorithm and energy buffer based combinatorial decentralized-centralized algorithm.
- Finally, we evaluate the performance of our proposed algorithms based on actual ship route trace data from dedicated navigation software. Extensive simulation results show that our proposed algorithms could provide simple yet efficient solutions in a maritime wireless communication network with sustainable energy.

The remainder of this paper is organized as follows. In Section II, we review the related works. System model is provided in Section III and the problem formulation is presented in Section V. Section VI validates our approaches by simulations. Section VII concludes the paper. We summarize used symbols

in TABLE I.

II. RELATED WORK

As a promising technology, there are many studies related to the maritime wideband network in both industry and academia [7]–[11]. The MarCom project [9] in Northern Europe shows how WiMAX technology can be applied in the maritime communication environment. The projects reported in [7], [8] provide high-quality connectivity back to the Internet, voice services, and corporate networks to WiMAX users. In [10], the WiMAX-based mesh technology for ship-to-ship communications with DTN features is explored to provide low-cost wireless communication services at sea and compare the performance between regular routing protocols and DTN routing protocols. In [11], an architectural prototype is constructed by utilizing DTN overlay to achieve file delivery to the Internet, which integrates the function of Automatic Identification System (AIS). However, most works concern about research issues under the scenario of maritime wireless networks with traditional energy.

With respect to green wireless communication, many works have been studied in the literature recent years. The authors of [12] identified that green-energy-powered access points (APs) provide a cost-effective solution for wireless local area networks (WLANs). In [13], the throw-box is assumed to be able to last for a certain period of time, which can calculate the average power from the capacity of the batteries or harvesting energy from solar panels. In [14], network deployment and resource management issues are investigated in the context of green mesh networks. A placement solution seeking paths with the minimum energy depletion probability is proposed to improve the network sustainability while ensures that the energy and QoS demands of mobile users can be fulfilled. In [15], a network planning problem in green wireless communication network is studied. The relay nodes placement and sub-carrier allocation (RNP-SA) issues are jointly formulated. Authors proposed top-down/bottom-up algorithms to minimize the number of APs powered by renewable energy sources with satisfying the quality of service (QoS) requirement of users. In [16], a mathematical framework is developed to study the impact of network dynamics on the perceived video quality. After that, the close-form expressions of the video quality are given in terms of start-up delay, playback and packet loss.

III. SYSTEM MODEL

We consider a green-energy-powered maritime wireless communication network, where a hosting vessel periodically captures surveillance video clips relevant for crucial spots in a vessel. Those videos should be uploaded to a content server, and posted on the dedicated maritime information network sites, so that relevant maritime authority administrator could view and download it. The system model is shown in Fig. 1, where the single vessel and two-vessels scenario are shown in Fig. 1 (A) and Fig. 1 (B), respectively. Several OFDM-based WiMAX infostations are deployed along the coastline, which is commonly used in wireless networks [17]–[19]. Packets can be transmitted over different subchannels without interference to each other. The video packets can be

TABLE I. Notations and definitions.

Symbol	Definition
$r_{jk}(d_{jk})(p_{jk})(s_{jk})$	The release time(deadline)(processing time)(starting time)of video packet j on vessel k
w_{jk}	Weight of packet j on vessel k
$x_{jks_{jk}}$	Binary variable denote whether packet j on vessel k is implemented at the time interval $[s_{jk}, s_{jk} + p_{jk}]$
$A(t)(L(t))$	The cumulative number of arriving and leaving energy
$X(t)$	A continuous process to approximate buffer size $R(t)$
$\alpha(\beta)$	Diffusion and drift diffusion coefficient
$\mu_a (v_a)$	The mean (variance) of energy inter-charging interval
$\mu_l (v_l)$	The mean (variance) of energy inter-discharge interval
x_0	The initial queue length (energy level)
$p(x, t; x_0)$	The conditional probability density function of the energy buffer size $X(t)$ at time t
$p_D(x, t; x_0)$	The probability density function of the buffer depletion duration D
$\mathcal{P}(0; x_0)$	The energy buffer depletion probability from x_0
$M_D(s)$	The moment generation function of D
$E(D) (Var(D))$	The mean(variance) of energy buffer depletion duration D
$\mathcal{P}(0; x_0)$	The energy buffer depletion probability from x_0
$F_D(T; x_0)$	The energy depletion probability before p_{jk} terminates

Fig. 1. System Model.

transmitted either through infostations or relayed by a DTN throw box. Infostations and the DTN throw boxes can harvest energy from natural environment by using solar panels or wind turbines. The packet frame follows the IEEE standard 802.16/WiMAX MAC frame structure.

A. Video Service

Video clips are divided into packets, and each packet has characteristics in terms of release time, playback deadline, and weight. The weight denotes its priority and contribution to the

importance of the video packets. Video packets, which are delivered before their playback deadline, are assumed to be successfully decoded at destination, and the profit of weight is gained. Denote r_{jk} and d_{jk} as the flexible release time and deadline for video packet j on vessel k . Let w_{jk} , p_{jk} and s_{jk} represent the weight of video packet j on vessel k , the processing time, and the starting time, respectively. Also $u \in \{1, \dots, t\}$ the starting time of another video packet is defined to avoid multiple video packets being scheduled simultaneously on one vessel. Obviously, r_{jk} , d_{jk} , p_{jk} and s_{jk} can hold the inequality $r_{jk} \leq s_{jk}$, and thus we have $s_{jk} + p_{jk} \leq d_{jk}$. To simplify the calculation, the above time indices are approximated to integers.

B. Sustainable Energy Model

We suppose that the infostations and DTN nodes are powered by sustainable energy. For each infostation and DTN node, a battery is installed to store harvested energy for traffic transmission and energy backup. Harvested energy would be charged in the energy buffer, meanwhile, discharged by proceeding video packets. With the general energy charging and discharging processes, we try to model the energy buffer as a $G/G/1$ queue. The energy charging, the arrival and service time interval are independent and identically distributed (*i.i.d*) with the mean and variance of the inter-charging interval, noted as μ_a and v_a , and the mean and variance of the energy inter-discharge interval are expressed as μ_l and v_l , respectively. In this paper, we consider the data packets scheduling under the situation that the harvested energy may not be enough to support the transmission traffic.

IV. PROBLEM FORMULATION

We jointly consider network throughput and the energy depletion probability as the metric of the formulated problem. In this work, vessels may transmit packets with different weights, and packets can be transmitted by vessels to infostations or

be sent and stored at the DTN throw box for other vessels to help the transmission. We design energy content aware video packets delivery schemes towards the maximum weights of accomplished data. To this end, we formally formulate the energy and content aware vessel throughput maximization problem (EVTMP), assuring energy sustainability of the network.

A. Energy and Content Aware Time-step-based Formulation

Our goal is to maximize the total weights of whole delivered packets, with minimizing the probability that infostation and DTN throw box depleting their energy when they serve or store traffic demands. The following formulation is based partially on these criteria.

Variable $x_{jks_{jk}}$ decides whether packet j is transmitted through vessel k at the time interval $[s_{jk}, s_{jk} + p_{jk}]$ as follows:

$$x_{jks_{jk}} = \begin{cases} 1, & \text{if packet } j \text{ is performed on vessel } k \text{ at time} \\ & \text{interval } [s_{jk}, s_{jk} + p_{jk}] \\ 0, & \text{otherwise.} \end{cases}$$

Energy and content aware time-step-based formulation is shown as follows:

$$\begin{aligned} \max \quad & \sum_{j=1}^n \sum_{s_{jk}=r_{jk}}^{d_{jk}-p_{jk}} w_{jk} \cdot x_{jks_{jk}} \\ \text{s.t.} \quad & \sum_{j=1}^n \sum_{s_{jk}=u-p_{jk}+1}^u x_{jks_{jk}} \leq 1 \quad k \in \{1, 2\}, \forall u \\ & \sum_{s_{jk}=r_{jk}}^{d_{jk}-p_{jk}} x_{jks_{jk}} \leq 1 \quad k \in \{1, 2\}, \forall j \\ & x_{jks_{jk}} \in \{0, 1\} \\ & \mathcal{P}(0; x_0) < \varepsilon \quad k \in \{1, 2\}, \forall j \end{aligned}$$

This formulation is a 0 – 1 integer nonlinear programming problem, which is known as $\mathcal{NP}$ -hard. It involves four indices: packet, vessel, time step, and energy constraint, i.e., depletion probability. The time steps coincide with the aforementioned packets. The first constraint avoids multiple packets scheduled simultaneously on one vessel; the second constraint means one packet can be scheduled only once; the third constraint shows that $x_{jks_{jk}}$ can be chosen as 0 or 1; the fourth constraint depicts the energy sustainability guarantee. $\mathcal{P}(0; x_0)$ is the energy depletion probability of the infostations and DTN throw box with the initial energy x_0 , which denotes how likely the infostations and DTN will deplete energy and become temporarily unavailable. In Section V, the expression of $\mathcal{P}(0; x_0)$ will be exploited by the queueing theory. Finally, $\varepsilon \ll 1$ is the threshold to ensure that the energy depletion probability should fulfill the requirement.

B. Complexity of EVTMP

We show that the EVTMP is $\mathcal{NP}$ -complete even if it is an offline problem. First, we do not consider energy constraint to simplify the problem. The EVTMP is transformed into a decision problem by exploiting a threshold value. The EVTMP-DECISION is defined as

whether there exists $\{w_{jk}, x_{jks_{jk}}\}$ with

$$\begin{cases} \max \sum_{j=1}^n \sum_{s_{jk}=r_{jk}}^{d_{jk}-p_{jk}} w_{jk} \cdot x_{jks_{jk}} \geq \bar{x} & (6a) \\ \sum_{j=1}^n \sum_{s_{jk}=u-p_{jk}+1}^u x_{jks_{jk}} \leq 1 \quad k \in \{1, 2\}, \forall u & (6b) \\ \sum_{s_{jk}=r_{jk}}^{d_{jk}-p_{jk}} x_{jks_{jk}} \leq 1 \quad k \in \{1, 2\}, \forall j & (6c) \\ x_{jks_{jk}} \in \{0, 1\}. & (6d) \end{cases}$$

The EVTMP-DECISION can be verified in polynomial time, with coefficients satisfy

$\max \sum_{j=1}^n \sum_{s_{jk}=r_{jk}}^{d_{jk}-p_{jk}} w_{jk} \cdot x_{jks_{jk}} \geq \bar{x}$, and for different $x_{jks_{jk}}$ with a total value not more than 1. Hence, EVTMP is $\mathcal{NP}$.

Then, the EVTMP can be easily transformed into the Knapsack Problem (KP). Therefore, the EVTMP-DECISION can be reduced from a known $\mathcal{NP}$ -complete problem in polynomial time, resulting in the EVTMP $\mathcal{NP}$ -hardness. Since the EVTMP without considering energy constraint belongs to $\mathcal{NP}$ and is $\mathcal{NP}$ -hard, we can conclude that the EVTMP considering energy restraint is $\mathcal{NP}$ -complete [20].

V. ENERGY AND CONTENT AWARE VIDEO TRANSMISSION FRAMEWORK

The optimization framework aims at completing delivery of

- (1) video packets before their playback deadlines to maximize the total weights of delivered data packets, subject to the energy
- (2) constraint. The framework jointly considers energy limitation, transient energy level, energy charging capability, and the
- (3) depletion probability of infostations and the DTN throw box to
- (4) fulfill the traffic demands. The video transmission scheduling
- (5) policy regarding to binary variable $x_{jks_{jk}}$ should concern the video packet characteristics (i.e., release time, playback deadlines, weights), available opportunities to connect infostations, and the battery energy limitation of infostations and DTN throw box. Since the formulated problem is $\mathcal{NP}$ -complete, there is no efficient polynomial time solution. Therefore, we try to design efficient heuristic algorithms to address the formulated problem.

In this section, tracking the dynamics of the charging capability and video uploading requirements, we present energy and content aware scheduling scheme to maximize the weights of delivered packets with the energy sustainability constraint. As such, we propose two algorithms to address the single vessel and two vessels cooperative transmission, i.e., an energy buffer-based decentralized online algorithm for single vessel and an energy buffer-based combinatorial decentralized-backward centralized algorithm for two vessels.

A. Leaky Bucket Energy Buffer Based Decentralized Online Algorithm for Single Vessel

In this subsection, a decentralized algorithm is designed to solve the EVTMP problem. Time slots can be allocated by infostations to upload data, but no reservation can be made in advance. Video packets are randomly generated, and a request message would be sent to the infostation within the communication range when a video packet is created. The infostation determines how to allocate time slots to transmit

the packet according to its information, the initial energy level, and the energy charging capability of infostation. After that, the infostation acknowledges or rejects the uploading request in the form of token distribution.

Queueing Model of Energy Buffer for Infostations We can obtain the charging and discharging process model of green energy as shown in [21]. Let $A(t)$ and $L(t)$ denote the cumulative number of charging and discharging energy unit at time t , respectively. The initial energy level of infostation is $Q(0) = x_0$. Harvested Energy from natural resource is stored in the energy buffer; meanwhile, it is discharged for video packets transmission. The residual energy in queue at time t is

$$Q(t) = A(t) - L(t). \quad (7)$$

Then, we investigate the energy depletion duration D of infostations, i.e., the duration from the start until the moment when AP depletes energy, which can be used to derive the probability that the infostations will use up energy when task is uploaded. We model the energy buffer as $G/G/1$ queue, where energy charging and discharging are modeled as random processes. Since the processes of charging and discharging are dynamic, the infostation or the DTN throw box may deplete its energy when $Q(t) = 0$.

Resorting to the diffusion approximation [22], [23], we approximate the discrete buffer size $R(t)$ as a continuous process $X(t)$, and thus the Wiener-Levy process (or Brownian motion) model is used [24] as follows,

$$dX(t) = X(t + dt) - X(t) = \beta dt + Z\sqrt{\alpha dt} \quad (8)$$

where $Z \sim N(0, 1)$ is white Gaussian process with zero mean and unit variance. α and β denote drift and diffusion coefficients, which can be expressed as

$$\begin{cases} \beta = E(\lim_{\Delta t \rightarrow 0} \frac{X(t)}{\Delta t}) = 1/\mu_a - 1/\mu_l \\ \alpha = Var(\lim_{\Delta t \rightarrow 0} \frac{X(t)}{\Delta t}) = v_a/\mu_a^3 + v_l/\mu_l^3. \end{cases} \quad (9)$$

With the initial energy level x_0 , the conditional probability density function (p.d.f) of the energy buffer size $X(t)$ at time t is

$$p(x, t; x_0) = \Pr(x \leq X(t) \leq x + dx | X(0) = x_0). \quad (10)$$

By using the Kolmogorov diffusion equation [24], we can obtain:

$$\frac{\partial p(x, t; x_0)}{\partial t} = \frac{\alpha}{2} \frac{\partial^2 p(x, t; x_0)}{\partial x^2} - \beta \frac{\partial p(x, t; x_0)}{\partial x}. \quad (11)$$

As the queue length cannot be negative, we can derive the queue length as follows,

$$p(x, 0; x_0) = \delta(x - x_0), \quad t = 0 \quad (12)$$

$$p(0, t; x_0) = 0, \quad t > 0, \quad (13)$$

where $\delta(x)$ is the Dirac delta function. By applying the method of images [25], [26], the p.d.f of the energy buffer size could

Fig. 2. Leaky bucket energy buffer diagram.

be expressed as

$$p(x, t; x_0) = \frac{\partial}{\partial x} \left\{ \Phi \left(\frac{x - x_0 - \beta t}{\sqrt{\alpha t}} \right) - \exp \left(\frac{2\beta x}{\alpha} \right) \Phi \left(-\frac{x + x_0 + \beta t}{\sqrt{\alpha t}} \right) \right\}, \quad (14)$$

where $\Phi(x)$ is the standard normal integral, which can be formulated as

$$\Phi(x) = \frac{1}{\sqrt{2\pi}} \int_{-\infty}^x \exp \left(-\frac{1}{2} y^2 \right) dy. \quad (15)$$

Given $D(x_0) = \min\{t \geq 0 | X(0) = x_0, X(t) = 0\}$ as the energy buffer depletion duration and the initial energy level x_0 , we can obtain the maximum energy duration for the service traffic. Then, we can apply the diffusion equation to capture the probability density function of D . The detail derivation of probability density function of D , i.e., $p_D(x, t; x_0)$ and $\mathcal{P}(0; x_0)$ is given in Appendix 1.

Leaky Bucket Energy Buffer-Based Decentralized Online algorithm for Single Vessel Algorithm 1 shows a Leaky bucket energy buffer-based decentralized online algorithm for a single vessel. Tokens are generated for each interval period within a token buffer. Each video packet is transmitted with a token until the buffer is empty. Fig. 2 shows a diagram of leaky bucket energy buffer. We assume the process of video packet generating and requesting can be modeled as a Poisson distribution with λt , where λ is the average number of video packet arrivals in infostations per unit time. If a video packet arrives at time t , the next video packet should arrive at time $t + \tau$, where τ is a random variable having an exponential distribution with parameter λ [27].

In Algorithm 1, with the concept of video packet instance [28], we have multiple choices of packet scheduling between release time and deadline. In this decentralized algorithm, the time slot reservation is allowed. However, the reservation cannot be guaranteed until the packet starts to be transmitted. Even though the packet is in process, it is also effected by rescheduling or abolishment with the arrival of new packets. At first, we calculate the longest survival time T for the infostation, which is the depletion duration from its initial energy level x_0 to the moment that the infostation used

up its energy.

$$F_D(T; x_0) = \int_0^T p_D(x, t; x_0) dt < \varepsilon \quad (16)$$

$$\int_0^T \left\{ -\frac{(x_0 + \beta t)^2}{2\alpha t} + \frac{1}{2} \left[\frac{(x_0 + \beta t)^2}{2\alpha t} \right]^2 \right\} \cdot \frac{x_0}{\sqrt{2\pi\alpha t^3}} dt \quad (17)$$

$$= \int_0^T \frac{x_0(x_0 + \beta t)^4}{8\alpha^4 t^{7/2} \sqrt{2\pi\alpha}} - \frac{x_0(x_0 + \beta t)^2}{2\alpha t^{5/2} \sqrt{2\pi\alpha}} dt \quad (18)$$

$$= \frac{\beta^4 t^{3/2} x_0}{30\alpha^{5/2}} + \frac{2t^{1/2} \beta^3 x_0^2}{5\alpha^{5/2}} - \frac{2t^{1/2} \beta^2 x_0}{5\alpha^{3/2}} \Big|_0^T \leq \varepsilon. \quad (19)$$

Since $p_D(x, t; x_0)$ is non-holonomic, the integral expression in Eq. 16 cannot be obtained directly. Based on the first order of Taylor series expansion, we can approximate the expression of T in Eq. 19, where T indicates the energy deplete duration. Based on the solution of univariate cubic equation [29], we can further obtain the solution of T . If we have a univariate cubic equation

$$ax^3 + bx^2 + cx + d = 0, \quad a \neq 0, \quad (20)$$

the solution of real number is:

$$x = -\frac{b}{3a} + \sqrt[3]{A + \sqrt{A^2 + B^3}} + \sqrt[3]{A - \sqrt{A^2 + B^3}}, \quad (21)$$

here $A = \frac{bc}{6a^2} - \frac{b^3}{27a^3} - \frac{d}{2a}$, and $B = \frac{c}{3a} - \frac{b^2}{9a^2}$.

When the vessel sails in the coverage of the infostation, the vessel would send a request for data transmission. Once the infostation receives the request, it would list all the packet instances that have not been transmitted. By considering occupied time intervals and depletion probability for each packet instance, this algorithm has the superiority for the following cases:

case (a): When an infostation receives a new request J_j , we schedule the packet in descending order of $\frac{w_i}{p_i}$ until $occupied \geq t'$.

case (b): In case that packet transmission is in progress, the packet J_j will be scheduled along with the packets already scheduled, if the summation of the current moment t and the processing time p_j is no more than T .

case (c): If the summation of current time t and the processing time p_j is more than T , the packets that have already been scheduled will be preempted by packet J_j . The metric of preemption is $w_j > \sum w_r \cdot (1 + \frac{l_j}{p_r})$, i.e., the packet with greater weight preempts existing scheduled packets. Otherwise, it will be appended to the list of I .

The number of tokens available in the token buffer is i , and the token distribution rate is p_i . In other words, the processing time of each packet determines token distribution rate. When a packet is processed, a token will be allocated for the next packet in the data buffer according to Algorithm 1. We truncate the intervals of token distribution, so that the packets that have received tokens will be aligned in the data buffer. This algorithm guarantees no congestion in the single infostation.

Algorithm 1: Energy buffer based decentralized online algorithm for single vessel

```

1  $I \leftarrow \emptyset$ ;
2  $occupied \leftarrow 0$ ;
3 for a new packet  $J_i$  arrives at time  $t$  do
4   if  $occupied + p_j < T$  then
5     if  $t > occupied$  then
6       schedule  $J_i$  at  $t$ ;
7        $occupied \leftarrow t + p_i$ ;
8     else
9       there exist some scheduled packets  $J_r$ 
10      overlapped with  $J_i$  during  $l_r$ 
11      if  $w_i > \sum_r \left(1 + \frac{l_r}{p_r}\right) w_r$  then
12        replace packets  $J_r$  with  $J_i$  at  $t$ ;
13         $I \leftarrow I \cup \{J_r\}$ ;
14         $occupied \leftarrow t + p_i$ ;
15      repeat
16        reschedule  $J_j \in I$  with highest  $\frac{w_j}{p_j}$  at
17         $occupied$ ;
18         $I \leftarrow I \setminus \{J_j\}$ ;
19         $occupied \leftarrow occupied + p_j$ ;
20      until no packets can be rescheduled;
21    else
22      schedule  $J_i$  at  $occupied$ ;
23       $occupied \leftarrow occupied + p_i$ ;
24    end if
25  end for
```

B. Energy Buffer Based Combinatorial Decentralized-Backward Centralized Algorithm for Two Vessels

Cooperative relaying transmission can further improve the total weight of delivered packets by creating more opportunities for wireless access. As route path of each ship is relatively stable, the global information in terms of the infostations deployment, the period of vessels passing the infostations, as well as the schedule of vessels, is known *a priori*. Video packets are randomly generated, and the vessels send request messages to the server. After that, the time slots are allocated based on the information of the packets. The packets, which should be store-carry-and-forward by another vessel via the infostations en route, are selected by the infostation server. To inform which packets should be stored in DTN throw box and wait for another vessel to fetch, the server sends the acknowledgement or rejection messages to the vessel. Therefore, in this case, two vessels are scheduled by a centralized server, which also schedules the green-energy-powered infostations and the DTN nodes.

1) Emergency Information Delivery Scenario: For the two-vessel scenario, one of the most important issues is how to allocate the uploading traffic between the two vessels to maximize the total weight of delivered video packets, while the energy constraint of infostations and the DTN throw box can be met. For emergent packets, vessel 1 may stop current data

transmission and help to transmit the video packets with urgent information immediately. After that, vessel 2 may help to relay the packet with urgent information and send these packets to the destination before the deadline, while the energy constraint of the DTN throw box should be fulfilled. We separate the scenario into following cases according to the existing energy level of DTN node and infostations:

- 1) If there is sufficient energy in the DTN throw box, vessel 1 will help to transmit all the available video packets.
- 2) If the energy is not sufficient to serve all packets, the server will forward the packets to the DTN node;
- 3) When vessel 2 comes across the DTN node, it decides whether to help relay the packets or not according to its stock;
- 4) When any infostation finishes uploading the packets that it receives from vessel 1, then vessel 1 will be informed via inter-infostations communication.

In the two-vessel scenario, vessel 1 is responsible for emergency information delivery (like warship), while vessel 2 acts as the relay node. Before vessel 2 comes across the DTN throw-box, it does not carry any data. The store-carry-and-forward mechanism of DTN node should consider the initial energy level, discharging and charging capacity. T is used to determine whether a packet can be stored in DTN node or not, which is the processing time of all potential packets.

$$F_D(T; x_0) = \int_0^T p_D(t; x_0) dt < \varepsilon. \quad (22)$$

2) **Maximum Carry Delay C:** The centralized algorithm determines which vessel should carry the packets under the energy constraint of the DTN node. We assume that the DTN node depletes its energy after receiving the packets from vessel 1. The discharging process of the energy buffer is not considered here, i.e., $\mu_l = v_l = 0$, while the initial energy and charging parameters of the energy buffer are $x_o = 0$, μ_a and v_a . In this scenario, $\beta_C = 1/\mu_a$ and $\alpha_C = v_a/\mu_a^3$. The minimal energy requirement of the DTN node is denoted as b . The maximal delay before passing the packet over to vessel is expressed as

$$C = \min\{t > 0 | X(0) = 0, X(t) = b\}. \quad (23)$$

The detail derivation of probability density function of C , i.e., $p_C(x, t; x_0)$ is given in Appendix 2. Let T_2 denote the duration from the DTN node receives vessel 1's packets to the time that vessel 2 comes across the DTN node. Then, the DTN node calculates the probability that its energy reaches b before T_2 .

$$F_C(T_2; 0) = \Pr(C \leq T_2) = \int_0^{T_2} p_C(x, t; 0) dt \quad (24)$$

$$\int_0^{T_2} \left\{ -\frac{(b - \beta t)^2}{2\alpha t} + \frac{1}{2} \left[\frac{(b - \beta t)^2}{2\alpha t} \right]^2 \right\} \cdot \frac{b}{\sqrt{2\pi\alpha}t^3} dt \quad (25)$$

$$= \int_0^{T_2} \frac{b(b - \beta t)^4}{8\alpha^4 t^{7/2} \sqrt{2\pi\alpha}} - \frac{b(b - \beta t)^2}{2\alpha t^{5/2} \sqrt{2\pi\alpha}} dt \quad (26)$$

$$= \frac{\beta^4 t^{3/2} b}{30\alpha^{5/2}} - \frac{2t^{1/2} \beta^3 b^2}{5\alpha^{5/2}} - \frac{2t^{1/2} \beta^2 b}{5\alpha^{3/2}} \Big|_0^{T_2} \leq \varepsilon. \quad (27)$$

We can obtain T_2 by applying the truncating expansion equation of the Taylor series in Eq. 24 and the solution of univariate cubic equation in Eq. 27.

3) **Energy Buffer Based Combinatorial Decentralized-Backward Centralized Algorithm:** We propose a combinatorial decentralized-backward centralized algorithm, taking into consideration of energy constraint. Before vessel 1 and vessel 2 arrive at the coverage of the DTN throw box, the algorithm is distributed. Furthermore, when both vessels locate within the transmission range of the DTN throw box, the DTN node will schedule the transmissions of the two vessels to exchange information. The distributed algorithm is similar to Algorithm 1. We omit the redundant description and focus on the traffic affiliated with the DTN throw box.

$J = \{j_i\}$, $i \in [1, n]$ is the set of video packets that cannot be scheduled by vessel 1; J_1 is the set of video packets transmitted to the DTN node originated from vessel 1, which is selected by Algorithm 2. As the ships' routes and ships' speeds are all relatively stable, they could be known *a priori*. Let x_0 denote the DTN initial energy when vessel 1 transmits data to it; x'_0 is the residual energy in the DTN node. x'_0 can guarantee that the DTN node have sufficient energy to make a transmission to vessel 2 if the length of stay in the DTN node for vessel 2 is very short. x''_0 indicates the energy level when vessel 2 contacts the DTN node; T_1 represents the total length of video packets, which is going to be transmitted to the DTN node; T_2 denotes the duration from the time that vessel 1 transmits the packets to DTN node until the time that vessel 2 receives the packets from the DTN node; T_3 is the time period for vessel 2 to receive the video packets, which are transmitted from the DTN node. In order to achieve the optimal residual threshold for the maximal energy utility based on the energy model, the following weight-driven DTN energy buffer management analytical framework is used.

Step 1: Given the DTN initial energy x_0 and the residual energy x'_0 , we can obtain T_1 as the following equation:

$$F_D(T_1; x_0) = \int_0^{T_1} p_D(x, t; x_0 - x'_0) dt < \varepsilon. \quad (28)$$

Step 2: If a packet's uploading time is larger than T_1 , i.e., $T_J > T_1$, we use $\frac{w_i}{p_i}$ to sort the priority of packets which should be stored in the DTN node. Otherwise, if a packet's uploading time is smaller than T_1 , i.e., $T_J < T_1$, it indicates that the energy is sufficient, which means that all the packets can be stored in the DTN node.

Step 3: When the DTN node is transmitting the data to vessel 2 within T_2 , the energy charging process works as follows

$$F_C(T_2; 0) = \Pr(C \leq T_2) = \int_0^{T_2} p_C(x, t; 0) dt. \quad (29)$$

By using transformation $b \leftarrow x''_0 - x'_0$, we can know whether the energy is sufficient to finish the transmission. If vessel

2 carries the packets, then we can calculate whether the packets can be successfully transmitted according to the energy constraint.

$$F_D(T_3; x_0) = \int_0^{T_3} p_D(x, t; x_0'') dt < \varepsilon. \quad (30)$$

If $T_3 > T_1$, the packets stored in the DTN node should be passed over to vessel 2, which is the optimal solution to avoid energy waste. We can get $x_0'' \geq x_0 - x_0'$.

Based on $b \leftarrow x_0'' - x_0$ and $x_0' = x_0$, we can obtain the value of x_0' as follows

$$F_C(T_2; 0) = \Pr(C \leq T_2) = \int_0^{T_2} p_C(x, t; 0) dt < \varepsilon. \quad (31)$$

Algorithm 2: *Energy buffer based combinatorial decentralized-backward centralized algorithm for two vessels*

```

1 Two vessels decentralized algorithm is the same with
  Algorithm 1;
2 Backward Centralized algorithm
  Input:  $x_0 = x_0' = \text{constant}$ ;  $T_2$ ;  $J$  is the set of total
    unscheduled packets in vessel 1, and  $T_J$  is total
    processing time of all the packets relatively;  $J_1$  is
    packets set to store in DTN node
  Output:  $x_0'$ ,  $J_1$ 
3  $J_1 \leftarrow \emptyset$ ;
4  $occupied \leftarrow t$ ;
5 Calculate  $x_0'$  according to Eq.27, Eq. 28 and Eq. 29;
  Calculate  $T_1$  according to Eq. 35, Eq. 19 and Eq. 28;
6 for moment  $t$  vessel 1 store data into DTN node do
7   while  $J \neq \emptyset$  do
8     Schedule  $J_i \in J$  which has the highest  $\frac{w_i}{p_i}$ ;
9     if  $occupied + p_i \leq T_1$  &  $occupied + p_i \leq e_i$  then
10       $occupied \leftarrow occupied + p_i$ ;
11       $J \leftarrow J \setminus \{J_i\} \setminus \{J_{e_i} < occupied + p_i\}$ ;
12       $J_1 \leftarrow J_1 \cup \{J_i\}$ ;
13       $i \leftarrow i + 1$ ;
14    else
15       $J \leftarrow J \setminus \{J_i\} \setminus \{J_{e_i} < occupied + p_i\}$ 
16    end if
17  end while
18 end for

```

In Algorithm 2, vessel 2 helps vessel 1 to transmit unscheduled packets, which are stored in the DTN node by vessel 1 in advance. At moment t , vessel 1 decides which packets should be stored into DTN node according to Algorithm 2. For each packet sent to the DTN node, a token is allocated. The number of tokens in the token buffer is i , and the token allocation rate can be derived by the processing time of video packet p_i .

4) **Normal Information Delivery Scenario:** Then, we consider the video packet delivery with normal information, where the videos from vessel 1 have normal weights except the emergent information, and vessel 2 also has video packets for transmission. In this scenario, the maximal information from

Fig. 3. Navigation routes for vessels in Busan Harbor of Korea.

vessel 1 stored in the DTN node is J_1 , since the video packets J_2 in vessel 2 do not impact on the energy level of the DTN node. However, the packets J_2 in vessel 2 as well as the new packets J_3 may conflict with the original packet from vessel 1 due to the overlapping processing time. After vessel 2 receives the video packets J_1 from the DTN throw box, the scheduling strategy will be the same with Algorithm 1. The total video packets can be expressed as $J \leftarrow J_1 \cup J_2 \cup J_3$. If the weights of packets J_2 are obviously higher than J_1 , another vessel 3 will replace vessel 2 to carry those packets from the DTN node, which is beyond the scope of this work.

C. Time complexity Analysis

In this section, we analyze the performance of the proposed two algorithms in terms of time complexity.

For Algorithm 1, the time complexity is determined by the worst case of packets overlapping and preemption. Thus, we consider the worst case that all the packets N are overlapping with packet 1. In this situation, the time complexity is calculated as follows: $1 + 2 + \dots + (N + 1) = \frac{N(N+1)}{2}$. Therefore, the Algorithm 1 runs in $\mathcal{O}(N^2)$ time, where N means the maximum number of overlapping packets.

For Algorithm 2, we allocate the scheduling of $J_i \in J$ which has the highest $\frac{w_i}{p_i}$. It takes $\mathcal{O}(\log N)$ time to run the binary search method, where N is the number of packets stored in DTN node.

VI. PERFORMANCE EVALUATION

We use a video packets delivery scheduling system to evaluate the performance of our scheduling algorithms based on the real vessel traces in the Busan Harbor surrounded by waterbodies around Korea as shown in Fig. 3. For each of vessel 1 and vessel 2, ten infostations are randomly distributed along their routes. Based on the BLM-Ship navigation software [30], we use the synthetic vessel trace method to estimate the trace, i.e., vessels sail in a straight line between the two adjacent position points, and the method of curve fitting to estimate the real-time location information of vessels. The locations of vessel 1 and vessel 2 are denoted as (φ_1, θ_1) and (φ_2, θ_2) , respectively, where φ and θ are the latitude and longitude of vessels. The great circle distance S in navigation

science can be obtained as follows:

$$\cos S = \sin \varphi_1 \cdot \sin \varphi_2 + \cos \varphi_1 \cdot \cos \varphi_2 \cdot \cos D\lambda \quad (32)$$

$$D\lambda = \theta_2 - \theta_1. \quad (33)$$

We can use $S = \arccos(\cos S)$ to obtain the great circle distance [31] and project the possible complete route.

TABLE II. Simulation parameters.

Name	Value	Name	Value
Packet size	100 bytes	System bandwidth	10 MHz
Data rate	50 Mbps	Frame duration T_F	5 ms
Network region	100×100 km ²		

We set the mean and variance of the energy charging interval as $\mu_a = 2.75$ and $v_a = 1.09$. The mean and variance of the energy inter-discharging interval are $\mu_l = 4.35$ and $v_l = 11.1$. The simulation configuration is shown in TABLE II. We compare our proposed algorithms with three classic scheduling algorithms, i.e., weight (packet with the heaviest weight is scheduled first), deadline (packet with the earliest deadline is scheduled first), and first-input-first-output (FIFO) (packet with the earliest release time is scheduled first), in term of normalized throughput, which is defined as the ratio of the throughput of delivered packets over the throughput of total packets. We modify the above three classic algorithms by considering the survival time T , and initial energy and energy consumption of infostations and DTN throw box.

Fig. 4 investigates the impact of packet deadline on normalized throughput for single vessel scenario. We can observe that our proposed algorithm can significantly outperform the other algorithms. This is because our algorithms first serve the packets with the maximum ratio of weight to processing time, i.e., packets which is more important to the video quality and needs less processing time than other packets. For the other three algorithms, weight algorithm outperforms deadline and FIFO algorithms. This is because the normalized throughput is closely related to the weight of packets, and the weight algorithm schedules the packets with the heaviest weight first. For deadline and FIFO algorithms, they only consider deadline and release time instead of weight, which leads to lower performance than the weight algorithm.

Fig. 5 and Fig. 6 show the impact of energy parameters on the normalized throughput for both single and two-vessel scenarios. We can observe that our algorithms outperform the other three algorithms. In Fig. 5(a) and Fig. 6(a), the normalized throughput decreases along with the increase in μ_a for both single and two-vessel scenarios. This is because energy may be insufficient for data transmission due to larger inter-charging interval, and the throughput of delivered packets is decreased accordingly. In Fig. 5(b) and Fig. 6(b), the normalized throughput increases with the growth of the mean of inter-discharging interval μ_l for both single and two-vessel scenarios. It can be found that the energy consumption decreases with larger inter-discharging interval, which means that infostations are less likely to deplete its energy, and thus can achieve higher normalized throughput.

In summary, our proposed algorithms for single vessel

(a) Single vessel scenario

(b) Two-vessel scenario

Fig. 4. Normalized throughput versus packet deadline.

and two vessels significantly outperform the three existing algorithms, because our algorithms consider both weight and processing time of the packets. The weight algorithm has better performance than FIFO and deadline algorithms, as weight has larger impact on the normalized throughput than deadline and release time.

VII. CONCLUSION

In this paper, we have investigated the network throughput and energy sustainability in the green-energy-powered maritime wireless network. We have modeled the green energy buffer as a $G/G/1$ queue. Based on the buffer model, we have formulated the energy and content aware vessel throughput maximization problem and proved the formulated problem is $\mathcal{NP}$ -complete. After that, two algorithms for both network scenarios of single vessel and two-vessel have been proposed to maximize the network throughput subject to the energy sustainability constraint. Our extensive simulation results show that our simple yet efficient algorithms can achieve high network throughput and energy sustainability. In our future work, we will study multi-vessel scheduling issues with various mobility patterns in green-energy-powered maritime wireless communications networks. Under the multi-vessel scenario, we need to jointly consider the scheduling scheme design and energy sustainability of each BS. Moreover, the routing

(a) Various mean of energy inter-charging interval of infostation

(b) Various mean of energy inter-discharging interval of infostation

Fig. 5. Normalized throughput of different algorithms for single vessel scenario.

paths design should be included to optimize both the energy sustainability and network throughput.

APPENDIX 1: DERIVATION OF PROBABILITY DENSITY FUNCTION OF D

By using the Kolmogorov diffusion equation [24], the probability density function of D could be obtained that

$$\frac{\partial p_D(x, t; x_0)}{\partial t} = \frac{\alpha}{2} \frac{\partial^2 p_D(x, t; x_0)}{\partial t^2} - \beta \frac{\partial p_D(x, t; x_0)}{\partial t}. \quad (34)$$

The conditional probability density function of the energy buffer depletion duration is

$$p_D(x, t; x_0) = \frac{x_0}{\sqrt{2\pi\alpha_D t^3}} \exp \left\{ -\frac{(x_0 + \beta_D t)^2}{2\alpha_D t} \right\}. \quad (35)$$

With Laplace transform, the moment generation function of D can be expressed as

$$M_D(s) = \exp \left\{ -\frac{x_0 (\beta_D + \sqrt{\beta_D^2 + 2\alpha_D s})}{\alpha_D} \right\}. \quad (36)$$

(a) Various mean of energy inter-charging interval of infostation

(b) Various mean of energy inter-discharging interval of infostation

Fig. 6. Normalized throughput of different algorithms for two-vessel scenario.

Then, we can obtain the mean and variance of the energy buffer depletion duration D ,

$$E(D) = -\frac{d}{ds} M_D(s) |_{s=0} = -\frac{x_0}{\beta_D} e^{-\frac{2\beta_D x_0}{\alpha_D}} \quad (37)$$

$$\begin{aligned} Var(D) &= -\frac{d^2}{ds^2} M_D(s) |_{s=0} - E^2(D) \\ &= e^{-\frac{2\beta_D x_0}{\alpha_D}} \left[2x_0 \beta_D^{-3} - x_0^2 \beta_D^{-2} \left(1 + e^{-\frac{2\beta_D x_0}{\alpha_D}} \right) \right]. \end{aligned} \quad (38)$$

$\mathcal{P}(0; x_0)$ indicates the energy buffer depletion probability from x_0 , which can be expressed as

$$\mathcal{P}(0; x_0) = \lim_{D \rightarrow 0} \int_0^D p_D(x, t; x_0) dt = \lim_{s \rightarrow 0} M_D(s) \quad (39)$$

$$\mathcal{P}(0; x_0) = \begin{cases} 1, & \text{for } \beta_D < 0 \\ \exp \left\{ -\frac{2x_0 \beta_D}{\alpha_D} \right\}, & \text{for } \beta_D > 0 \end{cases} \quad (40)$$

We can observe from Eq. 40 that the energy buffer depletes with probability 1 when the energy charge rate is lower than or equal to the energy discharge rate $1/\mu_a \leq 1/\mu_l$. For the case that $1/\mu_a > 1/\mu_l$, the energy buffer depletion probability depends on the initial energy level x_0 and the mean and variance of energy charging and discharging rates, etc.

Denote the processing time of a packet j on vessel k as p_{jk} , which means that the uploading of the video packet lasts for p_{jk} time slots. $D(x_0)$ indicates the energy buffer depletion duration with the initial energy x_0 . The infostation calculates the energy depletion probability before p_{jk} terminates,

$$F_D(T; x_0) = Pr(D \leq T) = \int_0^T p_D(x, t; x_0) dt. \quad (41)$$

APPENDIX 2: DERIVATION OF PROBABILITY DENSITY FUNCTION OF C

By applying diffusion approximation, we can obtain the probability density function of C as

$$\frac{\partial p_C(x, t; 0)}{\partial t} = \frac{\alpha}{2} \frac{\partial^2 p_C(x, t; 0)}{\partial t^2} - \beta \frac{\partial p_C(x, t; 0)}{\partial t} \quad (42)$$

Then, we derive that the length of the queue cannot exceed b .

$$p_C(x, 0; 0) = \delta(x), \quad t = 0 \quad (43)$$

$$p_C(b, t; 0) = 0, \quad t > 0. \quad (44)$$

We obtain the p.d.f by applying the method of images [25], [26] as follows

$$p_C(x, t; 0) = \frac{b}{\sqrt{2\pi\alpha_C t^3}} \exp \left\{ -\frac{(b - \beta_C t)^2}{2\alpha_C t} \right\}. \quad (45)$$

With the Laplace transform, the relative moment generating function can be expressed as

$$M_C(s) = \exp \left\{ \frac{b}{\alpha_C} \left[\beta_C - \sqrt{\beta_C^2 + 2\alpha_C s} \right] \right\}. \quad (46)$$

The mean and variance of the maximum carry delay C are obtained as

$$E(C) = -\frac{d}{ds} M_C(s) |_{s=0} = \frac{b}{\beta_C} = b\mu_a \quad (47)$$

$$Var(C) = -\frac{d^2}{ds^2} M_C(s) |_{s=0} - E^2(C) = b\nu_a. \quad (48)$$

REFERENCES

- [1] I. Maglogiannis, S. Hadjiefthymiades, N. Panagiotarakis, and P. Hartigan, "Next generation maritime communication systems," *International Journal of Mobile Communications*, vol. 3, no. 3, pp. 231–248, Mar. 2005.
- [2] Ren21, "Global status report," http://www.ren21.net/Portals/97/documents/GSR/GSR2011_Master18.pdf, 2011.
- [3] G. Wifi, "Solar-powered internet in Lascachobas, Haiti," <http://www.green-wifi.org/>, 2011.
- [4] P. Kim and U. Geva, "Wind-powered wireless mesh network," <http://ldt.stanford.edu/educ39109/POMI/MNet>, 2011.
- [5] J. Zhang, F.-Y. Wang, K. Wang, W.-H. Lin, X. Xu, and C. Chen, "Data-driven intelligent transportation systems: A survey," *Intelligent Transportation Systems, IEEE Transactions on*, vol. 12, no. 4, pp. 1624–1639, Dec. 2011.
- [6] W. Zhao, Y. Chen, M. Ammar, M. Corner, B. Levine, and E. Zegura, "Capacity enhancement using throwboxes in DTNs," in *Proc. IEEE MASS*, 2006, pp. 31–40.
- [7] "StratosMAX II," <http://www.stratosglobal.com/>.
- [8] "SEAPORT802," <http://www.digitalmarine.co>.
- [9] F. Bekkadal and K. Yang, "Novel maritime communications technologies," in *Proc. IEEE MMS*, 2010, pp. 338–341.
- [10] H.-M. Lin, Y. Ge, A.-C. Pang, and J. S. Pathmasuntharam, "Performance study on delay tolerant networks in maritime communication environments," in *Proc. IEEE OCEANS*, 2010, pp. 1–6.
- [11] P. Kolios and L. Lambrinos, "Optimising file delivery in a maritime environment through inter-vessel connectivity predictions," in *Proc. IEEE WiMob*, 2012, pp. 777–783.
- [12] A. Sayegh, T. Todd, and M. Smadi, "Resource allocation and cost in hybrid solar/wind powered WLAN mesh nodes /in Book: Wireless mesh networks," pp. 167–189, 2008.
- [13] N. Banerjee, M. D. Corner, and B. N. Levine, "An energy-efficient architecture for DTN throwboxes," in *Proc. IEEE INFOCOM*, 2007, pp. 776–784.
- [14] L. X. Cai, H. Poor, Y. Liu, T. H. Luan, X. Shen, and J. W. Mark, "Dimensioning network deployment and resource management in green mesh networks," *IEEE Wireless Communications*, vol. 18, no. 5, pp. 58–65, Oct. 2011.
- [15] Z. Zheng, L. Cai, R. Zhang, and X. Shen, "RNP-SA: Joint relay placement and sub-carrier allocation in wireless communication networks with sustainable energy," *IEEE Transactions on Wireless Communications*, vol. 11, no. 10, pp. 3818–3828, Oct. 2012.
- [16] T. H. Luan, L. X. Cai, and X. Shen, "Impact of network dynamics on user's video quality: Analytical framework and QoS provision," *IEEE Transactions on Multimedia*, vol. 12, no. 1, pp. 64–78, Jan. 2010.
- [17] M. Mehrjoo, M. K. Awad, and X. S. Shen, "Resource allocation in OFDM-based WiMAX/in Book: WiMAX network planning and optimization," pp. 113–131, Apr. 2009.
- [18] J. R. Gutierrez Del Arroyo and J. A. Jackson, "WiMAX OFDM for passive SAR ground imaging," *IEEE Transactions on Aerospace and Electronic Systems*, vol. 49, no. 2, pp. 945–959, Apr. 2013.
- [19] N. Vaipoulos, H. G. Sandalidis, and D. Varoutas, "Using a HAP network to transfer WiMAX OFDM signals: Outage probability analysis," *Journal of Optical Communications and Networking*, vol. 5, no. 7, pp. 711–721, July 2013.
- [20] M. Garey and D. Johnson, *Computers and Intractability: A Guide to the Theory of NP-Completeness*. Freeman, 1979.
- [21] L. X. Cai, Y. Liu, T. H. Luan, X. Shen, J. W. Mark, and H. V. Poor, "Adaptive resource management in sustainable energy powered wireless mesh networks," in *Proc. IEEE GLOBECOM*, 2011, pp. 1–5.
- [22] L. Kleinrock, *Queueing Systems: Volume 2: Computer Applications*, 1976.
- [23] A. O. Allen, *Probability, statistics, and queueing theory: with computer science applications*, 1990.
- [24] H. Kobayashi, "Application of the diffusion approximation to queueing networks I: Equilibrium queue distributions," *Journal of the ACM*, vol. 21, no. 2, pp. 316–328, Apr. 1974.
- [25] D. D. R. Cox and H. D. Miller, *The theory of stochastic processes*, 1977.
- [26] W. Feller, *An introduction to probability theory and its applications*, 2008.
- [27] F. A. Haight and F. A. Haight, "Handbook of the poisson distribution," 1967.
- [28] P. Berman and B. DasGupta, "Multi-phase algorithms for throughput maximization for real-time scheduling," *Journal of Combinatorial Optimization*, vol. 4, no. 3, pp. 307–323, Sept. 2000.
- [29] L. Hong, "A direct rigorous conversion from cartesian to geodetic coordinates based on the solution to univariate cubic equation," *Geomatics Spatial Information Technology*, vol. 6, pp. 48–50, June 2007.
- [30] B. I. G. Ltd, "User manual," <http://www.boloomo.com/shippingMain>.
- [31] Y. Li, A. C. Landsburg, R. A. Barr, and S. Calisal, "Improving ship maneuverability standards as a means for increasing ship controllability and safety," in *Proc. MTS/IEEE OCEANS*, 2005, pp. 1972–1981.

Tingting Yang (M'13) received the B.Sc. and Ph.D. degrees from Dalian Maritime University, China, in 2004 and 2010, respectively. She is currently an associate professor at Navigation College of Dalian Maritime University, China. Since September 2012, she has been a visiting scholar at the Broadband Communications Research (BBRC) Lab at the Department of Electrical and Computer Engineering, University of Waterloo, Canada. Her research interests are in the areas of maritime wideband communication networks, DTN networks, green wireless

communication. She serves as the associate Editor-in-Chief of the IET Communications, as well as the advisory editor for SpringerPlus. She also serves as a TPC Member for IEEE ICC'14 & ICC'15 Conference, IEEE SmartGridComm'14 Symposium and IEEE ScalCom'14 Conference.

Nan Cheng (S'13) is currently a Ph.D. candidate in the department of Electrical and Computer Engineering, the University of Waterloo, Waterloo, ON, Canada. He received his B.S. degree and M.S. degree from Tongji University, China, in 2009 and 2012, respectively. Since 2012, he has been a research assistant in the Broadband Communication Research group in ECE Department, the University of Waterloo. His research interests include vehicular communication networks, cognitive radio networks, and resource allocation in smart grid.

Zhongming Zheng (S'12) received the B.Eng. (2007) and M.Sc. (2010) degrees from City University of Hong Kong. Currently, he is pursuing his Ph.D degree in Electrical and Computer Engineering at University of Waterloo, under Broadband Communication Research Group. His research focuses on green wireless communication, smart grid and wireless sensor networks.

Hao Liang (S'09-M'14) received his Ph.D. degree in Electrical and Computer Engineering from the University of Waterloo, Canada, in 2013. From 2013 to 2014, he was a postdoctoral research fellow in the Broadband Communications Research (BBRC) Lab and Electricity Market Simulation and Optimization Lab (EMSOL) at the University of Waterloo. Since July 2014, he has been an Assistant Professor in the Department of Electrical and Computer Engineering at the University of Alberta, Canada. His research interests are in the areas of smart grid, wireless communications, and wireless networking. He is a recipient of the Best Student Paper Award from IEEE 72nd Vehicular Technology Conference (VTC Fall-2010), Ottawa, ON, Canada.

Dr. Liang was the System Administrator of IEEE Transactions on Vehicular Technology (2009-2013). He served as a Technical Program Committee (TPC) Member for major international conferences in both information/communication system discipline and power/energy system discipline, including IEEE International Conference on Communications (ICC), IEEE Global Communications Conference (Globecom), IEEE VTC, IEEE Innovative Smart Grid Technologies Conference (ISGT), and IEEE International Conference on Smart Grid Communications (SmartGridComm).

Ruilong Deng (S'11) received his BEng and PhD degrees both in Control Science and Engineering from Zhejiang University, China, in 2009 and 2014, respectively.

He visited Simula Research Laboratory in 2011 and the University of Waterloo from 2012 to 2013. Currently, he is a Postdoctoral Research Fellow in the School of Electrical and Electronics Engineering, Nanyang Technological University, Singapore. His research interests include wireless sensor network, cognitive radio, and smart grid.

Dr. Deng served as a TPC member for IEEE SmartGridComm'13 Demand Response Symposium, IEEE ICNC'15 Mobile Computing & Vehicle Communications Symposium, IEEE ICC'15 Communications QoS, Reliability & Modeling Symposium, and received Student Travel Grant for IEEE GLOBE-COM'13.

Xuemin (Sherman) Shen (IEEE M'97-SM'02-F'09) received the B.Sc.(1982) degree from Dalian Maritime University (China) and the M.Sc. (1987) and Ph.D. degrees (1990) from Rutgers University, New Jersey (USA), all in electrical engineering.

He is a Professor and University Research Chair, Department of Electrical and Computer Engineering, University of Waterloo, Canada. He was the Associate Chair for Graduate Studies from 2004 to 2008. Dr. Shen's research focuses on resource management in interconnected wireless/wired networks, wireless

network security, wireless body area networks, vehicular ad hoc and sensor networks. He is a co-author/editor of six books, and has published many papers and book chapters in wireless communications and networks, control and filtering. Dr. Shen served as the Technical Program Committee Chair for IEEE VTC'10 Fall, the Symposia Chair for IEEE ICC'10, the Tutorial Chair for IEEE VTC'11 Spring and IEEE ICC'08, the Technical Program Committee Chair for IEEE Globecom'07, the General Co-Chair for Chinacom'07 and QShine'06, the Chair for IEEE Communications Society Technical Committee on Wireless Communications, and P2P Communications and Networking. He also serves/served as the Editor-in-Chief for IEEE Network, Peer-to-Peer Networking and Application, and IET Communications; a Founding Area Editor for IEEE Transactions on Wireless Communications; an Associate Editor for IEEE Transactions on Vehicular Technology, Computer Networks, and ACM/Wireless Networks; and the Guest Editor for IEEE JSAC, IEEE Wireless Communications, IEEE Communications Magazine, and ACM Mobile Networks and Applications.

Dr. Shen is a registered Professional Engineer of Ontario, Canada, an IEEE Fellow, a Fellow of the Canadian Academy of Engineering, a Fellow of Engineering Institute of Canada, and a Distinguished Lecturer of IEEE Vehicular Technology Society and Communications Society.