Optofluidics: Guiding the Nanoparticles and Biomolecules with Light

Chin, Lip Ket; Shi, Yu Zhi; Zhao, H. T.; Liu, Patricia Yang; Yap, Peng Huat; Wang, K.; Wang, Gang; Ser, Wee; Liu, Ai Qun; Liedberg, Bo

2015

Chin, L. K., Shi, Y. Z., Zhao, H. T., Liu, P. Y., Yap, P. H., Wang, K., et al. (2015). Optofluidics: Guiding the Nanoparticles and Biomolecules with Light. IFMBE Proceedings, 1-2.

<https://hdl.handle.net/10356/80251>

https://doi.org/10.1007/978-3-319-19452-3_1

© 2015 Springer. This is the author created version of a work that has been peer reviewed and accepted for publication by IFMBE Proceedings, Springer. It incorporates referee's comments but changes resulting from the publishing process, such as copyediting, structural formatting, may not be reflected in this document. The published version is available at: [http://dx.doi.org/10.1007/978-3-319-19452-3_1].

Downloaded on 26 Apr 2023 17:33:37 SGT

Optofluidics: Guiding the Nanoparticles and Biomolecules with Light

L.K. Chin¹, Y.Z. Shi¹, H.T. Zhao¹, Patricia Y. Liu¹, P.H. Yap², K. Wang³, G. Wang¹, B. Liedberg⁴,
W. Ser¹, and A.Q. Liu¹

¹ School of Electrical and Electronic Engineering, Nanyang Technological University, Singapore 639798

² Lee Kong Chian School of Medicine, Nanyang Technological University, Singapore 639798

³ Institute of Biological Chemistry, Academia Sinica, Taipei 115, Taiwan

⁴ School of Materials Science and Engineering, Nanyang Technological University, Singapore 639798

Abstract— Optofluidics has recently gained huge research attentions because of its synergetic manipulations of light and liquids. Several optofluidic components and devices have been demonstrated in the last 10 years, leading to its applications in guiding nanoparticles and biomolecules in the microchannel.

Keywords— Optofluidics, nanoparticle manipulation, micro/nanofluidics and nanophotonics.

I. INTRODUCTION

Microfluidics represent the science and technology that process or manipulate small amount of fluids (10^{-9} to 10^{-18} liters) with dimensions of tens-to-hundreds of micrometers in microfluidic chip. Optofluidics aims to manipulate light and liquids at microscale, exploiting their interaction to create highly versatile devices that is significant scientifically and interests in biological and biomedical research areas. The novelties of the optofluidics are twofold [1]. First, liquids are used to carry substances to be analyzed in highly sensitive optical microdevices. Second, liquids is exploited to control optical microdevices, making them tunable, reconfigurable and adaptive. It is a new breakthrough research area that provides new opportunities for a wide range of traditional photonic devices, allowing tuning and reconfiguration at the micrometer scale using microfluidic manipulation.

II. NANOPARTICLE AND BIOMOLECULE GUIDING

Many novel innovations have been demonstrated, such as liquid-liquid waveguide [2], liquid lens [3-4], liquid gratings [5-7] and liquid prism [8] etc. Light propagation can be tuned by varying the refractive index contrast or the curvature of the interface. These components are operated in a fast flow rate or two-phase flow conditions whereby diffusion is insignificant. Several devices have been demonstrated such as microfluidic waveguide laser [9], evanescent wave sensor [10] and cell refractometers [11-13].

Recently, diffusion between liquids in a microchannel is exploited for light manipulation. Diffusion within the liquid

flow streams in the microchannel is studied to design different photonic components. When two or more miscible liquids are flowing in a microchannel, diffusion between the flow streams occur and a bidirectional gradient index profile (concentration and refractive index) is formed. We have demonstrated how lightwave can be bent in a bidirectional gradient index profile in the liquid waveguide, which supports novel wave-focusing and interference phenomena [14]. In addition, using the same approach with different bidirectional gradient index profile in the microchannel, an optofluidic Y-branch splitter with large-angle bending and tuning is demonstrated [15].

The manipulation and sorting of a small size of particle/molecule with dimensions of tens to hundreds of nanometers in a microfluidic chip is one of the most significant research approaches. In this talk, light is shaped efficiently to generate distinctive interference patterns in the optofluidic chip, which can be used to sort and assemble biological samples. For example, the optical field can be switched from the Bessel profile for particle sorting to the discrete interference patterns for particle assembly.

III. CONCLUSIONS

In conclusion, optofluidics is a perfect candidate for nanoparticle and biomolecule guiding because it is capable of not only manipulate liquid mixing and diffusion, but also shaping light propagation and optical force in the microchannel. It has high potential applications for nanomedicine, virus disease diagnosis and biomolecule studies.

ACKNOWLEDGMENT

The authors would like to acknowledge the financial support from Environmental and Water Industry (EWI) Development Council of Singapore (Grant No. 1102-IRIS-05) and Ministry of Education (Grant No. Tier-1 RG89/13).

REFERENCES

1. A. Q. Liu. Preface to special topic: Optofluidics. *Biomicrofluidics* 4:042901
2. D. B. Wolfe, R. S. Conroy, P. Garstecki et al. (2004) Dynamic control of liquid-core/liquid cladding optical waveguides. *Proceed. Natl. Acad. Sci.* 101:12434-12438
3. Y. C. Seow, A. Q. Liu, L. K. Chin et al. (2008) Different curvature of tunable liquid microlens via the control of laminar flow rate. *Appl. Phys. Lett.* 93:084101
4. L. K. Chin, A. Q. Liu, C. S. Lim et al. (2010) An optofluidic volume refractometer using Fabry-Pérot resonator with tunable liquid microlenses. *Biomicrofluidics* 4:024107
5. L. K. Chin, A. Q. Liu, Y. C. Soh et al. (2010) A reconfigurable optofluidic Michelson interferometer using tunable droplet grating. *Lab Chip* 10:1072-1078
6. L. K. Chin, A. Q. Liu, C. S. Lim et al. (2008) An on-chip liquid tunable grating using multiphase droplet microfluidics. *Appl. Phys. Lett.* 93:164107
7. J. Q. Yu, Y. Yang, A. Q. Liu et al. (2010) Microfluidic droplet grating for reconfigurable optical diffraction. *Optics Lett.* 35:1890-1892
8. S. Xiong, A. Q. Liu, L. K. Chin et al. (2011) An optofluidic prism tuned by two laminar flows. *Lab Chip* 11:1864-1869
9. Y. Yang, A. Q. Liu, L. K. Chin et al. (2012) Optofluidic waveguide as a transformation optics device for lightwave bending and manipulation. *Nature Communications* 3:651.
10. X. C. Li, J. Wu, A. Q. Liu et al. (2008) A liquid waveguide based evanescent wave sensor integrated onto a microfluidic chip. *App. Phys. Lett.* 93:193901.
11. W. Z. Song, X. M. Zhang, A. Q. Liu et al. (2006) Refractive index measurement of single living cells using on-chip Fabry-Pérot cavity. *Appl. Phys. Lett.* 89:203901.
12. L. K. Chin, A. Q. Liu, X. M. Zhang et al. (2007) Differential single living cell refractometry using grating resonant cavity with optical trap. *Appl. Phys. Lett.* 91:243901.
13. P. Y. Liu, L. K. Chin, W. Ser et al. (2014) An optofluidic imaging system to measure the biophysical signature of single waterborne bacteria. *Lab Chip* 14:4237-4243.
14. Y. Yang, A. Q. Liu, L. Lei et al. (2011) A tunable 3D optofluidic waveguide dye laser via two centrifugal Dean flow streams. *Lab Chip* 11:3182-3187
15. Y. Yang, L. K. Chin, J. M. Tsai et al. (2012) Transformation optofluidics for large-angle light bending and tuning. *Lab Chip* 12:3785-3790.

Author: Ai-Qun Liu
 Institute: Nanyang Technological University
 Street: 60 Nanyang Avenue
 City: Singapore
 Country: Singapore
 Email: eaqliu@ntu.edu.sg