Optical addressing of nanomechanical metamaterials with subwavelength resolution

Ou, Jun-Yu; Plum, Eric; Zheludev, Nikolay I.

2018

Ou, J.-Y., Plum, E., & Zheludev, N. I. (2018). Optical addressing of nanomechanical metamaterials with subwavelength resolution. *Applied Physics Letters*, 113(8), 081104-. doi:10.1063/1.5036966

<https://hdl.handle.net/10356/82977>

<https://doi.org/10.1063/1.5036966>

© 2018 The Author(s) (Published by AIP). All rights reserved. This paper was published in *Applied Physics Letters* and is made available with permission of The Author(s) (Published by AIP).

Downloaded on 26 Apr 2023 20:26:39 SGT

Optical addressing of nanomechanical metamaterials with subwavelength resolution

Jun-Yu Ou,^{1,a)} Eric Plum,^{1,a)} and Nikolay I. Zheludev^{1,2,a)}

¹Centre for Photonic Metamaterials and Optoelectronics Research Centre, University of Southampton, Highfield, Southampton SO17 1BJ, United Kingdom

²Centre for Disruptive Photonic Technologies, SPMS, TPI, Nanyang Technological University, Singapore 637371, Singapore

(Received 19 April 2018; accepted 2 August 2018; published online 22 August 2018)

Metamaterials that offer “on-demand” control of individual metamolecules are termed “randomly accessible metamaterials.” They can be useful for manipulation of the wavefront of electromagnetic radiation, for tailoring of the nearfield, and ultimately for multichannel data processing. Here, we demonstrate how light can be used to actuate individual metamaterial elements on demand. Selectivity is achieved by constructing the metamaterial from nanomechanical elements that are designed to have slightly different mechanical resonance frequencies. Actuation is controlled by modulation of the optical control signal at the mechanical resonance frequencies of targeted elements, providing an all-optical route to randomly accessible metamaterials with spatial resolution beyond the diffraction limit. *Published by AIP Publishing.* <https://doi.org/10.1063/1.5036966>

The ultimate vision of metamaterials is effectively continuous control over the properties of light at any point in time and space, i.e., with subwavelength pixelation.¹ The electromagnetic properties of metamaterials are determined by the composition and geometry of their subwavelength scale building blocks that are known as metamolecules. Therefore, metamolecule deformation² and modification of constituent materials via nonlinearities^{3,4} and phase transitions^{5,6} allow dynamic control over metamaterial properties. Selective control over individual metamaterial elements has been demonstrated using a microwave metamaterial based on mercury-filled microfluidic channels⁷ and a photonic metamaterial based on electrothermal actuation of individual nanostructures.⁸ However, such approaches are not scalable to large arrays of nanostructures as they require a separate control signal (channel or wire) to be physically routed to each element. In contrast, all-optical delivery of the control signal through free space enables scalable control over large metamaterial arrays. However, the spatial resolution of existing approaches is inherently limited by diffraction as they are based on imaging optical intensity or phase distributions on metamaterial arrays in order to induce phase transitions⁶ or to form interference patterns that control the light-metamaterial interaction.^{9,10}

Here, we demonstrate how individual nanomechanical metamaterial elements, which are spaced by much less than the wavelength of the optical control signal, can be actuated with light. Our metamaterial consists of identical plasmonic metamolecules supported by dielectric structures with unique mechanical resonances. Illumination of the metamolecules by near-infrared pump light leads to optically induced forces that cause resonantly enhanced displacement only if the pump is modulated at the element’s unique mechanical resonance frequency.

The metamaterial, which is shown in Fig. 1, consists of an array of Π -shaped gold metamolecules supported by pairs of silicon nitride strings (nanowires) separated by 95 and 110 nm gaps to allow relative movement of the horizontal and vertical gold bars that make up the metamolecules. Both gold and silicon nitride are 50 nm thick, and the metamolecule is $700 \times 700 \text{ nm}^2$ in size. A metamaterial based on similar Π -shaped metamolecules supported by narrower nanowires of $28 \mu\text{m}$ length was previously shown to exhibit a large optomechanical nonlinearity but did not allow addressing of individual metamaterial elements.¹¹ To realize addressable nanowire string pairs with different mechanical resonance frequencies in the present work, the string pairs supporting different rows of metamolecules were fabricated with different lengths from $24 \mu\text{m}$ to $28 \mu\text{m}$ in steps of $1 \mu\text{m}$. The nanostructure was fabricated from a commercially available silicon nitride membrane of 50 nm thickness by thermal evaporation of a 50-nm-thick gold layer followed by focused

FIG. 1. Optically addressable nanomechanical metamaterial. Scanning electron micrograph of the nanostructure and its unit cell (inset). Yellow represents gold and brown represents silicon nitride.

^{a)}Electronic addresses: jo2c09@orc.soton.ac.uk; erp@orc.soton.ac.uk; and niz@orc.soton.ac.uk

ion beam milling (FEI Helios 600 NanoLab), where the plasmonic resonators were fabricated before the strings were separated.

Maxwell stress tensor calculations and experiments have demonstrated that illumination at pump wavelengths close to an optical resonance of such mechanically reconfigurable metamolecules leads to light-induced actuation and an exceptionally large nonlinear optical response.^{11–16} Figure 2 shows both simulated (COMSOL) and measured (CRAIC microspectrophotometer) transmission, reflection, and absorption spectra of the metamaterial for light polarized with the electric field parallel to the nanowire strings. Measurements and simulations are in close agreement and show that the metamaterial has an absorption resonance at a wavelength of about 1250 nm.

FIG. 2. Optical properties of the reconfigurable metamaterial. (a) Simulated and (b) measured reflection (R), transmission (T), and absorption (A) spectra of the nanostructure. (c) In-plane optical forces per unit cell in units of P/c according to Maxwell stress tensor calculations, where P is the incident power and c is the speed of light in vacuum. Pump and probe wavelengths are indicated by dashed lines, and the insets of panel (a) show the optically induced charge distributions at these wavelengths in terms of the normalized electric field perpendicular to the unit cell's surface.

Light incident on the metamaterial will cause actuation due to thermal and electromagnetic optical forces. Absorption of light increases the temperature of the nanostructure, causing differential thermal expansion of gold and silicon nitride which will result in out-of-plane actuation of the nanowire strings. This actuation mechanism will be efficient for modulation that is slower than the structure's cooling timescale of tens of microseconds, i.e., up to modulation rates of tens of kHz. However, as discussed below, we observe resonant in-plane actuation of the nanostructure at MHz frequencies. Maxwell stress tensor calculations show that illumination of the nanostructure leads to significant optical forces that actuate strings within the metamaterial plane, see Fig. 2(c). Such in-plane optical forces are permitted in terms of symmetry as each string is closer to one neighbour than the other due to the gap sizes of 95 and 110 nm. They can be understood as forces acting between the optically induced oscillating dipole moments within the plasmonic metamolecules, time-averaged over the optical cycle.¹⁴ In-plane optical forces on neighbouring strings have equal magnitude and opposite direction; thus, they are either attractive or repulsive and alter the gap between neighbouring strings.

In order to actuate the metamaterial with light, we illuminated the nanostructure with an intensity modulated pump laser of 1550 nm wavelength [Fig. 3(a)], where the in-plane optical forces have a local maximum [Fig. 2(c)]. The resulting modulation of the metamaterial transmission was measured using a CW probe laser at a wavelength of 1310 nm, where the “slope” of the nearby transmission resonance ensures high sensitivity to perturbations of the metamaterial structure [Fig. 2(b)]. The probe signal was detected with a lock-in amplifier (Stanford Research SR844) that was locked to the modulation frequency of the pump laser. Both lasers were polarized with the electric field parallel to the nanowire strings, and the pump and probe intensities were 466 W/cm² and 89 W/cm² on the metamaterial, which was placed in an evacuated vacuum chamber with a pressure of 9×10^{-2} Torr to minimize air-damping of the nanomechanical oscillations. Figures 3(b) and 3(c) show the detected modulation of the metamaterial's transmission as a function of the pump modulation frequency alongside COMSOL simulations of the mechanical eigenmodes of the strings. Each string has two fundamental eigenmodes corresponding to oscillation parallel and perpendicular to the metamaterial plane. In the Π -resonator reconfigurable metamaterial, in-plane oscillation of the narrow strings leads to strong modulation of probe light and this is clearly seen as resonant peaks at 1.02, 1.13, 1.23, and 1.30 MHz, where the mechanical resonance frequencies are inversely proportional to the square of the string length. We note that only four of these mechanical resonances are observed as irreversible stiction, caused by charging and mechanical stress relaxation during focused ion beam milling, prevents in-plane oscillation of several strings including the 24 μ m strings. The 2 leftmost and 5 rightmost narrow strings shown in Fig. 1 are free to move. Notably, resonance quality factors (Q-factors) of 300 are observed for string lengths of 25 and 26 μ m, which are not affected by inhomogeneous broadening as only one narrow string of each of these lengths can oscillate freely. For string lengths

FIG. 3. Selective actuation of metamaterial strings with light. (a) Schematic of the experimental setup for actuating individual nanostrings with a 1550 nm wavelength pump laser modulated at frequency f and detecting the resulting modulation of a transmitted 1310 nm CW probe laser with a lock-in amplifier locked to the same frequency. (b) and (c) Detected transmission modulation $\Delta T/T$ at the probe wavelength as a function of the pump modulation frequency f . Insets show COMSOL simulations of the mechanical eigenmodes corresponding to the observed resonances.

of 27 and 28 μm , several narrow strings are free to move, which implies that slight differences between these strings result in inhomogeneous broadening of the transmission modulation associated with their mechanical resonances, which is likely to explain the lower observed Q-factors of 170 and 230, respectively. Much weaker light modulation associated with the out-of-plane oscillation eigenmode of the strings is seen around 800 kHz and evidence of the in-plane mode of the wide strings can be seen around 2.2 MHz.

Furthermore, thermal actuation due to optical absorption is visible at low modulation frequencies up to tens of kHz.

In analogy with acoustics, our work may be described as playing a “metamaterial guitar” with light, where plectrum becomes photon, string becomes nanostring, and kHz becomes MHz. What we report is essentially an optically addressable metamaterial array of optomechanical transducers.^{17–21} The interaction with light is determined by the metamaterial unit cell that provides freedom to design the optical response at the pump and probe wavelengths. In particular, this allows engineering of the optical and thermal forces that drive the actuation and arise from metamaterial excitation and absorption at the pump wavelength. Optical addressing of individual nanomechanical elements, strings in our case, becomes possible due to a slight size variation of the nanomechanical oscillators which results in different mechanical resonance frequencies for different oscillators while keeping the same optical resonators. This allows the amplitude of oscillation of each nanomechanical element to be controlled by the intensity of an optical control signal that is intensity-modulated at the element’s mechanical resonance frequency. In our case, metamaterial strings spaced by 700 nm have been actuated independently with light of 1550 nm wavelength, demonstrating that the resolution of our optical method is determined by nanofabrication rather than diffraction. We argue that independent amplitude modulation of multiple carrier frequencies provides a route to independent optical actuation of 1D,^{11–13,22} 2D,^{16,23} and even 3D arrays of nanomechanical metamaterial elements with spatial resolution that is not limited by diffraction. Instead, the spatial resolution and the carrier frequencies that will drive resonant actuation are determined by the size of the nanomechanical elements. Mechanical resonance frequencies of cantilevers and nanowire strings as employed here are proportional to t/L^2 , where L is the length and t is the thickness in the direction of oscillation, and reach GHz frequencies for sub-micron dimensions. We anticipate that the number of nanomechanical elements that can in principle be addressed independently with a single pump laser is on the order of the Q-factor of the mechanical resonance of an individual element, i.e., 300 in our case. This could be scaled up further by combining amplitude modulation with wavelength division multiplexing based on targeting distinct optical resonances of different metamaterial nanostructures with different pump lasers. Selective optical actuation of individual metamolecules will require metamolecules that act as both mechanical and optical resonators,^{16,23} such as a dielectric cantilever supporting a plasmonic resonator. Variation of either cantilever length or plasmonic resonator position on the cantilever could be used to realize metamolecules with unique mechanical resonance frequencies that could then be actuated individually with light.

As addressable nanomechanical metamaterials provide spatial and temporal control over electromagnetic waves, they are spatial light modulators, which can achieve subwavelength spatial resolution. Such control over metamaterial properties with subwavelength resolution is the basis for transformation optics²⁴ and could be used to realize devices that can be reconfigured dynamically to provide different optical functions. Furthermore, metamaterial arrays of

nanomechanical elements with unique mechanical resonance frequencies could also be exploited for super-resolution imaging and spectroscopy with a photodetector. For imaging, pump light illuminating each individual nanomechanical element would be detected by scanning the pump modulation frequency and reading the probe modulation at the corresponding mechanical resonance frequencies. For spectroscopy, each nanomechanical element would be covered with metamolecules that are sensitive to a different wavelength. A given pump wavelength would then be read with a probe beam while modulating incident pump light at the resonance frequency of the corresponding nanomechanical oscillator. In this case, the metamaterial would act as an array of optomechanical sensors detecting different wavelengths. This approach could be adapted for sensing of anything that influences the oscillation of a nanomechanical oscillator.

In conclusion, we demonstrate an optical method for controlling metamaterials which exploits nano-optomechanics to circumvent the optical diffraction limit. We report selective actuation of metamaterial elements spaced by 700 nm using light of 1550 nm wavelength and we argue that our approach provides a route to optical control of individual nanostructures forming 1D, 2D, and 3D metamaterial arrays. Further development of this concept could lead to super-resolution spatial light modulators, transformation optics devices, reconfigurable optical components, parallel optomechanical sensor arrays, super-resolution imaging devices, and miniaturized spectrometers.

This work was supported by the UK Engineering and Physical Sciences Research Council (Grant No. EP/M009122/1), the MOE Singapore (Grant No. MOE2016-T3-1-006), the Zepler Institute Research Collaboration Stimulus Fund (Grant 517719105) enabled by the 2017/18 UK Higher Education Innovation Fund, and the U.S. Office of Naval Research (Grant No. N62909-18-1-2026).

The data from this paper is available from the University of Southampton ePrints research repository: <http://doi.org/10.5258/SOTON/D0497>.

- ¹N. I. Zheludev, *Science* **348**(6238), 973–974 (2015).
- ²N. I. Zheludev and E. Plum, *Nat. Nanotechnol.* **11**, 16–22 (2016).
- ³D. J. Cho, W. Wu, E. Ponizovskaya, P. Chaturvedi, A. M. Bratkovsky, S.-Y. Wang, X. Zhang, F. Wang, and Y. R. Shen, *Opt. Express* **17**, 17652–17657 (2009).
- ⁴K. M. Dani, Z. Ku, P. C. Upadhyay, R. P. Prasankumar, S. R. J. Brueck, and A. J. Taylor, *Nano Lett.* **9**, 3565–3569 (2009).
- ⁵T. Driscoll, H.-T. Kim, B.-G. Chae, B.-J. Kim, Y.-W. Lee, N. M. Jokerst, S. Palit, D. R. Smith, M. Di Ventra, and D. N. Basov, *Science* **325**, 1518–1521 (2009).
- ⁶Q. Wang, E. T. F. Rogers, B. Gholipour, C.-M. Wang, G. Yuan, J. Teng, and N. I. Zheludev, *Nat. Photonics* **10**, 60–65 (2016).
- ⁷W. Zhu, Q. Song, L. Yan, W. Zhang, P.-C. Wu, L. K. Chin, H. Cai, D. P. Tsai, Z. X. Shen, T. W. Deng, S. K. Ting, Y. Gu, G. Q. Lo, D. L. Kwong, Z. C. Yang, R. Huang, A.-Q. Liu, and N. I. Zheludev, *Adv. Mater.* **27**, 4739–4743 (2015).
- ⁸P. Cencillo-Abad, J. Y. Ou, E. Plum, J. Valente, and N. I. Zheludev, *Nanotechnology* **27**, 485206 (2016).
- ⁹E. Plum, K. F. MacDonald, X. Fang, D. Faccio, and N. I. Zheludev, *ACS Photonics* **4**(12), 3000–3011 (2017).
- ¹⁰M. Papaioannou, E. Plum, J. Valente, E. Rogers, and N. I. Zheludev, *Light: Sci. Appl.* **5**, e16070 (2016).
- ¹¹J. Y. Ou, E. Plum, J. Zhang, and N. I. Zheludev, *Adv. Mater.* **28**, 729–733 (2016).
- ¹²M. Lapine, I. V. Shadrivov, D. A. Powell, and Y. S. Kivshar, *Nat. Mater.* **11**, 30–33 (2012).
- ¹³J. Zhang, K. F. MacDonald, and N. I. Zheludev, *Light: Sci. Appl.* **2**, e96 (2013).
- ¹⁴J. Zhang, K. F. MacDonald, and N. I. Zheludev, *Opt. Lett.* **39**, 4883–4886 (2014).
- ¹⁵R. Zhao, P. Tassin, T. Koschny, and C. M. Soukoulis, *Opt. Express* **18**, 25665–25676 (2010).
- ¹⁶A. Karvounis, J. Y. Ou, W. Wu, K. F. MacDonald, and N. I. Zheludev, *Appl. Phys. Lett.* **107**, 191110 (2015).
- ¹⁷M. Aspelmeier, T. J. Kippenberg, and F. Marquardt, *Rev. Mod. Phys.* **86**, 1391 (2014).
- ¹⁸M. Li, W. H. P. Pernice, C. Xiong, T. Baehr-Jones, M. Hochberg, and H. X. Tang, *Nature* **456**, 480–484 (2008).
- ¹⁹M. Li, W. H. P. Pernice, and H. X. Tang, *Nat. Nanotechnol.* **4**, 377–382 (2009).
- ²⁰R. Thijssen, E. Verhagen, T. J. Kippenberg, and A. Polman, *Nano Lett.* **13**(7), 3293–3297 (2013).
- ²¹S. Schmid, K. Wu, P. E. Larsen, T. Rindzevicius, and A. Boisen, *Nano Lett.* **14**(5), 2318–2321 (2014).
- ²²R. Thijssen, T. J. Kippenberg, A. Polman, and E. Verhagen, *ACS Photonics* **1**(11), 1181–1188 (2014).
- ²³B. J. Roxworthy and V. A. Aksyuk, *Nat. Commun.* **7**, 13746 (2016).
- ²⁴J. B. Pendry, D. Schurig, and D. R. Smith, *Science* **312**, 1780–1782 (2006).