Universality of oscillating boiling in Leidenfrost transition

Khavari, Mohammad; Tran, Tuan

2017

Khavari, M., & Tran, T. (2017). Universality of oscillating boiling in Leidenfrost transition. *Physical Review E*, 96, 043102-.

<https://hdl.handle.net/10356/86657>

<https://doi.org/10.1103/PhysRevE.96.043102>

© 2017 American Physical Society. This paper was published in *Physical Review E* and is made available as an electronic reprint (preprint) with permission of American Physical Society. The published version is available at: [<http://dx.doi.org/10.1103/PhysRevE.96.043102>]. One print or electronic copy may be made for personal use only. Systematic or multiple reproduction, distribution to multiple locations via electronic or other means, duplication of any material in this paper for a fee or for commercial purposes, or modification of the content of the paper is prohibited and is subject to penalties under law.

Downloaded on 26 Apr 2023 21:47:41 SGT

Universality of oscillating boiling in Leidenfrost transition

 Mohammad Khavari^{1,2} and Tuan Tran^{1,*}
¹*School of Mechanical & Aerospace Engineering, Nanyang Technological University, 50 Nanyang Avenue, 639798 Singapore*
²*Institute of Materials Research and Engineering, A*STAR, 3 Research Link, 117602 Singapore*

(Received 26 January 2017; published 3 October 2017)

The Leidenfrost transition leads a boiling system to the boiling crisis, a state in which the liquid loses contact with the heated surface due to excessive vapor generation. Here, using experiments of liquid droplets boiling on a heated surface, we report a phenomenon, termed oscillating boiling, at the Leidenfrost transition. We show that oscillating boiling results from the competition between two effects: separation of liquid from the heated surface due to localized boiling and rewetting. We argue theoretically that the Leidenfrost transition can be predicted based on its link with the oscillating boiling phenomenon and verify the prediction experimentally for various liquids.

 DOI: [10.1103/PhysRevE.96.043102](https://doi.org/10.1103/PhysRevE.96.043102)

I. INTRODUCTION

Boiling of liquid on a moderately heated surface removes heat effectively: The liquid absorbs heat after touching the surface, vaporizes, and the generated vapor is carried away by natural convection, letting liquid from the bulk replenish the surface. At elevated temperatures, this mechanism faces a fundamental problem, the so-called boiling crisis, whereby excessive vapor completely eliminates liquid-surface contact (the Leidenfrost effect), causing a severe drop in heat flux. Controlling the occurrence of the Leidenfrost effect therefore is vital to either applications intolerant of the boiling crisis [1] or those taking advantage of the liquid-surface separation [2]. Nonetheless, despite its centuries-old history dating back to 1756 [3], the transition to the Leidenfrost regime remains rich in empirical studies but incomplete in physical understanding [4].

Research efforts aiming at understanding the Leidenfrost phenomenon have focused on the case of *static* Leidenfrost droplets, i.e., droplets approaching a heated surface with negligible or small initial velocity and subsequently floating on the surface. The floating mechanism in this case has been studied in great detail: The viscous flow of vapor between a floating droplet and a heated surface provides a counterforce to the droplet's weight [5–8]. Similar hydrodynamical arguments have also been used to explain the bouncing behavior without contact of droplets falling on an unheated smooth surface with low velocity; the counterforce in this case is induced by the gas flow [9]. Although these theories have been used successfully to explain the floating mechanism in the static case, they have been assuming *a priori* existence of the gas-vapor layer, thus precluding reference to the contact boiling behavior and its role in the Leidenfrost transition. Their limitation already is hinted at by experimental evidence in the case of *dynamic* Leidenfrost droplets [10–12], i.e., those approaching the heated surface with high velocity. In such a case, the Leidenfrost transition becomes independent of the impact velocity, signaling another separating mechanism instead of the one based on the gas-vapor flows. As a result, these theories cannot be used to reveal the mechanism of the

Leidenfrost transition. The goal of this paper is to elucidate the Leidenfrost transition experimentally and theoretically.

II. EXPERIMENTS

We show that the boiling behavior at the Leidenfrost transition is dominated by a new phenomenon, namely, oscillating boiling. This boiling behavior results from the

FIG. 1. Snapshots showing the wetted area, measured by the total internal reflection (TIR) technique [11–14], of (a) the boiling process and (b) the rewetting process for acetone droplets with velocity $V_0 = 2.7 \text{ m s}^{-1}$ and surface temperature $T = 150^\circ\text{C}$. (c) Wetted area A_w vs t in the early stage of a droplet impacting on the top surface of a heated sapphire prism. (d) Wetted area A_w vs t during the entire impact process; the shaded area corresponds to the wetted area shown in (c). The inset: snapshots show the side view (upper panel) and the bottom view (lower panel) of the impact at different times. (e) Frequency f of oscillation vs V_0 for different values of T showing a weak dependence of f on V_0 . (f) Frequency $\bar{f}$ averaged across V_0 vs T . The solid line is the frequency V_{re}/R_d , where V_{re} is the rewetting velocity [Eq. (1)] and $R_d \approx 1 \text{ mm}$ is the droplet radius. All scale bars indicate a length scale of 1 mm.

*Corresponding author: ttran@ntu.edu.sg

TABLE I. Physical properties of the liquids at 20 °C, atmospheric pressure [30,34], and experimental conditions.

	Unit	Acetone	Ethanol	IPA	Water
σ	mN m ⁻¹	23.7	22.8	21.7	72.9
ρ_l	kg m ⁻³	790	800	781	999
T_b	°C	56	78	82	100
h_{fg}	kJ kg ⁻¹	552	1030	755	2454
C_p	kJ kg ⁻¹ K ⁻¹	2.16	2.4	2.6	4.18
$\dot{M}$	kg kmol ⁻¹	58.1	46	60.1	18
R_d	mm	1.0	1.0	1.0	1.2
V_0	m s ⁻¹	0.6–2.7	0.5–2.7	0.5–2.7	0.5–2.7
T	°C	20–370	20–210	20–230	20–520

competition between two effects: separation of liquid from the heated surface due to localized boiling and rewetting.

To show the oscillating boiling behavior, we visualize the surface's wetted areas and measure the total wetted area A_w as a function of time t (Fig. 1). For droplet impacts in a wide range of velocity, liquids (see Table I), and surface temperatures close to the Leidenfrost transition, A_w oscillates at remarkably high frequencies in the range of 12–32 kHz [Figs. 1(c) and 1(d)]. We observe that the frequency f of oscillation depends weakly on the impact velocity V_0 [Fig. 1(e)] but more significantly on the surface temperature T [Fig. 1(f)].

The repeating pattern of the total wetted area A_w typically consists of two distinct stages: an abrupt drop and a subsequent increase in A_w [Fig. 1(c)]. In the first stage, exemplified in Fig. 1(a), tiny dry spots first appear spontaneously and rather uniformly in the wetted area then expand and merge to create larger dry areas. This observation suggests that the decrease in A_w is caused primarily by *heterogeneous* boiling, a process of forming the vapor from the liquid on a solid surface at temperatures lower than boiling in a liquid (*homogeneous* boiling) [15,16]. In the second stage, however, the wetted areas merge and invade the dry ones in the direction perpendicular to the three-phase contact line, signifying a rewetting process [Fig. 1(b)]. On this basis, we postulate that heterogeneous boiling and rewetting are the two basic processes of the oscillating boiling behavior; the rapid fluctuation of A_w results from alternate domination of one process over the other (see Supplemental Material movies S1–S6 [20]).

III. THEORY

We now analyze the heterogeneous boiling process. On an ideally flat surface immersed in a liquid at temperature T_l and pressure P_l , vapor bubbles grow from embryos, tiny nanoscopic vapor pockets in the form of spherical caps attaching to the surface [Fig. 2(a), schematics]. For an embryo to grow into a vapor bubble, the pressure difference across the vapor-liquid interface must overcome the Laplace pressure. Equivalently, its radius must be larger than a critical value of $r_c = 2\sigma F / (P_v - P_l)$, where F is a correction factor to account for the partial spherical shape of the embryo [21]. Here, the vapor pressure P_v inside the embryo depends on T_l and P_l as $P_v = P_{\text{sat}}(T_l) \exp(\{v_l[P_l - P_{\text{sat}}(T_l)]\} / RT_l)$ [15], where v_l is the specific volume of the liquid, $P_{\text{sat}}(T_l)$ is the saturation pressure at T_l , and the liquid pressure P_l is

FIG. 2. (a) Critical size $2r_c$ of a vapor embryo (solid line) and evaporation time τ_h (dashed line) vs surface temperature T . Upper panel: schematic showing vapor embryos before and after merging to create a vapor layer. (b) Snapshots showing the rewetting process for acetone droplets impacting with velocity $V_0 = 2.3$ m s⁻¹ at low temperatures (left panel) and high temperatures (right panel); arrows indicate the motion of the three-phase contact line. Scale bars represent the length scale of 0.3 mm. The time stamps are measured from the first contact of impact. (c) Rewetting velocity V_{re} vs surface temperature T for acetone droplets for different impact velocities. (d) V_{re} vs T for different impact velocities for ethanol, isopropyl alcohol (IPA), and water. The solid lines show the prediction according to Eq. (1).

approximated using the atmospheric pressure. Owing to the very small size of the embryos, we assume that the temperature of the liquid surrounding the embryos is $T_l \approx T$, the surface temperature. If we denote J as the generation rate per unit area of embryos having radius r_c , J can be calculated readily using the thermodynamic conditions of the liquid [15,22]. It follows that the duration to populate a unit area by bubbles of radius r_c is $\tau_h = 1/Jr_c^2$. In Fig. 2(a), we show the plots of $2r_c$ and $\log_{10}(\tau_h)$ vs T for acetone at the vicinity of the Leidenfrost transition ($T_L = 180^\circ\text{C}$ for acetone). The reduction in r_c indicates a decrease in thickness of the vapor layer at higher T . Remarkably, we also observe a sharp drop in τ_h , implying that the required duration to generate a vapor layer becomes extremely small as T approaches the Leidenfrost transition. For instance, at $T = 180^\circ\text{C}$, $\tau_h = 1.6$ ns. This highlights the dominant role of the boiling process: A vapor layer is created immediately to separate the liquid from the surface if the liquid is heated sufficiently. However, we note that the boiling process takes away heat from the surface, causing its temperature to decrease, and as a result the heterogeneous boiling process is forced to stop.

As soon as the heterogeneous boiling process stops, the liquid in neighboring wetted areas merges and rewets the dry areas [Fig. 2(b)]. From the contact line's motion, indicated

FIG. 3. (a) Phase diagram of characteristic boiling regimes of acetone. The solid line represents the theoretical prediction of the Leidenfrost transition [Eq. (2)]; the dashed line and the dashed-dotted line, respectively, mark the Leidenfrost transition measured by TIR and side-view recordings. (b) Comparison between Leidenfrost temperatures obtained from theory (T_L^P) and those from experiments (T_L^M). The open markers on the diagonal line indicate T_L^P . Upward solid triangles indicate T_L^M obtained from TIR; downward solid triangles indicate T_L^M from side-view recordings. All other solid markers are T_L^M from previous studies [10,12,13,17–19]. The shaded area indicates $\pm 15\%$ deviation from the theoretical values.

in Fig. 2(b), we measure rewetting velocity V_{re} for different liquids and impact velocity V_0 . Generally, V_{re} is insensitive to V_0 and increases with surface temperature T [see Figs. 2(c) and 2(d)]. In order to understand this behavior, we note that a dry area resulting from heterogeneous boiling is covered by a vapor layer of thickness $h \approx 2r_c$ [Fig. 2(a), schematics]. Since the tested liquids have small viscosities, the rewetting process then is driven by capillary pressure $\sigma/2r_c$ and resisted only by inertia $\rho_l V_{re}^2$ [23,24]. Here, both the surface tension σ and the density ρ_l are functions of surface temperature T [25]. Balancing the capillary pressure and inertia gives an estimate for the rewetting velocity,

$$V_{re} \sim \left(\frac{\sigma}{2\rho_l r_c} \right)^{1/2} = \left(\frac{P_v - P_l}{4\rho_l F} \right)^{1/2}. \quad (1)$$

In Figs. 2(c) and 2(d), we show several plots of V_{re} vs T for all tested liquids with impacting velocity V_0 varying from 0.6 to 2.7 m s^{-1} . We observe excellent agreement with experimental results for acetone, ethanol, and IPA and an overestimate for water. We attribute a possible drop in surface temperature during impact to the discrepancy in the case of water: Due to its high latent heat and heat capacity compared to those of the other liquids, the surface temperature in actuality may drop considerably during impact [18]. This causes an overestimation of the liquid temperature T_l as well as the vapor pressure $P_v(T_l)$, leading to an overestimation of V_{re} [Eq. (1)]. Nonetheless, these results not only suggest that the measured rewetting velocity is consistent with our theoretical arguments for the rewetting process, but also confirm that the vapor layer thickness is well described by the critical size of the embryos. We conclude that the liquid-vapor dynamics in the oscillating boiling regime consist of two main processes: heterogeneous boiling followed by capillary-inertial rewetting.

We are now ready to derive an expression to determine the *dynamic* Leidenfrost transition, which marks the lower

bound of the Leidenfrost regime for impacting droplets; the surface temperature at this transition is termed as the *dynamic* Leidenfrost temperature T_L . We argue that, at $T = T_L$, the upward speed of vapor generation must be comparable to the downward speed V_0 of a liquid. Since the heterogeneous boiling process generates a vapor layer of thickness $h = 2r_c$ during the time τ_h , the upward speed of vapor generation is $V_v \sim 2r_c/\tau_h$. Thus the dynamic Leidenfrost temperature T_L satisfies the condition,

$$V_0 = \frac{2r_c(T_L)}{\tau_h(T_L)}. \quad (2)$$

This condition implicitly contains the dependence of T_L on V_0 and the liquid properties, and we use it to determine the Leidenfrost transition for our tested liquids.

We calculate T_L for acetone using Eq. (2) and show a plot of T_L vs V_0 (the solid line, Fig. 3) together with a phase diagram consisting of three different characteristic behaviors: Leidenfrost, *oscillating* boiling, and bubbly boiling [10,11] (Fig. 3). We identify and categorize these behaviors using TIR recordings of numerous impact experiments. We note that, although both the oscillating boiling and the bubbly boiling behaviors allow solid-liquid contact, only the former exhibits high-frequency switching between the heterogeneous boiling and rewetting processes, whereas the boiling dynamics of the latter are much slower because of low surface temperature. In the phase diagram, the boundary separating the Leidenfrost and oscillating boiling regimes indicates the experimentally determined T_L (the dashed line), which increases monotonically with V_0 and reaches a plateau of $T_L = 190^\circ\text{C}$ at $V_0 = 1.3 \text{ m s}^{-1}$, consistent with earlier studies [10,12]. We also show the Leidenfrost temperature determined by *side-view* recordings (the dashed-dotted line), a method incapable of directly detecting wetted areas during impact but instead relying on the ejection of small droplets as an indication of wetted areas [10]. The discrepancy between

values of T_L determined by side-view recordings and ones by the TIR technique, although not significant, therefore is expected. Nevertheless, the plateaued values of T_L measured by both techniques are in remarkable agreement with the predicted value of $T_L = 180^\circ\text{C}$ using Eq. (2) highlighting that the proposed prediction for T_L is valid for impacts at high velocity.

We emphasize that our prediction for T_L is not applicable for the case of low impact velocity, e.g., $V_0 \leq 1.3 \text{ m s}^{-1}$ where liquid-solid separation results from the viscous stress induced by air-vapor flows under impacting droplets. The viscous stress is responsible for phenomena, such as dimple formation [10,26], bubble entrapment [27], or even bouncing from unheated surfaces for droplets at low impact velocities [9]. We note that, for $V_0 \leq 1.3 \text{ m s}^{-1}$, the compressible effect is negligible and the thickness of the air-vapor film under a droplet decreases with increasing V_0 [26]. The increase in T_L with V_0 is expected to sustain the liquid-solid separation. Thus the deviation of the predicted values of T_L from the experimental ones at low impact velocity reveals the region where the viscous stress caused by the air-vapor flows becomes the dominant mechanism for separation.

In Fig. 3(b), we show a plot comparing the experimental Leidenfrost temperature (T_L^M) to the predicted one (T_L^P) for six different liquids having broadly different thermal and physical properties. For each liquid, we use the plateaued value of T_L [shown in Fig. 3(b)] as the experimentally measured one. The plot also consists of numerous experimental datasets from previous studies in which measurements of the dynamic Leidenfrost temperature were reported; most of them utilized the side-view technique to determine T_L . Except for water, we observe that all the experimental values of T_L are consistent within 15% deviation with the predicted ones; typically the TIR measured values are closer to theory than those obtained by the side-view technique. We note that, although the surface temperature is assumed constant in our simplified theory, it fluctuates considerably in reality [12,28,29] as a result of two competing heat transfer processes: one from the solid surface to the liquid and the other from the solid bulk to the surface. In addition, variations in surface roughness and impact velocity may contribute to a discrepancy between T_L^M and T_L^P . In the case of water, which has exceptionally high heat capacity and latent heat compared to other tested liquids (Table I), we expect a more severe drop in surface temperature, which may be the main cause of the vastly

disparate reported values for T_L^M (from 200°C to 410°C). The reduction in surface temperature, however, implies that the theory underestimates r_c and subsequently overestimates V_{re} , consistent with the result shown in Fig. 2(d) for water. In other words, the prediction of T_L for water is missing a prefactor to account for the substantial drop in surface temperature. A detailed analytical prediction of T_L for water, therefore, must be derived on the grounds of non-negligible fluctuation in surface temperature and merits further investigation.

IV. CONCLUSIONS

From our experimental measurements and analysis of T_L , we infer that there are two fundamentally different mechanisms for Leidenfrost transition at two extremes of velocity. At low impact velocity, the separation mechanism is associated mainly with the viscous stress induced in the air-vapor flows. By contrast, at high impact velocity, the mechanism for Leidenfrost transition is dictated by the heterogeneous boiling process, i.e., the kinetic limit of superheat at the solid-liquid interface. This explains the asymptotic behavior of the Leidenfrost transition at high impact velocity. The heterogeneous boiling process also causes the oscillating boiling behavior, i.e., high-frequency fluctuation of the wetted area due to alternative domination of either heterogeneous boiling or rewetting over the other. The transition to the Leidenfrost regime, therefore, reduces to the sustaining capability of the heterogeneous boiling process. For practical boiling applications at high temperatures, a direct implication from our theory is that, in order to avoid the boiling crisis, the properties of both the liquid and the boiling surface should be selected to obtain high rewetting velocity and subsequently to sustain heterogeneous boiling. Furthermore, the role of capillary-inertial rewetting in the transition to the boiling crisis on smooth surfaces can be further extended to design rough surfaces used in boiling. We conclude by highlighting that our findings offer a theoretical framework to treat the Leidenfrost transition, a crucial step toward achieving complete control of the Leidenfrost effect.

ACKNOWLEDGMENTS

We thank H. Kellay and P. Chakraborty for helpful discussions. This work was funded by Nanyang Technological University and A*STAR, Singapore. M.K. acknowledges a SINGA scholarship from A*STAR.

-
- [1] G. Berthoud, Vapor explosions, *Annu. Rev. Fluid Mech.* **32**, 573 (2000); J. Kim, Spray cooling heat transfer: The state of the art, *Int. J. Heat Fluid Flow* **28**, 753 (2007).
 - [2] H. Linke, B. J. Alemán, L. D. Melling, M. J. Taormina, M. J. Francis, C. C. Dow-Hygelund, V. Narayanan, R. P. Taylor, and A. Stout, Self-Propelled Leidenfrost droplets, *Phys. Rev. Lett.* **96**, 154502 (2006); I. U. Vakarelski, J. O. Marston, D. Y. C. Chan, and S. T. Thoroddsen, Drag Reduction by Leidenfrost Vapor Layers, *ibid.* **106**, 214501 (2011); I. U. Vakarelski, N. A. Patankar, J. O. Marston, D. Y. C. Chan, and S. T. Thoroddsen, Stabilization of Leidenfrost vapour layer by textured superhydrophobic surfaces, *Nature (London)* **489**, 274 (2012).
 - [3] J. Leidenfrost, On the fixation of water in diverse fire, *Int. J. Heat Mass Transfer* **9**, 1153 (1966).
 - [4] J. D. Bernardin and I. Mudawar, Validation of the quench factor technique in predicting hardness in heat treatable aluminum alloys, *Int. J. Heat Mass Transfer* **38**, 863 (1995); A Leidenfrost point model for impinging droplets and sprays, *J. Heat Transfer* **126**, 272 (2004); G. Liang and I. Mudawar, Review of drop impact on heated walls, *Int. J. Heat Mass Transfer* **106**, 103 (2017).
 - [5] B. S. Gottfried, C. J. Lee, and K. J. Bell, The Leidenfrost phenomenon: film boiling of liquid droplets on a flat plate, *Int. J. Heat Mass Transfer* **9**, 1167 (1966).

- [6] A.-L. Biance, C. Clanet, and D. Quéré, Leidenfrost drops, *Phys. Fluids* **15**, 1632 (2003).
- [7] J. Bernardin and I. Mudawar, The Leidenfrost point: Experimental study and assessment of existing models, *J. Heat Transfer* **121**, 894 (1999).
- [8] M. Rein, *Drop-Surface Interactions* (Springer, Wien/New York, 2002), Vol. 456.
- [9] J. De Ruiter, R. Lagraauw, D. van den Ende, and F. Mugele, Wettability-independent bouncing on flat surfaces mediated by thin air films, *Nat. Phys.* **11**, 48 (2015).
- [10] T. Tran, H. J. J. Staat, A. Prosperetti, C. Sun, and D. Lohse, Drop Impact on Superheated Surfaces, *Phys. Rev. Lett.* **108**, 036101 (2012).
- [11] M. Khavari, C. Sun, D. Lohse, and T. Tran, Fingering patterns during droplet impact on heated surfaces, *Soft Matter* **11**, 3298 (2015).
- [12] M. Shirota, M. A. J. van Limbeek, C. Sun, A. Prosperetti, and D. Lohse, Dynamic Leidenfrost Effect: Relevant Time and Length Scales, *Phys. Rev. Lett.* **116**, 064501 (2016).
- [13] N. Nagai and S. Nishio, Leidenfrost temperature on an extremely smooth surface, *Exp. Therm. Fluid Sci.* **12**, 373 (1996).
- [14] J. M. Kolinski, S. M. Rubinstein, S. Mandre, M. P. Brenner, D. A. Weitz, and L. Mahadevan, Skating on a Film of Air: Drops Impacting on a Surface, *Phys. Rev. Lett.* **108**, 074503 (2012).
- [15] V. P. Carey, *Liquid-Vapor Phase-Change Phenomena* (Hemisphere, New York, 1992).
- [16] R. Cole, Boiling nucleation, *Adv. Heat Transfer* **10**, 85 (1974).
- [17] G. P. Celata, M. Cumo, A. Mariani, and G. Zummo, Visualization of the impact of water drops on a hot surface: effect of drop velocity and surface inclination, *Heat Mass Transfer* **42**, 885 (2006).
- [18] J. Jung, S. Jeong, and H. Kim, Investigation of single-droplet/wall collision heat transfer characteristics using infrared thermometry, *Int. J. Heat Mass Transfer* **92**, 774 (2016).
- [19] S. L. Manzello and J. C. Yang, An experimental study of high Weber number impact of methoxy-nonafluorobutane $C_4F_9OCH_3$ (HFE-7100) and *n*-heptane droplets on a heated solid surface, *Int. J. Heat Mass Transfer* **45**, 3961 (2002); S. Chandra and C. T. Avedisian, On the collision of a droplet with a solid surface, *Proc. R. Soc. London, Ser. A* **432**, 13 (1991).
- [20] See Supplemental Material at <http://link.aps.org/supplemental/10.1103/PhysRevE.96.043102> for movies.
- [21] The factor $F = 0.5 + 0.75 \cos \theta - 0.25 \cos^3 \theta$ is the correction factor that accounts for partially wettable liquids with contact angle θ .
- [22] The embryo formation rate J relates to liquid properties and boiling conditions as [15] $J = \Gamma_1 \Gamma_2 \Gamma_3$, where $\Gamma_1 = \rho_{N,l}^{2/3} (1 + \cos \theta) / 2F$, $\Gamma_2 = [3F\sigma_{lv} / (\pi m)]^{1/2}$, $\Gamma_3 = \exp \{ -16\pi F\sigma_{lv}^3 / \{3k_B T_l [\eta P_{\text{sat}}(T_l) - P_l]^2\} \}$, and $\eta = \exp \{ v_l [P_l - P_{\text{sat}}(T_l)] / (RT_l) \}$. Here $\rho_{N,l} = N_A / (v_l \bar{M})$ is the number density of liquid molecules per unit volume, $m = \bar{M} / N_A$ is the mass of one molecule, $\bar{M}$ is the molecular mass in kg kmol^{-1} , $N_A = 6.02 \times 10^{26} \text{ kmol}^{-1}$ is the Avogadro constant, $k_B = 1.38 \times 10^{-23} \text{ J K}^{-1}$ is the Boltzmann constant, $R = \bar{R} / \bar{M}$ is the specific gas constant in $\text{J kg}^{-1} \text{ K}^{-1}$, and $\bar{R} = 8314.4 \text{ J K}^{-1} \text{ kmol}^{-1}$ is the universal gas constant.
- [23] M. Wu, T. Cubaud, and C.-M. Ho, Scaling law in liquid drop coalescence driven by surface tension, *Phys. Fluids* **16**, L51 (2004).
- [24] K. G. Winkels, J. H. Weijs, A. Eddi, and J. H. Snoeijer, Initial spreading of low-viscosity drops on partially wetting surfaces, *Phys. Rev. E* **85**, 055301(R) (2012).
- [25] Since the surface tension σ , specific volume v_l , and saturation pressure P_{sat} of each liquid depend strongly on the liquid temperature T_l , we interpolate their temperature-dependent values from the reported data for the tested liquids, including acetone, ethanol, water, and heptane [30], IPA [31,32] and HFE7100 [33].
- [26] E. Q. Li and S. T. Thoroddsen, Time-resolved imaging of a compressible air disc under a drop impacting on a solid surface, *J. Fluid Mech.* **780**, 636 (2015).
- [27] R. C. A. van der Veen, T. Tran, D. Lohse, and C. Sun, Direct measurements of air layer profiles under impacting droplets using high-speed color interferometry, *Phys. Rev. E* **85**, 026315 (2012); W. Bouwhuis, R. C. A. van der Veen, T. Tran, D. L. Keij, K. G. Winkels, I. R. Peters, D. van der Meer, C. Sun, J. H. Snoeijer, and D. Lohse, Maximal Air Bubble Entrainment at Liquid-Drop Impact, *Phys. Rev. Lett.* **109**, 264501 (2012).
- [28] M. Seki, H. Kawamura, and K. Sanokawa, Transient temperature profile of a hot wall due to an impinging liquid droplet, *J. Heat Transfer* **100**, 167 (1978).
- [29] M. A. J. van Limbeek, M. Shirota, P. Sleutel, C. Sun, A. Prosperetti, and D. Lohse, Vapour cooling of poorly conducting hot substrates increases the dynamic Leidenfrost temperature, *Int. J. Heat Mass Transfer* **97**, 101 (2016).
- [30] A. Faghri and Y. Zhang, *Transport Phenomena in Multiphase Systems* (Academic, Burlington, MA, 2006).
- [31] D. Ambrose, J. F. Counsell, I. J. Lawrenson, and G. B. Lewis, Thermodynamic properties of organic oxygen compounds XLVII. Pressure, volume, temperature relations and thermodynamic properties of propan-2-ol, *J. Chem. Thermodyn.* **10**, 1033 (1978).
- [32] B. C. Hoke, Jr. and J. C. Chen, Binary aqueous-organic surface tension temperature dependence, *J. Chem. Eng. Data* **36**, 322 (1991).
- [33] M. H. Rausch, L. Kretschmer, S. Will, A. Leipertz, and A. P. Fröba, Density, surface tension, and kinematic viscosity of hydrofluoroethers HFE-7000, HFE-7100, HFE-7200, HFE-7300, and HFE-7500, *J. Chem. Eng. Data* **60**, 3759 (2015).
- [34] D. R. Lide, *CRC Handbook of Chemistry and Physics* (CRC, Boca Raton, FL, 2004).