An analytical model for mixing based on time-interleaved sequential segmentation

Nguyen, Nam-Trung; Huang, Xiaoyang

2005

Nguyen, N. T., & Huang, X. Y. (2005). An analytical model for mixing based on time-interleaved sequential segmentation. *Microfluidics and Nanofluidics*, 1(4), 373-375.

<https://hdl.handle.net/10356/93884>

<https://doi.org/10.1007/s10404-005-0039-6>

© 2005 Springer-Verlag. This is the author created version of a work that has been peer reviewed and accepted for publication by *Microfluidics and Nanofluidics*, Springer-Verlag. It incorporates referee's comments but changes resulting from the publishing process, such as copyediting, structural formatting, may not be reflected in this document. The published version is available at: [<http://dx.doi.org/10.1007/s10404-005-0039-6>].

Downloaded on 26 Apr 2023 17:20:12 SGT

An analytical model for mixing based on time-interleaved sequential segmentation

Nam-Trung Nguyen[§], Xiaoyang Huang

[†] School of Mechanical and Production Engineering, Nanyang Technological University, 50 Nanyang Avenue, Singapore 639798

[§] To whom correspondence should be addressed (email: mntnguyen@ntu.edu.sg, Tel: (65) 6790 4457, Fax: (65) 6791 1859)

Abstract

Due to constraints caused by the laminar flow in microscale, effective and fast mixing is important for many microfluidic applications. From the scaling law, decreasing the mixing path can shorten the mixing time and enhance the mixing quality. One of the techniques for reducing mixing path is time-interleaved sequential segmentation. This technique divides solvent and solute into segments in axial direction. The mixing path can be controlled by the switching frequency and the mean velocity of the flow. In this brief communication, we present a simple time-dependent one-dimensional analytical model for time-interleaved sequential segmentation. The model considers an arbitrary mixing ratio between solute and solvent as well as the axial Taylor-Aris dispersion. The analytical solution indicates that the Peclet number is the key parameter for this mixing concept.

Keywords

micromixer, mass transfer, diffusion, dispersion, sequential segmentation, time-interleaved segmentation

Mixing in microscale is constrained by laminar flow behavior in microchannels. One of the many techniques for improving mixing is reducing the mixing path between solvent and solute [1]. In lamination techniques, solvent and solute remain in their particular streams. Mixing path is shorten perpendicularly to the axial flow direction. Time-interleaved sequential segmentation divides the solvent and solute into segments, which occupy the whole channel width. Mixing occurs through dispersion in flow direction. Sequential segmentation can be achieved by alternate switching of the inlet flows, using controlled valves for instance (Figure 1). The mixing ratio can be adjusted by the switching ratio. Deshmukh et al. [2] described this concept numerically and observed the mixing results experimentally. The segmentation process was controlled actively by integrated micropumps. Similar concepts realized by external pumps were reported later by Fujii et al. [3] and Okamoto et al. [4]. All previous works are based on numerical simulation and experimental observation. In this communication, we report a simple analytical model of this mixing concept to present better understanding of mixing based on sequential segmentation.

We start with a parallel plate model for the mixing channel. Pressure driven flow in microchannels with low aspect ratio ($W \gg H$) can be reduced to this model, Figure 2. The model assumes a flat velocity profile in the channel width direction (z -axis) and a Poiseuille velocity profile in the channel height (y -axis) [5]:

$$u(y) = 6U \left(1 - \frac{y}{H}\right) \frac{y}{H} \quad (1)$$

where U is the mean velocity in the flow direction along the x -axis. The parabolic velocity profile causes the so-called Taylor-Aris dispersion, which can be described by an effective diffusion coefficient D^* . Using the Taylor-Aris approach [6] and the velocity profile (1), the effective diffusion coefficient can be determined as [7]:

$$D^* = D + \frac{H^2 U^2}{210D} \quad (2)$$

where D is the molecular diffusion coefficient of the solute in the solvent and H is the channel height. It's to note that the Taylor-Aris approach considers dispersion far away from the channel inlet, which is not very accurate for our case. However, this paper will mainly focus on the transient concentration distribution along the flow direction as elaborated next.

With the effective diffusion coefficient D^* , the problem of time-interleaved sequential segmentation can be reduced to a simple one-dimensional macro transport model. The concentration distribution across the channel width and height is assumed to be uniform, thus only the concentration profile along the flow direction x needs to be considered. With a mean velocity U and a switching period T , the characteristic segment length is defined as $L = UT$. The general transport equation can be then reduced to the transient one-dimensional form:

$$\frac{\partial c}{\partial t} + U \frac{\partial c}{\partial x} = D^* \frac{\partial^2 c}{\partial x^2} \quad (3)$$

Figure 3 depicts this one-dimensional model with the boundary condition at the inlet. Figure 4 describes the periodic boundary condition at the inlet ($x = 0$):

$$c(t, 0) = \begin{cases} c_0 & 0 \leq t \leq \alpha T/2 \\ 0 & \alpha T/2 < t \leq T - \alpha T/2 \\ c_0 & T - \alpha T/2 < t \leq T \end{cases} \quad (4)$$

where c_0 , T , and α are the initial concentration of the solute, the period of the segmentation, and the mixing ratio, respectively.

Introducing the dimensionless variables $c^* = c/c_0$, $x^* = x/L$ and $t^* = t/T$, equation (3) has the dimensionless form:

$$\frac{\partial c^*}{\partial t^*} = \frac{1}{\text{Pe}} \frac{\partial^2 c^*}{\partial x^{*2}} - \frac{\partial c^*}{\partial x^*} \quad (5)$$

where the Peclet number is defined as $\text{Pe} = UL/D^*$. The dimensionless boundary condition of (4) is then:

$$c^*(t^*, 0) = \begin{cases} 1 & 0 \leq t^* \leq \alpha/2 \\ 0 & \alpha/2 < t^* \leq 1/2 \end{cases} \quad (6)$$

Solving the (5) using separation of variables with (6) and ($c^*(\infty) = \alpha$) results to the transient behavior of the concentration profile along the mixing channel:

$$c^*(x^*, t^*) = \alpha + \sum_{n=1}^{\infty} \frac{2 \sin(\alpha \pi n)}{\pi n} \Re \left\{ \exp \left[\frac{1}{2} \left(\text{Pe} - \sqrt{\text{Pe}^2 + 8\pi n \text{Pe} j} \right) x^* \right] \right. \\ \left. \times \exp(2\pi n t^* j) \right\} \quad (7)$$

where j is the imaginary unit, $\Re$ indicates the real component of a complex number. The concentration distributions along the mixing channel at different Peclet numbers and at different mixing ratios are depicted in Figure 5(a) and Figure 5(b), respectively. Figure 5(a) shows clearly that only a short mixing channel is required if the Peclet number is small, that means either a small mean velocity U or a short characteristic segment length L . A short segment length is caused by or a short switching time T or a high switching frequency $f = 1/T$. Sequential segmentation can achieve different final concentrations simply by adjusting the switching ratio α , Figure 5(b).

We reported a simple transient, one-dimensional model for mixing in microchannels based on time-interleaved sequential segmentation. The model describes well the concentration profile along the flow direction. If the segment length L and the switching time period T are used as the characteristic length and the characteristic time, Peclet number Pe and the mixing ratio α would be the two parameters characterizing this mixing concept. An arbitrary mixing ratio can be achieved by modulating the pulse width of the switching signal. Since this model assumes one dimensional distribution along the flow axis, the result may suit best for the distribution on the centerline along the channel.

References

- [1] Nguyen N T and Wu Z: (2005) Micromixers - a review, Journal of Micromechanics and Microengineering 15: R1-R16

- [2] Deshmukh A A, Liepmann D and Pisano A P: (2000) Continuous micromixer with pulsatile micropumps, Technical Digest of the IEEE Solid State Sensor and Actuator Workshop (Hilton Head Island, SC): 736
- [3] Fujii et al.: (2003) A plug and play microfluidic device, Lab on a Chip 3: 1937
- [4] Okamoto H, Ushijima T and Kitoh O: (2004) New methods for increasing productivity by using microreactors of planar pumping and alternating pumping types, Chemical Engineering Journal 101: 57-63
- [5] Bird R B, Stewart W E and Lightfoot E N (2002): Transport Phenomena (New York: Wiley)
- [6] Aris R: (1956) On the dispersion of a solute in a fluid flowing through a tube, Proc. Roy. Soc. A235: 67-77
- [7] Brenner H, Edwards D A (1993): Macrotransport Processes, Butterworth-Heinemann, Boston

List of Figures

Figure 1: Mixing concept based on time-interleaved sequential segmentation.

Figure 2: Model of the mixing channel.

Figure 3: Transient one-dimensional model for a micromixer with sequential segmentation.

Figure 4: The transient concentration at the inlet of the mixing channel.

Figure 5: Concentration profile along the flow direction at $t^* = 1$: (a) with different Peclet numbers ($\alpha = 0.5$); (b) with different mixing ratios ($Pe=100$).

Figure 1. Mixing concept based on time-interleaved sequential segmentation.

Figure 2. Model of the mixing channel.

Figure 3. Transient one-dimensional model for a micromixer with sequential segmentation.

Figure 4. The transient concentration at the inlet of the mixing channel.

Figure 5. Concentration profile along the flow direction at $t^* = 1$: (a) with different Peclet numbers ($\alpha = 0.5$); (b) with different mixing ratios ($Pe=100$).