Inclined wall plumes in porous media

Shu, Jian Jun; Pop, I.

1997

Shu, J. J., & Pop, I. (1997). Inclined Wall Plumes in Porous Media. *Fluid Dynamics Research*, 21(4), 303-317.

<https://hdl.handle.net/10356/94149>

[https://doi.org/10.1016/S0169-5983\(97\)81115-X](https://doi.org/10.1016/S0169-5983(97)81115-X)

© 1997 The Japan Society of Fluid Mechanics Incorporated and Elsevier Science B.V. This is the author created version of a work that has been peer reviewed and accepted for publication by Fluid dynamics research, The Japan Society of Fluid Mechanics Incorporated and Elsevier Science B.V. It incorporates referee's comments but changes resulting from the publishing process, such as copyediting, structural formatting, may not be reflected in this document. The published version is available at:
[[http://dx.doi.org/10.1016/S0169-5983\(97\)81115-X](http://dx.doi.org/10.1016/S0169-5983(97)81115-X)].

Downloaded on 26 Apr 2023 13:06:37 SGT

Inclined wall plumes in porous media

J.-J. Shu^{a,*}, I. Pop^b

^a *Department of Applied Mathematical Studies, University of Leeds, Leeds LS2 9JT, UK*

^b *Faculty of Mathematics, University of Cluj, CP 253, R-3400 Cluj, Romania*

Abstract

We present a numerical solution of the natural convection from inclined wall plumes which arise from a line thermal source imbedded at the leading edge of an adiabatic plate with arbitrary tilt angle between 0 and $\pi/2$, and embedded in a fluid-saturated porous medium. An appropriate transformation of the governing boundary-layer equations is proposed and a very efficient novel numerical solution is proposed to obtain rigorous numerical solutions of the transformed nonsimilar equations over a wide range of tilt angle from the vertical to the horizontal. Graphs are presented showing the effect of the tilt angle on the velocity and temperature profiles, as well as on the wall velocity and wall temperature. As far as we know, this problem has not yet been studied in the available literature.

Nomenclature

C_p	specific heat of fluid
f	dimensionless stream function
g	acceleration due to gravity
K	permeability of the porous medium
L	length of line source
Q	energy released from the line source
R_a	Rayleigh number
T	temperature
T^*	equivalent temperature of the line source
u, v	velocity components in the x, y directions
x, y	coordinates along and normal to the plate, respectively
α	effective thermal diffusivity of the porous medium
β	coefficient of thermal expansion

* Corresponding author.

ζ	plate inclination parameter
η	pseudo-similarity variable
θ	dimensionless temperature
λ	constraint variable
ξ	characteristic dimensionless coordinate
ρ	fluid density
Φ	tilt angle measured from the vertical
ψ	stream function

Subscripts

w	condition at the wall
∞	condition far from the wall

Superscript

'	differentiation with respect to η
---	--

1. Introduction

During the past two decades considerable research efforts have been devoted to the study of heat transfer induced by buoyancy effects in a porous medium saturated with fluids as evidenced by the literature published in the recent monograph by Nield and Bejan (1992). Interest in this convective heat transfer phenomena has been motivated by such diverse applications of the subject in contemporary technologies as thermal insulation of buildings, nuclear engineering systems, geothermal engineering, energy storage and recovery systems, storage of grain, fruits and vegetables, petroleum reservoirs, pollutant dispersion in aquifers, and catalytic reactors. There is no doubt that this area of convective heat transfer keeps attracting engineers and scientists from diversified disciplines such as mechanical engineering, chemical engineering, civil engineering, nuclear engineering, bio-engineering, food science and geothermal physics.

The steady buoyancy-induced flow arising from thermal energy sources is commonly referred to as a natural or mixed convection plume. Among such plumes, two general types may be identified – the free plume and the wall plume. The free plume is typified by the buoyant flow resulting from a point or a line source of heat. A typical wall plume is the flow resulting from a line source of heat imbedded at the leading edge of an adiabatic surface. Free and wall plumes arise in power plant steam lines, buried electrical cables, oil and gas distribution lines, volcanic eruption, disposal of nuclear wastes, hot-wire anemometry, industrial and agricultural water distribution lines, etc.

Natural convection resulting from a line or point source in an infinite Darcian porous medium (free plume) was first considered by Wooding (1963) and his analysis has been very much refined and generalized since then. On the basis of the boundary layer approximation similarity solutions were obtained by this author, assuming the Rayleigh number to be sufficiently high; it neglects the conduction in the axial direction, normal pressure gradient and the entrainment in the plume from the outer region. Similarity solutions for this problem were also obtained by Lai (1990a), while

Bejan (1978), Masuoka et al. (1986) have obtained similarity solutions for the problem of axisymmetric plume from a point heat source in a porous medium on the basis of the boundary-layer approximation. The point heat sources at low Rayleigh numbers in an unbounded Darcian porous medium were investigated by Hickox and Watts (1980) and Hickox (1981). Afzal and Salam (1990) have considered the case when the point heat source is bounded by an adiabatic conical surface. Bejan (1978), Nield and White (1982), Ganapathy and Purushothaman (1990), and Purushothaman et al. (1990) used a perturbation analysis for small Rayleigh number to study the transient and steady natural convection produced in an infinite fluid-saturated porous medium when a point or a horizontal line heat source starts to liberate heat. The higher-order boundary layers for natural convection from a horizontal line source of heat (free plume) in a Darcian porous medium were determined by Afzal (1985), and Shaw and Dawe (1985) using the method of matched asymptotic expansions. The Darcian mixed convection from a line thermal source imbedded at the leading edge of an adiabatic vertical surface (wall plume) in a saturated porous medium was numerically investigated by Kumari et al. (1988).

Coupled heat and mass transfer by natural convection at low Rayleigh number in an infinite Darcian porous medium has been considered by Poulikakos (1985) and Ganapathy (1994) for a point source, by Larson and Poulikakos (1986) for a line source and by Lai and Kulacki (1990) for a sphere. For a large Rayleigh number, Lai (1990b) obtained a similarity solution for a line source, and the closed-form solutions are presented for the special case of Lewis number equal to 1.

Natural or mixed convection flow from free or wall plumes in non-Darcian porous media were investigated by Cheng and Zheng (1986), Ingham (1988), Lai (1991a, b), Leu and Jang (1994, 1995), and Degan and Vasseur (1995). It was shown that the non-Darcian flow produces a much more peaked temperature profile than that predicted by the Darcian flow. This behaviour is qualitatively in agreement with the experiments reported by Cheng (1985) on the plume rising from a horizontal line source of heat. Nakayama (1993, 1994) has studied natural convection from a point heat source and from a line heat source in a porous medium saturated with a power-law fluid. Finally, we mention the more recent paper by Facas (1995), who was presented numerical solutions for the Darcian natural convection heat transfer from an elliptic heat source buried beneath a semi-infinite porous medium.

In this paper, we investigate the Darcian boundary-layer natural convection from inclined wall plumes which arise from a line thermal source imbedded at the leading edge of an adiabatic plate with arbitrary inclination from the vertical to the horizontal and immersed in a fluid-saturated porous medium. The problem is formulated based on the corresponding configuration for inclined wall plumes in a viscous (non-porous) fluid considered by Lin et al. (1996). To facilitate the analysis, a dimensionless stretched streamwise coordinate ξ (or ζ) has been proposed. In addition, dimensionless stream function and dimensionless temperature with proper scales based on ζ are defined to obtain a set of non-similar equations. Also, a new dependent constraint variable λ has been introduced to avoid numerical integration. The variable ξ (or ζ) also serves as an index of the inclination of the plate. For the limiting case of a vertical wall plume, $\xi = 0$, while for the limiting case of a horizontal wall plume, $\xi = 1$, respectively. In these limiting cases, the nonsimilar equations are readily reducible to the self-similar equations of the vertical and horizontal wall plumes. The new set of equations derived for arbitrary plate inclination from the vertical to the horizontal subject to an integral constraint equation of flux-conservation condition was solved by a very efficient numerical method. A considerable effort has been directed in this paper to develop

a new method to solve the governing nonsimilar equations, which can be also applied to the analyses of other plume configurations.

2. Governing equations

We consider here natural convection from a line heat source of strength Q imbedded at the leading edge of an adiabatic flat plate which is embedded in a fluid-saturated porous medium of ambient temperature T_∞ . The flat plate is inclined with an arbitrary angle Ψ to the vertical from 0 to $\pi/2$, including the vertical and horizontal orientations. The physical model and coordinate system are shown in Fig. 1. Cartesian coordinates (x, y) with associated velocity components (u, v) are used in the subsequent analysis. The thermophysical properties of the fluid are assumed constant except for the density in the buoyancy term in the momentum equation.

The governing equations for the steady, two-dimensional natural convection with the boundary-layer, Boussinesq, Darcy flow and negligible inertia approximations are as follows, see Ingham et al. (1985):

$$\frac{\partial u}{\partial x} + \frac{\partial v}{\partial y} = 0, \quad (1)$$

$$\frac{\partial u}{\partial x} = \frac{gK\beta}{\nu} \left(\frac{\partial T}{\partial y} \cos \Phi - \frac{\partial T}{\partial x} \sin \Phi \right), \quad (2)$$

$$u \frac{\partial T}{\partial x} + v \frac{\partial T}{\partial y} = \alpha \frac{\partial^2 T}{\partial y^2}, \quad (3)$$

Fig. 1. The physical model and coordinate system.

subject to the boundary conditions

$$v = 0, \quad \frac{\partial T}{\partial y} = 0 \quad \text{at } y = 0, \quad (4)$$

$$u \rightarrow 0, \quad T \rightarrow T_\infty \quad \text{as } y \rightarrow \infty, \quad (5)$$

where g is the acceleration due to gravity, T is the fluid temperature, K is the permeability, and α , β and ν are the effective thermal diffusivity, coefficient of thermal expansion and kinematic viscosity, respectively. In addition to these boundary conditions, the governing equations (1)–(3) are also subject to a constraint of energy conservation condition. That is, the total energy convected by the boundary-layer flow through the perpendicular plane at any $x > 0$ must be equal to the energy Q released from the line thermal source

$$\rho C_p L \int_0^\infty u(T - T_\infty) dy = Q. \quad (6)$$

Here ρ , L and C_p denote density, length of line thermal source and specific heat of fluid.

A significant step in formulating the problem for comprehensive solutions is the introduction of the characteristic dimensionless coordinate

$$\xi = 1 - \left[1 + \frac{(R_a \sin \Phi)^{1/4}}{(R_a \cos \Phi)^{1/3}} \right]^{-1}, \quad (7)$$

where the local Rayleigh number R_a is defined as

$$R_a = \frac{g K \beta T^* x}{\alpha \nu}$$

with the equivalent temperature T^* given by

$$T^* = \frac{Q}{\rho C_p \alpha L}.$$

This coordinate provides the basis for a unified framework within which the features of the relative strength of the longitudinal to the transverse components of buoyant force acting on the boundary-layer flow adjacent to the inclined plate.

In addition, a pseudo-similarity variable is defined as

$$\eta = \frac{y}{x} \zeta,$$

where

$$\zeta = (R_a \cos \Phi)^{1/3} + (R_a \sin \Phi)^{1/4}.$$

Furthermore, a dimensionless stream function and a dimensionless temperature are defined, respectively, as follows:

$$f(\xi, \eta) = \frac{\psi(x, y)}{\alpha \zeta}, \quad (8)$$

$$\theta(\xi, \eta) = \frac{T(x, y) - T_\infty}{T^*} \zeta \quad (9)$$

and

$$\lambda(\xi, \eta) = \int_0^\eta \theta \frac{\partial f}{\partial \eta} d\eta. \quad (10)$$

The differential equations and all boundary conditions transform to the following systems of equations:

$$\frac{\partial^2 f}{\partial \eta^2} = a_0(\xi) \frac{\partial \theta}{\partial \eta} + b_0(\xi) \frac{\partial \theta}{\partial \xi} + c_0(\xi) \eta \frac{\partial \theta}{\partial \eta} + d_0(\xi) \theta, \quad (11)$$

$$\frac{\partial^2 \theta}{\partial \eta^2} + p_0(\xi) \left[f \frac{\partial \theta}{\partial \eta} + \theta \frac{\partial f}{\partial \eta} \right] = q_0(\xi) \left[\frac{\partial \theta}{\partial \eta} \frac{\partial f}{\partial \xi} - \frac{\partial f}{\partial \eta} \frac{\partial \theta}{\partial \xi} \right], \quad (12)$$

$$\frac{\partial \lambda}{\partial \eta} = \theta \frac{\partial f}{\partial \eta}, \quad (13)$$

with boundary conditions

$$f(\xi, 0) = 0, \quad \frac{\partial \theta(\xi, 0)}{\partial \eta} = 0, \quad \lambda(\xi, 0) = 0, \quad \frac{\partial f(\xi, \infty)}{\partial \eta} = 0, \quad \lambda(\xi, \infty) = 1. \quad (14)$$

Here

$$a_0(\xi) = (1 - \xi)^3, \quad b_0(\xi) = \frac{\xi^5(1 - \xi)}{12}, \quad c_0(\xi) = \frac{\xi^4(8 + \xi)}{12},$$

$$d_0(\xi) = \frac{\xi^4(4 - \xi)}{12}, \quad p_0(\xi) = \frac{4 - \xi}{12}, \quad q_0(\xi) = \frac{\xi(1 - \xi)}{12}.$$

The constraint condition $\lambda(\xi, \infty)$ implies $\lim_{\eta \rightarrow \infty} \theta(\partial f / \partial \eta) = 0$, that is, either $\theta(\xi, \infty) = 0$ or $\partial f(\xi, \infty) / \partial \eta = 0$. We simply drop the boundary condition $\theta(\xi, \infty) = 0$ to avoid computational overdetermination.

For the limiting case of a vertical wall plume, $\xi = 0$, Eqs. (11)–(13) are readily reduced to the following self-similar equations:

$$f'' = \theta', \quad (15)$$

$$\theta'' + \frac{1}{3}(f\theta)' = 0, \quad (16)$$

$$\lambda' = \theta f', \quad (17)$$

where primes denote differentiation with respect to η . The analytical solution of these equations is given by

$$f(\eta) = \sqrt[3]{9} \tanh\left(\frac{\eta}{\sqrt[3]{24}}\right), \quad \theta(\eta) = \frac{\sqrt[3]{3}}{2 \cosh^2(\eta/\sqrt[3]{24})}, \quad \lambda(\eta) = \frac{1}{2} \tanh\left(\frac{\eta}{\sqrt[3]{24}}\right) \left[3 - \tanh^2\left(\frac{\eta}{\sqrt[3]{24}}\right) \right]. \quad (18)$$

For the other limiting case of a horizontal wall plume, $\xi = 1$, Eqs. (11)–(13) become:

$$f'' = \frac{3}{4} \eta \theta' + \frac{1}{4} \theta, \quad (19)$$

$$\theta'' + \frac{1}{4} (f\theta)' = 0, \quad (20)$$

$$\lambda' = \theta f'. \quad (21)$$

It is worth mentioning that these equations are so far the first time reported in the literature. However, they do not possess a closed-form analytical solution.

3. Numerical method

The solution to the nonsimilar equations (11)–(13) of the inclined wall plume in a porous medium with boundary conditions (14) is obtained numerically using finite differences. At Lin et al. (1996) noticed, it is very difficult to integrate the set of equations constrained by an integral equation (10), especially when this system of equations is nonsimilar. A considerable effort in this study has been directed toward developing a numerical method for the problem under consideration, which is different of that proposed by Lin et al. (1996). Thus, a new dependent variable, $\lambda(\xi, \eta)$, in Eq. (13), has been introduced to avoid numerical integration. The condition $\theta(\xi, \eta) = 0$ has thus been dropped to avoid computational overdetermination, because the constraint integral $\int_0^\infty \theta(\partial f / \partial \eta) d\eta = 1$ or $\lambda(\xi, \infty) = 1$ implies either $(\partial f / \partial \eta)(\xi, \infty) = 0$ or $\theta(\xi, \infty) = 0$.

Now, we write the equations as a first order system by introducing the new dependent variables $q(\xi, \eta)$ and $w(\xi, \eta)$ as follows:

$$\frac{\partial f}{\partial \eta} = q, \quad (22)$$

$$\frac{\partial q}{\partial \eta} = a_0(\xi)w + b_0(\xi) \frac{\partial \theta}{\partial \xi} + c_0(\xi)\eta w + d_0(\xi)\theta, \quad (23)$$

$$\frac{\partial \theta}{\partial \eta} = w, \quad (24)$$

$$\frac{\partial w}{\partial \eta} = -p_0(\xi)[fw + \theta q] + q_0(\xi) \left[w \frac{\partial f}{\partial \xi} - q \frac{\partial \theta}{\partial \xi} \right], \quad (25)$$

$$\frac{\partial \lambda}{\partial \eta} = \theta q. \quad (26)$$

The boundary conditions now become

$$f(\xi, 0) = 0, \quad w(\xi, 0) = 0, \quad \lambda(\xi, 0) = 0, \quad q(\xi, \infty) = 0, \quad \lambda(\xi, \infty) = 1.$$

We place an arbitrary rectangular net of points (ξ_n, η_j) on $0 \leq \xi \leq 1, \eta \geq 0$ and use the notation:

$$\begin{aligned} \xi_0 &= 0, \quad \xi_n = \xi_{n-1} + k_n, \quad n = 1, 2, \dots, K, \quad \xi_K = 1; \\ \eta_0 &= 0, \quad \eta_j = \eta_{j-1} + h_j, \quad j = 1, 2, \dots, J; \end{aligned} \quad (27)$$

If $(f_j^n, q_j^n, \theta_j^n, w_j^n)$ are to approximate (f, q, θ, w) at (ξ_n, η_j) , the difference approximations are defined, for $1 \leq j \leq J$, by

$$\frac{f_j^n - f_{j-1}^n}{h_j} = q_{j-1/2}^n, \quad (28)$$

$$\begin{aligned} \frac{q_j^{n-1/2} - q_{j-1}^{n-1/2}}{h_j} &= a_{n-1/2} w_{j-1/2}^{n-1/2} + b_{n-1/2} \frac{\theta_{j-1/2}^n - \theta_{j-1/2}^{n-1}}{k_n} \\ &\quad + c_{n-1/2} \eta_{j-1/2} w_{j-1/2}^{n-1/2} + d_{n-1/2} \theta_{j-1/2}^{n-1/2}, \end{aligned} \quad (29)$$

$$\frac{\theta_j^n - \theta_{j-1}^n}{h_j} = w_{j-1/2}^n, \quad (30)$$

$$\begin{aligned} \frac{w_j^{n-1/2} - w_{j-1}^{n-1/2}}{h_j} &= -p_{n-1/2} (fw + \theta q)_{j-1/2}^{n-1/2} + q_{n-1/2} \\ &\quad \times \left[w_{j-1/2}^{n-1/2} \frac{f_{j-1/2}^n - f_{j-1/2}^{n-1}}{k_n} - q_{j-1/2}^{n-1/2} \frac{\theta_{j-1/2}^n - \theta_{j-1/2}^{n-1}}{k_n} \right], \end{aligned} \quad (31)$$

$$\frac{\lambda_j^n - \lambda_{j-1}^n}{h_j} = (\theta q)_{j-1/2}^n, \quad (32)$$

where $\xi_{n-1/2} = (\xi_n + \xi_{n-1})/2$, $a_{n-1/2}$, $b_{n-1/2}$, $c_{n-1/2}$, $d_{n-1/2}$, $p_{n-1/2}$ and $q_{n-1/2}$ are the values of $a_0(\xi)$, $b_0(\xi)$, $c_0(\xi)$, $d_0(\xi)$, $p_0(\xi)$ and $q_0(\xi)$ at $\xi_{n-1/2}$, respectively, and for any function $z(\xi, \eta)$ we have introduced a notation for averages and intermediate values as

$$z_{j-1/2}^n = (z_j^n + z_{j-1}^n)/2, \quad z_j^{n-1/2} = (z_j^n + z_j^{n-1})/2, \quad z_{j-1/2}^{n-1/2} = (z_j^n + z_{j-1}^n + z_j^{n-1} + z_{j-1}^{n-1})/4. \quad (33)$$

Note that Eqs. (28), (30) and (32) are centered at $(\xi_n, \eta_{j-1/2})$, while Eqs. (29) and (31) are centered at $(\xi_{n-1/2}, \eta_{j-1/2})$, i.e. when a ξ derivative is absent, equations can be differenced about the point $(\xi_n, \eta_{j-1/2})$. It was found in practice that this damps high-frequency Fourier error components better than differencing about $(\xi_{n-1/2}, \eta_{j-1/2})$.

The boundary conditions become simply:

$$f_0^n = 0, \quad w_0^n = 0, \quad \lambda_0^n = 0, \quad q_J^n = 0, \quad \lambda_J^n = 1. \quad (34)$$

The nonlinear difference equations may now be solved recursively starting with $n = 0$ (on $\xi = \xi_0 = 0$). In the case of $n = 0$ we retain (28), (30), (32) and (34) with $n = 0$ and simply alter (29) and

(31) by setting $\xi_{n-1/2} = 0$ and using superscripts $n = 0$ rather than $n - \frac{1}{2}$ in the remaining terms. The resulting difference equations are then solved by Newton iteration. The details of implementation of Newton iteration is beyond the scope of this paper. Solutions are obtained on different sized grids and Richardson's extrapolation used to produce results of high accuracy.

4. Extrapolating the results

Since central difference are used the exact numerical solution of our difference equations (28)–(34) is a second-order accurate approximation. The local truncation errors of this difference scheme can be written as a Taylor series in powers of h^2 and k^2 where $k = \max_n k_n$ and $h = \max_j h_j$. It is therefore possible, as pointed out by Keller and Cebeci (1971), by solving the problem on different sized grids and using Richardson's extrapolation, to produce results of high accuracy provided the truncation errors are larger than the iteration errors. For example, each cell of the net (27) is divided into m subintervals both in the ξ direction and in the η direction where m is an integer. The problem is solved numerically for $m = 1, 2, 3$ and 4. If z_m denotes the results of any actual variable function $z(\xi, \eta)$ at a common grid point then the z_m has accuracy $O(k^2 + h^2)$. Since the truncation error is proportional to the square of k and h then

$$z_{12} = \frac{1}{3}(4z_2 - z_1), \quad z_{23} = \frac{1}{3}(9z_3 - 4z_2), \quad z_{34} = \frac{1}{7}(16z_4 - 9z_3)$$

have errors $O(k^4 + h^4)$ and

$$z_{123} = \frac{1}{8}(9z_{23} - z_{12}), \quad z_{234} = \frac{1}{12}(16z_{34} - 4z_{23}) \quad (35)$$

will be in error by $O(k^6 + h^6)$ and, finally,

$$z_{1234} = \frac{1}{15}(16z_{234} - z_{123}).$$

The results quoted are z_{1234} and error is estimated by maximum of the difference $|z_{1234} - z_{234}|$, which being a global error estimate measures the actual error in z .

In order to assess the accuracy of our numerical results, they were compared for a vertical wall ($\Phi = 0$, i.e. $\xi = 0$) with the analytical results given by Eq. (18). Thus, the value of $\theta(0)$ both from Eqs. (11)–(14) and from Eq. (18) when $\xi = 0$ is $\theta(0) = 0.72112478$, which shows that the agreement is excellent. We are, therefore, strongly confident that the present numerical scheme works very efficient.

5. Results and discussion

The application of the results obtained in this paper lies in the determination of the velocity and temperature profiles in the boundary layer as well as the wall velocity and wall temperature profiles. The dimensionless velocity $u/(\alpha/x)$ and temperature $(T - T_\infty)/T^*$ profiles over the dimensionless transverse coordinate y/x are depicted in Figs. 2 and 3 for different values of the tilt angle Φ and $R_a = 10^3$. It can be seen that these profiles look similar and they should be symmetric with the x -axis.

Fig. 2. Representative velocity profiles for $R_a = 10^3$.

Fig. 3. Representative temperature profiles for $R_a = 10^3$.

Fig. 4. Variations of wall velocity with Φ .

Fig. 5. Variations of wall temperature with Φ .

Also, these profiles are found to be quite similar in form to those of Leu and Jang (1994) for a line source of heat along the base of an adiabatic vertical plate. Further, one can see that the maximum of the velocity and temperature profiles occurs at the wall $y = 0$. In addition, the longitudinal velocity profiles decrease near the wall as Φ increases, while the temperature profiles increase monotonically with increasing values of Φ ; the fluid adjacent to the line source becomes hotter, and it begins to rise until it reaches a maximum. This is due to the decrease of the component of buoyancy force with increasing the tilt angle Φ . Thus, for a fixed angle Φ , the temperature increases near the wall and decreases more rapidly towards the outer edge of the plume and the width of the plume becomes less

Fig. 6. (a) Streamlines and (b) isotherms for $\Phi = 0$ and $Ra = 10^3$.

extensive. Therefore, the boundary and convective effects are more important for a wall plume than for a free plume (see, Leu and Jang, 1994, 1995).

The maximum dimensionless velocity and temperature profiles (i.e. wall velocity and wall temperature) are shown in Figs. 4 and 5 versus the tilt angle Φ , i.e. over the range of $0 \leq \xi \leq 1$ and some values of Ra . As expected, the wall velocity increases, while the wall temperature decreases with increasing the parameter Φ . This is because a more vigorous flow when the plate is tilted away from the horizontal. It is also noticed from Fig. 4 that the wall velocity increases, with the increase of

Fig. 7. (a) Streamlines and (b) isotherms for $\Phi = \pi/4$ and $R_a = 10^3$.

the Rayleigh number R_a . This causes a reduction of the wall temperature when R_a is increased (see, Fig. 5). Therefore, at larger values of R_a , the plume becomes thicker, resulting in increased entrainment of fluid in the boundary layer from the outer region. The entrainment depends on the extent of outer region, i.e. whether the fluid can entrain from entire or limited space. Furthermore, Figs. 4 and 5 show that the longitudinal velocity and temperature profiles at the wall do not change monotonically with the tilt angle Φ . Highest wall velocity and lowest wall temperature can be found

Fig. 8. (a) Streamlines and (b) isotherms for $\Phi = \pi/2$ and $Ra = 10^3$.

at $\Phi \approx \pi/6$. This may be due to the combined effects between transverse buoyancy and longitudinal buoyancy. This observation could be useful for engineering applications.

Finally, Figs. 6–8 illustrate the streamlines and isotherms of the inclined wall plume in a porous medium for the tilt angles $\Phi = 0, \pi/4$ and $\pi/2$ when $Ra = 10^3$. These figures clearly show that there are stable boundary-layer flows along the plate. The separation and wake formation have not been found. Moreover, the streamline plots show that the fluid is accelerating from a low-velocity point below the line plume to a high-velocity region above the line plume.

We conclude by noting that this flow configuration is of considerable importance in technology and the present work considers the resulting boundary-layer flow in order to determine the velocity and temperature profiles, as well as other physical aspects of interest. The results of the present study are important in technology, for example, in the positioning of components dissipating energy on vertical circuit boards placed in a porous medium and in the positioning of the boards themselves. Heat transfer and natural convection flow considerations are very important in this area and also in several frequently encountered manufacturing processes. The interaction of the flows arising from several elements, which constitute steady thermal sources, on a vertical insulating surface is an important problem and further work needs to be done on it in order to determine the nature of the resulting flow and heat transfer.

Acknowledgements

The authors are grateful to the referees for their constructive suggestions.

References

- Afzal, N. (1985) Two-dimensional buoyant plume in porous media: higher-order effects, *Int. J. Heat Mass Transfer* 28, 2029–2041.
- Afzal, N., Salam, M.Y. (1990) Natural-convection from point-source embedded in Darcian porous-medium, *Fluid Dyn. Res.* 6, 175–184.
- Bejan, A. (1978) Natural convection in an infinite porous medium with a concentrated heat source, *J. Fluid Mech.* 89, 97–107.
- Cheng, P. (1985) Natural-convection in a porous-medium: – external flows. In: S. Kakac, W. Aung, R. Viskanta (Eds), *Natural Convection Fundamentals and Applications*, Hemisphere, Washington, DC.
- Cheng, P., Zheng, T.M. (1986) Mixed convection in the thermal plume above a horizontal line source of heat in a porous-medium of infinite extent, In: *Proc. 8th Int. Conf. on Heat Transfer* 5, 2671–2675.
- Degan, G., Vasseur, P. (1995) The non-Darcy regime for boundary-layer natural-convection from a point-source of heat in porous-medium, *Int. Commun. in Heat Mass Transfer* 22, 381–390.
- Facas, G.N. (1995) Natural convection from a buried elliptic heat source, *Int. J. Heat Fluid Flow* 16, 519–526.
- Ganapathy, R., Purushothaman, R. (1990) Thermal convection from an instantaneous point heat source in a porous medium, *Int. J. Eng. Sci.* 28, 907–918.
- Ganapathy, R. (1994) Free convective heat and mass-transfer flow-induced by an instantaneous point-source in an infinite porous-medium, *Fluid Dyn. Res.* 14, 313–329.
- Hickox, C.E., Watts, H.A. (1980) Steady thermal convection from a concentrated source in a porous medium, *Trans. ASME, J. Heat Transfer* 102, 248–253.
- Hickox, C.E. (1981) Thermal convection at low Rayleigh number from concentrated sources in porous media, *Trans. ASME, J. Heat Transfer* 103, 232–236.
- Ingham, D.B., Merkin, J.H., Pop, I. (1985) Natural-convection from a semi-infinite flat-plate inclined at a small-angle to the horizontal in a saturated porous-medium, *Acta Mech.* 57, 183–202.
- Ingham, D.B. (1988) An exact solution for non-Darcy free-convection from a horizontal line source of heat, *Wärme-Stoffübertragung* 22, 125–127.
- Keller, H.B., Cebeci, T. (1971) Accurate numerical methods for boundary layer flows. I: two dimensional laminar flows, In: *Proc. 2nd Int. Conf. on Numerical Methods in Fluid Dynamics*, pp. 92–100.
- Kumari, M., Pop, I., Nath, G. (1988) Darcian mixed convection plumes along vertical adiabatic surfaces in a saturated porous-medium, *Wärme- Stoffübertragung* 22, 173–178.

- Lai, F.C., Kulacki, F.A. (1990) Coupled heat and mass transfer from a sphere buried in an infinite porous medium, *Int. J. Heat Mass Transfer* 33, 209–215.
- Lai, F.C. (1990a) Coupled heat and mass-transfer by natural-convection from a horizontal line source in saturated porous-medium, *Int. Commun. Heat Mass Transfer* 17, 489–499.
- Lai, F.C. (1990b) Natural-convection from a concentrated heat-source in a saturated porous-medium, *Int. Commun. Heat Mass Transfer* 17, 791–800.
- Lai, F.C. (1991a) Non-Darcy natural-convection from a line source of heat in saturated porous-medium, *Int. Commun. Heat Mass Transfer* 18, 445–457.
- Lai, F.C. (1991b) Non-Darcy mixed convection from a line source of heat in a saturated porous-medium, *Int. Commun. Heat Mass Transfer* 18, 875–887.
- Larson, S.E., Poulikakos, D. (1986) Double diffusion from a horizontal line source in an infinite porous medium, *Int. J. Heat Mass Transfer* 29, 492–495.
- Leu, J.-S., Jang, J.-Y. (1994) The wall and free plumes above a horizontal line source in non-Darcian porous media, *Int. J. Heat Mass Transfer* 37, 1925–1933.
- Leu, J.-S., Jang, J.-Y. (1995) The natural convection from a point heat source embedded in a non-Darcian porous medium, *Int. J. Heat Mass Transfer* 38, 1097–1104.
- Lin, H.-T., Chen, J.-J., Kung, L.-W., Yu, W.-S., Chen, Y.-M. (1996) Inclined and horizontal wall plumes, *Int. J. Heat Mass Transfer* 39, 2243–2252.
- Masuoka, T., Tohda, Y., Tsuruta, T., Yasuda, Y. (1986) Buoyant plume about concentrated heat source in stratified porous media, *Trans. Japanese Soc. Mech. Eng. Ser. B*, 2656–2662.
- Nakayama, A. (1993) Free convection from a horizontal line heat source in a power-law fluid-saturated porous medium, *Int. J. Heat Fluid Flow* 14, 279–283.
- Nakayama, A. (1994) A unified theory for non-Darcy free, forced, and mixed convection problems associated with a horizontal line heat source in a porous medium, *Trans. ASME, J. Heat Transfer* 116, 508–513.
- Nield, D.A., White, S.P. (1982) Natural convection in an infinite porous medium produced by a line heat source, In: McNabb, A., R.A. Wooding, M. Rosser (Eds.), *Mathematics and Models in Engineering Science*, Science Information Division, DSIR, Wellington, New Zealand, pp. 121–128.
- Nield, D.A., Bejan, A. (1992) *Convection in Porous Media*, Springer, New York.
- Poulikakos, D. (1985) On buoyancy induced heat and mass transfer from a concentrated source in an infinite porous medium, *Int. J. Heat Mass Transfer* 28, 621–629.
- Purushothaman, R., Ganapathy, R., Hiremath, P.S. (1990) Free convection in an infinite porous medium due to a pulsating point heat source, *Zeitschrift für Angewandte Mathematik Mechanik* 70, 41–47.
- Shaw, D.C., Dawe, R.A. (1985) Effects of a vertical discontinuity in a porous medium on a plane convection plume at high Rayleigh numbers, *Int. J. Heat Mass Transfer* 28, 789–794.
- Wooding, R.A. (1963) Convection in a saturated porous medium at large Rayleigh number or Peclet number, *J. Fluid Mech.* 15, 527–544.