Affine nonmagnetic transformation design and its application

Xu, Hongyi; Zhang, Baile; Barbastathis, George; Sun, Handong

2012

Xu, H., Zhang, B., Barbastathis, G., & Sun, H. (2012). Affine nonmagnetic transformation design and its application. 2012 Conference on Lasers and Electro-Optics (CLEO), 1-2.

<https://hdl.handle.net/10356/96961>

© 2012 Optical Society of America. This paper was published in 2012 Conference on Lasers and Electro-Optics (CLEO) and is made available as an electronic reprint (preprint) with permission of Optical Society of America. The paper can be found at the following official OpenURL:

[<http://ieeexplore.ieee.org.ezlibproxy1.ntu.edu.sg/xpl/login.jsp?tp=&arnumber=6326373&url=http%3A%2F%2Fieeexplore.ieee.org>]

One print or electronic copy may be made for personal use only. Systematic or multiple reproduction, distribution to multiple locations via electronic or other means, duplication of any material in this paper for a fee or for commercial purposes, or modification of the content of the paper is prohibited and is subject to penalties under law.

Downloaded on 26 Apr 2023 17:46:45 SGT

Affine Nonmagnetic Transformation Design and its Application

Hongyi Xu¹, Baile Zhang^{1, 2, 3*}, George Barbastathis^{2, 3}, Handong Sun^{1*}

1. Division of Physics and Applied Physics, School of Physical and Mathematical Sciences, Nanyang Technological University, Singapore 637371, Singapore.

2. Singapore-MIT Alliance for Research and Technology (SMART) Centre, Singapore 117543, Singapore.

3. Department of Mechanical Engineering, Massachusetts Institute of Technology, Cambridge, Massachusetts 02139, USA.

*Corresponding authors, electronic mail: blzhang@ntu.edu.sg, hdsun@ntu.edu.sg

Abstract: Based on the transformation optical design which possesses simultaneously unitary permeability and piece-wise homogeneity, transformation-optics devices can practically avoid magnetism and inhomogeneous parameters, and be implemented directly using existing dielectric materials with ideal performance.

OCIS codes: 160.3918, 160.1190, 230.7390

Transformation optics is applicable to invisibility cloaking [1, 2] and a broad variety of electromagnetic wave converters [3-5], and is moving from theoretical study to practical use. However, the original implementation of transformation-optics device necessitates the utilization of media that are both inhomogeneous and anisotropic. To address this challenge, homogeneous transformation methods [6, 7] were recently proposed and experimentally demonstrated [8-10]. A second limitation to date has still remained: The transformation typically results in non-unit values for the magnetic permeability μ , which, except being renormalization with scattering trade-off [11], is not known generally how to implement in optical wavelengths with conventional optical materials.

To tackle this problem, we introduce a transformation optical design which possesses simultaneously a unitary permeability (*i.e.* nonmagnetism) and homogeneous permittivity. Our design, admitting both macroscale and nanoscale fabrication, can be achieved using natural birefringence materials such as Calcite [8, 9], or via subwavelength anisotropic patterning [12, 13]. Moreover, our geometrical approach simplifies the problem to one of graphical design that in many cases can be carried out analytically.

Figure 1. (Color online) the area-preserving transformation from triangle AOB (blue) to $A'O'B'$ (green) along both x and y directions.

Consider a general two-dimensional (2D) affine coordinate transformation $x' = ax + by + c$, $y' = dx + ey + f$, from triangle AOB to $A'O'B'$ in the x - y plane, as shown in Fig. 1. The associated Jacobian matrix is $\bar{J} = [a, b; d, e]$. For transverse magnetic (TM) modes where the H field is perpendicular to the x - y plane, we obtain the transformed relative dielectric permittivity and permeability as $\bar{\epsilon}' = \bar{J} \bar{J}' / \det(\bar{J})$, $\mu' = 1 / \det(\bar{J})$. We can achieve unitary permeability μ' by imposing a unitary Jacobian $\det(\bar{J}) = 1$ [14]. The geometric interpretation is that the transformation is area-preserving, such that the area of the triangle AOB is always equal to that of $A'O'B'$.

As a special case ($\angle AOB = 90^\circ$) of the horizontal shear area-preserving (No transformation imposed along y direction) transformation (APT), we introduce the application of a 2D surface plasmonic (SP) resonator based on transverse magnetic (TM) bending adapters. Its APT method is illustrated in Fig. 2(a). The rectangular region $AOBC$ is a part of a rectangular planar waveguide. To form one arm of the bending adapter, we transform ΔAOB to the new triangle $\Delta A'O'B'$, where the angle α is the half-bending angle of the adapter. The final bending angle is 2α , formed by mirroring the structure with regard to axis BO' , as shown in the inset

figure. Without loss of generality, we set length $|OB|=1$, and fix the point A on the horizontal axis at location $(-L, 0)$. To impose the nonmagnetic condition we require that the area of triangle AOB should equal that of $AO'B$. Thus, O' should be placed such that $OO' \parallel AB$, i.e. $x_o + Ly_o = 0$. The Jacobian is thus unitary, leading to $\mu' = 1$. An equilateral polygonal resonator can be formed by using multiple bends under the condition $p2\alpha = 2\pi$ [Fig. 2(b)], where p is an integer. Furthermore if metallic material such as silver is placed in the center, SP resonance can be excited at the interface between metal and dielectrics [15-17], as shown in Fig. 2(c).

Figure 2. (Color online) (a) APT (from ABO to $AB'O'$) for one arm of the bending adapter. (b) A transformation optics based polygonal resonator formed by multiple bending adapters. (c) The distribution of magnetic field of a transformation optics based SP hexagonal resonator.

In summary, based on the transformation optical design which possesses simultaneously unitary permeability and piece-wise homogeneity, transformation-optics devices can practically avoid magnetism and inhomogeneous parameters, and be implemented directly using existing dielectric materials with ideal performance.

References

1. J. B. Pendry, D. Schurig, and D. R. Smith, "Controlling electromagnetic fields," *Science* **312**, 1780-1782 (2006).
2. U. Leonhardt, "Optical conformal mapping," *Science* **312**, 1777-1780 (2006).
3. D. A. Roberts, M. Rahm, J. B. Pendry, and D. R. Smith, "Transformation-optical design of sharp waveguide bends and corners," *Appl. Phys. Lett.* **93**, 251111 (2008).
4. M. Rahm, S. A. Cummer, D. Schurig, J. B. Pendry, and D. R. Smith, "Optical design of reflectionless complex media by finite embedded coordinate transformations," *Phys. Rev. Lett.* **100**, 063903 (2008).
5. D.-H. Kwon and D. H. Werner, "Transformation optical designs for wave collimators, flat lenses and right-angle bends," *New J. Phys.* **10**, 115023 (2008).
6. T. Han, C.-W. Qiu, and X. Tang, "Adaptive waveguide bends with homogeneous, nonmagnetic, and isotropic materials," *Opt. Lett.* **36**, 181-183 (2011).
7. H. Y. Xu, B. Zhang, G. Barbastathis, and H. D. Sun, "Compact optical waveguide coupler using homogeneous uniaxial medium," *J. Opt. Soc. Am. B* **28**, 2633-2636 (2011).
8. B. Zhang, Y. Luo, X. Liu, and G. Barbastathis, "Macroscopic Invisibility Cloak for Visible Light," *Phys. Rev. Lett.* **106**, 033901 (2011).
9. X. Chen, Y. Luo, J. Zhang, K. Jiang, J. B. Pendry, and S. Zhang, "Macroscopic invisibility cloaking of visible light," *Nat. Commun.* **2**, 176 (2011).
10. J. Zhang, L. Liu, Y. Luo, S. Zhang, and N. A. Mortensen, "Homogeneous optical cloak constructed with uniform layered structures," *Opt. Express* **19**, 8625-8631 (2011).
11. W. Cai, U. K. Chettiar, A. V. Kildishev, and V. M. Shalaev, "Optical cloaking with metamaterials," *Nat. Photon.* **1**, 224-227 (2007).
12. L. Pang, M. Nezhad, U. Levy, C.-H. Tsai, and Y. Fainman, "Form-birefringence structure fabrication in GaAs by use of SU-8 as a dry-etching mask," *Appl. Opt.* **44**, 2377-2381 (2005).
13. H. Gao, B. Zhang, and G. Barbastathis, "Photonic cloak made of subwavelength dielectric elliptical rod arrays," *Opt. Commun.* **284**, 4820-4823 (2011).
14. B. Vasic, G. Isic, R. Gajic, and K. Hingerl, "Coordinate transformation based design of confined metamaterial structures," *Phys. Rev. B* **79**, 085103 (2009).
15. Y. Liu, T. Zentgraf, G. Bartal, and X. Zhang, "Transformational Plasmon Optics," *Nano Letters* **10**, 1991-1997 (2010).
16. P. A. Huidobro, M. L. Nesterov, L. Martin-Moreno, and F. J. Garcia-Vidal, "Transformation Optics for Plasmonics," *Nano Letters* **10**, 1985-1990 (2010).
17. J. Zhang, S. Xiao, M. Wubs, and N. A. Mortensen, "Surface Plasmon Wave Adapter Designed with Transformation Optics," *ACS Nano* **5**, 4359-4364 (2011).